



Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 06/28/2022

Date of Issue: 05/12/2020

Version: 2.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Batiste™ Hint of Color (NA GHS 2015)

Product Code: 42015060, 42015061, 42015062

Synonyms: (Brilliant Blonde, Beautiful Brunette, Divine Dark)

Intended Use of the Product

Hair Care

Name, Address, and Telephone of the Responsible Party

Company

Church & Dwight Co. Inc.

500 Charles Ewing Blvd

Ewing Township, NJ 08628

T 1-800-524-1328

www.churchdwight.com

Emergency Telephone Number

Emergency Number : For Medical Emergency: 1-888-234-1828 (USA and Canada), 952-853-1925 (Outside USA and Canada)

For Chemical Emergency: ChemTel LLC (800)255-3924 (North America) +1 (813)248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable to this SDS differ from the labeling requirements of the CPSC and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

Classification of the Substance or Mixture

GHS-US/CA Classification

Flam. Aerosol 2 H223

Press. Gas (Comp.) H280

Simple Asphy

Full text of hazard classes and H-statements : see section 16

Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H223 - Flammable aerosol.

H280 - Contains gas under pressure; may explode if heated.

May displace oxygen and cause rapid suffocation.

Precautionary Statements (GHS-US/CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use.

P403+P410+P412 - Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Other Hazards

May displace oxygen and cause rapid suffocation. Contact with gas escaping the container can cause frostbite. Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US/CA)

No additional information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
n-Butane	(CAS-No.) 106-97-8	30-60	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy
Isobutane	(CAS-No.) 75-28-5	15-40	Flam. Gas 1, H220 Press. Gas (Liq.), H280 Simple Asphy
Starch	(CAS-No.) 9005-25-8	3-7	Comb. Dust
Ethyl alcohol	(CAS-No.) 64-17-5	1-5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319

Full text of H-statements: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%). The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: First, take proper precautions to ensure your own safety before attempting rescue (e.g. wear appropriate respiratory protective equipment, use the buddy system), then remove the exposed person to fresh air. Keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: For brief contact with a small amount: Rewarm with body heat. Get immediate medical advice/attention. For extensive contact or a large amount: Immediately call a poison center/doctor and follow their advice. Specific treatment is urgent, incorrect first-aid practices will aggravate the injury. Protect affected area with a loose cover until proper medical treatment is received. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Contact with gas escaping the container can cause frostbite. Asphyxia by lack of oxygen: risk of death.

Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Skin Contact: Contact with gas escaping the container can cause frostbite and freeze burns.

Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable aerosol.

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Fight fire remotely due to the risk of explosion. DO NOT fight fire when fire reaches containers. Evacuate area.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Smoke.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Do not get in eyes, on skin, or on clothing. Do not breathe gas, vapors, mist, spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Evacuate unnecessary personnel, isolate, and ventilate area. Eliminate ignition sources.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Materials for Containment and Cleaning Up

For Containment: Stop leak, if possible without risk. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills and dispose of waste safely. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Asphyxiating gas at high concentrations. Pressurized container: may burst if heated. Do not pierce or burn, even after use. Do not pressurize, cut, or weld containers.

Precautions for Safe Handling: Do not breathe gas. Avoid prolonged contact with eyes, skin and clothing. Do not spray on an open flame or other ignition source. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep only in the original container in a cool, well ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Specific End Use(s)

Hair Care

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Starch (9005-25-8)		
USA ACGIH	ACGIH OEL TWA	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) [1]	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)
USA NIOSH	NIOSH REL (TWA)	10 mg/m ³ (total dust) 5 mg/m ³ (respirable dust)
Alberta	OEL TWA	10 mg/m ³
British Columbia	OEL TWA	10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction)
Manitoba	OEL TWA	10 mg/m ³
New Brunswick	OEL TWA	10 mg/m ³
Newfoundland & Labrador	OEL TWA	10 mg/m ³
Nova Scotia	OEL TWA	10 mg/m ³
Nunavut	OEL STEL	20 mg/m ³
Nunavut	OEL TWA	10 mg/m ³
Northwest Territories	OEL STEL	20 mg/m ³
Northwest Territories	OEL TWA	10 mg/m ³
Ontario	OEL TWA	10 mg/m ³
Prince Edward Island	OEL TWA	10 mg/m ³
Québec	VEMP (OEL TWA)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL	20 mg/m ³
Saskatchewan	OEL TWA	10 mg/m ³
Yukon	OEL STEL	20 mg/m ³
Yukon	OEL TWA	30 mppcf 10 mg/m ³
Ethyl alcohol (64-17-5)		
USA ACGIH	ACGIH OEL STEL [ppm]	1000 ppm
USA ACGIH	ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
USA OSHA	OSHA PEL (TWA) [1]	1900 mg/m ³
USA OSHA	OSHA PEL (TWA) [2]	1000 ppm
USA NIOSH	NIOSH REL (TWA)	1900 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	1000 ppm
USA IDLH	IDLH [ppm]	3300 ppm (10% LEL)
Alberta	OEL TWA	1880 mg/m ³
Alberta	OEL TWA [ppm]	1000 ppm
British Columbia	OEL STEL [ppm]	1000 ppm
Manitoba	OEL STEL [ppm]	1000 ppm
New Brunswick	OEL TWA	1880 mg/m ³
New Brunswick	OEL TWA [ppm]	1000 ppm
Newfoundland & Labrador	OEL STEL [ppm]	1000 ppm
Nova Scotia	OEL STEL [ppm]	1000 ppm
Nunavut	OEL STEL [ppm]	1250 ppm
Nunavut	OEL TWA [ppm]	1000 ppm
Northwest Territories	OEL STEL [ppm]	1250 ppm

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Northwest Territories	OEL TWA [ppm]	1000 ppm
Ontario	OEL STEL [ppm]	1000 ppm
Prince Edward Island	OEL STEL [ppm]	1000 ppm
Québec	VECD (OEL STEL) [ppm]	1000 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm
Saskatchewan	OEL TWA [ppm]	1000 ppm
Yukon	OEL STEL	1900 mg/m ³
Yukon	OEL STEL [ppm]	1000 ppm
Yukon	OEL TWA	1900 mg/m ³
Yukon	OEL TWA [ppm]	1000 ppm
n-Butane (106-97-8)		
USA ACGIH	ACGIH OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
USA NIOSH	NIOSH REL (TWA)	1900 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	800 ppm
USA IDLH	IDLH [ppm]	1600 ppm (>10% LEL)
Alberta	OEL TWA [ppm]	1000 ppm
British Columbia	OEL STEL [ppm]	1000 ppm (Butane, all isomers)
Manitoba	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
New Brunswick	OEL TWA	1900 mg/m ³
New Brunswick	OEL TWA [ppm]	800 ppm
Newfoundland & Labrador	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Nova Scotia	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Nunavut	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Nunavut	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Northwest Territories	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Northwest Territories	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Ontario	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, all isomers))
Prince Edward Island	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Québec	VEMP (OEL TWA)	1900 mg/m ³
Québec	VEMP (OEL TWA) [ppm]	800 ppm
Saskatchewan	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Saskatchewan	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Yukon	OEL STEL	1600 mg/m ³
Yukon	OEL STEL [ppm]	750 ppm
Yukon	OEL TWA	1400 mg/m ³
Yukon	OEL TWA [ppm]	600 ppm
Isobutane (75-28-5)		
USA ACGIH	ACGIH OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
USA NIOSH	NIOSH REL (TWA)	1900 mg/m ³
USA NIOSH	NIOSH REL TWA [ppm]	800 ppm
British Columbia	OEL STEL [ppm]	1000 ppm (Butane, all isomers)
Manitoba	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Newfoundland & Labrador	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Nova Scotia	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Nunavut	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Nunavut	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Northwest Territories	OEL STEL [ppm]	1250 ppm (Butane, all isomers)
Northwest Territories	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
Ontario	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, all isomers))
Prince Edward Island	OEL STEL [ppm]	1000 ppm (explosion hazard (Butane, isomers))
Saskatchewan	OEL STEL [ppm]	1250 ppm (Butane, all isomers)

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Saskatchewan	OEL TWA [ppm]	1000 ppm (Butane, all isomers)
--------------	---------------	--------------------------------

Exposure Controls

Appropriate Engineering Controls: For occupational/workplace settings: Suitable eye/body wash equipment should be available in the vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Use explosion-proof equipment. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Oxygen detectors should be used when asphyxiating gases may be released.

Personal Protective Equipment: For occupational/workplace settings and bulk quantities: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Respiratory protection of the dependent type.



Materials for Protective Clothing: For occupational/workplace settings: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection: For occupational/workplace settings: Wear protective gloves. If material is cold, wear thermally resistant protective gloves.

Eye Protection: For occupational/workplace settings: Chemical safety goggles.

Skin and Body Protection: For occupational/workplace settings: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Thermal Hazard Protection: Wear thermally resistant protective clothing.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Gas
Appearance	: Colorless aerosol with (Yellow, Brown, or Dark Brown) Powder
Odor	: Comparable to reference
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: No data available
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Lower Flammable Limit	: No data available
Upper Flammable Limit	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: 0.7888 (Water = 1)
Specific Gravity	: 0.7888
Solubility	: Water: Partially
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: No data available
Explosive Properties	: Contains gas under pressure; may explode if heated

SECTION 10: STABILITY AND REACTIVITY

Reactivity:

Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Chemical Stability:

Contains gas under pressure; may explode if heated. Flammable aerosol. Pressurized container: may burst if heated.

Possibility of Hazardous Reactions:

Hazardous polymerization will not occur.

Conditions to Avoid:

Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

Incompatible Materials:

Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data:

No additional information available

Skin Corrosion/Irritation: Not classified

Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: In elevated concentrations may cause asphyxiation, central nervous system effects, and increased breathing rate. Symptoms of asphyxiation include headache, dizziness, rapid breathing, increased pulse, mood changes, tremors, cyanosis, muscular weakness, narcosis, numbness of the extremities, unconsciousness and death.

Symptoms/Injuries After Skin Contact: Contact with gas escaping the container can cause frostbite and freeze burns.

Symptoms/Injuries After Eye Contact: Contact with gas escaping the container can cause frostbite, freeze burns, and permanent eye damage.

Symptoms/Injuries After Ingestion: Not considered a potential route of exposure, but contact with gas escaping the container can cause freeze burns and frostbite.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Ethyl alcohol (64-17-5)	
LD50 Oral Rat	10470 mg/kg
LD50 Dermal Rat	20 ml/kg
LC50 Inhalation Rat	124.7 mg/l/4h
n-Butane (106-97-8)	
LC50 Inhalation Rat	30957 mg/m ³ (Exposure time: 4 h)
LC50 Inhalation Rat	276798.8 ppm

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Not classified.

Ethyl alcohol (64-17-5)	
LC50 Fish 1	11200 mg/l
EC50 - Crustacea [1]	9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

ErC50 algae	1000 mg/l
NOEC Chronic Crustacea	9.6 mg/l

Persistence and Degradability

Batiste™ Hint of Color (NA GHS 2015)	
Persistence and Degradability	Not established.

Bioaccumulative Potential

Batiste™ Hint of Color (NA GHS 2015)	
Bioaccumulative Potential	Not established.

Ethyl alcohol (64-17-5)	
Log POW	-0.32

n-Butane (106-97-8)	
Log POW	2.89

Isobutane (75-28-5)	
BCF Fish 1	1.57 – 1.97
Log POW	2.88 (at 20 °C)

Mobility in Soil

No additional information available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations. Do not pierce or burn, even after use.

Additional Information: Do not puncture or incinerate container. Hazardous waste (ignitable) due to the presence of flammable liquids and gases.

Ecology - Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In Accordance with DOT

Proper Shipping Name : AEROSOLS
Hazard Class : 2.1
Identification Number : UN1950
Label Codes : 2.1
ERG Number : 126



In Accordance with IMDG

Proper Shipping Name : AEROSOLS
Hazard Class : 2.1
Identification Number : UN1950
Label Codes : 2.1
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U



In Accordance with IATA

Proper Shipping Name : AEROSOLS, FLAMMABLE
Identification Number : 2.1
Hazard Class : UN1950
Label Codes : 2.1
ERG Code (IATA) : 10L



Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

In Accordance with TDG

Proper Shipping Name : AEROSOLS
Hazard Class : 2.1
Identification Number : UN1950
Label Codes : 2.1



SECTION 15: REGULATORY INFORMATION

US Federal and International Regulations

Batiste™ Hint of Color (NA GHS 2015)	
SARA Section 311/312 Hazard Classes	Physical hazard - Gas under pressure Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Simple asphyxiant
Starch (9005-25-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on the Canadian DSL (Domestic Substances List) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory) Listed on the NCI (Vietnam - National Chemicals Inventory)	
EPA TSCA Regulatory Flag	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
Ethyl alcohol (64-17-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on the Canadian DSL (Domestic Substances List) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List) Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on NZIoC (New Zealand Inventory of Chemicals) Listed on the Japanese ISHL (Industrial Safety and Health Law) Listed on INSQ (Mexican National Inventory of Chemical Substances) Listed on the TCSI (Taiwan Chemical Substance Inventory) Listed on the NCI (Vietnam - National Chemicals Inventory)	
n-Butane (106-97-8)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active Listed on the Canadian DSL (Domestic Substances List) Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) Listed on the Canadian IDL (Ingredient Disclosure List) Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory) Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances) Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory Listed on KECL/KECI (Korean Existing Chemicals Inventory) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on the NCI (Vietnam - National Chemicals Inventory)

Isobutane (75-28-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory - Status: Active
Listed on the Canadian DSL (Domestic Substances List)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)
Listed on the NCI (Vietnam - National Chemicals Inventory)

US State Regulations

Starch (9005-25-8)

U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Ethyl alcohol (64-17-5)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

n-Butane (106-97-8)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Isobutane (75-28-5)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Canadian Regulations

Starch (9005-25-8)

Listed on the Canadian DSL (Domestic Substances List)

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

n-Butane (106-97-8)

Listed on the Canadian DSL (Domestic Substances List)

Isobutane (75-28-5)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 06/28/2022

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

Batiste™ Hint of Color (NA GHS 2015)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable to this SDS differ from the labeling requirements of the CPSC and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

GHS Full Text Phrases:

Comb. Dust	Combustible Dust
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 2	Flammable liquids Category 2
Press. Gas (Comp.)	Gases under pressure Compressed gas
Press. Gas (Liq.)	Gases under pressure Liquefied gas
Simple Asphy	Simple Asphyxiant
H220	Extremely flammable gas
H223	Flammable aerosol
H225	Highly flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H319	Causes serious eye irritation

This Product Safety Data Sheet is offered solely for your information, consideration and investigation. Church & Dwight Co., Inc. provides no warranties; either expressed or implied, and assumes no responsibility for the accuracy or completeness of data contained herein. Church & Dwight Co., Inc. urges persons receiving this information to make their own determination as to the information suitability for their particular application.

Church&Dwight NA GHS SDS 2015