



Batiste™ Touch of Gloss™ - (NA GHS 2015 - EN)

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Revision Date: 05/25/2022

Date of Issue: 10/19/2020

Supersedes Date: 07/12/2021

Version: 1.3

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: Batiste™ Touch of Gloss™ - (NA GHS 2015 - EN)

Product Code: 42014319, 42014320, 42014321

Synonyms: Champagne Sorbet, Wildberry Blossom, Coconut Crush

Intended Use of the Product

Hair Shine Spray

Name, Address, and Telephone of the Responsible Party

Company

Church & Dwight

500 Charles Ewing Blvd

Ewing Township, NJ 08628

T 1-800-524-1328

www.churchdwight.com

Emergency Telephone Number

Emergency Number : For Medical Emergency: 1-888-234-1828 (USA and Canada), 952-853-1925 (Outside USA and Canada)
For Chemical Emergency: ChemTel LLC (800)255-3924 (North America) +1 (813)248-0585 (International)

SECTION 2: HAZARDS IDENTIFICATION

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable to this SDS differ from the labeling requirements of the CPSC and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

Classification of the Substance or Mixture

GHS-US/CA Classification

Flam. Aerosol 1 H222

Press. Gas (Comp.) H280

Eye Irrit. 2 H319

Aquatic Acute 1 H400

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

Label Elements

GHS-US/CA Labeling

Hazard Pictograms (GHS-US/CA)



Signal Word (GHS-US/CA)

: Danger

Hazard Statements (GHS-US/CA)

: H222 - Extremely flammable aerosol.
H280 - Contains gas under pressure; may explode if heated.
H319 - Causes serious eye irritation.
H400 - Very toxic to aquatic life.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US/CA)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.

Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, and eye protection.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P391 - Collect spillage.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.
P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations.

Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US/CA)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| Name | Product Identifier | % * | GHS Ingredient Classification |
|---------------|--------------------|---------|---|
| Ethyl alcohol | (CAS-No.) 64-17-5 | 38 – 40 | Flam. Liq. 2, H225 Eye Irrit. 2A, H319 |

Full text of H-phrases: see section 16

*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

SECTION 4: FIRST AID MEASURES

Description of First-aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Immediately rinse with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if irritation develops or persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Obtain medical attention.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes serious eye irritation.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None known.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Water spray, fog, carbon dioxide (CO₂), alcohol-resistant foam, dry chemical, or sand.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Flammable aerosol.

Explosion Hazard: Container may explode in heat of fire. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers. Fight fire remotely due to the risk of explosion. DO NOT fight fire when fire reaches containers. Evacuate area.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Silicon oxides. Formaldehyde. Hydrocarbons.

Other Information: Do not allow run-off from fire fighting to enter drains or water courses.

Reference to Other Sections

Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid breathing (vapor, mist, spray). Avoid all contact with skin, eyes, or clothing. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protective equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel. Stop leak if safe to do so.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit. Evacuate unnecessary personnel, isolate, and ventilate area. Eliminate ignition sources.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

Methods and Materials for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Stop the source of the release, if safe to do so. Consider the use of water spray to disperse vapors. Isolate the area until gas has dispersed. Ventilate and gas test area before entering. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Pressurized container: may burst if heated. Do not pierce or burn, even after use.

Precautions for Safe Handling: Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, spray. Do not spray on an open flame or other ignition source. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.

Storage Conditions: Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Keep only in the original container in a cool, well ventilated place away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.

Incompatible Materials: Strong oxidizers. Inorganic acids. Halogens.

Specific End Use(s)

Hair Shine Spray

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

Ethyl alcohol (64-17-5)

Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | | |
|-------------------------|--------------------------------------|--|
| USA ACGIH | ACGIH STEL (ppm) | 1000 ppm |
| USA ACGIH | ACGIH chemical category | Confirmed Animal Carcinogen with Unknown Relevance to Humans |
| USA OSHA | OSHA PEL (TWA) (mg/m ³) | 1900 mg/m ³ |
| USA OSHA | OSHA PEL (TWA) (ppm) | 1000 ppm |
| USA NIOSH | NIOSH REL (TWA) (mg/m ³) | 1900 mg/m ³ |
| USA NIOSH | NIOSH REL (TWA) [ppm] | 1000 ppm |
| USA IDLH | US IDLH (ppm) | 3300 ppm (10% LEL) |
| Alberta | OEL TWA (mg/m ³) | 1880 mg/m ³ |
| Alberta | OEL TWA (ppm) | 1000 ppm |
| British Columbia | OEL STEL (ppm) | 1000 ppm |
| Manitoba | OEL STEL (ppm) | 1000 ppm |
| New Brunswick | OEL TWA (mg/m ³) | 1880 mg/m ³ |
| New Brunswick | OEL TWA (ppm) | 1000 ppm |
| Newfoundland & Labrador | OEL STEL (ppm) | 1000 ppm |
| Nova Scotia | OEL STEL (ppm) | 1000 ppm |
| Nunavut | OEL STEL (ppm) | 1250 ppm |
| Nunavut | OEL TWA (ppm) | 1000 ppm |
| Northwest Territories | OEL STEL (ppm) | 1250 ppm |
| Northwest Territories | OEL TWA (ppm) | 1000 ppm |
| Ontario | OEL STEL (ppm) | 1000 ppm |
| Prince Edward Island | OEL STEL (ppm) | 1000 ppm |
| Québec | VECD (ppm) | 1000 ppm |
| Saskatchewan | OEL STEL (ppm) | 1250 ppm |
| Saskatchewan | OEL TWA (ppm) | 1000 ppm |
| Yukon | OEL STEL (mg/m ³) | 1900 mg/m ³ |
| Yukon | OEL STEL (ppm) | 1000 ppm |
| Yukon | OEL TWA (mg/m ³) | 1900 mg/m ³ |
| Yukon | OEL TWA (ppm) | 1000 ppm |

Exposure Controls

Appropriate Engineering Controls: For occupational/workplace settings: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Use explosion-proof equipment. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed.

Personal Protective Equipment: For occupational/workplace settings and bulk quantities: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing: For occupational/workplace settings: Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing.

Hand Protection: For occupational/workplace settings: Wear protective gloves.

Eye Protection: For occupational/workplace settings: Chemical safety goggles.

Skin and Body Protection: For occupational/workplace settings: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State : Liquid

Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

| | |
|--|--|
| Appearance | : Clear |
| Odor | : Not available |
| Odor Threshold | : Not available |
| pH | : 6.34 – 6.76 |
| Evaporation Rate | : Not available |
| Melting Point | : Not available |
| Freezing Point | : Not available |
| Boiling Point | : Not available |
| Flash Point | : Not available |
| Auto-ignition Temperature | : Not available |
| Decomposition Temperature | : Not available |
| Flammability (solid, gas) | : Not applicable |
| Lower Flammable Limit | : Not available |
| Upper Flammable Limit | : Not available |
| Vapor Pressure | : Not available |
| Relative Vapor Density at 20°C | : Not available |
| Relative Density | : Not available |
| Specific Gravity | : Not available |
| Solubility | : Not available |
| Partition Coefficient: N-Octanol/Water | : Not available |
| Viscosity | : Not available |
| Explosive Properties | : Contains gas under pressure; may explode if heated |
| Heat of Combustion | : 35.5673 - 35.6051 kJ/g |

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Reacts violently with strong oxidizers. Increased risk of fire or explosion.

Chemical Stability: Flammable aerosol. Contains gas under pressure; may explode if heated. Pressurized container: may burst if heated.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.

Incompatible Materials: Strong oxidizers. Inorganic acids. Halogens.

Hazardous Decomposition Products: Not expected to decompose under ambient conditions. Thermal decomposition may produce: Carbon oxides (CO, CO₂). Silicon oxides. Formaldehyde. Hydrocarbons.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity (Oral): Not classified

Acute Toxicity (Dermal): Not classified

Acute Toxicity (Inhalation): Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified (pH: 6.34 – 6.76)

Eye Damage/Irritation: Causes serious eye irritation. (pH: 6.34 – 6.76)

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Contact causes severe irritation with redness and swelling of the conjunctiva.

Symptoms/Injuries After Ingestion: Ingestion may cause adverse effects.

Chronic Symptoms: None known.

Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

| | |
|-------------------------|-----------------------------|
| Ethyl alcohol (64-17-5) | |
| LD50 Oral Rat | 10470 mg/kg |
| LD50 Dermal Rat | 20 ml/kg |
| LC50 Inhalation Rat | 124.7 mg/l/4h |
| ATE US/CA (dermal) | 15,780.00 mg/kg body weight |

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

| | |
|-------------------------|--|
| Ethyl alcohol (64-17-5) | |
| LC50 Fish 1 | 11200 mg/l |
| EC50 Daphnia 1 | 9268 – 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna) |
| LC50 Fish 2 | > 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static]) |
| ErC50 (algae) | 1000 mg/l |
| NOEC Chronic Crustacea | 9.6 mg/l |

Persistence and Degradability

| | |
|-------------------------------|---|
| Batiste™ Touch of Gloss™ | |
| Persistence and Degradability | May cause long-term adverse effects in the environment. |

Bioaccumulative Potential

| | |
|---------------------------|------------------|
| Batiste™ Touch of Gloss™ | |
| Bioaccumulative Potential | Not established. |
| Ethyl alcohol (64-17-5) | |
| Log POW | -0.32 |

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations, Do not pierce or burn, even after use

Additional Information: Hazardous waste due to pressurized container. Hazardous waste (ignitable) due to the presence of flammable liquids and gases.

Ecology - Waste Materials: Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

In Accordance with DOT

Proper Shipping Name : AEROSOLS
Hazard Class : 2.1
Identification Number : UN1950
Label Codes : 2.1
Marine Pollutant : Marine pollutant
ERG Number : 126



In Accordance with IMDG

Proper Shipping Name : AEROSOLS
Hazard Class : 2.1
Identification Number : UN1950
Label Codes : 2.1
EmS-No. (Fire) : F-D
EmS-No. (Spillage) : S-U



Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Marine pollutant : Marine pollutant

In Accordance with IATA

Proper Shipping Name : AEROSOLS, FLAMMABLE

Identification Number : 2.1

Hazard Class : UN1950

Label Codes : 2.1

ERG Code (IATA) : 10L



In Accordance with TDG

Proper Shipping Name : AEROSOLS

Hazard Class : 2.1

Identification Number : UN1950

Label Codes : 2.1

Marine Pollutant (TDG) : Marine pollutant



SECTION 15: REGULATORY INFORMATION

US Federal and International Regulations

Batiste™ Touch of Gloss™

SARA Section 311/312 Hazard Classes

Physical hazard - Gas under pressure

Physical hazard - Flammable (gases, aerosols, liquids, or solids)

Health hazard - Serious eye damage or eye irritation

Ethyl alcohol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on KECL/KECI (Korean Existing Chemicals Inventory)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on the TCSI (Taiwan Chemical Substance Inventory)

US State Regulations

Ethyl alcohol (64-17-5)

U.S. - Massachusetts - Right To Know List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

Ethyl alcohol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Date of Preparation or Latest Revision : 05/25/2022

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

Batiste™ Touch of Gloss™

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

This product is labeled in accordance with regulations administered by the Consumer Product Safety Commission (CPSC). The use pattern and exposure in the workplace are generally not consistent with those experienced by consumers. The requirements of the Occupational Safety and Health Administration applicable to this SDS differ from the labeling requirements of the CPSC and, as a result, this SDS may contain additional health hazard information not pertinent to consumer use and not found on the product label.

GHS Full Text Phrases:

| | |
|--------------------|--|
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Eye Irrit. 2 | Serious eye damage/eye irritation Category 2 |
| Eye Irrit. 2A | Serious eye damage/eye irritation Category 2A |
| Flam. Aerosol 1 | Flammable aerosol Category 1 |
| Flam. Liq. 2 | Flammable liquids Category 2 |
| Press. Gas (Comp.) | Gases under pressure Compressed gas |
| H222 | Extremely flammable aerosol |
| H225 | Highly flammable liquid and vapor |
| H280 | Contains gas under pressure; may explode if heated |
| H319 | Causes serious eye irritation |
| H400 | Very toxic to aquatic life |
| H411 | Toxic to aquatic life with long lasting effects |

This Product Safety Data Sheet is offered solely for your information, consideration and investigation. Church & Dwight Co., Inc. provides no warranties; either expressed or implied, and assumes no responsibility for the accuracy or completeness of data contained herein. Church & Dwight Co., Inc. urges persons receiving this information to make their own determination as to the information suitability for their particular application.

Church&Dwight NA GHS SDS 2015