# SAFETY DATA SHEET



# **Section 1. Identification**

**GHS** product identifier : CITGO HyDurance AW CP Fluid

**Synonyms** : Hydraulic Oil Code : 633623001

## Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

Supplier's details : CITGO Petroleum Corporation

> P.O. Box 4689 Houston, TX 77210 sdsvend@citgo.com

**Emergency telephone** number (with hours of

operation)

: Technical Contact: (800) 248-4684 Medical Emergency: (832) 486-4700 CHEMTREC Emergency: (800) 424-9300

(United States Only)

# Section 2. Hazards identification

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : Not classified.

#### **GHS** label elements

Signal word : No signal word.

**Hazard statements** : No known significant effects or critical hazards.

**Precautionary statements** 

General **Prevention**  : Keep out of reach of children.

: Do not get in eyes, on skin, or on clothing.

Response

: Wash with plenty of soap and water or use a recognized skin cleanser.

**Storage** 

: Store in accordance with all local, regional, national and international regulations. Store in a dry place and a closed container. Empty containers may contain material residues which can ignite with explosive force. Misuse of empty containers can be dangerous if used to store toxic, flammable, or reactive materials. Cutting or welding of empty containers can cause fire, explosion, or release of toxic fumes from residues. Do not pressurize or expose empty containers to open flame, sparks, or heat. Keep container closed and drum bungs in place. All label warnings and precautions must be observed. Return empty drums to a qualified reconditioner. Consult appropriate federal, state and local authorities before reusing, reconditioning, reclaiming, recycling, or disposing of empty containers and/or waste residues of this material.

**Disposal** 

Dispose of contents and container in accordance with all local, regional, national and international regulations. Don't Pollute. Conserve Resources. Return used oil to collection centers.

Hazards not otherwise classified

: Injection of pressurized hydrocarbons can cause severe permanent tissue damage. Initial symptoms may be minor. Injection of petroleum hydrocarbons requires immediate medical attention.

Date of issue/Date of revision Date of previous issue Version: 14.01 1/12 : 4/28/2025 : 11/7/2024

# Section 3. Composition/information on ingredients

Substance/mixture
Other means of
identification

: Mixture: Hydraulic Oil

### **CAS** number/other identifiers

**CAS number** : Not applicable.

Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated heavy naphthenic	≥50 - ≤75	64742-52-5
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≥50 - ≤75	72623-87-1
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	64742-54-7
Paraffin oils (petroleum), catalytic dewaxed light	≥10 - ≤25	64742-71-8
Distillates, petroleum, hydrotreated, light naphthenic	≥10 - ≤25	64742-53-6

<sup>\* =</sup> Various \*\* = Mixture \*\*\* = Proprietary

Any concentration shown as a range is to protect confidentiality or is due to process variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

## **Description of necessary first aid measures**

**Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Get medical attention if irritation

occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get

medical attention if symptoms occur.

**Skin contact**: Flush contaminated skin with plenty of water. Remove contaminated clothing and

shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. Remove victim to fresh air and keep at rest in a position

comfortable for breathing. Do not induce vomiting unless directed to do so by medical

personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

# Potential acute health effects

**Eye contact** : No known significant effects or critical hazards.

**Inhalation** : No known significant effects or critical hazards.

**Skin contact**: Injection of pressurized hydrocarbons can cause severe permanent tissue damage.

Initial symptoms may be minor.

**Ingestion**: No known significant effects or critical hazards.

### **Over-exposure signs/symptoms**

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In the event of injection in underlying tissue, immediate treatment should include

extensive incision, debridement and saline irrigation. Inadequate treatment can result in

ischemia and gangrene. Early symptoms may be minimal.

**Specific treatments**: Treat symptomatically and supportively.

**Protection of first-aiders**: No action shall be taken involving any personal risk or without suitable training.

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 2/12

# Section 4. First aid measures

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

# **Extinguishing media**

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

# Specific hazards arising from the chemical

decomposition products

**Hazardous thermal** 

: In a fire or if heated, a pressure increase will occur and the container may burst.

 Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides phosphorus oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 3/12

# Section 7. Handling and storage

## **Precautions for safe handling**

**Protective measures** 

Advice on general occupational hygiene

- Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

> Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

# Section 8. Exposure controls/personal protection

### **Control parameters**

Occupational exposure limits

Ingredient name	Exposure limits
Distillates (petroleum), hydrotreated heavy naphthenic	OSHA PEL (United States, 5/2018). [Oil mist, mineral]  TWA: 5 mg/m³ 8 hours.  ACGIH TLV (United States, 1/2023).  [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]  TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]  TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist ACGIH TLV (United States).  TWA: 5 mg/m  OSHA PEL (United States).  TWA: 5 mg/m³
Distillates (petroleum), hydrotreated heavy paraffinic	OSHA PEL (United States, 5/2018). [Oil mist, mineral]  TWA: 5 mg/m³ 8 hours.  ACGIH TLV (United States, 1/2023).  [Mineral Oil, pure, highly and severely refined]  TWA: 5 mg/m³ 8 hours. Form: Inhalable fraction  NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]  TWA: 5 mg/m³ 10 hours. Form: Mist
Paraffin oils (petroleum), catalytic dewaxed light	STEL: 10 mg/m³ 15 minutes. Form: Mist ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely

Date of issue/Date of revision **Version** : 14.01 4/12 : 4/28/2025 Date of previous issue : 11/7/2024

# Section 8. Exposure controls/personal protection

Distillates, petroleum, hydrotreated, light naphthenic

refined

TWA: 5 mg/m³ 8 hours. Form: Inhalable

fraction

NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist OSHA PEL (United States, 5/2018). [Oil

mist, mineral]

TWA: 5 mg/m<sup>3</sup> 8 hours.

OSHA PEL (United States, 5/2018). [Oil

mist, mineral]

TWA: 5 mg/m<sup>3</sup> 8 hours.

ACGIH TLV (United States, 1/2023). [Mineral Oil, pure, highly and severely refined]

TWA: 5 mg/m³ 8 hours. Form: Inhalable

fraction

NIOSH REL (United States, 10/2020). [OIL MIST MINERAL]

TWA: 5 mg/m³ 10 hours. Form: Mist STEL: 10 mg/m³ 15 minutes. Form: Mist

Appropriate engineering controls

Environmental exposure controls

- : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
- : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Hygiene measures** 

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Avoid skin contact with liquid. Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Leather boots are not protective for liquid contact.

**Respiratory protection** 

: Avoid inhalation of gases, vapors, mists or dusts. Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 5/12

# Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

Physical state : Liquid.

Color : Blue-Green

Odor : Mild petroleum odor pH : Not available.

Boiling point, initial boiling point, and boiling range

: Not available.

Flash point

: Open cup: 180°C (356°F) [Cleveland]

Lower and upper explosive

(flammable) limits

: Not available.

Vapor pressure

: <0.013 kPa (<0.1 mm Hg)

Relative vapor density

: Not available.

Relative density

: 0.87

Density lbs/gal

7.25 lbs/galNot available.

Density gm/cm<sup>3</sup> Gravity, °API

: 31

**Auto-ignition temperature** 

: Not available.

Viscosity

: Kinematic (40°C (104°F)): 25 mm²/s (25 cSt)

Viscosity SUS

: 125 SUS @100 F

Flow time (ISO 2431)

: Not available.

Particle characteristics

Median particle size

: Not applicable.

# Section 10. Stability and reactivity

**Reactivity**: Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide

under US GHS Definition(s).

**Chemical stability**: The product is stable.

**Possibility of hazardous** 

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : No specific data.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition products should

not be produced.

# Section 11. Toxicological information

Information on toxicological effects

**Acute toxicity** 

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 6/12

# Section 11. Toxicological information

Product/ingredient name	Result	Species	Dose	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	LD50 Oral	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates (petroleum), hydrotreated heavy paraffinic	LD50 Dermal	Rat	>5000 mg/kg	-
	LD50 Oral	Rat	>5000 mg/kg	-
Distillates, petroleum, hydrotreated, light naphthenic	LD50 Oral	Rat	>5000 mg/kg	-

### **Conclusion/Summary**

Distillates (petroleum), hydrotreated heavy naphthenic: Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. Distillates (petroleum), hydrotreated heavy paraffinic: Mineral oil mists derived from highly refined oils are reported to have low acute and sub-acute toxicities in animals. Effects from single and short-term repeated exposures to high concentrations of mineral oil mists well above applicable workplace exposure levels include lung inflammatory reaction, lipoid granuloma formation and lipoid pneumonia. In acute and sub-acute studies involving exposures to lower concentrations of mineral oil mists at or near current work place exposure levels produced no significant toxicological effects. Distillates (petroleum), hydrotreated light naphthenic: INHALATION (LC50) Acute: 9.6 mg/L (Female Rat).

INHALATION (LC50) Acute: 10.5 mg/L (Male Rat).
DRAIZE EYE Acute: Non-irritating (Rabbit).
DRAIZE DERMAL Acute: Mild skin irritant (Rabbit).
BUEHLER DERMAL Acute: Non-sensitizing (Guinea Pig).

28-Day DERMAL Sub-Chronic: Mild to moderate skin irritant (Rabbit & Rat).

A life-time dermal application of severely hydrotreated light naphthenic oils produced skin masses on mice which correlated with the skin irritation response levels of the test animals. Additional studies attribute these masses to a weak promotional activity. These studies indicate that light naphthenic oils are not mutagenic, tumor initiators nor complete chemical carcinogens. These materials have not been determined to be carcinogenic by IARC, NTP or OSHA.

### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Distillates, petroleum, hydrotreated, light naphthenic		Rabbit		24 hours 0.5 MI	-

Skin : No additional information.Eyes : No additional information.Respiratory : No additional information.

Sensitization

Not available.

Obia

Skin: No additional information.Respiratory: No additional information.

Mutagenicity
Not available.

**Conclusion/Summary**: No additional information.

### Carcinogenicity

Not available.

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 7/12

CITGO HyDurance AW CP Fluid

# Section 11. Toxicological information

Conclusion/Summary

: No additional information.

Reproductive toxicity

Not available.

**Conclusion/Summary** 

: No additional information.

Teratogenicity

Not available.

**Conclusion/Summary**: No additional information.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

# **Aspiration hazard**

Name	Result
Distillates, petroleum, hydrotreated, light naphthenic	ASPIRATION HAZARD - Category 1

Information on the likely

: Not available.

routes of exposure

Potential acute health effects

Eye contactInhalationNo known significant effects or critical hazards.No known significant effects or critical hazards.

**Skin contact** : Injection of pressurized hydrocarbons can cause severe permanent tissue damage.

Initial symptoms may be minor.

**Ingestion** : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

## Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 8/12

# Section 11. Toxicological information

# **Numerical measures of toxicity**

**Acute toxicity estimates** 

N/A

# **Section 12. Ecological information**

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Distillates (petroleum), hydrotreated heavy naphthenic	Acute EC50 >10000 mg/l Fresh water	Daphnia - Daphnia magna	48 hours
·	Acute LC50 >100 mg/l Fresh water Acute NOEL >100 mg/l Fresh water	Fish - Pimephales promelas Algae - Pseudokirchneriella subcapitata	96 hours 72 hours

Conclusion/Summary

: Not available.

### Persistence and degradability

**Conclusion/Summary**: Not available.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy naphthenic	-	-	Inherent

# **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
Distillates (petroleum), hydrotreated heavy naphthenic	>6	-	high

## **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

### Other adverse effects

: No known significant effects or critical hazards.

# Section 13. Disposal considerations

### **Disposal methods**

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 9/12

# **Section 14. Transport information**

	DOT Classification	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class(es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according: Not available.

to IMO instruments

# Section 15. Regulatory information

U.S. Federal regulations

**United States inventory (TSCA 8b)**: All components are active or exempted. Clean Water Act (CWA) 307: zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate);

toluene; chrysene; naphthalene; benzene

Clean Water Act (CWA) 311: toluene; naphthalene; benzene

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

### **SARA 302/304**

**Composition/information on ingredients** 

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

: HNOC - Injection Hazards Classification

Composition/information on ingredients

Name	%	Classification
Distillates, petroleum, hydrotreated, light naphthenic		ASPIRATION HAZARD - Category 1 HNOC - Injection Hazards

# **SARA 313**

	Product name	CAS number	%
Supplier notification	chrysene	218-01-9	<0.001

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

# **State regulations**

CITGO HyDurance AW CP Fluid

# Section 15. Regulatory information

: The following components are listed: OIL MIST, MINERAL; OIL MIST, MINERAL; **Massachusetts** 

MINERAL OIL, PETROLEUM PARAFFIN OILS, CATALYTIC DEWAXED LIGHT;

MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT NAPHTHENIC

**New York** : None of the components are listed.

The following components are listed: MINERAL OIL (UNTREATED and MILDLY **New Jersey** 

TREATED)

**Pennsylvania** : None of the components are listed.

### California Prop. 65 Clear and Reasonable Warnings (2018)

MARNING: This product can expose you to chemicals including Ethyl acrylate, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Ingredient name	%	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
toluene	<0.1	No.	Yes.	-	Yes.
ethyl acrylate	<0.001	Yes.	No.	-	-
2-ethylhexyl acrylate	<0.001	Yes.	No.	-	-
chrysene	<0.001	Yes.	No.	Yes.	-
naphthalene	<0.0001	Yes.	No.	Yes.	-
benzene	trace	Yes.	Yes.	Yes.	Yes.

### **International regulations**

# Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

# Inventory list

**United States** : All components are active or exempted.

**Australia** : Not determined.

Canada : All components are listed or exempted.

China : Not determined.

**Japan** Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

Malaysia : Not determined **New Zealand** : Not determined. **Philippines** : Not determined. Republic of Korea : Not determined. **Taiwan** : Not determined. **Thailand** : Not determined. **Turkey** : Not determined. : Not determined. **Viet Nam** 

# Section 16. Other information

## **National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Date of issue/Date of revision : 4/28/2025 Version: 14.01 Date of previous issue : 11/7/2024 11/12

# Section 16. Other information

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

## Procedure used to derive the classification

Classification	Justification
Not classified.	

### **History**

Date of printing : 4/28/2025 Date of issue/Date of : 4/28/2025

revision

Date of previous issue : 11/7/2024 Version : 14.01

**Key to abbreviations** : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

THE INFORMATION IN THIS SAFETY DATA SHEET (SDS) WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS OR ACCURACY. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS SDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS SDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE OR APPLICATION.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND/OR DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR ANY LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

CITGO is a registered trademark of CITGO Petroleum Corporation

Date of issue/Date of revision : 4/28/2025 Date of previous issue : 11/7/2024 Version : 14.01 12/12