

CITRISTRIP® Paint & Varnish Stripping Gel is easy to use because it stays wet and active for 24 hours allowing stripping of multiple layers in one step. It removes five layers of dried latex paint in under one hour and is safe for indoor use. This special orange stripper has a citrus scent. Use CITRISTRIP® to remove multiple layers of dried latex and oil-based paint, varnish, lacquer, polyurethane and shellac from wood, metal and masonry surfaces. 64 oz. covers 12 sq. ft.

DIRECTIONS FOR USE:

1. Protect hands with chemical-resistant gloves and eyes with chemical splash goggles.
2. Shake well. Pour into a container and apply a heavy coat (1/16" thick) with a paint brush.
3. After 30 minutes (24 hours as long as formula remains wet), scrape a small test area to see if finish is ready for removal. For overnight stripping, after applying, cover application with plastic until ready to scrape. Gently scrape in direction of wood grain with a plastic stripping tool. For stubborn areas, use an abrasive stripping pad dipped into CITRISTRIP®. A toothbrush, toothpick or stripping brush will help remove old finish buried in recesses.
4. Use a clean abrasive pad dipped in After Wash or Odorless Mineral Spirits to loosen remaining finish and remove any residue. Surface should be completely clean and dry before refinishing.

Helpful Tips: Test in an inconspicuous area before use on any synthetic surface as strippers can damage these surfaces. Do not use on fiberglass, plastic or vinyl. May discolor aluminum. For best results, use in temperatures between 65° and 85°F and away from strong breeze and hot sun. Protect surrounding areas with a heavy plastic drop cloth.

WARNING. CAUSES SERIOUS EYE IRRITATION. SKIN IRRITANT. Contains Benzyl Alcohol, Hydrocarbons, Phosphoric Acid. Do not mix with any other product. Avoid contact with eyes and prolonged contact with skin. Do not swallow. Contains a bittering agent to discourage accidental swallowing. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area.

FIRST AID: IN CASE OF EYE CONTACT, immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes. Seek medical attention. **IN CASE OF SKIN CONTACT,** flush thoroughly with water for 15 minutes. If irritation persists, get medical attention. Remove any contaminated clothing and wash before reuse. **IF SWALLOWED,** do not induce vomiting. Call the Poison Control Center at 1-800-222-1222 and get immediate medical attention.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Remover • **Max VOC:** 50%

For assistance call:
The Barr Help Line 844-969-1376, Monday - Friday, 8:00am - 4:30pm CT

Consejos útiles: Pruebe en un área discreta antes de usar en cualquier superficie sintética que los decapantes puedan dañar. No lo utilice en fibra de vidrio, plástico ni en vinilo. Para obtener mejores resultados, utilícelo en temperaturas entre los 65 °F y 85 °F (18 °C y 29 °C) y manténgalo lejos de la brisa fuerte y la luz directa del sol. Proteja las áreas circundantes con una lona gruesa.

¡PELIGRO! PROVOCA QUEMADURAS. EVITE EL CONTACTO CON LA PIEL, LOS OJOS Y LAS MEMBRANAS MUCOSAS. Contiene 2-(2-aminoeto)etanol. No mezcle con ningún otro producto. Evite el contacto con los ojos y el contacto prolongado con la piel. No ingerir. Contiene una sustancia amarga para desalentar la ingestión accidental. Si se utiliza bajo techo, abra todas las ventanas y las puertas y mantenga una ventilación cruzada de aire fresco en movimiento a través del área de trabajo.

PRIMEROS AUXILIOS: EN CASO DE CONTACTO CON LA PIEL, lave inmediatamente con jabón y agua. Si persiste la irritación, busque atención médica. **EN CASO DE CONTACTO CON LOS OJOS,** enjuague inmediatamente con agua, quítese los lentes de contacto en caso de llevarlos; y continúe enjuagando con agua durante al menos 15 minutos. Si persiste la irritación, solicite atención médica. **EN CASO DE INGESTIÓN,** llame al centro de control toxicológico (1-800-222-1222), a la sala de emergencias de un hospital o a un médico para recibir más instrucciones.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

Categoría de producto: Removedor de pintura
COV máx.: 50%

**25%
FASTER
STRIPPING**

**Citrus
Scent**

CITRISTRIP

**PAINT & VARNISH
STRIPPING GEL**

STILL NO HARSH FUMES

**Removes Multiple Layers
of Dried Latex
& Oil-Based Paint**



Learn More!



WARNING. CAUSES SERIOUS EYE IRRITATION. SKIN IRRITANT. Read entire label prior to use or storage.

¡PELIGRO! CAUSA SERIA IRRITACION DE LOS OJOS. IRRITANTE DE LA PIEL. Lea toda la etiqueta antes de usar o almacenar este producto.

**64 FL OZ
(1.893 L)**

INSTRUCCIONES DE USO:

1. Proteja sus manos con guantes resistentes a productos químicos y sus ojos con gafas protectoras contra productos químicos.
2. Agítese bien. Vierta en un contenedor y aplique con una brocha.
3. Después de 30 minutos (hasta por 24 horas), raspe una pequeña área de prueba para ver si el acabado está listo para removerse. Para obtener el decapado durante la noche, después de aplicar, cubra la aplicación con plástico hasta que esté lista para raspar. Raspe lentamente en la dirección de la fibra de la madera con una herramienta para desmontar de plástico. Para las áreas difíciles utilice una fibra abrasiva empapada con CITRISTRIP®. Un cepillo de dientes, un palillo o un cepillo con cerdas de metal ayudará a eliminar el acabado viejo de los recovecos.
4. Utilice una almohadilla abrasiva limpia bañada en After Wash o en aguarrás mineral inodoro para aflojar el acabado restante y remover cualquier residuo. La superficie debe estar completamente limpia y seca antes de aplicar el nuevo acabado.



©2024
Sold by W.M. Barr & Co. Inc.
Memphis, TN 38113
www.citristrip.com

HCSG803 / J11034

