

# Safety Data Sheet

Australia

Section 1. Identification

HiLoad™ 16/600 Superose™ 6 pg [120 mL] **Product name** 

Catalogue Number 29323952

Product type Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Laboratory chemicals Liquid chromatography.

Scientific research and development

Company details

Manufacturer

Cytiva Amersham Place Little Chalfont Buckinghamshire

HP7 9NA United Kingdom +44 1494 508000

Global Life Sciences Solutions Australia Pty Ltd

495 Blackburn Road Mount Waverley VIC 3149

Australia

Supplier

tfn: 1800 150 522

000 and +61 2 9846 4000 **Emergency telephone number** 

Section 2. Hazard(s) identification

FLAMMABLE LIQUIDS - Category 3 Classification of the substance

or mixture SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A

**GHS label elements** 

**Hazard pictograms** 





**WARNING** Signal word

**Hazard statements** Flammable liquid and vapour. Causes serious eye irritation.

**Precautionary statements** 

Prevention Wear eye or face protection: Recommended: safety glasses with side-shields. Keep away from

heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and Response

easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national and international

regulations.

Supplemental label elements Not applicable.

Article Number 29323952



Validation date 29 September 2025

Page: 1/9

Other hazards which do not

None known

result in classification

## Section 3. Composition and ingredient information

Substance/mixture Mixture Other means of identification Not available.

Ingredient name % (w/w) Identifiers CAS: 64-17-5 ethanol 14 - 19

EC: 200-578-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

The total concentration of ingredients in this product, reported or not in this section, is 100%.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

### Description of necessary first aid measures

Eye contact Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check

for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing,

if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen

tight clothing such as a collar, tie, belt or waistband.

Skin contact Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get

medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before

Ingestion Wash out mouth with water. Remove dentures if any. If material has been swallowed and the

exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or

waistband.

# Most important symptoms/effects, acute and delayed

## Potential acute health effects

Eye contact Causes serious eye irritation.

Inhalation No known significant effects or critical hazards. No known significant effects or critical hazards. Skin contact Ingestion No known significant effects or critical hazards.

## Over-exposure signs/symptoms

Eye contact Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation No specific data. Skin contact No specific data. Ingestion No specific data.

## Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities have

been ingested or inhaled.

No specific treatment. Specific treatments

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. It may be

dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Firefighting measures

### **Extinguishing media**

Suitable extinguishing media

Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising from

the chemical

Flammable liquid and vapour. Runoff to sewer may create fire or explosion hazard. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent

explosion.

Hazardous thermal decomposition products Decomposition products may include the following materials:

carbon dioxide carbon monoxide

Special protective actions for

fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

For non-emergency personnel No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosionproof equipment. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosionproof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

# Section 7. Handling and storage

# Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities Store between the following temperatures: 4 to 30°C (39.2 to 86°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

# Section 8. Exposure controls and personal protection

## **Control parameters**

## Occupational exposure limits

Ingredient name

ethanol Safe Work Australia (Australia, 1/2024)

TWA 8 hours: 1880 mg/m3. TWA 8 hours: 1000 ppm.

**Exposure limits** 

Biological exposure indices

No exposure indices known.

Appropriate engineering controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations

below any lower explosive limits. Use explosion-proof ventilation equipment.

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

Wash hands, forearms and face thoroughly after handling chemical products, before eating, Hygiene measures

smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk assessment

indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree

of protection: chemical splash goggles. Recommended: safety glasses with side-shields

Skin protection

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn at all

times when handling chemical products if a risk assessment indicates this is necessary.

Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. 1 - 4 hours

(breakthrough time): butyl rubber, neoprene

**Body protection** Personal protective equipment for the body should be selected based on the task being performed

and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Recommended: lab coat

Other skin protection Appropriate footwear and any additional skin protection measures should be selected based on the

task being performed and the risks involved and should be approved by a specialist before handling

this product.

Respiratory protection Based on the hazard and potential for exposure, select a respirator that meets the appropriate

standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: A respirator is

not needed under normal and intended conditions of product use.

# Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

**Appearance** 

Physical state Liquid.

Colour White. White to yellowish. Alcohol-like. [Slight] Odour

Odour threshold 180 ppm

рΗ 5.5 to 8.5 [Conc. (% w/w): 100%]

Melting point/freezing point **Boiling point or initial boiling** 

point and boiling range

Not available. Not available

Flash point Closed cup: 38 to 43°C (100.4 to 109.4°F)

**Burning time** Not applicable. **Burning rate** Not applicable. Not available. **Evaporation rate** Not available. **Flammability** Lower and upper explosive

(flammable) limits

Not available.

HiLoad™ 16/600 Superose™ 6 pg [120 mL] 29323952 Vapour pressure Not available Vapour Pressure at 20°C Vapour pressure at 50°C Ingredient name kPa mm Hg Method kPa Method mm Ha ethanol 42.94865 5.7 water 17.5 2.3 0 0 Agarose Relative vapour density Not available. Relative density Not available. Solubility(ies) Media Result cold water Easily soluble hot water Easily soluble Solubility in water Not available.

Miscible with water

Partition coefficient: n-octanol/

water

Not applicable.

**Auto-ignition temperature** Not available.

Ingredient name °C °F Method ethanol 455 851 DIN 51794

**Decomposition temperature** Not available. SADT Not available.

Viscosity Dynamic (room temperature): Not available.

Kinematic (room temperature): Not available. Kinematic (40°C (104°F)): Not available.

Flow time (ISO 2431) Not available.

**Particle characteristics** 

Median particle size Not applicable.

# Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or its ingredients.

Chemical stability The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid Avoid all possible sources of ignition (spark or flame). Do not pressurise, cut, weld, braze, solder,

drill, grind or expose containers to heat or sources of ignition.

Incompatible materials Reactive or incompatible with the following materials:

oxidising materials

Hazardous decomposition

products

Under normal conditions of storage and use, hazardous decomposition products should not be

produced.

# Section 11. Toxicological information

# Information on toxicological effects

**Acute toxicity** 

Product/ingredient name Result ethanol Rat - Oral - LD50 7060 mg/kg

Toxic effects: Lung, Thorax, or Respiration - Other changes

Rat - Inhalation - LC50 Vapour

124700 mg/m3 [4 hours]

Conclusion/Summary

[Product]

Not available.

# Skin corrosion/irritation

Not available

Conclusion/Summary

[Product]

Repeated exposure may cause skin dryness or cracking.

# Serious eye damage/eye irritation

Not available.

Conclusion/Summary

Not available.

[Product]

Article Number 29323952 Page: 5/9

## Respiratory corrosion/irritation

Not available.

Conclusion/Summary

[Product]

Not available.

## Respiratory or skin sensitization

Not available.

Skin

Conclusion/Summary

Not available.

[Product]

Respiratory

Conclusion/Summary

[Product]

Not available.

Germ cell mutagenicity

Not available.

Conclusion/Summary

[Product]

Not available.

Carcinogenicity

Not available.

Conclusion/Summary

[Product]

Not available.

Reproductive toxicity

Not available.

Conclusion/Summary

[Product]

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes of

exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

Potential acute health effects

**Eye contact** Causes serious eye irritation.

InhalationNo known significant effects or critical hazards.Skin contactNo known significant effects or critical hazards.IngestionNo known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** Adverse symptoms may include the following:

pain or irritation watering

redness

InhalationNo specific data.Skin contactNo specific data.



Ingestion

No specific data

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate effects Not available. Potential delayed effects Not available

Long term exposure

Potential immediate effects Not available. Potential delayed effects Not available.

Potential chronic health effects

Not available.

Conclusion/Summary

[Product]

Not available.

General No known significant effects or critical hazards. Carcinogenicity No known significant effects or critical hazards. Mutagenicity No known significant effects or critical hazards. Reproductive toxicity No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

**Acute toxicity estimates** 

Product/ingredient name Oral (mg/ Dermal Inhalation Inhalation Inhalation kg) (mg/kg) (gases) (vapours) (dusts and (ppm) (mg/l) mists) (mg/l) ethanol 7000 N/A N/A 124.7 N/A

Other information

Adverse symptoms include the following: kidney abnormalities, liver abnormalities Adverse symptoms may include the following: central nervous system depression

# Section 12. Ecological information

# **Toxicity**

Product/ingredient name

ethanol

Result

Acute - LC50 - Marine water Fish - Bleak - Alburnus alburnus

Size: 8 to 10 cm 11 g/l [96 hours] Effect: Mortality

Chronic - NOEC - Marine water Algae - Green algae - Ulva pertusa

4.995 mg/l [96 hours] Effect: Reproduction Acute - EC50 - Fresh water

Crustaceans - Ostracod - Cypris subglobosa

1074 mg/l [48 hours] Effect: Intoxication

Chronic - NOEC - Fresh water

Daphnia - Water flea - Daphnia magna - Neonate

Age: <24 hours 100 µl/l [21 days] Effect: Mortality

Acute - EC50 - Marine water Algae - Green algae - Ulva pertusa

Size: 9.4 mm 3306 mg/l [96 hours] Effect: Reproduction

Conclusion/Summary[Product] Not available.

Persistence and degradability

Product/ingredient name

ethanol

Result **Aerobic** 

100% [20 days] - Readily

Conclusion/Summary[Product] Not available.

Article Number 29323952

Validation date 29 September 2025

Page: 7/9

Aquatic half-life Biodegradability Product/ingredient name **Photolysis** ethanol Readily

**Bioaccumulative potential** 

Product/ingredient name LogPow **BCF Potential** ethanol -0.35 0.66 Low

Mobility in soil

Soil/water partition coefficient Not available.

Other adverse effects No known significant effects or critical hazards.

## Section 13. Disposal considerations

### Disposal methods

The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

# Section 14. Transport information

	ADG	ADR/RID	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
Proper shipping name	-	-	-	-
Class	-	-	-	-
Label				
PG	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	Remarks IATA Special Provision A 58 - Aqueous solutions containing 24% or less alcohol by volume is not subject to these regulations.

Special precautions for user

Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to **IMO** instruments

Not available.

# Section 15. Regulatory information

# Standard for the Uniform Scheduling of Medicines and Poisons

## Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

## International regulations

## Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed

## **Montreal Protocol**

Not listed.

## Stockholm Convention on Persistent Organic Pollutants

Not listed

## Rotterdam Convention on Prior Informed Consent (PIC)

Not listed

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed

## **Inventory list**

Australia All components are listed or exempted.

United States Not determined.

Canada inventory All components are listed or exempted.

China All components are listed or exempted.

Japan inventory (CSCL): All components are listed or exempted.

Japan inventory (ISHL): Not determined.

**New Zealand** All components are listed or exempted.

# Section 16. Any other relevant information

## History

**Date of printing** 29 September 2025 **Date of previous issue** 05 August 2025

Date of issue 29 September 2025 Version

sds author@cytiva.com

ADG = Australian Dangerous Goods

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by

the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

### Procedure used to derive the classification

Classification Justification

FLAMMABLE LIQUIDS - Category 3 On basis of test data SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A Calculation method



Indicates information that has changed from previously issued version.

## Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Article Number 29323952

9529323952