	Page: 1
SAFETY DATA SHEET	Revision Date: 08/18/2021
	Print Date: 03/10/2023
	SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179	Version: 1.9

SECTION 1. IDENTIFICATION

Product identifier

Trade name : Praestol™ K 260 FL FLOCCULANT
 ™ Trademark, Solenis or its subsidiaries or affiliates,
 registered in various countries

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Flocculating agent

Details of the supplier of the safety data sheet Solenis Canada ULC 942 Brant St. Burlington, ON L7R 3X8 Canada RegulatoryRequestsNA@solenis.com	Emergency telephone number 1-844-SOLENIS (844-765-3647) Product Information Contact your local Solenis representative
--	--

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the Hazardous Products Regulations

Eye irritation : Category 2A

GHS label elements

Hazard pictograms :




Signal word : Warning

Hazard statements : H319 Causes serious eye irritation.

Precautionary statements :

Prevention:
 P264 Wash skin thoroughly after handling.
 P280 Wear eye protection/ face protection.

Response:
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P337 + P313 If eye irritation persists: Get medical advice/

	Page: 2
SAFETY DATA SHEET	Revision Date: 08/18/2021
	Print Date: 03/10/2023
	SDS Number: R0557329
Praesto TM K 260 FL FLOCCULANT TM Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179	Version: 1.9

attention.

Other hazards

Material can create slippery conditions.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Static Accumulator

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrotreated petroleum distillates	64742-47-8	≥ 20 - < 30
Ethoxylated alcohols (C12-16)	68551-12-2	≥ 1.5 - < 5

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.


If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.

In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
Lung irritation


		Page: 3
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

confusion
 irregular heartbeat
 Convulsions
 Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.
 This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting.
 Causes serious eye irritation.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon monoxide
 Carbon dioxide (CO₂)
 Nitrogen oxides (NO_x)
 Hydrocarbons
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Material can create slippery conditions.
 Water may cause extremely slippery conditions.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

 Strong bonds. Trusted solutions.		Page: 4
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Material can create slippery conditions.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.


SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid spillage on floor as the product can become very slippery.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
------------	---------	----------------------------------	----------------------------------	-------

 Strong bonds. Trusted solutions.	Page: 5
SAFETY DATA SHEET	Revision Date: 08/18/2021
	Print Date: 03/10/2023
	SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179	Version: 1.9

			concentration	
Hydrotreated petroleum distillates	64742-47-8	TWA	200 mg/m3 (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA	525 mg/m3	CA ON OEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Material : Impervious gloves

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.


Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.


SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : viscous

Colour : white

	Page: 6
SAFETY DATA SHEET	Revision Date: 08/18/2021
	Print Date: 03/10/2023
	SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179	Version: 1.9

Odour	: mild, hydrocarbon-like
Odour Threshold	: No data available
pH	: ca. 3.7 (20 °C) Concentration: 10 g/l
Melting point/freezing point	: < -15 °C
Boiling point/boiling range	: 103 °C
Flash point	: > 100 °C Method: Cleveland open cup
Evaporation rate	: < 1
Flammability (solid, gas)	: No data available
Self-ignition	: No data available
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 23.3 hPa (20 °C) Method: ASTM D 2879-86
Relative vapour density	: No data available
Relative density	: 1.03 - 1.04
Density	: ca. 1.03 g/cm ³
Solubility(ies)	
Water solubility	: soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s (40 °C)

	Page: 7
SAFETY DATA SHEET	Revision Date: 08/18/2021
	Print Date: 03/10/2023
	SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179	Version: 1.9

Based on a similar product formulation.

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents
strong reducing agents

Hazardous decomposition products : Carbon monoxide
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Hydrotreated petroleum distillates:


Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Ethoxylated alcohols (C12-16):

Acute oral toxicity : LD50 (Rat): 1,380 mg/kg

		Page: 8
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		SDS Number: R0557329
		Version: 1.9

Skin corrosion/irritation

Not classified based on available information.

Product:

Result : Possibly irritating to skin

Remarks : May cause skin irritation in susceptible persons.

Components:

Hydrotreated petroleum distillates:

Result : Mildly irritating to skin

Ethoxylated alcohols (C12-16):

Result : Not irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.
Causes serious eye irritation.

Components:

Hydrotreated petroleum distillates:

Result : Mildly irritating to eyes

Ethoxylated alcohols (C12-16):

Result : Risk of serious damage to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity


Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

 Strong bonds. Trusted solutions.		Page: 9
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrotreated petroleum distillates:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:


Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 35.9 mg/l
Exposure time: 96 h
Remarks: Test conducted using environmentally representative water.

LC50 (Oncorhynchus mykiss (rainbow trout)): 1.09 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
Remarks: Test conducted using well water.

NOEC (Oncorhynchus mykiss (rainbow trout)): 0.36 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
Remarks: Test conducted using well water.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Ceriodaphnia dubia (water flea)): 1.08 mg/l
Exposure time: 48 h
Remarks: Test conducted using environmentally representative water.

EC50 (Daphnia magna (Water flea)): 1.49 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

 Strong bonds. Trusted solutions.		Page: 10
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

Remarks: Test conducted using well water.

NOEC (Daphnia magna (Water flea)): 0.36 mg/l

Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

Remarks: Test conducted using well water.

Components:

Hydrotreated petroleum distillates:

Ecotoxicology Assessment

Acute aquatic toxicity : No toxicity at the limit of solubility

Chronic aquatic toxicity : No toxicity at the limit of solubility

Ethoxylated alcohols (C12-16):

Toxicity to fish : LC50 (Fish): > 1 - 10 mg/l

Exposure time: 96 h

Test Type: static test

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): > 1 - 10 mg/l

aquatic invertebrates

Exposure time: 48 h

Test Type: static test

Toxicity to algae/aquatic : ErC50 (green algae): > 0.1 - 1.0 mg/l

plants

Exposure time: 96 h

Test Type: static test

Toxicity to daphnia and other : EC50 (Daphnia (water flea)): 0.17 mg/l

aquatic invertebrates

Exposure time: 21 d

(Chronic toxicity)

Ecotoxicology Assessment

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

Product:


Biochemical Oxygen : Biochemical oxygen demand
Demand (BOD) 383,000 mg/l

Chemical Oxygen Demand : 1,930,000 mg/l
(COD) Method: Chemical oxygen demand

Components:

Ethoxylated alcohols (C12-16):

Biodegradability : Result: Readily biodegradable.

		Page: 11
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praesto TM K 260 FL FLOCCULANT TM Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

TDG

Not regulated as a dangerous good

		Page: 12
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praesto TM K 260 FL FLOCCULANT TM Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

The components of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: All substances listed as active on the TSCA inventory
AIIC	: On the inventory, or in compliance with the inventory
DSL	: This product contains one or more components that are not on the Canadian DSL and have annual quantity limits.
ENCS	: Not in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory

Canadian lists

No substances are subject to a Significant New Activity Notification.


SECTION 16. OTHER INFORMATION

Further information

Revision Date : 08/18/2021

Full text of other abbreviations

CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	: Time-weighted average exposure value

		Page: 13
SAFETY DATA SHEET		Revision Date: 08/18/2021
		Print Date: 03/10/2023
		SDS Number: R0557329
Praestol™ K 260 FL FLOCCULANT ™ Trademark, Solenis or its subsidiaries or affiliates, registered in various countries 657179		Version: 1.9

CA QC OEL / STEV : Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Safety Data Sheet

Key literature references and sources of data

SOLENIS Internal data

SOLENIS internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. This SDS has been prepared by the Solenis Environmental Health and Safety Department.

CA / EN