

**SKILCRAFT® Pro Strip™/MC
Heavy Duty Floor Stripper**

Revision: 2024-07-31

Version: 03.0

1. IDENTIFICATION

Product name: SKILCRAFT® Pro Strip™/MC
Heavy Duty Floor Stripper
MS0801585

Recommended use:

- Floor stripper
- Industrial/Institutional
- This product is intended to be diluted prior to use

Uses advised against: Uses other than those identified are not recommended

Manufacturer, importer, supplier:

US Headquarters Diversey, Inc. 1300 Altura Rd., Suite 125 Fort Mill, SC 29708 Phone: 1-888-352-2249 SDS Internet Address: https://sds.diversey.com	Canadian Headquarters Diversey Canada, Inc. 6150 Kennedy Road Unit 3 Mississauga, Ontario L5T 2J4 Phone: 1-800-668-7171
--	---

Emergency telephone number: 1-800-851-7145; 1-651-917-6133 (Int'l)

2. HAZARDS IDENTIFICATION

Classification for the undiluted product

Skin corrosion, Category 1B
Serious eye damage, Category 1
Carcinogenicity, Category 2
Reproductive toxicity, Category 2
Specific target organ toxicity (single exposure), Category 3



Signal word: Danger.

Hazard Statements

CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. SUSPECTED OF CAUSING CANCER. SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD. MAY CAUSE RESPIRATORY IRRITATION.

Precautionary Statements

Causes burns/ serious damage to mouth, throat and stomach. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. Use only in a well-ventilated area. Wear protective gloves, protective clothing and eye or face protection. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. IF exposed or concerned: Get medical advice or attention. Immediately call a Poison Center (1-800-851-7145) or physician. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of in accordance with all federal, state and local applicable regulations. SUPPLEMENTAL INFORMATION: DO NOT MIX WITH AMMONIA, BLEACH OR OTHER CHLORINATED COMPOUNDS. Mix only with water. Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat.

Health hazards not otherwise classified (HHNOC) - Not applicable

Physical hazards not otherwise classified (PHNOC) - Not applicable

**SKILCRAFT® Pro Strip™/MC
Heavy Duty Floor Stripper**

Classification for the diluted product 1:2

Skin corrosion/irritation Category 1B
Serious eye damage/eye irritation Category 1
Specific target organ toxicity (single exposure) Category 3

**Signal word:**

Danger.

Hazard and Precautionary Statements**CAUSES SEVERE SKIN BURNS AND SERIOUS EYE DAMAGE. MAY CAUSE RESPIRATORY IRRITATION.**

Causes burns/ serious damage to mouth, throat and stomach. Do not breathe vapors. Avoid contact with eyes, skin and clothing. Wash affected areas thoroughly after handling. Use only in a well-ventilated area. Wear protective gloves, protective clothing and eye or face protection. IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes. Immediately call a Poison Center (1-800-851-7145) or physician. Wash contaminated clothing before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of in accordance with all federal, state and local applicable regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS**Classified Ingredients**

Ingredient(s)	CAS #	Weight %
Monoethanolamine	141-43-5	10 - 30%
Benzyl alcohol	100-51-6	7 - 13%
2-(2-butoxyethoxy)ethanol	112-34-5	1 - 5%
Sodium xylene sulfonate	1300-72-7	1 - 5%
Alcohol, C9-C11, ethoxylated	68439-46-3	0.5 - 1.5%
Diethanolamine	111-42-2	> 0.1 - 1%

4. FIRST AID MEASURES**Undiluted Product:**

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash with plenty of water for at least 15 minutes.

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

Most Important Symptoms/Effects: No information available.

Immediate medical attention and special treatment needed Not applicable.

Diluted Product:

Eyes: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes.

Skin: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water for at least 15 minutes. Wash contaminated clothing before reuse

Inhalation: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Ingestion: IF SWALLOWED: Rinse mouth. DO NOT induce vomiting unless directed to do so by medical personnel. Drink a cupful of milk or water.

5. FIRE-FIGHTING MEASURES

Specific methods: No special methods required
Suitable extinguishing media: The product is not flammable. Extinguish fire using agent suitable for surrounding fire.
Specific hazards: Corrosive material (See sections 8 and 10).

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Extinguishing media which must not be used for safety reasons: No information available.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Put on appropriate personal protective equipment (see Section 8.).
Environmental precautions and clean-up methods: Clean-up methods - large spillage. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling: Can react to release hazardous gases. May vigorously react with acids resulting in spattering and excessive heat. Do not mix with other products or chemicals except as directed on the label. Mix only with water. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Do not taste or swallow. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage: Keep tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines:

Ingredient(s)	ACGIH	OSHA
Monoethanolamine	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m ³ (TWA)
2-(2-butoxyethoxy)ethanol	10 ppm (TWA)	-
Diethanolamine	1 mg/m ³ (TWA)	-

Undiluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

It is the responsibility of the employer to determine the potential risk of exposure to hazardous chemicals for employees in the workplace in order to determine the necessity, selection, and use of personal protective equipment.

Eye protection: Chemical-splash goggles.
Hand protection: Chemical-resistant gloves.
Skin and body protection: Protective footwear. Wear suitable protective clothing.
Respiratory protection: In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

Diluted Product:

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels.

Personal Protective Equipment

Eye protection: Chemical-splash goggles.
Hand protection: Chemical-resistant gloves.
Skin and body protection: Protective footwear. Wear suitable protective clothing.
Respiratory protection: No personal protective equipment required under normal use conditions.
Hygiene measures: Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid

Evaporation Rate: No information available

Odor threshold: No information available.

Melting point/freezing point (°C): Not determined

Autoignition temperature: No information available

Solubility in other solvents: No information available

Density: 1.025 Kg/L

Bulk density: No information available

Flash point (°F): > 200.1 °F > 93.4 °C

Kinematic viscosity mPa.s

6

VOC: 20.1 % *

Flammability (Solid or Gas): Not applicable

Sustained combustion: Not applicable

Explosion limits: - upper: Not determined - lower: Not determined

Color: Clear , Straw

Odor: Product specific Solvent

Boiling point/range: Not determined

Decomposition temperature: Not determined

Solubility: Completely Soluble

Relative Density (relative to water): 1.02

Vapor density: No information available

Vapor pressure: No information available.

Partition coefficient (n-octanol/water): No information available

Elemental Phosphorus: 0.00 % by wt.

pH: >= 11.5

Corrosion to metals: Not corrosive to metals

Dilution pH: > 11

Dilution Flash Point (°F): > 200.1 °F > 93.4 °C

VOC % by wt. at use dilution: 6.6 %

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVITY

Reactivity:

Not Applicable

Stability:

The product is stable

Possibility of hazardous reactions:

May vigorously react with acids resulting in spattering and excessive heat.

Hazardous decomposition products:

None reasonably foreseeable.

Materials to avoid:

Acids. Strong acids. Do not mix with any other product or chemical unless specified in the use directions.

Conditions to avoid:

None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Skin contact, Inhalation, Ingestion, Eye contact

Delayed, immediate, or chronic effects and symptoms from short and long-term exposure

Skin contact: Corrosive. Causes severe burns. Symptoms may include burns, blisters, redness and pain (which may be delayed).

Eye contact: Corrosive. Causes serious eye damage. Symptoms may include pain, burning sensation, redness, watering, blurred vision or loss of vision.

Ingestion: Causes burns/ serious damage to mouth, throat and stomach. Symptoms may include stomach pain and nausea.

Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract. Symptoms may include coughing and difficulty breathing.

Sensitization: No known effects.

Target Organs (SE): No information available

Target Organs (RE):

Carcinogen Listings: This product contains a component that is classified by the International Agency for Research on Cancer (IARC) as Group 2B, "Possibly carcinogenic to humans", which is generally based on limited evidence of carcinogenicity in humans and less than sufficient evidence of carcinogenicity in experimental animals. No data is available on the product itself.

Ingredient(s)	CAS #	NTP	IARC	OSHA
Diethanolamine	111-42-2		2B	

Numerical measures of toxicity

ATE - Oral (mg/kg): >2000

ATE - Dermal (mg/kg): >2000

ATE - Inhalatory, gases (mg/l): >20000

ATE - Inhalatory, mists (mg/l): >5

ATE - Inhalatory, vapors (mg/l): >20

12. ECOLOGICAL INFORMATION

Ecotoxicity: No information available.

Persistence and Degradability: No information available.

Bioaccumulation: No information available.

Mobility: No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products (undiluted product): This product, as sold, if discarded or disposed, is not a hazardous waste according to Federal regulations (40 CFR 261). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

Waste from residues / unused products (diluted product): This product, when diluted as stated on this SDS, is not a hazardous waste according to Federal regulations (40 CFR 261). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the waste solution meets RCRA criteria for hazardous waste. Dispose in compliance with all Federal, state, provincial, and local laws and regulations.

RCRA Hazard Class (undiluted product): Not Regulated

RCRA Hazard Class (diluted product): Not Regulated

Contaminated Packaging: Do not re-use empty containers.

14. TRANSPORT INFORMATION

DOT/TDG/IMDG: The information provided below is the full transportation classification for this product. This description does not account for the package size(s) of this product, that may fall under a quantity exception, according to the applicable transportation regulations. When shipping dangerous goods, please consult with your internal, certified hazardous materials specialist to determine if any exceptions can be applied to your shipment.

DOT (Ground) Bill of Lading Description: UN2491, ETHANOLAMINE SOLUTIONS, 8, III

IMDG (Ocean) Bill of Lading Description: UN2491, ETHANOLAMINE SOLUTIONS, 8, III

15. REGULATORY INFORMATION

International Inventories at CAS# Level

TSCA

All components are listed or otherwise exempt

DSL

All components are listed or otherwise exempt



WARNING: This product can expose you to chemicals including Diethanolamine which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

US RIGHT TO KNOW (RTK)

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
Water	7732-18-5	-	-	-	-
Monoethanolamine	141-43-5	X	X	X	-
Benzyl alcohol	100-51-6	X	-	X	-
2-(2-butoxyethoxy)ethanol	112-34-5	-	X	-	-
Sodium xylene sulfonate	1300-72-7	-	-	-	-
Alcohol, C9-C11, ethoxylated	68439-46-3	-	-	-	-
Diethanolamine	111-42-2	X	X	X	X

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-(2-butoxyethoxy)ethanol	112-34-5	1 - 5%			X

Diethanolamine	111-42-2	> 0.1 - 1%	100		X
----------------	----------	------------	-----	--	---

Clean Air Act/Clean Water Act

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
2-(2-butoxyethoxy)ethanol	X		

Canadian Regulations

Ingredient(s)	CAS #	NPRI
2-(2-butoxyethoxy)ethanol	112-34-5	X

16. OTHER INFORMATION

NFPA (National Fire Protection Association)

Rating Scale: (Low Hazard) 0 - 4 (Extreme Hazard)

Health 3
 Flammability 0
 Instability 0
 Special Hazards -

Diluted Product:

Health 3
 Flammability 0
 Instability 0
 Special Hazards -

Revision: 2024-07-31
 Version: 03.0

Reason for revision: Not applicable
 Prepared by: North American Regulatory Affairs
 Additional advice: • Does not contain an added fragrance

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.