

**DUPONT™ SEALANT FOR TYVEK®  
FLUID APPLIED SYSTEM**  
(USE BACKER ROD AS NECESSARY)

**DUPONT™ TYVEK® FLUID APPLIED  
FLASHING AND JOINT COMPOUND**  
(2" ONTO FACE OF WALL)

GYPSUM BOARD

WINDOW FRAME

SEALANT  
BY OTHERS

**DUPONT™  
STRAIGHTFLASH™**

**DUPONT™ TYVEK®  
FLUID APPLIED WB**

CMU WALL

BRICK VENEER

**NOTE**

- 1) INTERIOR VAPOR RETARDER MAY BE REQUIRED IN SOME REGIONS.
- 2) THIS INFORMATION IS PROVIDED BY DUPONT AS REFERENCE ONLY; PLEASE CONSULT LOCAL BUILDING CODES, REGULATIONS AND LAWS TO DETERMINE THE APPROPRIATE CONSTRUCTION METHODS AND MATERIALS NEEDED.

SCALE: NOT TO SCALE

REVISION DATE: 4/28/10

DRAWING: FA-B-W102s

## FLANGED WINDOW SILL - METHOD 1

BRICK VENEER / CMU WALL / FLUID APPLIED FLASHING



**Tyvek.**  
FLUID APPLIED WB