



<sup>1</sup>REFER TO THE *FACADE CONSIDERATIONS* SECTION OF THE APPLICABLE DUPONT INSTALLATION GUIDELINES TO HELP DETERMINE THE APPROPRIATE **TYVEK® WRB** FOR THE CLADDING TYPE.

<sup>2</sup>VAPOR RETARDER REQUIREMENTS AND PERMITTED USE PER APPLICABLE BUILDING CODES.

<sup>3</sup>**GREAT STUFF PRO™ CONSTRUCTION ADHESIVE, GREAT STUFF PRO™ GAPS & CRACKS INSULATING FOAM SEALANT** AT THESE LOCATIONS IS ONLY REQUIRED FOR AIR SEALING.

<sup>4</sup>REFER TO DUPONT TECHNICAL BULLETIN *CHEMICAL COMPATIBILITY OF REPRESENTATIVE BUILDING SEALANTS AND ADHESIVES/PRIMERS* FOR MORE INFORMATION.

<sup>5</sup>TERMINATION OF **TYVEK® WRB** ONTO STYROFOAM™ BRAND XPS INSULATION WITH CHEMICALLY COMPATIBLE SEALANT APPROVED FOR SINGLE-FAMILY BUILDINGS ONLY.

<sup>6</sup>DUPONT REQUIRES THAT **DUPONT™ FLASHING TAPE** BE COVERED WITHIN 120 DAYS OF INSTALLATION, **DUPONT™ STRAIGHTFLASH™** MUST BE COVERED WITHIN 270 DAYS.

<sup>7</sup>DUPONT RECOMMENDED BEST PRACTICE OR AS REQUIRED BY CODE.

<sup>8</sup>A CHEMICALLY-COMPATIBLE ADHESIVE/PRIMER IS REQUIRED WHEN INSTALLING **DUPONT SELF-ADHERED FLASHING PRODUCTS** OVER CONCRETE AND FIBERGLASS MAT GYPSUM SHEATHING.

#### NOTES:

- FASTEN **STYROFOAM™ BRAND XPS INSULATION** USING 1" CAP FASTENERS LONG ENOUGH TO PENETRATE FRAMING A MINIMUM OF 3/4-INCH.
- SECURE **TYVEK® WRB** TO WOOD STRUCTURE IN ACCORDANCE WITH APPLICABLE INSTALLATION GUIDELINES.
- REFER TO LOCAL BUILDING CODES AND APPLICABLE INSTALLATION GUIDELINES REGARDING USE AND INTEGRATION OF **TYVEK® WRB** WITH FLASHING AND WEEP SCREED.
- REFER TO LOCAL BUILDING CODES TO ENSURE MATERIAL SELECTION COMPLIANCE (ex. SHEATHING, FRAMING, INSULATION, ETC.).
- USE OF FOAM PLASTICS IN AREAS OF "VERY HEAVY" TERMITE INFESTION PROBABILITY SHALL BE IN ACCORDANCE WITH LOCAL BUILDING CODES.
- EXPOSED EXTERIOR INSULATION APPLIED TO BASEMENT WALLS, CRAWL SPACE WALLS AND PERIMETER OF SLAB-ON-GRADE FLOORS SHALL HAVE A RIGID, OPAQUE, AND WEATHER-RESISTANT PROTECTIVE COVERING.

SCALE: NOT TO SCALE

REVISION DATE: 3/12/25

DRAWING: SF-OP-1201B.2-MA

## BASE OF WALL DETAIL

RESIDENTIAL WOOD FRAME STRUCTURE w/TYVEK® WRB™ INSTALLED OVER STYROFOAM™ BRAND XPS INSULATION - CLADDING NEUTRAL (METHOD 2)

**DUPONT**  
**Tyvek**