

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

SECTION 1. IDENTIFICATION

Product identifier

Product name AFFINITY® 24 EC

Other means of identification

Product code 50001761

Chemical nature Mixture

Recommended use of the chemical and restrictions on use

Recommended use Can be used as herbicide only.

Restrictions on use Use as recommended by the label.

Manufacturer or supplier's details

Manufacturer FMC Corporation
2929 WALNUT ST
PHILADELPHIA PA 19104
USA
+1 (215) 299-6000 (Corporate)
SDS-Info@fmc.com, +1-(800)-346-0833 (FMC Cust. Service)

Supplier Address FMC Corporation
2929 Walnut Street
Philadelphia PA 19104
USA

Emergency telephone

For leak, fire, spill or accident emergencies, call:
1 800 / 424-9300 (CHEMTREC - U.S.A.)
1 703 / 741-5970 (CHEMTREC - International)
1 703 / 527-3887 (CHEMTREC - Alternate)

Medical emergency:
U.S.A. & Canada: +1 800 / 331-3148
All other countries: +1 651 / 632-6793 (Collect)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Carcinogenicity : Category 2

Aspiration hazard : Category 1

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version 1.1 Revision Date: 11/13/2025 SDS Number: 50001761 Date of last issue: 05/01/2019
Date of first issue: 05/01/2019

GHS label elements

Hazard pictograms

:



Signal Word

:

DANGER

Hazard Statements

:

H304 May be fatal if swallowed and enters airways.
H351 Suspected of causing cancer.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

Very toxic to aquatic life with long lasting effects.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

:

Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5	≥ 70 - < 90
carfentrazone-ethyl (ISO)	128639-02-1	≥ 20 - < 30
butan-1-ol	71-36-3	≥ 1 - < 5
4-hydroxy-4-methylpentan-2-one	123-42-2	≥ 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

-
- | | |
|---|--|
| General advice | : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended. |
| If inhaled | : Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice. |
| In case of skin contact | : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes. |
| In case of eye contact | : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital. |
| Most important symptoms and effects, both acute and delayed | : May be fatal if swallowed and enters airways.
Suspected of causing cancer. |
| Notes to physician | : Treat symptomatically. |
-

SECTION 5. FIRE-FIGHTING MEASURES

- | | |
|---------------------------------------|--|
| Suitable extinguishing media | : Dry chemical, CO2, water spray or regular foam. |
| Unsuitable extinguishing media | : Do not spread spilled material with high-pressure water streams. |
| Specific hazards during fire fighting | : Do not allow run-off from fire fighting to enter drains or water courses. |
| Hazardous combustion products | : Carbon oxides
Fire may produce irritating, corrosive and/or toxic gases.
Nitrogen oxides (NOx)
Fluorine compounds
Hydrogen cyanide
Hydrogen chloride
Chlorinated compounds |

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.
- Special protective equipment for fire-fighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
If it can be safely done, stop the leak.
Do not touch or walk through the spilled material.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Never return spills in original containers for re-use.
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version 1.1 Revision Date: 11/13/2025 SDS Number: 50001761 Date of last issue: 05/01/2019
Date of first issue: 05/01/2019

Conditions for safe storage : Prevent unauthorized access.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5	TWA	200 mg/m ³ (total hydrocarbon vapor)	ACGIH
carfentrazone-ethyl (ISO)	128639-02-1	TWA (Inhalable particulate matter)	1 mg/m ³	ACGIH
butan-1-ol	71-36-3	TWA	20 ppm	ACGIH
		C	50 ppm 150 mg/m ³	NIOSH REL
		TWA	100 ppm 300 mg/m ³	OSHA Z-1
		C	50 ppm 150 mg/m ³	OSHA P0
4-hydroxy-4-methylpentan-2-one	123-42-2	TWA	50 ppm	ACGIH
		TWA	50 ppm 240 mg/m ³	NIOSH REL
		TWA	50 ppm 240 mg/m ³	OSHA Z-1
		TWA	50 ppm 240 mg/m ³	OSHA P0

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection

Material : Wear chemical resistant gloves, such as barrier laminate, butyl rubber or nitrile rubber.

Remarks : The suitability for a specific workplace should be discussed

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

- with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Protective measures : Ensure that eye flushing systems and safety showers are located close to the working place.
Wear suitable protective equipment.
When using do not eat, drink or smoke.
Always have on hand a first-aid kit, together with proper instructions.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and immediately after handling the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Color : brown, orange
- Odor : Aromatic
- Odor Threshold : No data available
- pH : 5.3
Concentration: 10 g/l
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Flash point : 168.1 °F / 75.6 °C
Method: closed cup
- Upper explosion limit / Upper : No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

flammability limit

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 9 lb/gal

Solubility(ies)
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.
Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.
Avoid formation of aerosol.

Incompatible materials : Avoid strong acids, bases, and oxidizers.

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Product:

Acute oral toxicity : LD50 (Rat): 4,077 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.31 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4.688 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

carfentrazone-ethyl (ISO):

Acute oral toxicity : LD50 (Rat, female): 5,143 mg/kg
Method: US EPA Test Guideline OPP 81-1
Symptoms: Tremors
GLP: yes

LD50 (Rat, female): > 5,000 mg/kg
Method: OECD Test Guideline 425
GLP: yes
Assessment: The substance or mixture has no acute oral toxicity
Remarks: no mortality

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.09 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: EPA OPP 81 - 3
Symptoms: Tremors, chromodacryorrhea, nasal discharge
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: no mortality

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Acute dermal toxicity : LD50 (Rat, male and female): > 4,000 mg/kg
Method: US EPA Test Guideline OPP 81-2
GLP: yes
Assessment: The component/mixture is minimally toxic after single contact with skin.
Remarks: no mortality

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 2.292 mg/kg

Acute toxicity estimate: 1,000 mg/kg
Method: Expert judgment

Acute inhalation toxicity : LC0 (Rat): > 17.76 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: no mortality

Acute dermal toxicity : LD50 (Rabbit): 3,430 mg/kg

4-hydroxy-4-methylpentan-2-one:

Acute oral toxicity : LD50 Oral (Rat, male and female): 3,002 mg/kg
Method: OECD Test Guideline 401
Symptoms: Lethargy, ataxia, Coma

Acute inhalation toxicity : LC0 (Rat, male and female): >= 7.6 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Method: OECD Test Guideline 403
Remarks: no mortality

Acute dermal toxicity : LD0 (Rat, male and female): > 1,875 mg/kg
Method: OECD Test Guideline 402

Skin corrosion/irritation

Not classified based on available information.

Product:

Species : Rabbit
Result : slight irritation

Remarks : May cause skin irritation and/or dermatitis.

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rabbit
Assessment : Repeated exposure may cause skin dryness or cracking.
Result : No skin irritation
Remarks : Minimal effects that do not meet the threshold for classifica-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

tion.
Based on data from similar materials

carfentrazone-ethyl (ISO):

Species	:	Rabbit
Assessment	:	Not classified as irritant
Method	:	US EPA Test Guideline OPP 81-5
Result	:	slight irritation
GLP	:	yes

butan-1-ol:

Species	:	Rabbit
Result	:	Skin irritation

4-hydroxy-4-methylpentan-2-one:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	slight irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result	:	slight irritation
--------	---	-------------------

Remarks	:	May cause irreversible eye damage.
---------	---	------------------------------------

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species	:	Rabbit
Assessment	:	No eye irritation
Remarks	:	Minimal effects that do not meet the threshold for classification. Based on data from similar materials

carfentrazone-ethyl (ISO):

Species	:	Rabbit
Result	:	slight irritation
Assessment	:	Not classified as irritant
Method	:	EPA OPP 81-4
GLP	:	yes

butan-1-ol:

Species	:	Rabbit
Result	:	Irreversible effects on the eye

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

4-hydroxy-4-methylpentan-2-one:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Method	:	OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Product:

Result	:	Does not cause skin sensitization.
--------	---	------------------------------------

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Test Type	:	Maximization Test
Species	:	Guinea pig
Result	:	Not a skin sensitizer.
Remarks	:	Based on data from similar materials

carfentrazone-ethyl (ISO):

Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	US EPA Test Guideline OPP 81-6
Result	:	Does not cause skin sensitization.
GLP	:	yes

Test Type	:	Local lymph node assay (LLNA)
Species	:	Mouse
Method	:	OECD Test Guideline 429
Result	:	Does not cause skin sensitization.
GLP	:	yes

butan-1-ol:

Result	:	Not a skin sensitizer.
--------	---	------------------------

4-hydroxy-4-methylpentan-2-one:

Test Type	:	Maximization Test
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitization.

Germ cell mutagenicity

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Genotoxicity in vitro : Test Type: reverse mutation assay
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Bone marrow chromosome aberration.
Species: Rat
Application Route: inhalation (vapor)
Result: negative

carfentrazone-ethyl (ISO):

Genotoxicity in vitro : Test Type: reverse mutation assay
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
GLP: yes

Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: U.S. EPA 84-2
Result: negative
GLP: yes

Test Type: Ames test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative
GLP: yes

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative
GLP: yes

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (male and female)
Result: negative
GLP: yes

Test Type: unscheduled DNA synthesis assay

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Species: Rat (male)
Result: negative
GLP: yes

Germ cell mutagenicity - Assessment : No genotoxic potential.

butan-1-ol:

Genotoxicity in vitro : Test Type: gene mutation test
Method: OECD Test Guideline 476
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

4-hydroxy-4-methylpentan-2-one:

Genotoxicity in vitro : Test Type: reverse mutation assay
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 473
Result: negative

Test Type: In vitro mammalian cell gene mutation test
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative

Germ cell mutagenicity - Assessment : Weight of evidence does not support classification as a germ cell mutagen.

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rat, male and female
Application Route : inhalation (vapor)
Exposure time : 12 month(s)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

NOAEC : 1.8 mg/l
Result : negative
Remarks : Based on data from similar materials

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

carfentrazone-ethyl (ISO):

Species : Rat, female
Application Route : Ingestion
Exposure time : 2 Years
NOAEL : 3 mg/kg bw/day
LOAEL : 12 mg/kg bw/day
Method : U.S. EPA 83-5
Result : no increase in tumors observed
Target Organs : Liver
GLP : yes

Species : Mouse, female
Application Route : Ingestion
Exposure time : 80 weeks
NOAEL : 10 mg/kg bw/day
LOAEL : 110 mg/kg bw/day
Method : U.S. EPA 83-5
Result : no increase in tumors observed
Target Organs : Liver
GLP : yes

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Components:

carfentrazone-ethyl (ISO):

Effects on fertility : Test Type: Multi-generation study
Species: Rat, male and female
Application Route: Ingestion
Fertility: NOEL: 4,000 ppm
Result: negative

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat, female
Application Route: Oral
General Toxicity Maternal: NOEL: 100 mg/kg bw/day
Embryo-fetal toxicity.: NOEL: 600 mg/kg bw/day
Result: negative

Test Type: Embryo-fetal development
Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: NOEL: 150 mg/kg bw/day
Embryo-fetal toxicity.: NOEL: > 300 mg/kg bw/day
Result: negative

Reproductive toxicity - Assessment : Animal testing showed no reproductive toxicity.

4-hydroxy-4-methylpentan-2-one:

Effects on fertility : Test Type: one-generation reproductive toxicity
Species: Rat, male and female
Application Route: Oral
Dose: 30, 100, 300, 1000mg/kg/bw
Duration of Single Treatment: 45 d
General Toxicity Parent: LOAEL: 300 mg/kg bw/day
General Toxicity F1: NOAEL: 300 mg/kg bw/day
Method: OECD Test Guideline 422

Effects on fetal development : Species: Rat
Application Route: Oral
Dose: 100, 300, 1000mg/kg/day
Duration of Single Treatment: 21 d
General Toxicity Maternal: NOAEL: > 1,000 mg/kg bw/day
Embryo-fetal toxicity.: NOAEL: > 1,000 mg/kg bw/day
Method: OECD Test Guideline 414

Species: Rabbit
Application Route: Oral
Dose: 0, 100, 300, 800mg/kg/bw/day
Duration of Single Treatment: 29 d
General Toxicity Maternal: LOAEL: 800 mg/kg bw/day
Embryo-fetal toxicity.: LOAEL: 300 mg/kg bw/day
Method: OECD Test Guideline 414

Reproductive toxicity - Assessment : Some evidence of adverse effects on sexual function and fertility, and/or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Components:

carfentrazone-ethyl (ISO):

Remarks : No significant adverse effects were reported

butan-1-ol:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

4-hydroxy-4-methylpentan-2-one:

Target Organs : Respiratory Tract

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.

Components:

carfentrazone-ethyl (ISO):

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Species : Rat, male and female

NOAEC : 0.9 - 1.8 mg/l

Application Route : inhalation (vapor)

Exposure time : 12 Months

carfentrazone-ethyl (ISO):

Species : Mouse, male

NOAEL : 143 mg/kg

LOAEL : 571 mg/kg

Application Route : Oral

Exposure time : 90 days

Method : EPA 82-1

GLP : yes

Target Organs : Blood, Liver

Species : Dog, male and female

NOEL : 150 mg/kg

LOAEL : 500 mg/kg

Application Route : Oral

Exposure time : 90 days

Target Organs : Blood

Species : Dog, male and female

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

NOEL	: 50 mg/kg
NOAEL	: 150 mg/kg
LOAEL	: 500 mg/kg
Application Route	: Oral
Exposure time	: 12 months
GLP	: yes
Target Organs	: Blood

Species	: Rat, male
NOAEL	: 58 mg/kg
Exposure time	: 90 d
Method	: EPA 82-1
GLP	: yes

butan-1-ol:

Species	: Rat
NOAEL	: 1,500 mg/m ³
Application Route	: Inhalation

4-hydroxy-4-methylpentan-2-one:

Species	: Rat, male and female
NOAEL	: 600 mg/kg bw/day
Application Route	: Oral
Exposure time	: 13 weeks
Dose	: 0, 25, 150, 600mg/kg bw/day
Method	: OECD Test Guideline 408

Species	: Rat, male and female
LOAEL	: 300 mg/kg bw/day
Application Route	: Oral
Exposure time	: 45 d
Dose	: 30, 100, 300, 1000mg/kgbw
Method	: OECD Test Guideline 422

Species	: Rat, male and female
NOAEL	: 1000 ppm
Application Route	: inhalation (vapor)
Exposure time	: 6 weeks
Dose	: 50, 225, 1000 ppm
Method	: OECD Test Guideline 412

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

May be fatal if swallowed and enters airways.

carfentrazone-ethyl (ISO):

The substance does not have properties associated with aspiration hazard potential.

Experience with human exposure

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Skin contact : Symptoms: Repeated exposure may cause skin dryness or cracking.

Neurological effects

Components:

carfentrazone-ethyl (ISO):

No neurotoxicity observed in animal studies.

Further information

Product:

Remarks : Solvents may degrease the skin.

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Remarks : Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 2 - 5 mg/l
Exposure time: 96 h

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 1.4 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 1 - 3 mg/l
Exposure time: 24 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EL50 (Daphnia magna (Water flea)): 0.89 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : LL50 (Tetrahymena pyriformis): 677.9 mg/l
Exposure time: 72 h
Test Type: Growth inhibition

carfentrazone-ethyl (ISO):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.55 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

LC50 (Menidia beryllina (Silerside)): 1.14 mg/l
Exposure time: 96 h
Test Type: flow-through test

LC50 (Oncorhynchus mykiss (rainbow trout)): 1.6 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: EPA OPP 72-1

LC50 (Lepomis macrochirus (Bluegill sunfish)): 2 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 9.8 mg/l
End point: Immobilization
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: No toxicity at the limit of solubility.

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0.0133 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

NOEC (Selenastrum capricornutum (green algae)): 0.00933 mg/l

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

End point: Growth rate
Exposure time: 72 h
Method: OECD Test Guideline 201
GLP: yes

EbC50 (*Selenastrum capricornutum* (green algae)): 16 µg/l
Exposure time: 120 h

EC50 (*Navicula pelliculosa* (Diatom)): 12 µg/l
Exposure time: 72 h
Test Type: static test

EC50 (*Skeletonema costatum* (Diatom)): 15 µg/l
Exposure time: 72 h
GLP: yes

Toxicity to fish (Chronic toxicity) : NOEC (*Oncorhynchus mykiss* (rainbow trout)): 22 µg/l
Exposure time: 89 d
Test Type: Early Life-Stage
Method: OECD Test Guideline 210
GLP: yes

NOEC (*Oncorhynchus mykiss* (rainbow trout)): 0.118 mg/l
Exposure time: 102 d
Test Type: flow-through test
Method: US EPA Test Guideline OPP 72-4

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (*Daphnia magna* (Water flea)): 0.309 mg/l
End point: Growth
Exposure time: 21 d
Method: OECD Test Guideline 202

NOEC (*Daphnia magna* (Water flea)): 0.316 mg/l
End point: Growth
Exposure time: 21 d
Method: OECD Test Guideline 202

NOEC (*Daphnia*): 35 mg/l
End point: reproduction
Exposure time: 21 d
Method: US EPA Test Guideline OPPTS 850.1300
Remarks: Information given is based on data obtained from similar product.

Toxicity to microorganisms : NOEC (activated sludge): 1,000 mg/l
Test Type: Respiration inhibition
Method: OECD Test Guideline 209

Toxicity to soil dwelling organisms : NOEC (*Eisenia fetida* (earthworms)): 820 mg/kg

Method: OECD Test Guideline 216
Remarks: No significant adverse effect on Nitrogen minerali-

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

zation.

Method: OECD Test Guideline 217

Remarks: No significant adverse effect on Carbon mineralization.

Toxicity to terrestrial organisms : LD50 (Anas platyrhynchos (Mallard duck)): > 5,620 ppm
End point: Acute oral toxicity
Remarks: Dietary

LC50 (Colinus virginianus (Bobwhite quail)): > 5,620 ppm
End point: Acute oral toxicity
Remarks: Dietary

LD50 (Colinus virginianus (Bobwhite quail)): > 2,000 mg/kg
End point: Acute oral toxicity
Method: EPA OPP 71-1

LD50 (Colinus virginianus (Bobwhite quail)): > 2,250 mg/kg
End point: Acute oral toxicity
Method: EPA OPP 71-1

NOEL (Colinus virginianus (Bobwhite quail)): 1000 ppm
End point: Reproduction Test

LD50 (Apis mellifera (bees)): > 200 µg/bee
End point: Acute oral toxicity

LD50 (Apis mellifera (bees)): > 200 µg/bee
End point: Acute contact toxicity

Ecotoxicology Assessment

Toxicity Data on Soil : Harmful to the soil environment.

butan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1,376 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1,328 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): 225 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

EC50 (Pseudokirchneriella subcapitata (green algae)): 225 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 4.1 mg/l
Exposure time: 21 d

Toxicity to microorganisms : EC50 (Anabaena flos-aquae (cyanobacterium)): 225 mg/l
Exposure time: 4 d

EC50 (Natural microorganism): 4,390 mg/l
Exposure time: 17 h

4-hydroxy-4-methylpentan-2-one:

Toxicity to fish : LC50 (Oryzias latipes (Orange-red killifish)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (algae)): > 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (algae)): >= 1,000 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : LOEC (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC50 (activated sludge): > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F
Remarks: Based on data from similar materials

carfentrazone-ethyl (ISO):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.9 %

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Exposure time: 28 d
Method: OECD Test Guideline 301B

Stability in water : Degradation half life: 3.6 h pH: 9

Degradation half life: 8.6 d pH: 7

Photodegradation :

butan-1-ol:

Biodegradability : Result: Readily biodegradable.
Remarks: Expected to be biodegradable

4-hydroxy-4-methylpentan-2-one:

Biodegradability : Inoculum: activated sludge
Result: Readily biodegradable.
Method: OECD Test Guideline 301A

Bioaccumulative potential

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Bioaccumulation : Remarks: The product/substance has a potential to bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 3.72
Method: QSAR

carfentrazone-ethyl (ISO):

Bioaccumulation : Species: Oncorhynchus mykiss (rainbow trout)
Bioconcentration factor (BCF): 176
Exposure time: 28 d
Method: OECD Test Guideline 305E
Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 3.7 (68 °F / 20 °C)

butan-1-ol:

Partition coefficient: n-octanol/water : Pow: 1 (77 °F / 25 °C)

4-hydroxy-4-methylpentan-2-one:

Partition coefficient: n-octanol/water : log Pow: -0.09
Method: QSAR

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Mobility in soil

Components:

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified:

Distribution among environmental compartments : Remarks: Expected to partition to sediment and wastewater solids. Moderately volatile.

carfentrazone-ethyl (ISO):

Distribution among environmental compartments : Koc: 866, log Koc: 2.93
Remarks: Mobile in soils

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Carfentrazone-ethyl)

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : no

IATA-DGR

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Carfentrazone-ethyl)

Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Carfentrazone-ethyl)

Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Road

UN/ID/NA number : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Carfentrazone-ethyl)

Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
------------	---------	--------------------	-----------------------------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

butan-1-ol	71-36-3	100	100 (F003)
------------	---------	-----	------------

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
Acute toxicity (any route of exposure)
Carcinogenicity
Reproductive toxicity
Aspiration hazard
Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

butan-1-ol	71-36-3	>= 1 - < 5 %
------------	---------	--------------

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

butan-1-ol	71-36-3	>= 1 - < 5 %
------------	---------	--------------

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

butan-1-ol	71-36-3
------------	---------

Pennsylvania Right To Know

Solvent naphtha (petroleum), heavy arom.; Kerosine — unspecified	64742-94-5
carfentrazone-ethyl (ISO)	128639-02-1
butan-1-ol	71-36-3

Maine Chemicals of High Concern

Product does not contain any listed chemicals

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

Product does not contain any listed chemicals

California List of Hazardous Substances

butan-1-ol 71-36-3

California Permissible Exposure Limits for Chemical Contaminants

butan-1-ol 71-36-3

The ingredients of this product are reported in the following inventories:

TCSI	: On the inventory, or in compliance with the inventory
TSCA	: Product contains substance(s) not listed on TSCA inventory.
AIIC	: Not in compliance with the inventory
DSL	: This product contains chemical substance(s) exempt from CEPA DSL Inventory requirements. It is regulated as a pesticide subject to Pest Control Products Act (PCPA) requirements. Read the PCPA label, authorized under the Pest Control Products Act, prior to using or handling this pest control product.
ENCS	: Not in compliance with the inventory
ISHL	: On the inventory, or in compliance with the inventory
KECI	: On the inventory, or in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
NZIoC	: Not in compliance with the inventory
TECI	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

FIFRA information

This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version
1.1

Revision Date:
11/13/2025

SDS Number:
50001761


Date of last issue: 05/01/2019
Date of first issue: 05/01/2019

Avoid breathing dust or spray mist., Avoid contact with skin, eyes and clothing., Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals., Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet., Remove and wash contaminated clothing before reuse., This product is toxic to fish and invertebrates.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



0 No health threat, 1 Slightly Hazardous, 2 Hazardous, 3 Extreme danger, 4 Deadly

HMIS® IV:

HEALTH	*	3
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / C	:	Ceiling value not be exceeded at any time.
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / C	:	Ceiling limit
OSHA Z-1 / TWA	:	8-hour time weighted average

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

US / EN

Prepared by:

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



AFFINITY® 24 EC

Version	Revision Date:	SDS Number:	Date of last issue: 05/01/2019
1.1	11/13/2025	50001761	Date of first issue: 05/01/2019

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.

© 2021-2025 FMC Corporation. All Rights Reserved.

End of Safety Data Sheet