

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

SECTION 1. IDENTIFICATION

Product identifier

Product name Carbosulfan 250 g/L EC

Other means of identification

Product code 50000905

Recommended use of the chemical and restrictions on use

Recommended use Insecticide

Restrictions on use Use as recommended by the label.

Manufacturer or supplier's details

Manufacturer FMC Corporation
2929 WALNUT ST
PHILADELPHIA PA 19104
USA
+1 (215) 299-6000
SDS-Info@fmc.com

Supplier Address FMC Corporation
2929 Walnut Street
Philadelphia PA 19104
USA

Emergency telephone

For leak, fire, spill or accident emergencies, call:
1 800 / 424-9300 (CHEMTREC - U.S.A.)
1 703 / 741-5970 (CHEMTREC - International)
1 703 / 527-3887 (CHEMTREC - Alternate)

Medical emergency:
U.S.A. & Canada: +1 800 / 331-3148
All other countries: +1 651 / 632-6793 (Collect)

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 3

Acute toxicity (Oral) : Category 3

Acute toxicity (Inhalation) : Category 2

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Acute toxicity (Dermal)	: Category 4
Eye irritation	: Category 2A
Skin sensitization	: Sub-category 1B
Carcinogenicity	: Category 2
Specific target organ toxicity - single exposure	: Category 1 (Nervous system)
Specific target organ toxicity - single exposure	: Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	: Category 1 (Nervous system)
Aspiration hazard	: Category 1

GHS label elements

Hazard pictograms	:	   
-------------------	---	--

Signal Word	: DANGER
-------------	----------

Hazard Statements	: H226 Flammable liquid and vapor. H301 Toxic if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H330 Fatal if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 Suspected of causing cancer. H370 Causes damage to organs (Nervous system). H372 Causes damage to organs (Nervous system) through prolonged or repeated exposure.
-------------------	--

Precautionary Statements	: Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
--------------------------	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
P284 Wear respiratory protection.

Response:

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. Rinse mouth.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307 + P311 IF exposed: Call a POISON CENTER or doctor/ physician.
P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P363 Wash contaminated clothing before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

Very toxic to aquatic life with long lasting effects.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version 1.0 Revision Date: 10/27/2025 SDS Number: 50000905 Date of last issue: -
Date of first issue: 10/27/2025

Chemical name	CAS-No.	Concentration (% w/w)
carbosulfan (ISO)	55285-14-8	27
Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics	128601-23-0	$\geq 30 - < 50$
Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	$\geq 20 - < 30$
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	68584-23-6	$\geq 1 - < 5$
2-ethylhexan-1-ol	104-76-7	$\geq 1 - < 5$

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : Move to fresh air.
Call a physician or poison control center immediately.
If unconscious, place in recovery position and seek medical advice.
If experiencing any discomfort, immediately remove from exposure. Light cases: Keep person under surveillance. Get medical attention immediately if symptoms develop. Serious cases: Get medical attention immediately or call for an ambulance.
- In case of skin contact : Take victim immediately to hospital.
If on skin, rinse well with water.
Wash off immediately with plenty of water for at least 15 minutes.
Take off all contaminated clothing immediately.
Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.
- Most important symptoms : Contains a cholinesterase inhibitor. Symptoms may include

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

and effects, both acute and delayed

nausea, diarrhea, vomiting, decreased appetite, indigestion, muscle cramps, fatigue, insomnia, dizziness, headache, and lack of energy.
Swallowing or inhaling may result in sudden shortness of breath, coughing, nausea and or abdominal pain.
Exposure to skin may result in mild symptoms include itching, hives or rash, and skin redness. More severe symptoms include sneezing, itchy watery eyes, and difficulty breathing.
Toxic if swallowed.
May be fatal if swallowed and enters airways.
Harmful in contact with skin.
May cause an allergic skin reaction.
Causes serious eye irritation.
Fatal if inhaled.
May cause respiratory irritation.
May cause drowsiness or dizziness.
Suspected of causing cancer.
Causes damage to organs.
Causes damage to organs through prolonged or repeated exposure.

Protection of first-aiders : Avoid inhalation, ingestion and contact with skin and eyes.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Dry chemical, CO₂, water spray or regular foam.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : High volume water jet
Do not spread spilled material with high-pressure water streams.

Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Fire may produce irritating, corrosive and/or toxic gases.
Carbon oxides
Sulfur oxides
Nitrogen oxides (NO_x)
Hydrogen cyanide

Specific extinguishing methods : Remove undamaged containers from fire area if it is safe to do so.
Use a water spray to cool fully closed containers.

Further information : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment : Firefighters should wear protective clothing and self-contained for fire-fighters breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Use personal protective equipment.
If it can be safely done, stop the leak.
Do not touch or walk through the spilled material.
Never return spills in original containers for re-use.
Mark the contaminated area with signs and prevent access to unauthorized personnel.
Only qualified personnel equipped with suitable protective equipment may intervene.
For disposal considerations see section 13.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Never return spills in original containers for re-use.
Collect as much of the spill as possible with a suitable absorbent material.
Pick up and transfer to properly labeled containers.
Keep in suitable, closed containers for disposal.

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors).
Keep away from open flames, hot surfaces and sources of ignition.

Advice on safe handling : For personal protection see section 8.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Avoid formation of respirable particles.
Dispose of rinse water in accordance with local and national regulations.
Smoking, eating and drinking should be prohibited in the application area.

Avoid formation of aerosol.
Do not breathe vapors/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Prevent unauthorized access.
No smoking.
Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified	64742-56-9	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Personal protective equipment

Respiratory protection	:	In the case of dust or aerosol formation use respirator with an approved filter. No personal respiratory protective equipment normally required.
Hand protection	:	
Material	:	Protective gloves
Remarks	:	The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	:	Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Protective measures	:	Plan first aid action before beginning work with this product.
Hygiene measures	:	General industrial hygiene practice. Avoid contact with skin, eyes and clothing. Do not inhale aerosol. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	:	liquid
Color	:	dark amber
Odor	:	hydrocarbon-like
Odor Threshold	:	No data available
pH	:	No data available
Melting point/ range	:	No data available
Boiling point/boiling range	:	No data available

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Flash point	:	108.5 °F / 42.5 °C
		Method: closed cup
Evaporation rate	:	No data available
Flammability (liquids)	:	Sustains combustion
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	7.74 lb/gal
Solubility(ies)		
Water solubility	:	emulsifiable
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Non-oxidizing
Molecular weight	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
------------	---	---

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Chemical stability	:	No decomposition if stored and applied as directed.
Possibility of hazardous reactions	:	No decomposition if stored and applied as directed. Vapors may form explosive mixture with air.
Conditions to avoid	:	Avoid extreme temperatures. Avoid formation of aerosol. Heat, flames and sparks.
Incompatible materials	:	Avoid strong acids, bases, and oxidizers.
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Toxic if swallowed.
Harmful in contact with skin.
Fatal if inhaled.

Product:

Acute oral toxicity	:	LD50 (Rat): 59.9 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 0.265 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rabbit): > 1,520 mg/kg

Components:

carbosulfan (ISO):

Acute oral toxicity	:	LD50 (Rat, female): 185 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, female): 0.15 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 (Rat): > 2,000 mg/kg

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Acute oral toxicity	:	LD50 (Rat, female): 3,492 mg/kg
Acute inhalation toxicity	:	LC50 (Rat, male and female): > 6.193 mg/l Exposure time: 4 h Test atmosphere: vapor Assessment: The substance or mixture has no acute inhalation toxicity

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,160 mg/kg

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat, male and female): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LD50 (Rat, male and female): > 1.9 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male and female): > 4,000 mg/kg
Remarks: Based on data from similar materials

2-ethylhexan-1-ol:

Acute oral toxicity : LD50 (Rat, male): 2,047 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4.3 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat, male and female): > 3,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Product:

Species	:	Rabbit
Assessment	:	Causes mild skin irritation.
Result	:	slight irritation

Components:

carbosulfan (ISO):

Species	:	Rabbit
Result	:	slight irritation

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Mild skin irritation

Assessment	:	Repeated exposure may cause skin dryness or cracking.
------------	---	---

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Species	:	Rabbit
Result	:	No skin irritation
Remarks	:	Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Assessment	:	Irritating to skin.
------------	---	---------------------

2-ethylhexan-1-ol:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Species	:	Rabbit
Result	:	Irritation to eyes, reversing within 21 days
Assessment	:	Irritating to eyes.

Components:

carbosulfan (ISO):

Species	:	Rabbit
Result	:	slight irritation

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Species	:	Rabbit
---------	---	--------

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Result : No eye irritation

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Species	: Rabbit
Result	: No eye irritation
Method	: OECD Test Guideline 405
Remarks	: Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Assessment : Risk of serious damage to eyes.

2-ethylhexan-1-ol:

Species	: Rabbit
Result	: Irritation to eyes, reversing within 21 days
Method	: OECD Test Guideline 405

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Based on available data, the classification criteria are not met.

Product:

Species	: laboratory animal
Result	: Probability or evidence of low to moderate skin sensitization rate in humans
Remarks	: Causes sensitization.

Components:

carbosulfan (ISO):

Test Type	: Buehler Test
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: Not a skin sensitizer.

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Test Type	: Maximization Test
Species	: Guinea pig
Method	: OECD Test Guideline 406

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Test Type	: Buehler Test
Routes of exposure	: Skin contact
Species	: Guinea pig

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Method	:	OECD Test Guideline 406
Result	:	Not a skin sensitizer.
Remarks	:	Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Test Type	:	Buehler Test
Species	:	Guinea pig
Result	:	Not a skin sensitizer.
Remarks	:	Based on data from similar materials

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Components:

carbosulfan (ISO):

Genotoxicity in vitro	:	Test Type: reverse mutation assay Test system: Salmonella typhimurium Result: negative Test Type: reverse mutation assay Test system: Escherichia coli Result: negative Test Type: gene mutation test Test system: Chinese hamster cells Result: negative Test Type: Chromosome aberration test in vitro Test system: Chinese hamster cells Result: negative
Genotoxicity in vivo	:	Test Type: chromosome aberration assay Species: mice Result: negative

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Genotoxicity in vitro	:	Test Type: reverse mutation assay Metabolic activation: with and without metabolic activation Result: negative
Genotoxicity in vivo	:	Test Type: Bone marrow chromosome aberration. Species: Rat Result: negative

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Genotoxicity in vitro	:	Test Type: reverse mutation assay Metabolic activation: Metabolic activation Method: OECD Test Guideline 471 Result: positive
-----------------------	---	--

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (male and female)
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative
Remarks: Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Genotoxicity in vitro : Test Type: reverse mutation assay
Method: OECD Test Guideline 471
Result: negative
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse (male and female)
Application Route: Intraperitoneal injection
Exposure time: 72 hrs
Method: Mutagenicity (micronucleus test)
Remarks: Based on data from similar materials

2-ethylhexan-1-ol:

Genotoxicity in vitro : Test Type: reverse mutation assay
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test
Species: Mouse
Application Route: Intraperitoneal injection
Result: negative

Carcinogenicity

Suspected of causing cancer.

Product:

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies

Components:

carbosulfan (ISO):

Species : Mouse
Exposure time : 2 Years
NOAEL : 2.5 mg/kg bw/day
Result : negative

Species : Rat
Exposure time : 2 Years
NOAEL : 1 mg/kg bw/day

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Result : negative

Carcinogenicity - Assessment : Weight of evidence does not support classification as a carcinogen

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Species : Mouse, female
Application Route : Dermal
Exposure time : 78 weeks
Result : negative
Remarks : Based on data from similar materials

2-ethylhexan-1-ol:

Species : Rat
Application Route : Oral
Exposure time : 24 month(s)
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Components:

carbosulfan (ISO):

Effects on fertility : Test Type: Three-generation study
Species: Rat
Application Route: Oral
General Toxicity Parent: NOAEL: 1.2 mg/kg bw/day
Fertility: NOAEL: 1.2 mg/kg bw/day
Result: negative

Effects on fetal development : Test Type: Embryo-fetal development
Species: Rat
Application Route: Oral
General Toxicity Maternal: NOAEL: 2 mg/kg bw/day
Developmental Toxicity: NOAEL: 2
Result: negative

Test Type: Embryo-fetal development
Species: Rabbit
Application Route: Oral
General Toxicity Maternal: NOAEL: 5 mg/kg bw/day

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Developmental Toxicity: NOAEL: 10
Result: negative

Reproductive toxicity - Assessment : Weight of evidence does not support classification for reproductive toxicity

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Effects on fertility : Test Type: Three-generation study
Species: Rat
Application Route: Inhalation
Result: negative

Effects on fetal development : Test Type: Pre-natal
Species: Rat
Application Route: inhalation (vapor)
Method: OECD Test Guideline 414
Result: negative
Remarks: Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Effects on fertility : Test Type: one-generation reproductive toxicity
Species: Rat, male and female
Application Route: Oral
Method: OECD Test Guideline 415
Result: No effects on fertility and early embryonic development were detected.

2-ethylhexan-1-ol:

Effects on fetal development : Test Type: Embryo-fetal development
Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 414
Result: negative

STOT-single exposure

May cause respiratory irritation.
May cause drowsiness or dizziness.
Causes damage to organs (Nervous system).

Product:

Target Organs : Nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

Components:

carbosulfan (ISO):

Target Organs : Nervous system, Bladder, Gastro-intestinal system, Blood
Assessment : The substance or mixture is classified as specific target organ

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

toxicant, single exposure, category 1.

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or dizziness.

2-ethylhexan-1-ol:

Assessment : May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Nervous system) through prolonged or repeated exposure.

Product:

Target Organs : Nervous system
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Components:

carbosulfan (ISO):

Target Organs : Nervous system, Bladder, Gastro-intestinal system, Blood
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 1.

Repeated dose toxicity

Components:

carbosulfan (ISO):

Species : Rat
NOAEL : 2 mg/kg bw/day
Application Route : Oral
Exposure time : 90 days

Species : Dog
NOAEL : 1.6 mg/kg bw/day
Application Route : Oral
Exposure time : 6 months

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Species : Rat, males
NOAEC : 1.8 mg/l
Application Route : inhalation (vapor)
Exposure time : 12 months
Remarks : Based on data from similar materials

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Species : Rat, male and female

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

NOAEL : 500 mg/kg
Application Route : Oral
Method : OECD Test Guideline 407
Remarks : Based on data from similar materials

Species : Rat, male and female
NOAEL : 50 mg/m³
Application Route : Inhalation
Method : OECD Test Guideline 412
Remarks : Based on data from similar materials

Species : Rat, male and female
NOAEL : > 1,000 mg/kg
Application Route : Dermal
Method : OECD Test Guideline 410
Remarks : Based on data from similar materials

2-ethylhexan-1-ol:

Species : Rat
: 250 mg/kg
Application Route : Oral
Exposure time : 13 Weeks
Method : OECD Test Guideline 408

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Components:

carbosulfan (ISO):

The substance does not have properties associated with aspiration hazard potential.

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
Concentrations substantially above the TLV value may cause narcotic effects.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

carbosulfan (ISO):

Toxicity to fish	:	LC50 (Lepomis macrochirus (Bluegill sunfish)): 0.015 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 0.0015 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (microalgae)): > 20 mg/l Exposure time: 96 h
Toxicity to fish (Chronic toxicity)	:	NOEC (Pimephales promelas (fathead minnow)): 0.00828 mg/l Exposure time: 21 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC (Daphnia magna (Water flea)): 0.0032 mg/l Exposure time: 21 d
Toxicity to terrestrial organisms	:	(Apis mellifera (bees)): 1.035 µg/bee Remarks: Oral (Apis mellifera (bees)): 0.18 µg/bee Remarks: Contact LD50 (Anas platyrhynchos (Mallard duck)): 10 mg/kg

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: water accommodated fractions (WAF)
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 3.2 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	NOELR (Pseudokirchneriella subcapitata (green algae)): 0.22 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 EL50 (Pseudokirchneriella subcapitata (green algae)): 7.9

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (activated sludge): > 99 mg/l
Exposure time: 10 min
Method: OECD Test Guideline 209

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): 1,000 mg/l
Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test Type: semi-static test
Method: OECD Test Guideline 211

Toxicity to microorganisms : NOEL: > 1.93 mg/l
Exposure time: 0.16 h

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Toxicity to fish : LL50 (Marine species): 10,000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

LL50 (Pimephales promelas (fathead minnow)): 1,000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l
Exposure time: 48 h
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l
Exposure time: 96 h
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC (activated sludge): 10,000 mg/l
Method: OECD Test Guideline 209
GLP: yes

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

2-ethylhexan-1-ol:

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 17.1 - 28.2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 39 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC10 (Desmodesmus subspicatus (green algae)): 3.2 mg/l
Exposure time: 72 h

EC50 (Desmodesmus subspicatus (green algae)): 11.5 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50 (Anabaena flos-aquae (cyanobacterium)): 16.6 mg/l
Exposure time: 72 h

Persistence and degradability

Components:

carbosulfan (ISO):

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 28 %
Exposure time: 28 d

Stability in water : Remarks: Hydrolyzes readily.

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified:

Biodegradability : Result: Inherently biodegradable.
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Biodegradability : Result: Not readily biodegradable.

2-ethylhexan-1-ol:

Biodegradability : Result: Readily biodegradable.

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

carbosulfan (ISO):

Bioaccumulation : Species: Fish
Bioconcentration factor (BCF): 990
Remarks: Can accumulate in aquatic organisms.

Partition coefficient: n-octanol/water : log Pow: 5.37
pH: 8
Method: OECD Test Guideline 107

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics:

Partition coefficient: n-octanol/water : log Pow: 2.92 - 3.59
Method: QSAR

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts:

Partition coefficient: n-octanol/water : log Pow: 22.1

2-ethylhexan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 2.9 (77 °F / 25 °C)

Mobility in soil

Components:

carbosulfan (ISO):

Distribution among environ- : Remarks: Slightly mobile in soils

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

mental compartments

Stability in soil :

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	:	UN 2991
Proper shipping name	:	CARBAMATE PESTICIDE, LIQUID, TOXIC, FLAMMABLE (Carbosulfan, Carbofuran)
Class	:	6.1
Subsidiary risk	:	3
Packing group	:	II
Labels	:	6.1 (3)
Environmentally hazardous	:	yes

IATA-DGR

UN/ID No.	:	UN 2991
Proper shipping name	:	Carbamate pesticide, liquid, toxic, flammable

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

(Carbosulfan, Carbofuran)

Class	: 6.1
Subsidiary risk	: 3
Packing group	: II
Labels	: Toxic, Flammable Liquids
Packing instruction (cargo aircraft)	: 662
Packing instruction (passenger aircraft)	: 654
Environmentally hazardous	: yes

IMDG-Code

UN number	: UN 2991
Proper shipping name	: CARBAMATE PESTICIDE, LIQUID, TOXIC, FLAMMABLE (Carbosulfan, Carbofuran)
Class	: 6.1
Subsidiary risk	: 3
Packing group	: II
Labels	: 6.1 (3)
EmS Code	: F-E, S-D
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR Road

UN/ID/NA number	: UN 2991
Proper shipping name	: Carbamate pesticides, liquid, toxic, flammable (Carbosulfan, Carbofuran)
Class	: 6.1
Subsidiary risk	: 3
Packing group	: II
Labels	: TOXIC, FLAMMABLE LIQUID
ERG Code	: 131
Marine pollutant	: no

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
carbosulfan (ISO)	55285-14-8	1000	3731

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

2-ethylhexan-1-ol	104-76-7	>= 1 - < 5 %
-------------------	----------	--------------

Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A:

naphthalene	91-20-3	>= 0 - < 0.1 %
-------------	---------	----------------

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3:

naphthalene	91-20-3	>= 0 - < 0.1 %
-------------	---------	----------------

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Distillates (petroleum), solvent-dewaxed light paraffinic;	64742-56-9
Baseoil — unspecified	
2-ethylhexan-1-ol	104-76-7

Pennsylvania Right To Know

Aromatic hydrocarbons, C9; Alkylbenzenes; C9-aromatics	128601-23-0
Distillates (petroleum), solvent-dewaxed light paraffinic;	64742-56-9
Baseoil — unspecified	
carbosulfan (ISO)	55285-14-8
Soybean oil, epoxidized	8013-07-8
2-ethylhexan-1-ol	104-76-7
naphthalene	91-20-3

Maine Chemicals of High Concern

Product does not contain any listed chemicals

Vermont Chemicals of High Concern

Product does not contain any listed chemicals

Washington Chemicals of High Concern

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Product does not contain any listed chemicals

California Prop. 65

WARNING: This product can expose you to chemicals including naphthalene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California List of Hazardous Substances

Distillates (petroleum), solvent-dewaxed light paraffinic; Baseoil — unspecified	64742-56-9
---	------------

The ingredients of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: Product contains substance(s) not listed on TSCA inventory.
AIIC	: Not in compliance with the inventory
DSL	: This product contains chemical substance(s) exempt from CEPA DSL Inventory requirements. It is regulated as a pesticide subject to Pest Control Products Act (PCPA) requirements. Read the PCPA label, authorized under the Pest Control Products Act, prior to using or handling this pest control product.
ENCS	: Not in compliance with the inventory
ISHL	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: Not in compliance with the inventory
TECI	: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC


Version
1.0

Revision Date:
10/27/2025

SDS Number:
50000905

Date of last issue: -
Date of first issue: 10/27/2025

NFPA 704:



0 No health threat, 1 Slightly Hazardous, 2 Hazardous, 3 Extreme danger, 4 Deadly

HMIS® IV:

HEALTH	*	4
FLAMMABILITY		2
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL	:	USA. NIOSH Recommended Exposure Limits
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
ACGIH / TWA	:	8-hour, time-weighted average
NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI -

SAFETY DATA SHEET

according to the OSHA Hazard Communication Standard



Carbosulfan 250 g/L EC

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	10/27/2025	50000905	Date of first issue: 10/27/2025

Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

FMC Corporation believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. You can contact FMC Corporation to insure that this document is the most current available from FMC Corporation. No warranty of fitness for any particular purpose, warranty of merchantability or any other warranty, expressed or implied, is made concerning the information provided herein. The information provided herein relates only to the specified product designated and may not be applicable where such product is used in combination with any other materials or in any process. The user is responsible for determining whether the product is fit for a particular purpose and suitable for the user's conditions and methods of use. Since the conditions and methods of use are beyond the control of FMC Corporation, FMC Corporation expressly disclaims any and all liability as to any results obtained or arising from any use of the products or reliance on such information.

US / EN

Prepared by:

FMC Corporation

FMC and the FMC Logo are trademarks of FMC Corporation and/or an affiliate.

© 2021-2025 FMC Corporation. All Rights Reserved.

End of Safety Data Sheet