

GOOF OFF

Works The 1st Time!

PRO STRENGTH REMOVER



ASPHALT
& TAR*



ADHESIVE
& GLUE



DRIED LATEX
PAINT

REMOVES THE
TOUGHEST STUFF*
ULTRA FAST - ULTRA STRONG

⚠ DANGER! EXTREMELY FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY.
VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. CONTENTS UNDER PRESSURE.

Read entire label prior to use or storage.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO REPENTINO
O EXPLOTAR. VAPOR DAÑINO. NOCIVO O MORTAL SI SE INGIERE. IRRITA LOS OJOS. CONTENIDO BAJO PRESIÓN.

Lea la etiqueta completa antes de su uso o almacenamiento.

NET WEIGHT 3 OZ (85 g)

Goof Off® Pro Strength Remover cuts through the toughest adhesives quickly. It works the first time to remove what ordinary removers can't handle. Use it to eliminate costly messes and mistakes from adhesives. It works faster and better than other removers!

GREAT FOR: Crayon, Adhesives & Glue, Stickers & Decals, Caulk, Dried Latex Paint, Tar & Road Grime*, Bugs & Tree Sap*. **FOR USE ON:** Fully cured varnished and oil-base painted surfaces, baseboard, metals, glass, brick, wood, concrete, grout, fiberglass, hand tools, most automotive surfaces.

DIRECTIONS: Always use safety goggles. People with sensitive skin should use solvent resistant gloves. Apply to a cloth, then blot or rub lightly. You may need to rewash some surfaces to renew gloss. **CONCRETE, METAL:** Apply directly. Agitate with brush. Then blot, rinse or power wash residue. Repeat if necessary. **Helpful Tips:** Always test on an inconspicuous area first, as every hard surface is different. Damages many plastics, worn vinyl floors, vinyl siding, some automotive paints, and some carpets.

DANGER! EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL OTHER SOURCES OF IGNITION. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience dizziness – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** A dust mask does not provide protection against vapors.

DANGER! HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT. Contains Acetone and Xylene. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid contact with eyes and contact with skin. Avoid breathing of vapors or mist and contact with skin, eyes and clothing. Do not swallow.

⚠ WARNING: This product can expose you to chemicals including Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

FIRST AID: IF SWALLOWED, do not induce vomiting. Call the Poison Control Center (1-800-222-1222), hospital emergency room or physician immediately for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes. If irritation persists, get medical attention. **IN CASE OF SKIN CONTACT,** immediately wash with soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN.

Product Category: General Purpose Adhesive Remover • **Max VOC:** 20%.

*Regulations only allow use on painted automobile surfaces.

Product Information Hotline: 1-877-GOOFFOFF • 1-877-466-3633

For more ingredient information:

Visit www.barringredients.com or call 1-833-880-5319

©2024, W.M. Barr & Co., Inc.

Memphis, TN 38113

www.gooffproducts.com



F66583
C1367