

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 1 of 7

Revision: 06/18/2020

Supersedes Revision: 05/27/2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Goof Off Toilet Drop-Ins	
Company Name:	W. M. Barr 2105 Channel Avenue Memphis, TN 38113	Phone Number: (901)775-0100
Web site address:	www.wmbarr.com	
Emergency Contact:	3E 24 Hour Emergency Contact	(800)451-8346
Information:	W.M. Barr Customer Service	(800)398-3892
Intended Use:	Rust Stain Preventer	
Product Code:	ESX20002	

2. HAZARDS IDENTIFICATION

Self-Heating Substances, Category 1

Acute Toxicity: Inhalation, Category 4

Acute Toxicity: Oral, Category 4

Skin Corrosion/Irritation, Category 1B



GHS Signal Word: **Danger**

GHS Hazard Phrases: Self-heating; may catch fire.
Harmful if swallowed or if inhaled.
Causes severe skin burns and eye damage.
Harmful if inhaled.

GHS Precautionary Phrases: Keep cool and protect from sunlight.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash hands thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.

GHS Response Phrases: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a POISON CENTER or doctor/physician.
Specific treatment see label.
Rinse mouth.
Wash contaminated clothing before reuse.

GHS Storage and Disposal Phrases: Store locked up.
Maintain air gap between stacks/pallets.
Store bulk masses greater than 25 kg at temperatures not exceeding 30 °C.
Store away from other materials.
Dispose of contents/container according to local, state and federal regulations.

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 2 of 7

Revision: 06/18/2020

Supersedes Revision: 05/27/2015

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.
Potential Health Effects **See above.
(Acute and Chronic):

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Hazardous Components (Chemical Name)	Concentration
68140-00-1	Amides, coco, N-(hydroxyethyl) {N-(2-hydroxyethyl)dodecanamide}	20.0 -30.0 %
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	20.0 -30.0 %
7757-82-6	Sodium sulfate	5.0 -30.0 %
7775-14-6	Sodium Hydrosulfite (Dithionous acid, Disodium salt, Sodium dithionite)	10.0 -20.0 %
25265-71-8	Propanol, Oxybis- (Dipropylene glycol)	< 5.0 %
9004-62-0	Hydroxethyl cellulose	< 5.0 %
112926-00-8	Precipitated silica {Silica-Amorphous}	< 5.0 %
151-21-3	Sodium lauryl sulfate {Dodecyl sulfate, sodium salt}	< 3.0 %

Additional Chemical Information Specific percentage of composition is being withheld as a trade secret.

4. FIRST AID MEASURES

Emergency and First Aid Procedures:

INHALATION:
If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

SKIN CONTACT:
Wash with soap and large quantities of water and seek medical attention if irritation from contact persists.

EYE CONTACT:
Immediately flush with water for at least 15 minutes. Get medical attention immediately.

INGESTION:
Do not induce vomiting, unless directed to by medical personnel. Call your poison control center, hospital, emergency room, or physician immediately for instructions. Do not give anything by mouth to an unconscious person.

Signs and Symptoms Of Exposure: See Potential Health Effects.

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 3 of 7

Revision: 06/18/2020
Supersedes Revision: 05/27/2015

5. FIRE FIGHTING MEASURES

Flash Pt:	No data.
Explosive Limits:	LEL: No data. UEL: No data.
Autoignition Pt:	No data.
Suitable Extinguishing Media:	Non-combustible material - use extinguishing media for underlying cause of fire.
Unsuitable Extinguishing Media:	None known.
Fire Fighting Instructions:	Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when any material is involved in a fire.
Flammable Properties and Hazards:	None known.
Hazardous Combustion Products:	Carbon monoxide, carbon dioxide

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:	Material is solid. Sweep up and place in a suitable container for use or proper disposal according to applicable regulations.
---	---

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:	Avoid contact with eyes, skin, and clothing. Wash thoroughly after handling.
Precautions To Be Taken in Storing:	Keep away from children. Store in original packaging.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS #	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	ACGIH TLV	TLV: 3 ppm STEL: 6 ppm	
		OSHA PELs	PEL: 3 ppm	
112926-00-8	Precipitated silica {Silica-Amorphous}	ACGIH TLV	TLV: 10 mg/m3	
		OSHA PELs	PEL: 80 mg/m3/(%SiO2)	
Respiratory Equipment (Specify Type):	Not expected to be needed for the solid form of product.			
Eye Protection:	Wear safety glasses, a faceshield, or chemical safety goggles if the potential for eye contact exists.			
Protective Gloves:	Wear impermeable gloves resistant to chemicals.			
Other Protective Clothing:	Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure.			
Engineering Controls (Ventilation etc.):	Ventilation is normally not required when handling or using this product to keep exposure to airborne contaminants below the exposure limit.			
	Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.			

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 4 of 7

Revision: 06/18/2020
Supersedes Revision: 05/27/2015

Work/Hygienic/Maintenance Practices: Wash hands thoroughly after use and before eating, drinking, or smoking. Do not eat, drink, or smoke in the work area.
Discard any clothing or other protective equipment that cannot be decontaminated.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: ☐ Gas ☐ Liquid ☒ Solid
Appearance and Odor: White solid object.
pH: No data.
Melting Point: No data.
Boiling Point: No data.
Flash Pt: No data.
Evaporation Rate: No data.
Flammability (solid, gas): No data available.
Explosive Limits: LEL: No data. UEL: No data.
Vapor Pressure (vs. Air or mm Hg): No data.
Vapor Density (vs. Air = 1): No data.
Specific Gravity (Water = 1): 1.66
Density: 13.8 LB/GL
Solubility in Water: No data.
Octanol/Water Partition Coefficient: No data.
Percent Volatile: < 1.0 %
Autoignition Pt: No data.
Decomposition Temperature: No data.
Viscosity: No data.

10. STABILITY AND REACTIVITY

Stability: Unstable ☐ Stable ☒
Conditions To Avoid - Instability: No data available.
Incompatibility - Materials To Avoid: In combination with sodium sulfate, aluminum and magnesium will explode at 1472 degrees Fahrenheit; strong mineral acids and bases; strong oxidizing agents; strong acids; combustible materials; sodium chlorite
Hazardous Decomposition or Byproducts: Oxides of sulfur and sodium; carbon monoxide, carbon dioxide, nitrogen oxides, ammonia
Possibility of Hazardous Reactions: Will occur ☐ Will not occur ☒
Conditions To Avoid - Hazardous Reactions: No data available.

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 5 of 7

Revision: 06/18/2020

Supersedes Revision: 05/27/2015

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Product has not been tested as a whole. Refer to section 2 for acute and chronic effects.

CAS# 141-43-5:
Acute toxicity, LD50, Oral, Rat, 1720. MG/KG.
Result:
Brain and Coverings: Other degenerative changes.
Autonomic Nervous System: Other (direct) parasympathomimetic.
Autonomic Nervous System: Parasympatholytic.
- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN 55802, Vol/p/yr: 42,417, 1977

Open irritation test., Skin, Species: Rabbit, 505.0 MG, Moderate.
Result:
Peripheral Nerve and Sensation: Sensory change involving segmental distribution.
Behavioral: Alteration of classical conditioning.
- Union Carbide Data Sheet, Union Carbide Corp., 39 Old Ridgebury Rd., Danbury, CT 06817, Vol/p/yr: 1/13, 1972

Standard Draize Test, Eyes, Species: Rabbit, 250.0 UG, Severe.
Result:
Peripheral Nerve and Sensation: Sensory change involving segmental distribution.
Behavioral: Change in motor activity (specific assay).
Behavioral: Alteration of classical conditioning.
- American Journal of Ophthalmology., Ophthalmic Pub. Co., 435 N. Michigan Ave., Suite 1415, Chicago, IL 60611, Vol/p/yr: 29,1363, 1946

CAS# 151-21-3:
Acute toxicity, LD50, Oral, Rat, 1288. MG/KG.
Result:
Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).
- Food and Cosmetics Toxicology., For publisher information, see FCTOD7, London United Kingdom, Vol/p/yr: 5,763, 1967

Standard Draize Test, Skin, Species: Rabbit, 50.00 MG, 24 H, Severe.
Result:
Blood: Pigmented or nucleated red blood cells.
Blood: Other changes.
Blood: Changes in erythrocyte (RBC) count.
- BIOFAX Industrial Bio-Test Laboratories, Inc., Data Sheets., Vol/p/yr: 23-3, 1971

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
68140-00-1	Amides, coco, N-(hydroxyethyl) {N-(2-hydroxyethyl)dodecanamide}	n.a.	n.a.	n.a.	n.a.
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	n.a.	n.a.	n.a.	n.a.
7757-82-6	Sodium sulfate	n.a.	n.a.	n.a.	n.a.
7775-14-6	Sodium Hydrosulfite (Dithionous acid, Disodium salt, Sodium dithionite)	n.a.	n.a.	n.a.	n.a.
25265-71-8	Propanol, Oxybis- (Dipropylene glycol)	n.a.	n.a.	n.a.	n.a.

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 6 of 7

Revision: 06/18/2020
Supersedes Revision: 05/27/2015

9004-62-0	Hydroxethyl cellulose	n.a.	n.a.	n.a.	n.a.
112926-00-8	Precipitated silica {Silica-Amorphous}	n.a.	n.a.	n.a.	n.a.
151-21-3	Sodium lauryl sulfate {Dodecyl sulfate, sodium salt}	n.a.	n.a.	n.a.	n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information: Product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in accordance with all applicable local, state, and federal regulations.

14. TRANSPORT INFORMATION

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Not regulated by DOT.

Cleaning Compound, Solid.

DOT Hazard Class:

UN/NA Number:

Additional Transport Information: The shipper / supplier may be able to apply one of the following exceptions if allowed under 49 CFR Regulations: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49 CFR Hazmat Regulations. Please consult 49 CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
68140-00-1	Amides, coco, N-(hydroxyethyl) {N-(2-hydroxyethyl)dodecanamide}	No	No	No
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	No	No	No
7757-82-6	Sodium sulfate	No	No	No
7775-14-6	Sodium Hydrosulfite (Dithionous acid, Disodium salt, Sodium dithionite)	No	No	No
25265-71-8	Propanol, Oxybis- (Dipropylene glycol)	No	No	No
9004-62-0	Hydroxethyl cellulose	No	No	No
112926-00-8	Precipitated silica {Silica-Amorphous}	No	No	No
151-21-3	Sodium lauryl sulfate {Dodecyl sulfate, sodium salt}	No	No	No

CAS #	Hazardous Components (Chemical Name)	Other US EPA or State Lists
68140-00-1	Amides, coco, N-(hydroxyethyl) {N-(2-hydroxyethyl)dodecanamide}	TSCA: Inventory
141-43-5	Ethanol, 2-Amino- {Ethanolamine; Monoethanolamine; beta-Aminoethyl alcohol}	TSCA: Inventory
7757-82-6	Sodium sulfate	TSCA: Inventory
7775-14-6	Sodium Hydrosulfite (Dithionous acid, Disodium salt, Sodium dithionite)	TSCA: Inventory
25265-71-8	Propanol, Oxybis- (Dipropylene glycol)	TSCA: Inventory, 8A PAIR, 8D TERM
9004-62-0	Hydroxethyl cellulose	TSCA: Inventory

SAFETY DATA SHEET

Goof Off Toilet Drop-Ins

Page: 7 of 7

Revision: 06/18/2020

Supersedes Revision: 05/27/2015

112926-00-8 Precipitated silica {Silica-Amorphous}
151-21-3 Sodium lauryl sulfate {Dodecyl sulfate, sodium salt}
TSCA: Inventory

Additional Regulatory Information

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

16. OTHER INFORMATION

Revision Date: 06/18/2020

Preparer Name: W.M. Barr EHS Dept (901)775-0100

Additional Information About This Product: No data available.

Company Policy or Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.