MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

| IDENTITY AND DISTRIBUTOR'S INFORMATION | | | | | | | | | |
|---|--|------|--|---|----------|-------|------------|----------------|--|
| NFPA Rating: Health-1; Flammability-3; Reactivity-0; Special-0 HMIS Rating: Health-1; Flammability-3; Reactivity-0; Personal Protection-B | | | | | | | | | |
| | | | | DOT Hazard Classification: ORM-D | | | | | |
| Address: | P. O. BOX 909 | -, - | | | | | | | |
| Address: | | | | | | | D | | |
| 1 / | | | | | | | | | |
| , , | | | | | | | | | |
| | | | Date Prepared: 12/03/97 Prepared By: DL Information Calls: (770) 422-2071 | | | | | | |
| SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION | | | | | | | | | |
| COMPONENTS-CHEMICAL NAMES AND COMMON NAMES | | | CAS Number | SARA | OSHA PEL | ACGIH | Carcinogen | | |
| | 1% or greater; Carcinogens 0.1% or greater) | | | | III LIST | (ppm) | TLV (ppm) | Ref. Source ** | |
| The specific chemical identities of the ingredients of this mixture are considered to be trade secrets and are in accordance with the provisions of section 1910:1200 of Title 29 of the Code of Federal Regulations. | | | | NJ TSRN 238BA | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS | | | | | | | | | |
| Boiling Point: N/A Specific Gravity (H2O=1): Concentrate Only = < 1 | | | | | | | | | |
| - · | | | • | /apor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A | | | | | |
| | • ' | | | Evaporation Rate (= 1): N/E | | | | | |
| | | | | Vater Reactive: No | | | | | |
| Appearance and Odor: Clear liquid with fragrance. | | | | | | | | | |
| SECTION 3 - FIRE AND EXPLOSION HAZARD DATA | | | | | | | | | |
| | LAMMABILITY as per USA FLAME PROJECTION TEST Auto Ignition Temperature Flammability Limits in Air by % in Volume | | | | | | | | |
| | | | SPECIAL FIRE FIGHTING PROCEDURES: Provide shielding for personnel. | | | | | | |
| | | | Wear self-contained breathing apparatus. Cool containers with water fog to | | | | | | |
| | | | prevent rupturing & spewing. | | | | | | |
| Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture. | | | | | | | | | |
| SECTION 4 - REACTIVITY HAZARD DATA | | | | | | | | | |
| STABILITY [X] STABLE [] UNSTABLE HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR | | | | | | | OCCUR | | |
| Incompatibility (Mat. to avoid): Alkalis, oxidizing materials, amines. Conditions to Avoid: Open flame, welding arcs | | | | | | | - | | |
| Hazardous Decomposition Products: CO, CO2. | | | | | | | | | |
| SECTION 5 - HEALTH HAZARD DATA | | | | | | | | | |
| PRIMARY ROUTES OF ENTRY: [X]INHALATION []INGESTION []SKIN ABSORPTION []EYE []NOT HAZARDOUS | | | | | | | | | |
| ACUTE EFFECTS Vapor concentrations around 1000 ppm may cause slight transient irritation to the upper respiratory tract. | | | | | | | | | |
| Inhalation: Excessive inhalation of vapors can be harmful and may cause headache, dizziness, asphyxia, anesthetic effects and possible unconsciousness. | | | | | | | | | |
| Eye Contact: Irritation. Skin Contact: May cause slight irritation. | | | | | | | | | |
| Ingestion: Possible chemical pneumonitis if aspirated into lungs. Nausea. | | | | | | | | | |
| CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) May cause mucous membrane irritation, overnight headache, and general weakness. | | | | | | | | | |
| Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions. | | | | | | | | | |
| EMERGENCY FIRST AID PROCEDURES | | | | | | | | | |
| Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention. | | | | | | | | | |
| Skin Contact: Wash with soap and water. If irritated, seek medical attention. | | | | | | | | | |
| Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention. | | | | | | | | | |
| Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention. | | | | | | | | | |
| SECTION 6 - CONTROL AND PROTECTIVE MEASURES | | | | | | | | | |
| Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by U.S. Bureau of Mines for organic vapor. | | | | | | | | | |
| Protective Gloves: Latex, if skin easily irritated. Eye Protection: Safety glasses recommended. | | | | | | | | | |
| Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV. | | | | | | | | | |
| Other Protective Clothing & Equipment: None | | | | | | | | | |
| Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing. | | | | | | | | | |
| SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE | | | | | | | | | |
| Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER. | | | | | | | | | |
| | s: Aerosol cans when vented to atmospheric pr | | | <u> </u> | | | | | |
| Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F. | | | | | | | | | |
| Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors. Remove ignition sources. | | | | | | | | | |

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only

THIS MSDS IS CURRENT AS OF JANUARY 10, 2000. The DATE PREPARED section is the original date assembled and remains current

THIS MSDS IS CURRENT AS OF JANUARY 10, 2000. The DATE PREPARED section is the original date assembled and remains current until a change is necessary. This is tracked internally at the manufacturer by these date codes and therefore must remain as the originating date.