

Stratus Building Solutions

1976 Innerbelt Business Center Dr.
St. Louis, MO 63114

MATERIAL SAFETY DATA SHEET

Revision Date: 6/3/2009

MSDS No. N-945

Emergency Phones: 314-731-2000

PLEASE NOTE: This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL and STATE RIGHT-TO-KNOW regulations. Also make this information available to any employee who requests it. It is your obligation to comply with these regulations.

SECTION I - PRODUCT IDENTITY

PRODUCT NAME: #5 Oxy Carpet N' Spot

Formula: Mixture, Hydrogen Peroxide, d-Limonene, surfactant and water.

HMS RATINGS

Health = 0 (Minimal)	Flammability = 0 (Minimal)
Reactivity = 1 (Slight)	Protection = B (Goggles and gloves)

SECTION II - HAZARDOUS INGREDIENTS

PERCENT	TLV	CARCINOGEN (OSHA/TPARC)
< 8		No
1-5	*	No

SECTION III - CHEMICAL AND PHYSICAL

Appearance: Clear Liquid	Boiling Point: 210° F
Color: Orange	Melting Point: N/A
pH: 3.0-3.5	Spec. Gravity (H ₂ O = 1): 1.00
Water Solubility: Complete	Visc. Product (mm Hg): N/A
Viscosity, Cp @ 25°C: A-3 Gardner	VOC Content: 8%

SECTION IV - FIRE AND EXPLOSION HAZARDS

Flash Point (Method): > 180 F Cl Cp. EST.	Explosion Limits: Upper: 7 Lower: 1
---	--

Extinguishing Media: Water fog, CO₂, halon system, foam for alcohols.
Special Firefighting Procedures and Hazards: In general, no special aspects.

SECTION V - REACTIVITY INFORMATION

Stable: <input checked="" type="checkbox"/>	Unstable: <input type="checkbox"/>
Precautions: Incompatibility: Oxidizing agents.	
Hazardous Decomposition Products: If in a fire, CO, CO ₂ , and hydrocarbons.	
Hazardous Polymerization: Occurs: <input type="checkbox"/> Does Not Occur: <input checked="" type="checkbox"/>	

SECTION VI - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Inhalation: Breathing of mists or vapor causes irritation. Wear approved organic mist respirator if necessary. Provide ventilation in confined spaces. Remove to fresh air. Give artificial respiration or oxygen if needed.

Skin: Extended contact may cause irritation and defatting. Wear protective gloves. Flush skin thoroughly with water for 15 minutes. Remove contaminated clothing and wash before wearing again.

Eyes: May cause irritation from misting. Flush with water for 15 minutes. If irritation persists consult a doctor.

Ingestion: May cause mild gastric disturbances or nausea. Avoid swallowing. Drink lots of water or milk. Do not induce vomiting. If irritation persists get medical attention.

Most likely routes of entry: Skin, Eyes.

Other Important Medical or Precautionary Information: None

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills and Leaks: Small spills can be flushed into normal drainage or into ground with copious amounts of water, or taken up with absorbent material. Do not drain to sewer without dilution. Larger spills should be contained by diking or other methods and held for disposal or reuse.

Storage and Handling: Keep away from heat, sparks and open flames. Check daily for any container leaks.

Waste Disposal: May be disposable in sewers if local regulations permit. Otherwise, send to licensed treatment and disposal facility for handling and disposal. Observe label precautions.

Empty Containers: Rinse well before handling and disposal. Observe label precautions.

Other Precautions: n/a

SECTION VIII - REGULATORY INFORMATION

Reportable for SARA Title III, § 313 (Form R): None

The information herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, Stratus Building Solutions cannot give any guarantees regarding information from other sources, and expressly does not make any warranties, nor assume any liability, for its use.