

Material Safety Data Sheet

May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
 (Non-Mandatory-Form)
 Form Approved
 OMB No. 1218-0072

IDENTITY (As Used on Label and List) SR #3		<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>	
Section I		NA = Not Applicable NIA = No Information Available	
Manufacturer's Name Sunburst Chemicals, Inc.		Emergency Telephone Number 1-866-303-6943 (7 days/24 hours)	
Address (Number, Street, City, State, and ZIP Code) 220 W. 86th Street		Telephone Number For Information (952) 884-3144	
Bloomington, MN 55420		Date Prepared 05-30-06	
		Signature of Preparer (optional)	

Section II - Hazardous Ingredients/Identify Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Oxalic Acid	NIA	NIA		

Section III - Physical/Chemical Characteristics

Bolling Point	212°F.	Specific Gravity (H ₂ O=1)	1.18
Vapor Pressure (mm Hg.)	NIA	Melting Point	NA
Vapor Density (AIR=1)	NIA	Evaporation Rate (Butyl Acetate = 1)	NIA
Solubility in Water Complete.			
Appearance and Odor Colorless liquid, odorless.			

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) None.	Flammable Limits	LEL NA	UEL NA
Extinguishing Media Water, CO ₂ , Dry chemical.			
Special Fire Fighting Procedures None.			
Unusual Fire and Explosion Hazards None.			

HMIS	NFPA			
2 HEALTH	HEALTH HAZARD	FIRE HAZARD Flash Points	SPECIFIC HAZARD	REACTIVITY
0 FLAMMABILITY	4 Deadly	4 Below 73°F (Boiling pt. below 100°F)	Oxidizer OX	4 May detonate
0 REACTIVITY	3 Extreme danger	3 Below 73°F (Boiling pt. at/above 100°F)	Acid ACID	3 Shock and heat may detonate
B PERSONAL PROTECTION	2 Hazardous	and/or at/above 73°F - not exceeding 100°F	Alkali ALK	2 Violent chemical change
	1 Slightly hazardous	2 Above 100°F, Not Exceeding 200°F	Corrosive COR	1 Unstable if heated
	0 Normal material	1 Above 200°F	Use NO WATER	X 0 Stable
		X 0 Will not burn	Radioactive	

Fdrive/Pubs/MSDS_Sht/Laundry/SR #3.doc

Section V - Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	

Incompatibility (*Materials to Avoid*)

Chlorine Bleach.

Hazardous Decomposition or Byproducts

Chlorine Gas.

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI - Health Hazard Data

Routes(s) of Entry:	Inhalation?	Skin?	Ingestion?
	NO	NO	NO

Health Hazards (*Acute and Chronic*)

ACUTE - irritation to eyes and skin, distress to digestive tract, poison if ingested.

CHRONIC - NIA.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Signs and Symptoms of Exposure

EXTERNAL - redness of skin or eyes, burning sensation. INTERNAL - foul taste, burning sensation in mouth and throat, nausea.

Medical Conditions Generally Aggravated by Exposure

Open sores or wounds.

Emergency and First Aid Procedures

EXTERNAL - thoroughly rinse with water for at least 15 minutes. Get medical attention if irritation persists. INTERNAL - drink a large quantity of milk, raw eggs or water. Get immediate medical attention.

Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled

Absorb spilled material with an absorbent material such as clay, sawdust, or sand. Sweep up as much of this as possible and place in a sealed, labeled container or in a proper landfill. Thoroughly rinse the affected area with water.

Waste Disposal Method

Spilled material should be collected as above for disposal in a landfill according to Federal, State, and Local regulations. Any rinsing of the affected area should also be in accordance with Federal, State and Local regulations.

Precautions to Be Taking in Handling and Storing

Keep tightly closed when not in use.

Other Precautions

Avoid contact of product (or its use solutions) with skin, eyes or clothing. Keep out of reach of children.

Section VIII - Control MeasuresRespiratory Protection (*Specify Type*)

Not required.

Ventilation	Local Exhaust	Special
	NA	NIA
	Mechanical (<i>General</i>)	Other
	NIA	NIA

Protective Gloves

Rubber or vinyl recommended.

Eye Protection

Safety glasses, goggles recommended.

Other Protective Clothing or Equipment

Not required.

Work/Hygienic Practices

Always wash hands after handling.

F:\drive\Pub\MSDS_Sht\ Laundry\SR #3.doc