



## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

#### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** **NON-SPILLABLE Battery**  
**OTHER PRODUCT NAMES:** Valve Regulated Lead Acid Battery (gel/absorbed electrolyte), Electric Storage Battery  
 Battery Non-Spillable 49 CFR 173.159a

**MANUFACTURER:** East Penn Manufacturing Company  
**ADDRESS:** Dekaroad  
 Lyon Station, PA 19536 USA

**EMERGENCY TELEPHONE NUMBERS:** US/CN: CHEMTREC 1-800-424-9300  
 Outside US/CN: CHEMTREC 1-703-527-3887






**NON-EMERGENCY HEALTH/SAFETY INFORMATION:** 610-682-6361

**CHEMICAL FAMILY:** This product is a gel/absorbed electrolyte type lead acid storage battery.

**PRODUCT USE:** Consumer/Industrial/Commercial electrical storage batteries.

#### SECTION 2: HAZARDS IDENTIFICATION

##### GHS Classification:

Health	Environmental	Physical
Acute Toxicity – Category 4 Skin Corrosion – Category 1A Eye Damage – Category 1 Reproductive – Category 1A Carcinogenicity (lead)– Category 1B Carcinogenicity (arsenic)– Category 1A Carcinogenicity(acid mist)–Category1A Specific Target Organ Toxicity (repeated exposure) –Category 2 GHS Label: <div style="display: flex; justify-content: space-around; align-items: center;">    </div>	Aquatic Chronic – 1 Aquatic Acute – 1 <div style="display: flex; justify-content: center; align-items: center;">  </div>	Explosive Chemical, Division 1.3 <div style="display: flex; justify-content: center; align-items: center;">  </div>

**Signal Word: DANGER !**



**SAFETY DATA SHEET**  
**VALVE REGULATED LEAD ACID BATTERY,**  
**NON-SPILLABLE**

<u>Hazard Statements</u>	<u>Precautionary Statements</u>
<p><b><u>Health</u></b> Harmful if swallowed, inhaled, or in contact with skin. Causes severe skin burns and eye damage. Causes serious eye damage. May damage fertility or the unborn child if ingested or inhaled. May cause cancer if ingested or inhaled. Causes damage to central nervous system, blood and kidneys through prolonged or repeated exposure if ingested or inhaled. May cause harm to breast-fed children.</p> <p><b><u>Environmental</u></b> Very toxic to aquatic life with long lasting effects.</p> <p><b><u>Physical</u></b> May form explosive air/gas mixture during charging. Extremely flammable gas (hydrogen). Explosive; fire, blast or projection hazard. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.</p>	<p><b><u>Prevention</u></b> Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing, eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Causes skin irritation, serious eye damage. Contact with internal components may cause irritation or severe burns. Avoid contact with internal acid/gel. Irritating to eyes, respiratory system, and skin. Avoid contact during pregnancy/while nursing.</p> <p><b><u>Response</u></b> IF SWALLOWED OR CONSUMED: rinse mouth, Do NOT induce vomiting. Call a poison center/doctor if you feel unwell. IF ON CLOTHING OR SKIN (or hair): Remove/Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed/concerned, or if you feel unwell seek medical attention/advice.</p> <p><b><u>Storage and Disposal</u></b> Store locked up, in a well-ventilated area. In accordance with local and national regulation. Avoid release to the environment. Collect spillage. Dispose of contents/container in accordance with local/regional/national/international regulations. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use only outdoors or in well ventilated area Keep out of reach of children.</p>

**EMERGENCY OVERVIEW:**

May form explosive air/gas mixture during charging. Contact with internal components may cause irritation or severe burns. Irritating to eyes, respiratory system, and skin. Prolonged inhalation or ingestion may result in serious damage to health. Pregnant women exposed to internal components may experience reproductive/developmental effects.

Additional Information

No health effects are expected related to normal use of this product as sold.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**INGREDIENTS (Chemical/Common Names):**

Lead and Lead Compounds, inorganic  
Electrolyte (Sulfuric acid and water)  
Antimony

**CAS No.:**

7439-92-1  
7664-93-9  
7440-36-0

**% by Wt:**

60-75 (average: 67)  
5-15 (average:10)  
0-0.1 (average:<0.1)

**EC No.:**

231-100-4  
231-639-5  
231-146-5



## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

Polypropylene

9003-07-0

2-10 (average: 4)

NA

NA – Not applicable/ND – Not determined

#### Additional Information

These ingredients reflect components of the finished product related to performance of the product as distributed into commerce. Inorganic lead, lead compounds and electrolyte (sulfuric acid) are the primary components. Other metals (ie. Sn, Cu, As) may be present at concentrations below the applicable reporting threshold.

#### **SECTION 4: FIRST AID MEASURES**

- EYE CONTACT:** Sulfuric Acid and Lead: Flush eyes immediately with large amounts of water for at least 15 minutes while lifting lids. Seek immediate medical attention if eyes have been exposed directly to acid.
- SKIN CONTACT:** Sulfuric Acid: Flush affected area(s) with large amounts of water using deluge emergency shower, if available, shower for at least 15 minutes. Remove contaminated clothing, including shoes. If symptoms persist, seek medical attention. Wash contaminated clothing before reuse. Discard contaminated shoes.  
Lead: Wash immediately with soap and water.
- INGESTION:** Sulfuric Acid: Give large amounts of water. Do NOT induce vomiting or aspiration into the lungs may occur and can cause permanent injury or death; consult physician.
- INHALATION:** Sulfuric Acid: Remove to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Consult a physician.  
Lead: Remove from exposure, gargle, wash nose and lips; consult physician.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

**FLASH POINT:** Not Applicable.

**FLAMMABLE LIMITS:** LEL= 4.1% (Hydrogen Gas in air); UEL=74.2%

**EXTINGUISHING MEDIA:** CO<sub>2</sub>; foam; dry chemical. Do not use carbon dioxide directly on cells. Avoid breathing vapors. Use appropriate media for surrounding fire.

**FIRE-FIGHTING PROCEDURES:** Use positive pressure, self-contained breathing apparatus. Beware of acid splatter during water application and wear acid-resistant clothing, gloves, face and eye protection. If batteries are on charge, shut off power to the charging equipment, but note that strings of series connected batteries may still pose risk of electric shock even when charging equipment is shut down.

**HAZARDOUS COMBUSTION PRODUCTS:** Highly flammable hydrogen gas is generated during charging and operation of batteries. If ignited by burning cigarette, naked flame or spark, may cause battery explosion with dispersion of casing fragments and corrosive liquid electrolyte. Carefully follow manufacturer's instructions for installation and service. Keep away all sources of gas ignition and do not allow metallic articles to simultaneously contact the negative and positive terminals of a battery.

#### Additional Information

Fire-fighting water runoff and dilution water may be toxic and corrosive and may cause adverse environmental impacts.

#### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Content is corrosive. In the event of a rupture, spill or release stop flow of material, contain/absorb small spills with dry sand, earth, and vermiculite. Do not use combustible materials. If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc. Wear acid-resistant clothing, boots, gloves, and face shield. Do not allow discharge of un-neutralized acid to sewer. Acid must be managed in accordance with approved local, state, and federal requirements. Consult state environmental agency and/or federal EPA.

#### Additional Information

**Lead acid batteries are recyclable.** Contact your East Penn representative for recycling information.

#### **SECTION 7: HANDLING AND STORAGE**



## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

**Handling:** Unless involved in recycling operations, do not breach the casing or empty the contents of the battery. There may be increasing risk of electric shock from strings of connected batteries. Keep containers tightly closed when not in use. If battery case is broken, avoid contact with internal components. Keep vent caps on and cover terminals to prevent short circuits. Place cardboard between layers of stacked automotive batteries to avoid damage and short circuits. Keep away from combustible materials, organic chemicals, reducing substances, metals, strong oxidizers and water. Use banding or stretch wrap to secure items for shipping.

**Storage:** Store batteries under roof in cool, dry, well-ventilated areas separated from incompatible materials and from activities that may create flames, spark or heat. Store on smooth, impervious surfaces provided with measures for liquid containment in the rupture, spill or release of electrolyte. Keep away from metallic objects that could bridge the terminals on a battery and create a dangerous short-circuit.

**Charging:** There is a possible risk of electric shock from charging equipment and from strings of series connected batteries, whether or not being charged. Shut-off power to chargers whenever not in use and before detachment of any circuit connections. Batteries being charged will generate and release flammable hydrogen gas. Charging space should be ventilated. Keep battery vent caps in position. Prohibit smoking and avoid creation of flames and sparks nearby. Wear face and eye protection when near batteries being charged.

#### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

##### Exposure Limits (mg/m<sup>3</sup>)

Ingredients	OSHA PEL	ACGIH	US NIOSH	Quebec PEV	Ontario OEL	EU OEL
Lead, inorganic	0.05	0.05	0.05	0.05	0.05	0.15 (b)
Antimony	0.5	0.5	0.5	0.5	0.5	0.5 (b,d)
Tin	2	2	2			
Copper	1	1	1	1	1 (a)	0.1 (e)
Arsenic	0.01	0.01	0.01			
Sulfuric Acid	1	0.2	1	1	0.2	0.05 (c)
Polypropylene	N.E.	N.E.	N.E.	N.E.	N.E.	N.E.

(a) As dusts/mists (b) As inhalable aerosol (c) Thoracic fraction (d) Based on OEL's of Austria, Belgium, Denmark, France, Netherlands, Switzerland, & U.K. (e) Based on OEL of Netherlands

##### ENGINEERING CONTROLS/SYSTEM DESIGN INFORMATION:

Store and handle in well-ventilated area. If mechanical ventilation is used, components must be acid-resistant. Handle batteries cautiously to avoid rupture, spill or release. Make certain vent caps are on securely. If battery case is damaged, avoid bodily contact with internal components. Wear protective clothing, eye and face protection, charging or handling batteries. Do not allow metallic materials to simultaneously contact both the positive and negative terminals of the batteries. Charge batteries in areas with adequate ventilation. General dilution ventilation is acceptable.

##### RESPIRATORY PROTECTION (NIOSH/MSHA approved):

None required under normal conditions. When concentrations of sulfuric acid mist are known to exceed PEL, use NIOSH or MSHA-approved respiratory protection.

##### EYE PROTECTION:

If battery case is damaged, use chemical goggles or face shield.

##### SKIN PROTECTION:

If battery case is damaged, use rubber or plastic acid-resistant gloves with elbow-length gauntlet, acid-resistant apron, clothing and boots.

**OTHER PROTECTION:** In areas where water and sulfuric acid solutions are handled in concentrations greater than 1%, emergency eyewash stations and showers should be provided, with unlimited water supply.



**Wash Hands after handling.**



## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

#### Additional Information

-  Batteries are housed in polypropylene cases which are regulated as total dust or respirable dust only when they are ground up during recycling. The OSHA PEL for dust is 15 mg/m<sup>3</sup> as total dust or 5 mg/m<sup>3</sup> as respirable dust.
-  May be required to meet Domestic Requirements for a Specific Destination(s).

#### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE:</b>	Industrial/commercial lead acid battery
<b>ODOR:</b>	Odorless
<b>ODOR THRESHOLD:</b>	Manufactured article; no apparent odor. Electrolyte is a gel with a sharp, penetrating, pungent odor.
<b>PHYSICAL STATE:</b>	Sulfuric Acid: Liquid/Gel; Lead: solid
<b>pH:</b>	~1 to 2
<b>BOILING POINT:</b>	203-240° F (as sulfuric acid)
<b>MELTING POINT:</b>	NA
<b>FREEZING POINT:</b>	NA
<b>VAPOR PRESSURE:</b>	10 mmHg
<b>VAPOR DENSITY (AIR = 1):</b>	> 1
<b>SPECIFIC GRAVITY (H<sub>2</sub>O = 1):</b>	1.27-1.33
<b>EVAPORATION RATE (n-BuAc=1):</b>	< 1
<b>SOLUBILITY IN WATER:</b>	100% (as sulfuric acid)
<b>FLASH POINT:</b>	Below room temperature (as hydrogen gas)
<b>AUTO-IGNITION TEMPERATURE:</b>	NA
<b>LOWER EXPLOSIVE LIMIT (LEL):</b>	4% (as hydrogen gas)
<b>UPPER EXPLOSIVE LIMIT (UEL):</b>	74% (as hydrogen gas)
<b>PARTITION COEFFICIENT:</b>	NA
<b>VISCOSITY (poise @ 25° C):</b>	Not Available
<b>DECOMPOSITION TEMPERATURE:</b>	Not Available

#### SECTION 10: STABILITY AND REACTIVITY

<b>STABILITY:</b>	This product is stable under normal conditions at ambient temperature.
<b>INCOMPATIBILITY (MATERIAL TO AVOID):</b>	<u>Electrolyte:</u> Contact with combustibles and organic materials may cause fire and explosion. Also reacts violently with strong reducing agents, metals, sulfur trioxide gas, strong oxidizers, and water. Contact with metals may produce toxic sulfur dioxide fumes and may release flammable hydrogen gas. <u>Lead compounds:</u> Avoid contact with strong acids, bases, halides, halogenates, potassium nitrate, permanganate, peroxides, nascent hydrogen, and reducing agents. <u>Arsenic compounds:</u> strong oxidizers; bromine azide. NOTE: hydrogen gas can react with inorganic arsenic to form the highly toxic gas-arsine
<b>HAZARDOUS DECOMPOSITION BY-PRODUCTS:</b>	<u>Electrolyte:</u> Sulfur trioxide, carbon monoxide, sulfuric acid mist, sulfur dioxide, hydrogen sulfide. <u>Lead compounds:</u> Temperatures above the melting point are likely to produce toxic metal fume, vapor, or dust; contact with strong acid or base or presence of nascent hydrogen may generate highly toxic arsine gas.
<b>HAZARDOUS POLYMERIZATION:</b>	Will not occur
<b>CONDITIONS TO AVOID:</b>	Prolonged overcharge at high current; sources of ignition.

#### SECTION 11: TOXICOLOGICAL INFORMATION

##### ACUTE TOXICITY (Test Results Basis and Comments):

Inhalation LD<sub>50</sub>:

Electrolyte: LC<sub>50</sub> rat 375 mg/m<sup>3</sup> ; LC<sub>50</sub> guinea pig: 510 mg/m<sup>3</sup>



## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

Elemental Lead: Acute Toxicity Point Estimate =4500 ppm V (based on lead bullion)

Elemental Arsenic: No data

Oral LD<sub>50</sub>:

Electrolyte: rat 2140 mg/kg

Elemental Lead: Acute Toxicity Estimate (ATE) = 500mg/kg body weight (based on lead bullion)

Elemental Arsenic: LD<sub>50</sub> mouse: 145 mg/kg

Elemental Antimony: LD<sub>50</sub> rat: 100 mg/kg

**Routes of Entry:** Sulfuric Acid: Harmful by all routes of entry. Lead Compounds: Hazardous exposure can occur only when product is heated, oxidized or otherwise processed or damaged to create dust, vapor or fume. The presence of nascent hydrogen may generate highly toxic arsine gas.

**Inhalation:** Sulfuric Acid: Breathing of sulfuric acid vapors or mists may cause severe respiratory irritation.

Lead Compounds: Inhalation of lead dust or fumes may cause irritation of upper respiratory tract and lungs.

**Ingestion:** Sulfuric Acid: May cause severe irritation of mouth, throat, esophagus and stomach. Lead Compounds: Acute ingestion may cause abdominal pain, nausea, vomiting, diarrhea and severe cramping. This may lead rapidly to systemic toxicity and must be treated by a physician.

**Skin Contact:** Sulfuric Acid: Severe irritation, burns and ulceration. Lead Compounds: Not absorbed through the skin.

Arsenic Compounds: Contact may cause dermatitis and skin hyperpigmentation.

**Eye Contact:** Sulfuric Acid: Severe irritation, burns, cornea damage, and blindness.

Lead Compounds: May cause eye irritation.

**Effects of Overexposure Acute:** Sulfuric Acid: Severe skin irritation, damage to cornea, upper respiratory irritation. Lead Compounds: Symptoms of toxicity include headache, fatigue, abdominal pain, loss of appetite, muscular aches and weakness, sleep disturbances and irritability.

**Effects of Overexposure – Chronic:** Sulfuric Acid: Possible erosion of tooth enamel, inflammation of nose, throat & bronchial tubes. Lead Compounds: Anemia; neuropathy, particularly of the motor nerves, with wrist drop; kidney damage; reproductive changes in males and females. Repeated exposure to lead and lead compounds in the workplace may result in nervous system toxicity. Some toxicologists report abnormal conduction velocities in persons with blood lead levels of 50µg/100 ml or higher. Heavy lead exposure may result in central nervous system damage, encephalopathy and damage to the blood-forming (hematopoietic) tissues.

**Carcinogenicity:** Sulfuric Acid: The International Agency for Research on Cancer (IARC) has classified “strong inorganic acid mist containing sulfuric acid” as a Category I carcinogen, a substance that is carcinogenic to humans. This classification does not apply to liquid forms of sulfuric acid or sulfuric acid solutions contained within a battery. Inorganic acid mist (sulfuric acid mist) is not generated under normal use of this product. Misuse of the product, such as overcharging, may result in the generation of sulfuric acid mist. Lead Compounds: Lead is listed as a 2B carcinogen, likely in animals at extreme doses. Proof of carcinogenicity in humans is lacking at present. Arsenic: Listed by National Toxicology Program (NTP), International Agency for Research on Cancer (IARC), OSHA and NIOSH as a carcinogen only after prolonged exposure at high levels.

**Medical Conditions Generally Aggravated by Exposure:** Overexposure to sulfuric acid mist may cause lung damage and aggravate pulmonary conditions. Contact of sulfuric acid with skin may aggravate diseases such as eczema and contact dermatitis. Lead and its compounds can aggravate some forms of kidney, liver and neurologic diseases.

#### Additional Health Data:

All heavy metals, including the hazardous ingredients in this product, are taken into the body primarily by inhalation and ingestion. Most inhalation problems can be avoided by adequate precautions such as ventilation and respiratory protection covered in Section 8. Follow good personal hygiene to avoid inhalation and ingestion: wash hands, face, neck and arms thoroughly before eating, smoking or leaving the work site. Keep contaminated clothing out of non-contaminated areas, or wear cover clothing when in such areas. Restrict the use and presence of food, tobacco and cosmetics to non-contaminated areas. Work clothes and work equipment used in contaminated areas must remain in designated areas and never taken home or laundered with personal non-contaminated clothing. This product is intended for industrial use only and should be isolated from children and their environment.

The 19<sup>th</sup> Amendment to EC Directive 67/548/EEC classified lead compounds, but not lead in metal form, as possibly toxic to reproduction. Risk phrase 61: May cause harm to the unborn child, applies to lead compounds, especially soluble forms.





## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

#### SECTION 12: ECOLOGICAL INFORMATION

**Environmental Fate:** Lead is very persistent in soil and sediments. No data on environmental degradation. Mobility of metallic lead between ecological compartments is slow. Bioaccumulation of lead occurs in aquatic and terrestrial animals and plants but little bioaccumulation occurs through the food chain. Most studies include lead compounds and not elemental lead.

**Environmental Toxicity:**

Sulfuric acid: 24-hr LC<sub>50</sub>, fresh water fish (*Brachydanio rerio*): 82 mg/l  
96-hr LOEC, fresh water fish (*Cyprinus carpio*): 22 mg/l (lowest observable effect concentration)  
Lead : 48-hr LC<sub>50</sub> (modeled for aquatic invertebrates): <1mg/L, based on lead bullion  
Arsenic: 24-hr LC<sub>50</sub>, freshwater fish (*Carrassius auratus*)>5000g/L

Additional Information

- ☐ No known effects on stratospheric ozone depletion.
- ☐ Volatile organic compounds: 0% (by Volume)
- ☐ Water Endangering Class (WGK): NA

#### SECTION 13: DISPOSAL CONSIDERATIONS (UNITED STATES)

**WASTE DISPOSAL  
METHOD:**

Spent batteries: Send to secondary lead smelter for recycling. Contact your East Penn Mfg. representative for more information related to lead acid battery recycling. Spent lead acid batteries are not regulated as hazardous waste when the requirements of 40 CFR Section 266.80 are met. If applicable; EPA hazardous waste number D002 (corrosivity) and D008 (lead). Electrolyte: Place neutralized slurry into sealed acid resistant containers and dispose of as hazardous waste, as applicable. Large water diluted spills, after neutralization and testing, should be managed in accordance with approved local, state, and federal requirements. Consult state environmental agency and/or federal EPA. Follow local, State/Provincial, and Federal/National regulations applicable to as-used, end-of-life characteristics to be determined by end-user.

#### SECTION 14: TRANSPORT INFORMATION

Not regulated pursuant to 49 CFR 173.159a of the DOT Hazardous Materials Regulation provided that each package is marked "NON-SPILLABLE" or "NON-SPILLABLE BATTERY".

For Air shipments reference IATA Dangerous Goods Regulations Special Provision A-67.

For ocean shipments reference IMDG Special Provision #238.

Note: Batteries which have met the test requirements for "non-spillable batteries" in shipment must be protected against short circuit and securely packaged.

Label: NON-SPILLABLE

Additional Information

Transport requires proper packaging and paperwork, including the Nature and Quantity of goods, per applicable origin/destination/customs points as-shipped.

#### SECTION 15: REGULATORY INFORMATION

**INVENTORY STATUS:**

All components are listed on the TSCA; EINECS/ELINCS; and DSL, unless noted otherwise below.

**U.S. FEDERAL REGULATIONS:**

**TSCA Section 8b – Inventory Status:** All chemicals comprising this product are either exempt or listed on the TSCA Inventory.



## SAFETY DATA SHEET

### VALVE REGULATED LEAD ACID BATTERY, NON-SPILLABLE

**TSCA Section 12b** – (40 CFR Part 707.60(b)) No notice of export will be required for articles, except PCB articles, unless the Agency so requires in the context of individual section 5,6, or 7 actions.

**TSCA Section 13** –(40 CFR Part 707.20): No import certification required (EPA 305-B-99-001, June 1999, Introduction to the Chemical Import Requirements of the Toxic Substances Control Act, Section IV.A)

**RCRA:** Spent Lead Acid Batteries are subject to streamlined handling requirements when managed in compliance with 40 CFR section 266.80 or 40 CFR part 273. If applicable; EPA hazardous waste number D002 (corrosivity) and D008 (lead).

**STATE REGULATIONS (US):** \***Proposition 65 Warning Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. Batteries also contain other chemicals known to State of California to cause cancer. Wash hands after handling.**

#### **EPA SARA Title III:**

**Section 302 EPCRA Extremely Hazardous Substances (EHS):** Sulfuric acid is a listed "Extremely Hazardous Substance" under EPCRA, with a Threshold Planning Quantity (TPQ) of 1,000 lbs. EPCRA Section 302 notification is required if 500 lbs. or more of sulfuric acid is present at one site (40 CFR 370.10). For more information consult 40 CFR Part 355.

**Section 304 CERCLA Hazardous Substances:** Reportable Quantity (RQ) for spilled 100% sulfuric acid under CERCLA (Superfund) and EPCRA (Emergency Planning and Community Right to Know Act) is 1,000 lbs. State and local reportable quantities for spilled sulfuric acid may vary.

**Section 311/312 Hazard Categorization:** EPCRA Section 312 Tier II reporting is required for non-automotive batteries if sulfuric acid is present in quantities of 500 lbs. or more and/or if lead is present in quantities of 10,000 lbs. or more. For more information consult 40 CFR 370.10 and 40 CFR 370.40.

**Section 313 EPCRA Toxic Substances:** 40 CFR Section 372.38(b) states: If toxic chemical is present in an article at a covered facility, a person is not required to consider the quantity of the toxic chemical present in such article when determining whether an applicable threshold has been met under 40 CFR's 372.25,372.27, or 372.28 or determining the amount of release to be reported under 40 CFR 372.30. This exemption applies whether the person received the article from another person or the person produced the article. However, this exemption applies only to the quantity of the toxic chemical present in the article.

The reporting of lead and sulfuric acid (and their releases) in lead acid batteries used in cars, trucks, most cranes, forklifts, locomotive engines, and aircraft for the purposes of EPCRA Section 313 is not required. Lead acid batteries used for these purposes are exempt for Section 313 reporting per the "Motor Vehicle Exemption." See page B-22 of the [U.S. EPA Guidance Document for Lead and Lead Compound Reporting under EPCRA Section 313](#) for additional information of this exemption.

Always check your state/local requirements as they may differ.

**Supplier Notification:** This product contains toxic chemicals that may be reportable under EPCRA Section 313 Toxic Chemical Release Inventory (Form R) requirements. For a manufacturing facility under SIC codes 20 through 39, the following information is provided to enable you to complete the required reports:

<u>Toxic Chemical</u>	<u>CAS Number</u>	<u>Approximate % by Weight</u>
Lead	7439-92-1	67
Electrolyte (Sulfuric Acid/Water Solution)	7664-93-9	10
Antimony	7440-36-0	< 1.0
Arsenic	7440-38-2	<0.1

See 40 CFR Part 370 for more details.

#### Additional Information

This product may be subject to Restriction of Hazardous Substances (RoHS) regulations in Europe and China, or may be regulated under additional regulations and laws not identified above, such as for uses other than described or as-designed/as-intended by the manufacturer, or for distribution into specific domestic destinations.

---

#### **SECTION 16: OTHER INFORMATION**

---

##### **OTHER INFORMATION:**

NFPA Hazard Rating for Sulfuric acid:





**SAFETY DATA SHEET**  
**VALVE REGULATED LEAD ACID BATTERY,**  
**NON-SPILLABLE**

Flammability (Red) = 0  
Health (Blue) = 3  
Reactivity (Yellow) = 2  
Sulfuric acid is water-reactive if concentrated.

Distribution into Quebec to follow Canadian Controlled Product Regulations (CPR) 24(1) and 24(2).  
Distribution into the EU to follow applicable Directives to the Use, Import/Export of the product as-sold.

**SDS PREPARATION INFORMATION:**

DATE OF ISSUE: 13 May 2015

**DISCLAIMER:**

This Safety Data Sheet is based upon information and sources available at the time of preparation or revision date. Information in the SDS was obtained from sources which we believe are reliable, but are beyond our direct supervision or control. We make no Warranty of Merchantability, Fitness for any particular purpose or any other Warranty, Expressed or Implied, with respect to such information and we assume no liability resulting from its use. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. It is the obligation of each user of this product to determine the suitability of this product and comply with the requirements of all applicable laws regarding use and disposal of this product. For additional information concerning East Penn Manufacturing Co. products or questions concerning the content of this SDS please contact your East Penn representative.