Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 USA **Telephone: 1-87-Permatex** 

(877) 376-2839

Emergency: 800-255-3924

International Emergency: +01-813-248-0585

**Canadian Corporate Office: ITW Permatex Canada** 8450 Lawson Road, Unit 1 Milton, ON L9T 0J8 Toll Free: (800) 924-6994

(905) 693-8900

Emergency: ChemTel (800) 255-3924

# **Material Safety Data Sheet**

#### PRODUCT IDENTIFICATION

**Product Name:** Spray Nine®

**Product Type:** Multi-Purpose Germicidal Cleaner

**Product Trade Name:** 26801

2. COMPOSITION/INFORMATION ON INGREDIENTS			
Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
2-BUTOXYETHANOL 111-76-2	1-5	20 ppm	50 ppm; 240 mg/m <sup>3</sup>
ETHOXYLATED C9-C11 ALCOHOLS 68439-46-3	1-5	NA	NA

# HAZARDS IDENTIFICATION

Product may cause reversible eye and skin irritation. **Effects of Acute Exposure:** 

May irritate respiratory system upon frequent or prolonged use

**Primary Routes of Entry:** Eye and skin contact, inhalation

Signs and Symptoms of

**Exposure:** 

Overexposure may cause eye and skin redness May cause inflammation of mucous membranes and

irritation Ingestion may cause nausea and vomiting

Medical Conditions Recognized as

Being Aggravated by Exposure:

None known. Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this

product.

**Chronic Health Hazard** None known

#### FIRST AID MEASURES

**Eye Contact:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue

flushing for at least 15 minutes. Contact a physician if irritation persists.

Immediately remove contaminated clothing and excess contaminant. Flush with water for at least 15 **Skin Contact:** 

minutes. Wash thoroughly with soap and water. Consult a physician if irritation develops

If swallowed, DO NOT induce vomiting. Give victim water, call a physician immediately. Never give Ingestion:

anything by mouth to an unconscious person

Move to fresh air; get medical attention if symptoms persist Inhalation:

Notes to Physician: Treat symptomatically

# FIRE FIGHTING MEASURES

**Hazardous Products of Combustion:** 

**Unusual Fire/Explosion Hazards:** 

Flash Point °F(C°):

Carbon dioxide, Dry chemical, Foam **Recommended Extinguishing Media:** 

**Special Fire-Fighting Procedures:** 

Wear suitable protective equipment. Use water spray to cool exposed

containers.

182°F/83°C TCC

Oxides of carbon, Oxides of nitrogen Does not sustain combustion (ASTM D4206). Sensitivity to static discharge is not expected

Sensitivity to Static Discharge: None reasonably foreseeable **Mechanical Sensitivity:** 

Product Name: Spray Nine®

#### 5. FIRE FIGHTING MEASURES

Lower Explosive Limit: Not determined Upper Explosive Limit: Not determined

#### 6. ACCIDENTAL RELEASE MEASURES

Spills may cause slippery floors. Prevent spill from entering drainage/sewer systems, waterways and surface water. Notify local health authorities and other appropriate agencies if such contamination occurs.

Mild

# 7. HANDLING AND STORAGE

Keep out of the reach of children. Keep containers tightly closed in a cool, well-ventilated place. Store below 100°F. Do not allow freezing.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses

Skin:Chemical resistant glovesVentilation:Use only in well ventilated area.Respiratory Protection:Not required under normal use

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear, colorless to slightly Odor: colored solution

Boiling Point: ~212°F/~100°C Freezing Point: ~32°F/~0°C pH: ~12.6 Solubility in Water: Completely soluble 71.022 g/ml Vapor Pressure: ~18 mm Hg

Vapor Density (Air=1): >1 % Volatile: ~9

VOC(Wt.%): <4% by weight Evaporation Rate: <1 (butyl acetate = 1)

#### 10. STABILITY AND REACTIVITY

Chemical Stability:StableHazardous Polymerization:Will not occur.Incompatabilities:Strong oxidizers

**Conditions to Avoid:** Avoid temperatures greater than 100°F. Freezing conditions.

Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen

#### 11. TOXICOLOGICAL INFORMATION

**Product Toxicity** 

 Eyes:
 Skin:
 Inhalation LC50:
 Oral LD50:

 Draize Test: 27.3 out of 110
 Draize Test 2.5 out of 10
 >200 g/L (Rat)
 >5,000 mg/kg (Rat)

LD50: >5,000 mg/kg (Rat)

#### 12. ECOLOGICAL INFORMATION

No data available

# 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

#### 14. TRANSPORTATION INFORMATION

**Ground Transport (DOT)** 

DOT Shipping Name: Not Regulated None None None

# **TDG(Transport of Dangerous Goods) Canada**

Proper Shipping Name: Not Regulated

Hazard Class: None UN/ID No: None

#### 15. REGULATORY INFORMATION

SARA 302 Extremely Hazardous

None

Substances:

Product Name: Spray Nine®

# 15. REGULATORY INFORMATION

2-butoxyethanol (Glycol ethers) **SARA 313 Toxic Chemicals:** 

Acute health hazard SARA (311, 312) Hazard Class:

**TSCA Inventory Status:** All components of this product are listed (or exempt) on the EPA TSCA inventory.

No California Prop 65 chemicals are known to be present. **California Proposition 65:** 

**WHMIS Hazard Class:** Exempt

#### 16. OTHER INFORMATION

HEALTH 1, FLAMMABILITY 0, PHYSICAL HAZARD 0, PERSONAL PROTECTION B HMIS is a registered trademark of the National Paint and Coatings Assn.

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 0, REACTIVITY 0

NFPA is a registered trademark of the National Fire Protection Assn.

Denise Boyd, Manager-Environmental, Health & Safety Prepared By: Revision Date: February 10, 2010

Permatex. Inc. 10 Columbus Blvd. Hartford, CT USA 06106 Company: Formula Index: 04

**Telephone No.:** 1-87-Permatex (877) 376-2839

#### **DISCLAIMER OF LIABILITY:**

The information contained herein is based on data we believe to be reliable as of the date of preparation of the Material Safety Data Sheet. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products may be used. We assume no liability or responsibility for loss or damage resulting from the improper or abnormal use or handlling of our products, from incompatible product combinations, from the failure to follow instructions and warnings in the product's label and Material Safety Data Sheet, or from any failure to adhere to recommended practices.