

## 1. Identification

1000016120 **Product number** 

**Product identifier** 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

**Revision date** 03-13-2018 **Company information** Sprayway, Inc.

1000 INTEGRAM DR

Pacific, MO 63069 United States

Company phone 1-630-628-3000 **Emergency telephone US** 1-866-836-8855 **Emergency telephone outside** 1-952-852-4646

Version # 02

Supersedes date 03-12-2018 Recommended use Cleaner Recommended restrictions None known.

## 2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas Health hazards Skin corrosion/irritation Category 2 Serious eve damage/eve irritation Category 2A

Carcinogenicity Category 2 Reproductive toxicity Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated Category 2

exposure

**OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye **Hazard statement** 

irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through

prolonged or repeated exposure.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable Response

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing. If exposed or concerned: Get medical

advice/attention. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated

clothing and wash before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Store in a well-ventilated place.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

**Environmental hazards** Hazardous to the aquatic environment, acute Category 3

Hazardous to the aquatic environment,

Category 3

Hazard(s) not otherwise

classified (HNOC)

None known.

long-term hazard

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
1-Bromopropane		106-94-5	90 - 100
Carbon Dioxide		124-38-9	2.5 - 10
1,2-Butylene Oxide		106-88-7	0.1 - 1
Other components below re	portable levels		0.1 - 1

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get Skin contact

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Not likely, due to the form of the product. In the unlikely event of swallowing contact a physician or Ingestion

poison control center. Rinse mouth.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause

chronic effects.

Indication of immediate medical attention and special

treatment needed **General information**  Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Water spray. Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO2).

None known.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

Specific methods

equipment/instructions

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Cool containers exposed to flames with water until well after the fire is out.

General fire hazards Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

SDS US Product #: 1000016120 Version #: 02 Revision date: 03-13-2018 Issue date: 03-12-2018

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent product from entering drains. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Level 1 Aerosol.

Store locked up. Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value
Carbon Dioxide (CAS 124-38-9)	PEL	9000 mg/m3
		5000 ppm
US. ACGIH Threshold Limit Value	s	
Components	Туре	Value
1-Bromopropane (CAS 106-94-5)	TWA	0.1 ppm
Carbon Dioxide (CAS 124-38-9)	STEL	30000 ppm
,	TWA	5000 ppm

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

US. NIOSH: Pocket Guide to Chemical Hazards			
Components	Туре	Value	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
,		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
1,2-Butylene Oxide (CAS 106-88-7)	TWA	5.9 mg/m3	
,		2 ppm	

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

**Exposure guidelines** 

US - California OELs: Skin designation

1-Bromopropane (CAS 106-94-5) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eve/face protection Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Other

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

**Physical state** 

Form Aerosol. Compressed gas.

Color Not available. Odor Not available. **Odor threshold** Not available. рH Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available. range Not available. Flash point

Not available. **Evaporation rate** Not available. Flammability (solid, gas)

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper Not available.

(%)

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

Not available.

SDS US Product #: 1000016120 Version #: 02 Revision date: 03-13-2018 Issue date: 03-12-2018

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 14.8 psig @70F estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 1.341 estimated

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**Material is stable under normal conditions. **Possibility of hazardous**Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Heat. Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

Toxic gas.

## 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting. May cause irritation to the respiratory

system.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause

respiratory irritation. Skin irritation. May cause redness and pain.

## Information on toxicological effects

**Acute toxicity** Narcotic effects. May cause respiratory irritation.

Components	Species	Test Results
1,2-Butylene Oxide (CAS 106-88-7)		
<u>Acute</u>		

**Dermal**LD50 Rabbit

.D50 Rabbit 1500 - 2950 mg/kg, 24 Hours

1.77 ml/kg, 24 Hours

SDS US

Inhalation

Vapor

LC50 Rat > 6.3 mg/l

Oral

LD50 Rat 1 - 1.58 mg/kg

1100 μl/kg

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

Product #: 1000016120 Version #: 02 Revision date: 03-13-2018 Issue date: 03-12-2018 5 / 10

Components Species Test Results
1.3 ml/kg

1-Bromopropane (CAS 106-94-5)

Acute Dermal

LD50 Rabbit  $\Rightarrow$  10 ml/kg, 24 Hours

Rat > 2000 mg/kg, 24 Hours

Inhalation

LC50 Rat 14374 ppm, 4 Hours

35 mg/m3, 4 Hours 25 - 35 mg/l, 6 Hours

Oral

LD50 Rabbit 540 mg/kg

Rat > 2000 mg/kg

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

Causes serious eve irritation.

irritation

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,2-Butylene Oxide (CAS 106-88-7) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

1-Bromopropane (CAS 106-94-5) Reasonably Anticipated to be a Human Carcinogen.

**Reproductive toxicity** May damage fertility or the unborn child.

Specific target organ toxicity -

single exposure

May cause respiratory irritation. May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not likely, due to the form of the product.

Chronic effects May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
1,2-Butylene Oxide (	CAS 106-88-7)		
Aquatic			
Algae	IC50	Algae	500 mg/L, 72 Hours
Crustacea	EC50	Daphnia	69.8 mg/L, 48 Hours
Fish	LC50	Fish	160, 96 Hours
1-Bromopropane (CA	AS 106-94-5)		
Aquatic			
Fish	LC50	Fathead minnow (Pimep	hales promelas) 67.3 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

1-Bromopropane 2.1

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

> under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

DOT

**UN number** UN1950

UN proper shipping name Aerosols, non-flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.2 Subsidiary risk 2.2 Label(s)

Not applicable. **Packing group** Special precautions for user Not available.

Packaging exceptions 306 Packaging non bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

**IATA** 

UN1950 **UN number** 

**UN** proper shipping name Aerosols, non-flammable

Transport hazard class(es)

Class 2.2 Subsidiary risk 2.2 Label(s)

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only **Packaging Exceptions** 

Allowed with restrictions. LTD QTY

**IMDG** 

**UN number** UN1950 **UN proper shipping name AEROSOLS** 

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

Transport hazard class(es)

Class 2.2 Subsidiary risk -Label(s) None

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No.

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Packaging Exceptions LTD QTY

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



**General information** 

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,2-Butylene Oxide (CAS 106-88-7) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

Product #: 1000016120 Version #: 02 Revision date: 03-13-2018 Issue date: 03-12-2018

## SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
1,2-Butylene Oxide	106-88-7	0.1 - 1

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,2-Butylene Oxide (CAS 106-88-7)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not re

Not regulated.

(SDWA)

## US state regulations

## US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

# US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

1,2-Butylene Oxide (CAS 106-88-7)

1-Bromopropane (CAS 106-94-5)

### **US. Massachusetts RTK - Substance List**

1,2-Butylene Oxide (CAS 106-88-7)

1-Bromopropane (CAS 106-94-5)

Carbon Dioxide (CAS 124-38-9)

#### US. New Jersey Worker and Community Right-to-Know Act

1,2-Butylene Oxide (CAS 106-88-7)

1-Bromopropane (CAS 106-94-5)

Carbon Dioxide (CAS 124-38-9)

### US. Pennsylvania Worker and Community Right-to-Know Law

1.2-Butvlene Oxide (CAS 106-88-7)

1-Bromopropane (CAS 106-94-5)

Carbon Dioxide (CAS 124-38-9)

#### **US. Rhode Island RTK**

1,2-Butylene Oxide (CAS 106-88-7)

# **US. California Proposition 65**

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

#### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Nitromethane (CAS 75-52-5) Listed: May 1, 1997

### US - California Proposition 65 - CRT: Listed date/Developmental toxin

1-Bromopropane (CAS 106-94-5) Listed: December 7, 2004

#### US - California Proposition 65 - CRT: Listed date/Female reproductive toxin

1-Bromopropane (CAS 106-94-5) Listed: December 7, 2004

### US - California Proposition 65 - CRT: Listed date/Male reproductive toxin

1-Bromopropane (CAS 106-94-5) Listed: December 7, 2004

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

SDS US

Country(s) or region Inventory name On inventory (yes/no)\*

Korea Existing Chemicals List (ECL)

New Zealand

New Zealand Inventory

Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

 Issue date
 03-12-2018

 Revision date
 03-13-2018

Version # 02

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

**Revision information**This document has undergone significant changes and should be reviewed in its entirety.

Product name: 18 OZ SPRAYWAY SAFETY SOLVENT LB 12PK

Product #: 1000016120 Version #: 02 Revision date: 03-13-2018 Issue date: 03-12-2018 10 / 10

Yes