

DMP3500101
Product Identifier: Arctic Power
Revision Date: 05/29/2015

SAFETY DATA SHEET

This SDS complies with 29 CFR 1910.1200 (Hazard Communication Standard)

IMPORTANT: Read this SDS before handling & disposing of this product. Pass this information on to employees, customers, and users of this product.

1. Identification

1.1. Product identifier

Product Identity Artic Power
Alternate Names Artic Power
Product Code 350-01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Freezer Cleaner

Application Method See Label Instructions.

1.3. Details of the supplier of the safety data sheet

Company Name Diamond Products Inc.

1216 Bozeman Ave. Helena, MT 59601

Emergency

24 hour Emergency Telephone No. Infotrac: 1 800-535-5053

Emergency: (406) 449-6570

Customer Service: Diamond Products Inc. (406) 449-6570

2. Hazard(s) identification

2.1. Classification of the substance or mixture

Flam. Liq. 2;H225 Highly Flammable liquid and vapor.

Acute Tox. 3;H301+311+331 Toxic if swallowed, Toxic in contact with skin, Toxic if inhaled.

Skin Irrit. 2;H315 Causes skin irritation.

Eye Dam. 1;H318 Causes serious eye damage. STOT SE 1;H370 Causes damage to organs.

STOT RE 2;H373

May cause damage to organs (Kidney) through prolonged or repeated exposure if

swallowed.

2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



Danger

H225 Highly flammable liquid and vapor.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H370 Causes damage to organs.

H373 May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.

[Prevention]:

P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.

P233 Keep container tightly closed.

P240 Ground / bond container and receiving equipment.

P241 Use explosion-proof electrical / ventilating / light / equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust / fume / gas / mist / vapors / spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection / face protection.

[Response]:

P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P330: Rinse mouth.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310: Immediately call a POISON CENTER/doctor

P312 Call a POISON CENTER or doctor / physician if you feel unwell.

P308+311: IF exposed or concerned: Call a POISON CENTER or doctor.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

P321 Specific treatment (see information on this label).

P332+313 If skin irritation occurs: Get medical advice / attention.

P362+364 Take off contaminated clothing and wash before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

[Storage]:

P403+235: Store in a well ventilated place. Keep cool.

P405 Store locked up.

[Disposal]:

P501 Dispose of contents / container in accordance with local / national regulations.

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Methanol CAS Number: 0000067-56-1	50 - 100	Flam. Liq. 2;H225 Acute Tox. 3;H301+311+331 STOT SE 1;H370	[1][2]
Potassium hydroxide. CAS Number: 0001310-58-3	1.0 - 10	Acute Tox. 4;H302 Skin Corr. 1A;H314	[1][2]
Ethylene glycol CAS Number: 0000107-21-1	1.0 - 10	Acute Tox. 4;H302 STOT RE. 2;H373	[1][2]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First aid measures

4.1. Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention.

Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give

artificial respiration. If unconscious place in the recovery position and obtain immediate

medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and

seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Overview Exposure to solvent vapor concentrations from the component solvents in excess of the

stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular

weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents

^[1] Substance classified with a health or environmental hazard.

^[2] Substance with a workplace exposure limit.

^[3] PBT-substance or vPvB-substance.

^{*}The full texts of the phrases are shown in Section 16.

may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation

and soreness with possible reversible damage. See section 2 for further details.

Inhalation May cause drowsiness or dizziness. Toxic if inhaled.

Eyes Causes serious eye damage.

Skin Causes skin irritation. Toxic in contact with skin.

Ingestion Toxic if swallowed.

5. Fire-fighting measures

5.1. Extinguishing media

Dry chemical, alcohol-resistant foam, carbon dioxide or water spray.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

5.3. Advice for fire-fighters

Wear self-contained breathing apparatus and protective clothing.

ERG Guide No. 128

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3. Methods and material for containment and cleaning up

Small spills: Mop up with water.

Large spills: Absorb with inert material and place in suitable containers.

Dispose of in accordance with local, state and federal regulations.

7. Handling and storage

7.1. Precautions for safe handling

Store in accordance with the National Fire Protection Association's publication NFPA 30, Flammable and Combustible Liquids Code. 29 CFR 1910.106 applies to the handling, storage, and use of flammable and combustible

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

liquids. Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.

Handle containers carefully to prevent damage and spillage. Keep containers tightly closed.

Incompatible materials: Caustics. Acids. Oxidizers, Reducing agents, Alkali metals.

See section 2 for further details. - [Storage]:

7.3. Specific end use(s)

No data available.

8. Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0000067-56-1	000067-56-1 Methanol		TWA 200 ppm (260 mg/m3)
		ACGIH	TWA: 200 ppm STEL: 250 ppm TLV
		NIOSH	TWA 200 ppm (260 mg/m3) ST 250 ppm (325 mg/m3)
		Supplier	No Established Limit
0001310-58-3 Potassium hydroxide.		OSHA	No Established Limit
	ACGIH	Ceiling: 2 mg/m3	
		NIOSH	C 2 mg/m3
	Supplier	No Established Limit	
0000107-21-1 Ethylene glycol		OSHA	No Established Limit
		ACGIH	100 mg/m3 (TLV)
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	e Value	
0000067-56-1	Methanol	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0001310-58-3	Potassium hydroxide.	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;	
0000107-21-1	Ethylene glycol	OSHA	Select Carcinogen: No	
		NTP	Known: No; Suspected: No	
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3 No; Group 4: No;	

8.2. Exposure controls

Respiratory Organic vapor respirator if vapor concentrations exceed TLV.

Eyes Use chemical goggles.

chemical resistant gloves, such as nitrile or PVC.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the

use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits

Chemical resistant clothing such as coveralls/apron and boots should be worn. Wear

suitable respiratory protection must be worn.

using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

Skin

9. Physical and chemical properties

AppearanceClear LiquidOdorAlcohol

Odor threshold

pH

12.5 – 13.5

Melting point / freezing point

Initial boiling point and boiling range

150 - 180 °F

Flash Point

49.5°F

Evaporation rate (Ether = 1)

Not available

Flammability (solid, gas)

Not Applicable

Upper/lower flammability or explosive limits

Lower Explosive Limit: 6%

Upper Explosive Limit: 36%

Vapor pressure (Pa) Not available

Vapor Density >1.0

Specific Gravity 0.85 g/ml

Solubility in Water Complete

Partition coefficient n-octanol/water (Log Kow) Not Measured

Auto-ignition temperature Not available

Decomposition temperature Not available

Viscosity (cSt) Not available

9.2. Other information

VOC Content

No other relevant information.

10. Stability and reactivity

Not available

10.1. Reactivity

Hazardous Polymerization will not occur.

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Vapors may form explosive mixture with air.

10.4. Conditions to avoid

Extreme heat, sparks and open flame.

10.5. Incompatible materials

Caustics. Acids. Oxidizers.

10.6. Hazardous decomposition products

Oxides of Carbon

11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Methanol - (67-56-1)	1,187 – 2,769, Rat	17,100.00, Rabbit	128.20, Rat - Category: NA	No data available	No data available
Potassium hydroxide (1310-58-3)	365.00, Rat - Category: 4	No data available	No data available	No data available	No data available
Ethylene glycol - (107-21-1)	4,700, Rat	10,626.00, Rabbit	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description	
Acute toxicity (oral)	3	Toxic if swallowed	
Acute toxicity (dermal)	3	Toxic in contact with skin	
Acute toxicity (inhalation)	3	Toxic if inhaled	
Skin corrosion/irritation	2	Causes skin irritation.	
Serious eye damage/irritation	2	Causes serious eye irritation.	
Respiratory sensitization		Not Applicable	
Skin sensitization		Not Applicable	
Germ cell mutagenicity		Not Applicable	
Carcinogenicity		Not Applicable	
Reproductive toxicity		Not Applicable	
STOT-single exposure	1	Causes damage to organs.	
STOT-repeated exposure	2	May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.	
Aspiration hazard		Not Applicable	

12. Ecological information

12.1. Toxicity

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and GHS and is not classified as dangerous for the environment, but contains substance(s) dangerous for the environment. See section 3 for details

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Methanol - (67-56-1)	15,400.00, Lepomis macrochirus	>10,000.00, Daphnia magna	22,000.00 (96 hr), Scenedesmus capricornutum
Ethylene glycol - (107-21-1)	18,500.00, Oncorhynchus mykiss	24,000 41,000., Daphnia magna	Not Available
Potassium hydroxide (1310-58-3)	Not Available	Not Available	Not Available

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

13. Disposal considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

14. Transport information

DOT (Domestic Surface Transportation)

14.1. UN number UN2924

14.2. UN proper shipping

name

UN2924, Flammable Liquid, Corrosive N.O.S., (Methanol, Potassium Hydroxide), 3, II

14.3. Transport hazard DOT

class(es)

DOT Hazard Class: 3

14.4. Packing group

14.5. Environmental hazards

IMDG Marine Pollutant: No

14.6. Special precautions for user

No further information

15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected

regulations are represented.

Toxic Substance All components of this material are either listed or exempt from listing on the TSCA

Control Act (TSCA) Inventory.

WHMIS Classification B2 D2B

US EPA Tier II Hazards Fire: Yes

Sudden Release of Pressure: No

Reactive: No

Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs:

Potassium hydroxide. (1,000.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethylene glycol

Methanol

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

Methanol

Proposition 65 - Female Repro Toxins (>0.0%):

Methanol

Proposition 65 - Male Repro Toxins (>0.0%):

Methanol

New Jersey RTK Substances (>1%):

Ethylene glycol

Methanol

Potassium hydroxide

Pennsylvania RTK Substances (>1%):

Ethylene glycol

Methanol

Potassium hydroxide

16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our

products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H301: Toxic if swallowed

H302 Harmful if swallowed.

H311: Toxic in contact with skin

H314: Causes severe skin burns and eye damage

H331: Toxic if inhaled

H370: Causes damage to organs

H373: May cause damage to organs through prolonged or repeated exposure

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

The information herein is presented in good faith and believed to be correct as of the date hereof. However, Diamond Products, Inc., makes no representation as to the completeness and accuracy thereof. Users must make their own determination as to the suitability of the product for their purposes prior to use. No representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature with respect to the product or the information herein is made hereunder. Diamond Products, Inc., shall in no event be responsible for any damages of whatsoever nature directly or indirectly resulting from the publication or use of or reliance upon information contained herein.

End of Document