

Safety Data Sheet

Copyright, 2023, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document group:
 10-9287-3
 Version number:
 20.01

 Issue Date:
 2023/06/30
 Supercedes Date:
 2021/10/07

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3MTM Matting Adhesive

Product Identification Numbers

61-5000-4187-8

1.2. Recommended use and restrictions on use

Intended Use

Adhesive

Specific Use

Urethane-based adhesive for use with 3M matting tape and/or edging materials.

Restrictions on use

Not applicable

1.3. Supplier's details

Company: 3M Canada Company

Division: Commercial Solutions Division

Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1

Telephone: (800) 364-3577 **Website:** www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone:1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Skin Corrosion/Irritation: Category 2. Reproductive Toxicity: Category 1B.

Carcinogenicity: Category 2.

Dagg. 1 of 10

Specific Target Organ Toxicity (single exposure): Category 3. Specific Target Organ Toxicity (repeated exposure): Category 1.

2.2. Label elements

Signal word

Danger

Symbols

Flame Exclamation mark | Health Hazard |

Pictograms







Hazard statements

Highly flammable liquid and vapour.

Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. Suspected of causing cancer.

Causes damage to organs through prolonged or repeated exposure: cardiovascular system | endocrine system immune nervous system | kidney/urinary tract | sensory organs | system

Precautionary statements

Prevention:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Use non-sparking tools. Take action to prevent static discharges. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear protective gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash exposed skin thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF exposed or concerned: Get medical advice/attention. In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Other hazards

None known.

20% of the mixture consists of ingredients of unknown acute oral toxicity.

1% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Methyl Ethyl Ketone	78-93-3	60 - 70 Trade Secret *	2-Butanone
Toluene	108-88-3	15 - 25 Trade Secret *	No Data Available
ADIPATE-BUTANEDIOL-4,4'- DIPHENYLMETHANE DIISOCYANTE- HEXANEDIOL RESIN	30662-91-0		Hexanedioic acid, polymer with 1,4-butanediol, 1,6-hexanediol and 1,1'-methylenebis[4-isocyanatobenzene]
N,N'-BIS(2,6- DIISOPROPYLPHENYL)CAR BODIIMIDE	2162-74-5	0.1 - 1 Trade Secret *	Benzenamine, N,N'-methanetetraylbis[2,6-bis(1-methylethyl)-
Ethylbenzene	100-41-4	0 - 0.1	Benzene, ethyl-

^{*}The actual concentration of this ingredient has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness). Target organ effects following prolonged or repeated exposure. See Section 11 for additional details.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

Hazardous Decomposition or By-Products

<u>Substance</u> Carbon monoxide Carbon dioxide Condition
During Combustion
During Combustion

Page: 3 of 12

5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapours in the spill area to burn or explode. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Cover spill area with a fire-extinguishing foam. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Wear low static or properly grounded shoes. Use personal protective equipment (gloves, respirators, etc.) as required. To minimize the risk of ignition, determine applicable electrical classifications for the process using this product and select specific local exhaust ventilation equipment to avoid flammable vapor accumulation. Ground/bond container and receiving equipment if there is potential for static electricity accumulation during transfer.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from acids. Store away from oxidizing agents.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Ethylbenzene	100-41-4	ACGIH	TWA:20 ppm	
Toluene	108-88-3	ACGIH	TWA:20 ppm	
Methyl Ethyl Ketone	78-93-3	ACGIH	TWA:200 ppm;STEL:300 ppm	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

Page: 4 of 12

CMRG: Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Provide ventilated enclosure for curing. Curing enclosures must be exhausted to outdoors or to a suitable emission control device. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Use explosion-proof ventilation equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Colour	Colourless
Odour	Solvent
Odour threshold	No Data Available
pH	Not Applicable
Melting point/Freezing point	Not Applicable
Boiling point	80 °C
Flash Point	-1.1 °C [Test Method: Tagliabue Closed Cup]
Evaporation rate	2.7 [Ref Std:ETHER=1]
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	1.37 %
Flammable Limits(UEL)	11.5 %
Vapour Pressure	<=9,465.9 Pa [@ 20 °C]
Vapour Density and/or Relative Vapour Density	2.5 [<i>Ref Std:</i> AIR=1]

Density	0.95 g/ml	
Relative density	0.95 [Ref Std:WATER=1]	
Water solubility	Nil	
Solubility- non-water	No Data Available	
Partition coefficient: n-octanol/ water	No Data Available	
Autoignition temperature	No Data Available	
Decomposition temperature	No Data Available	
Viscosity/Kinematic Viscosity	2,000 - 3,000 mPa-s [@ 23 °C] [Details:MITS data]	
Volatile Organic Compounds	No Data Available	
Percent volatile	95.1 % weight [Details: Test Method: Calculated per SCAQMD]	
VOC Less H2O & Exempt Solvents	No Data Available	
Molecular weight	No Data Available	

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sparks and/or flames

10.5. Incompatible materials

Strong acids

Strong oxidizing agents

10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

May be harmful if inhaled. Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin Contact:

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain.

Eve Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Cardiac Effects: Signs/symptoms may include irregular heartbeat (arrhythmia), changes in heart rate, damage to heart muscle, heart attack, and may be fatal. Immunological Effects: Signs/symptoms may include alterations in the number of circulating immune cells, allergic skin and /or respiratory reaction, and changes in immune function. Endocrine Effects: Signs/symptoms may include disruption of gonadal, thyroid, adrenal, or pancreatic function; changes in hormone production; alterations in circulating hormone levels; and/or changes in tissue response to hormones. Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

Prolonged or repeated exposure by ingestion may cause:

Ocular Effects: Signs/symptoms may include blurred or significantly impaired vision. Auditory Effects: Signs/symptoms may include hearing impairment, balance dysfunction and ringing in the ears. Olfactory Effects: Signs/symptoms may include decreased ability to detect odours and/or complete loss of smell. Neurological Effects: Signs/symptoms may include personality changes, lack of coordination, sensory loss, tingling or numbness of the extremities, weakness, tremors, and/or changes in blood pressure and heart rate.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
Ethylbenzene	100-41-4	Grp. 2B: Possible human carc.	International Agency for Research on Cancer

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Acute Toxicity			
Name	Route	Species	Value
Overall product	Inhalation-		No data available; calculated ATE >20 - =50 mg/l
-	Vapor(4 hr)		
Overall product	Ingestion		No data available; calculated ATE >2,000 - =5,000
			mg/kg
Methyl Ethyl Ketone	Dermal	Rabbit	LD50 > 8,050 mg/kg
Methyl Ethyl Ketone	Inhalation-	Rat	LC50 34.5 mg/l
	Vapor (4		
	hours)		
Methyl Ethyl Ketone	Ingestion	Rat	LD50 2,737 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg

Page: 7 of 12

Toluene	Inhalation-	Rat	LC50 30 mg/l
	Vapor (4		
	hours)		
Toluene	Ingestion	Rat	LD50 5,550 mg/kg
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Dermal	Rat	LD50 > 2,000 mg/kg
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Ingestion	Rat	LD50 >300, <2000 mg/kg
Ethylbenzene	Dermal	Rabbit	LD50 15,433 mg/kg
Ethylbenzene	Inhalation-	Rat	LC50 17.4 mg/l
	Vapor (4		
	hours)		
Ethylbenzene	Ingestion	Rat	LD50 4,769 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Methyl Ethyl Ketone	Rabbit	Minimal irritation
Toluene	Rabbit	Irritant
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Rat	Minimal irritation
Ethylbenzene	Rabbit	Mild irritant

Serious Eve Damage/Irritation

Name	Species	Value
Methyl Ethyl Ketone	Rabbit	Severe irritant
Toluene	Rabbit	Moderate irritant
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Rabbit	Mild irritant
Ethylbenzene	Rabbit	Moderate irritant

Skin Sensitization

Name	Species	Value
Toluene	Guinea	Not classified
	pig	
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	Guinea	Not classified
	pig	
Ethylbenzene	Human	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Methyl Ethyl Ketone	In Vitro	Not mutagenic
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic
N,N'-BIS(2,6-DIISOPROPYLPHENYL)CARBODIIMIDE	In Vitro	Not mutagenic
Ethylbenzene	In vivo	Not mutagenic
Ethylbenzene	In Vitro	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

<u>cur em ogemeny</u>			
Name	Route	Species	Value
Methyl Ethyl Ketone	Inhalation	Human	Not carcinogenic
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification
Ethylbenzene	Inhalation	Multiple	Carcinogenic
		animal	

3M™ Matting Adhesive	

	species	

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	Not classified for development	Rat	LOAEL 8.8 mg/l	during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse
N,N'-BIS(2,6- DIISOPROPYLPHENYL)CARBODIIMID E	Ingestion	Not classified for development	Rat	NOAEL 3 mg/kg/day	premating into lactation
N,N'-BIS(2,6- DIISOPROPYLPHENYL)CARBODIIMID E	Ingestion	Not classified for male reproduction	Rat	NOAEL 3 mg/kg/day	28 days
N,N'-BIS(2,6- DIISOPROPYLPHENYL)CARBODIIMID E	Ingestion	Toxic to female reproduction	Rat	NOAEL 1 mg/kg/day	premating into lactation
Ethylbenzene	Inhalation	Not classified for development	Rat	NOAEL 4.3 mg/l	premating & during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Inhalation	central nervous system depression	May cause drowsiness or dizziness	official classifica tion	NOAEL Not available	
Methyl Ethyl Ketone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme nt	NOAEL Not available	
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	not applicable
Methyl Ethyl Ketone	Ingestion	kidney and/or bladder	Not classified	Rat	LOAEL 1,080 mg/kg	not applicable
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
Ethylbenzene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Ethylbenzene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	
Ethylbenzene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professio nal judgeme	NOAEL Not available	

Page: 9 of 12

		nt	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Methyl Ethyl Ketone	Dermal	nervous system	Not classified	Guinea pig	NOAEL Not available	31 weeks
Methyl Ethyl Ketone	Inhalation	liver kidney and/or bladder heart endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles	Not classified	Rat	NOAEL 14.7 mg/l	90 days
Methyl Ethyl Ketone	Ingestion	liver	Not classified	Rat	NOAEL Not available	7 days
Methyl Ethyl Ketone	Ingestion	nervous system	Not classified	Rat	NOAEL 173 mg/kg/day	90 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks
N,N'-BIS(2,6- DIISOPROPYLPHENYL) CARBODIIMIDE	Ingestion	heart endocrine system immune system kidney and/or bladder	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 4 mg/kg/day	28 days
N,N'-BIS(2,6- DIISOPROPYLPHENYL) CARBODIIMIDE	Ingestion	bone, teeth, nails, and/or hair hematopoietic system liver nervous system	Not classified	Rat	NOAEL 16 mg/kg/day	28 days

Page: 10 of 12

Ethylbenzene	Inhalation	kidney and/or	Some positive data exist, but the	Rat	NOAEL 1.1	2 years
Emplochizene	Illiaiation	bladder	data are not sufficient for	Kat	mg/l	2 years
		bladdel			mg/i	
			classification			
Ethylbenzene	Inhalation	liver	Some positive data exist, but the	Mouse	NOAEL 1.1	103 weeks
			data are not sufficient for		mg/l	
			classification			
Ethylbenzene	Inhalation	hematopoietic	Not classified	Rat	NOAEL 3.4	28 days
•		system			mg/l	
Ethylbenzene	Inhalation	auditory system	Not classified	Rat	NOAEL 2.4	5 days
-					mg/l	-
Ethylbenzene	Inhalation	endocrine system	Not classified	Mouse	NOAEL 3.3	103 weeks
					mg/l	
Ethylbenzene	Inhalation	gastrointestinal tract	Not classified	Rat	NOAEL 3.3	2 years
-					mg/l	
Ethylbenzene	Inhalation	bone, teeth, nails,	Not classified	Multiple	NOAEL 4.2	90 days
•		and/or hair		animal	mg/l	•
		muscles		species		
Ethylbenzene	Inhalation	heart immune	Not classified	Multiple	NOAEL 3.3	2 years
,		system respiratory		animal	mg/l	,
		system		species		
Ethylbenzene	Ingestion	liver kidney and/or	Not classified	Rat	NOAEL 680	6 months
•		bladder			mg/kg/day	

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard
Ethylbenzene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea

Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory. The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Document group:	10-9287-3	Version number:	20.01
Issue Date:	2023/06/30	Supercedes Date:	2021/10/07

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Page: 12 of 12