

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND DISTRIBUTOR'S INFORMATION					
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special-B		HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B			
Manufactured For: Hillyard Industries, Inc. Address: 302 N. 4 th Street Address: St. Joseph, MO 64501		DOT Hazard Classification: ORM-D Identity (trade name as used on label): I-Force Brake & Parts Cleaner EF (# HIL0111354)			
Phone: (816)-233-1321 ext. 8285 or http://www.hillyard.com		MSDS Number: A00732 Revision- 3			
EMERGENCY RESPONSE NUMBER: Chemtrec 1-800-424-9300		Date Prepared: 10/22/04 Prepared By: TR			
NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA		Information Calls: (770) 422-2071			
SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)		CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)
HEPTANE		142-82-5	No	500	400
ACETONE		67-64-1	No	1000	750
CARBON DIOXIDE		124-38-9	No	5000	5000
SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS					
Boiling Point: N/A		Specific Gravity (H2O=1): Concentrate Only = 0.728			
Vapor Pressure: PSIG @ 70°F (Aerosols): 80-100		Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A			
Vapor Density (Air = 1): N/E		Evaporation Rate (= 1): N/E			
Solubility in Water: None		Water Reactive: No			
Appearance and Odor: Clear forceful spray with aliphatic/ketone solvent odor.					
SECTION 3 - FIRE AND EXPLOSION HAZARD DATA					
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) EXTREMELY FLAMMABLE		Auto Ignition Temperature N/E		Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E	
FLASH POINT AND METHOD USED (non-aerosols): N/A		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.			
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.					
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.					
SECTION 4 - REACTIVITY HAZARD DATA					
STABILITY [X] STABLE [] UNSTABLE		HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR			
Incompatibility (Mat. to avoid): Strong oxidizing agents.		Conditions to Avoid: Open flame, welding arcs, heat, sparks.			
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.					
SECTION 5 - HEALTH HAZARD DATA					
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS					
ACUTE EFFECTS					
Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation.					
Eye Contact: Slight irritation.			Skin Contact: Slight irritation due to defatting of skin.		
Ingestion: Irritation.					
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation may result in central nervous system effects.					
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.					
EMERGENCY FIRST AID PROCEDURES					
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.					
Skin Contact: Wash with soap and water. If irritated, seek medical attention.					
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.					
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.					
SECTION 6 - CONTROL AND PROTECTIVE MEASURES					
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH approved for organic vapor.					
Protective Gloves: Neoprene			Eye Protection: Safety glasses recommended.		
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.					
Other Protective Clothing & Equipment: None					
Hygienic Work Practices: Wash with soap and water before handling food.					
SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE					
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or federal regulations. DO NOT FLUSH TO SEWER.					
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.					
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.					
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination.					

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

**** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only**