

# MATERIAL SAFETY DATA SHEET from STEARNS PACKAGING CORPORATION

## SECTION I—PRODUCT/MANUFACTURER'S IDENTITY

### IDENTITY (As Used On Label and List):

Angora Fabric Softener R-T-U

**SYNONYMS:** ST-29, ST-1050, ST-1055, ST-1056, ST-1060, ST-1200  
Fabric Softener

**FORMULA ID NUMBER:** LL-60

**EPA REG #:** None

**USDA ACCEPTANCE DATE/CATEGORY CODE:** None

**COMPANY:** STEARNS PACKAGING CORPORATION  
**ADDRESS:** 4200 Sycamore Ave. (53714), P.O. Box 3216  
Madison, Wisconsin (WI) 53704-0216  
**PHONE:** 1 (608) 246-5150  
**FAX:** 1 (608) 246-5149  
**INTERNET:** www.stearnspkg.com  
**EMAIL:** stearns@stearnspkg.com

HAZARD RATING	
1	Flammability
1	Health
0	Reactivity
None	Special Hazard

4 = Extreme

3 = High

2 = Moderate

1 = Slight

0 = Insignificant

**For Transportation Emergency Involving Hazardous Materials Contact: CHEM-TEL 1 (800) 255-3924**

### Shipping Information:

**DOT SHIPPING NAME:** Compound, cleaning, NOI, liquid. Item 48580, Sub. 3, Class 55  
**DOT SHIPPING NUMBER:** None  
**HAZARD LABEL:** None  
**HAZARD CLASS:** None

## SECTION II—HAZARDOUS INGREDIENTS OR IDENTITY INFORMATION

### HAZARDOUS CHEMICAL IDENTITY &

<u>CAS#</u>	<u>HAZARD</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>OTHER LIMITS</u>	<u>% (OPTIONAL)</u>
? Methyl bis (tallow amido ethyl) 2 hydroxyethyl ammonium methyl sulfate 68410-69-5	Irritant				
? Isopropanol 67-63-0	Flammable		400 ppm (TWA)	500 ppm (STEL)	

SARA SECTION 313 TITLE III NOTIFICATION REQUIRED: No; CHEMICAL IN PRODUCT: None; CAS#: N/A; WEIGHT % OF CHEM: N/A

## SECTION III—PHYSICAL/CHEMICAL CHARACTERISTICS

<b>BOILING POINT:</b>	210°F	<b>VAPOR PRESSURE (mm Hg):</b>	Not Determined
<b>SPECIFIC GRAVITY (WATER=1):</b>	1.000	<b>VAPOR DENSITY (AIR=1):</b>	Not Determined
<b>MELTING POINT:</b>	Not Determined	<b>EVAPORATION RATE:</b>	< 1 (Butyl Acetate=1)
<b>SOLUBILITY IN WATER:</b>	Complete	<b>pH (CONCENTRATE):</b>	6.5 ± 0.5
<b>APPEARANCE AND ODOR:</b>	Light blue liquid Clean, fresh scent	<b>pH (1% SOLUTION):</b>	Not Determined

## SECTION IV—FIRE AND EXPLOSION HAZARD DATA

**FLASH POINT (METHOD USED):** Non-combustible, >200°F

**EXTINGUISHING MEDIA:** CO<sub>2</sub>, water, dry chemical

**FLAMMABLE LIMITS:** LEL: Not Applicable UEL: Not Applicable

**SPECIAL FIRE FIGHTING PROCEDURES:** Use NIOSH approved respirator for sulfur and nitrogen compounds. Combustion products may include sulfur and nitrogen compounds if exposed to extreme heat.

**FIRE & EXPLOSION HAZARDS:** Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by pilot lights, other flames, sparks, heaters, smoking, electrical motors or other ignition sources at locations distant from material handling point. Never use cutting or welding torch on or near drum (even when empty); product (or residue) may ignite explosively.

## SECTION V—REACTIVITY DATA

<b>STABILITY:</b>	Stable
<b>INCOMPATIBILITY (MATERIALS TO AVOID):</b>	Strong oxidizing agents
<b>HAZARDOUS DECOMPOSITION OR BYPRODUCTS:</b>	Sulfur and nitrogen compounds if exposed to extreme heat
<b>CONDITIONS TO AVOID:</b>	Freezing and extremes of heat
<b>HAZARDOUS POLYMERIZATION:</b>	Will not occur

## SECTION VI—HEALTH HAZARD DATA/FIRST AID PROCEDURES

**HEALTH HAZARDS (ACUTE AND CHRONIC):** Irritation of exposed tissues, especially eyes, skin, throat, nasal cavities and other mucous membranes.

**CARCINOGENICITY:** NTP: No  
IARC Monographs: No  
OSHA Regulated: No

**SIGNS AND SYMPTOMS OF OVEREXPOSURE:** **Skin:** Irritation of exposed tissues. **Eyes:** Liquid can cause irritation. High concentrations (> 400 ppm) of isopropanol can also cause irritation. **Ingestion:** Causes diarrhea, nausea, vomiting, cramps, and gastrointestinal irritation. May aggravate pre-existing liver and kidney problems. **Inhalation:** Can cause drowsiness. Causes irritation of mucous membranes at exposures of 400 ppm for 3 to 5 minutes. Extreme overexposure can cause unconsciousness and death. Isopropyl Alcohol can be detected by its smell at concentrations below 200 ppm.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Persons with pre-existing skin disorders may be susceptible to defatting, dermatitis and cracking.

### EMERGENCY AND FIRST AID PROCEDURES:

**Eyes:** If contact with eyes occurs, flush with plenty of cool water for 15 minutes. Consult a physician.  
**Skin:** May be irritating to skin. If contact occurs, flush with water and wear gloves in the future to minimize exposure. Wash hands thoroughly after handling. Discontinue use if irritation persists and consult a physician.  
**Inhalation:** Remove from exposure. Obtain medical attention immediately.  
**Ingestion:** May be harmful if swallowed. If ingested, drink large amounts of water or milk. **DO NOT** induce vomiting. Get medical attention immediately. Avoid contamination of foods.  
**Note to Physician:** No specific antidote. Use supportive care. Treatment should be based on judgment of the physician in response to the reactions of the patient.

## SECTION VII—PRECAUTIONS FOR SAFE HANDLING AND USE

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Eliminate all ignition sources. Persons not wearing proper protective equipment should be excluded from the area of the spill. Stop spill at sources, dike area of spill to prevent spreading. Pump liquid to salvage tank. Absorb liquid on absorbent material and shovel into containers. This product is toxic to fish. Prevent runoff to sewers, streams, or other bodies of water.

**WASTE DISPOSAL METHOD:** Waste disposal must be done in accordance with all local, city or municipality, county, state, and federal regulations. Consult your state department of natural resources or the EPA for specific questions not answerable through other sources. Wastewater should never enter a fresh water body without treatment. Incineration is the recommended disposal method for all chemical wastes. Material collected on absorbent material may be landfilled in accordance with all applicable regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Store at room temperature. Keep container closed when not in use. Do not mix with other chemicals or cleaning agents.

**OTHER PRECAUTIONS:** Always keep product out of the reach of children.

## SECTION VIII—OTHER REGULATORY INFORMATION

## SECTION IX—CONTROL MEASURES

**RESPIRATORY PROTECTION:** In general, respirators are not needed if the product is used in a well-ventilated area.  
**VENTILATION:** Local Exhaust: Recommended to control below TLV of 400 ppm for isopropanol.  
Mechanical (General): Recommended to control below TLV of 400 ppm for isopropanol.  
**SKIN PROTECTION:** Neoprene, rubber, or other chemical resistant gloves. Wear protective clothing to prevent repeated or prolonged contact.  
**EYE PROTECTION:** Splash goggles, or safety glasses if splashing is not a concern.  
**WORK/HYGIENIC PRACTICES:** As good hygiene dictates.

Stearns Packaging Corporation makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Stearns Packaging Corporation as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Stearns Packaging Corporation assume any liability arising out of the use by others of this product referred to herein. The data in this MSDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. Stearns Packaging Corporation does not recommend blending this product with any other chemicals. All information, recommendations and data contained herein concerning this product are based upon information available at the time of writing from recognized technical sources.