Stratus Building

Solutions

1976 Innerbelt Business Center Dr. St. Louis, MO 63114

MATERIAL SAFETY DATA SHEET

Revision Date: 6/18/2009

Emergency Phones: 314-731-2000

PLEASE NOTE: This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who wark with this material. Please need the information on these schools, and then provide this information to those people of your company whose responsibility it is to comply with FEDERAL and STATE RICHT-TO-KNOW regulations. Also make this information available to any employee who requests it. It is your obligation to comply with those regulations.

SECTION I - PRODUCT IDENTITY

PRODUCT NAME: #8 Bath & Bowl Cleaner

NWH	HMIS KATINGS	
Hoath = 1 (Slight)	Flammability = 0 (Minimal)	
Reactivity = 0 (Minimal)	Protection = B (Goggles & Gloves)	
SECTION II - HAZ		
Nono	4850) ⊼TI	CARCINOGEN OSHA,TP,IARC)

SECTION III - CHEMICAL AND PHYSICAL	Uquid Beling Potts: 4212'F Nething Potts: WA Spot. 504 (4,60 = 1); 1,025 (9,54 lbs(ga)) Vapor Pressure (mm Hg); NA VCC Conflent; 0%	SECTION IV - FIRE AND EXPLOSION HAZARDS	to Boiling Explosion Limits: Uppor: N/A
SE	ish Red Liquid ico Addod ste	SECTI	None to Boiling
	Appearance: Cloar Pirklath Red Liquid Odor: Mild – No Fragrance Addod pH; < 1 Vator Solubility: Complate Viscosity: Water Thin		Flash Point (Method): None to Boiling

Uppor: N/A

None to Boiling

Flash Point (Method):

Extraguishing Modia: Water fog, foam, alcohol foam, CO ₂ , dry chomical Special Fletighting Procedures and Hazards: In general, no special aspects.	Aomical ocial aspects.
O A NOILOGO	MANITA MADATA MATATA
Stable: 🔯	Unatable:
Procautions: incompatibility: Nono known	
Hazardous Decemposition Products: If in a fire: CO, CO2, hydrocarbons.	ocarbons.
Hazardous Polymorization; Occurs;	Does Not Occur.

GS-998 Page 2 of 2

GS-999 Page 1 of 2

SECTION VI - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Breathing of mists may cause instation. If there is a problom, move party to fresh air. Inholation:

Extended contact could cause Irritation. Some personnel are more sensitive than others, wear gloves if necessary. Skh: Can causo initation. Wour glasses or goggles as needed. If material gets into eyes, flush with water immediately for 15 minutes. If initiation pensists, consult a physician.

No offects reported

ingestion: Eyos:

MSDS No. GS-998

Most likely routes of entry. Skin, Eyes.

Other Important Medical or Presautionary Information: None

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spilis and Leaks; Small spills can be flushed into normal drainage or into ground with copious amounts of water, or taken up with absorbent material. Do not drain to sewer without dilution. Larger spills should be contained by diking or other mothods and hold for disposal or rouse.

Storage and Handling: Keep away from heat, sparks and open flames. Check daily for any containor leaks.

٠.

Waste Disposal: Dispose of material according to local sanitation regulations. Observe label precautions.

Embly Containers: Rinso well before handling and disposal. Observe fabol precautions.

Other Precautions: N/A

SECTION VIII - REGULATORY INFORMATION

Reportable for SARA Title III, \$.313 (Form R): None

The information harein has been compiled from sources believed to be reliable and is accurate to the bost of our knowledge. However, Stratus Building Solutions cannot give any guarantees regarding information from other sources, and expressly does not make any warranties, nor assumes any liability, for its use.