Safety Data Sheet

Issuing Date 01-Nov-2014

Revision Date 02-Mar-2015

Revision Number 0

PRODUCT AND COMPANY IDENTIFICATION

Sealed Maintenance Free Lead-Acid Golf Batteries: **Product Name**

DTA, EV, GF Series

Recommended Use SLA Battery. Lead Acid (Non-Spillable) Battery.

Supplier Address: Harris Battery Co., Inc. 10708 Industrial PKWY Bolivar, OH 44612

Phone: 800-367-7670 Fax: 330-874-9936

Email: info@harrisbattery.com

HAZARDS IDENTIFICATION

Emergency Overview

NOTE: Under normal conditions of battery use, internal components will not present a health hazard. The following information is provided for battery acid and lead exposure that may occur during battery production or container breakage or under extreme heat conditions such as fire.

In case of rupture:

Corrosive

The product causes burns of eyes, skin and mucous membranes

Appearance: No information available, Physical State: Solid. **Odor:** Odorless

Potential Health Effects

Principle Routes of Exposure Skin contact.

Acute Toxicity

Main Symptoms

Eves Corrosive to the eyes and may cause severe damage including blindness.

Skin

Harmful by inhalation. Contact with moist mucous membranes of the respiratory Inhalation

system can cause caustic condition resulting in burns.

Harmful if swallowed. Can burn mouth, throat, and stomach. Ingestion

Lead compounds may be absorbed by ingestion, by inhalation and through the Chronic Effects

skin. Lead may damage kidney function, the blood forming system and the

reproductive system. Avoid repeated exposure.

Severe exposures can lead to shock, circulatory collapse, and death Lead poisoning is characterized by a metallic taste in the mouth, loss of appetite

indigestion, nausea, vomiting, constipation, sleep disturbances and overall

weakness

Aggravated Medical Conditions None known.

Environment Hazard See Section 12 for additional Ecological Information

COMPOSITION/INFORMATION ON INGREDIENTS 3.

Chemical Name	CAS-No	Weight %
Inorganic Lead/Lead Compounds	7439-92-1	70~80
Tin	7440-31-5	0.1~0.3
Calcium	7440-70-2	0.01~0.03
Arsenic	7440-38-2	< 0.0015
Dilute Sulfuric Acid	7664-93-9	15~25
Case Material: Polypropylene(PP)	9003-07-0	~4

4. FIRST AID MEASURES

General Advice First aid is upon rupture of sealed battery.

Immediate medical attention is required. Rinse immediately with plenty of water, also **Eye Contact**

under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not

rub affected area.

Immediate medical attention is required. Wash off immediately with soap and plenty **Skin Contact**

of water removing all contaminated clothes and shoes.

Move to fresh air. Call a physician or Poison Control Center immediately. If not Inhalation

breathing, give artificial respiration. If breathing is difficult, give oxygen.

Immediate medical attention is required. Call a physician or Poison Control Center Ingestion

immediately. Do NOT induce vomiting. Drink plenty of water. Never give anything by

mouth to an unconscious person. Remove from exposure, lie down.

Notes to Physician Treat symptomatically.

Protection of First-aiders Use personal protective equipment. Avoid contact with skin, eyes and clothing.

5. FIRE-FIGHTING MEASURES

Flammable Properties Not flammable. Flash Point Not determined.

Use extinguishing measures that are appropriate to local Suitable Extinguishing Media

circumstances and the surrounding environment.

Uniform Fire Code · Corrosive: Acid-Liquid

Hazardous Combustion Products Hazardous metal fumes and oxides.

Explosion Data Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of Specific Hazards Arising from the Chemical

irritating gases and vapors. In the event of fire and/or explosion

do not breathe fumes.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA Health Hazard 3 Flammability 0 Stability 2 Physical and Chemical Hazards

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Use personal protective equipment. Do not touch damaged containers or spilled

material unless wearing appropriate protective clothing. Do not get in eyes, on skin,

or on clothing.

Environmental Precautions Refer to protective measures listed in Sections 7 and 8.

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up In case of rupture: Use personal protective equipment. Dam up. Soak up with inert

absorbent material. Take up mechanically and collect in suitable container for

disposal. Clean contaminated surface thoroughly.

Other Information Refer to protective measures listed in Sections 7 and 8.

7. HANDLING AND STORAGE

Handling Handle in accordance with good industrial hygiene and safety practice.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Chemical Name ACGIH TLV		OSHA PEL	NIOSH IDLH
Lead 7439-92-1	TWA: 0.05 mg/m3	TWA: 50 μg/m3 Action Level: 30 μg/m3 Poison, See 29 CFR 1910.1025	IDLH: 100 mg/m3 TWA: 0.050 mg/m3
Sulfuric acid 7664-93-9	TWA: 0.2 mg/m3 thoracic fraction	TWA: 1 mg/m3 (vacated) TWA: 1 mg/m3	IDLH: 15 mg/m3 TWA: 1 mg/m3
Tin 7440-31-5	TWA: 2 mg/m3	TWA: 2 mg/m3 Sn except oxides (vacated) TWA: 2 mg/m3	IDLH: 100 mg/m3 TWA: 2 mg/m3

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value.

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits.

NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965

F.2d 962 (11th Cir., 1992).

Engineering Measures Showers

Eyewash stations Ventilation systems

Personal Protective Equipment

Eye/Face Protection Skin and Body ProtectionTightly fitting safety goggles.
Wear protective gloves/clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits

are exceeded or irritation is experienced, ventilation and evacuation may be required.

Handle in accordance with good industrial hygiene and safety practice. **Hygiene Measures**

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Odor Odorless. No information available, Black. **Odor Threshold Physical State** No information available Solid

No information available

Auto-ignition No information Flash Point No information available.

Temperature available **Boiling** information Nο

Decomposition Temperature No information available Point/Range available

Melting Point/Range No information available

Nο information Flammability Limits in Air **Explosion Limits** No information available

available No information

available

No data available

Water Solubility Immiscible in water Solubility

Vapor Pressure Partition Coefficient:

Evaporation Rate No information available

Vapor Density No data available noctanol/water

10. STABILITY AND REACTIVITY

Stability Stable under recommended storage conditions.

Incompatible Products Incompatible with strong acids and bases. Incompatible with oxidizing agents.

Conditions to Avoid Exposure to air or moisture over prolonged periods.

Hazardous Decomposition Products Thermal decomposition can lead to release of toxic/corrosive gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

Irritation Causes severe irritation and or burns

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Sulfuric acid	= 2140 mg/kg (Rat)	-	= 510 mg/m3(Rat) 2 h

Chronic Toxicity

Lead compounds may be absorbed by ingestion, by inhalation and through the skin. Lead may damage kidney function, the blood forming system and the reproductive system. Avoid repeated **Chronic Toxicity**

exposure.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lead	A3	Group 2A	Reasonably Anticipated	X
Sulfuric acid	A2	Group 1	Known	X
ABS resin		Group 3		

ACGIH: (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

NTP: (National Toxicity Program)

Known - Known Carcinogen

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity	Product is or contains a chemical which is a known or suspected reproductive hazard.	
Developmental Toxicity	Contains ingredients that have suspected developmental hazards. Inorganic lead compounds can cause developmental damage.	
Target Organ Effects	None known.	

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Lead		LC50: 0.44 mg/L (96 h semi-static) Cyprinus carpio LC50: 1.17 mg/L (96 h flow-through) Oncorhynchus mykiss LC50: 1.32 mg/L (96 h static) Oncorhynchus mykiss		EC50: 600 µg/L (48 h) water flea
Sulfuric acid		LC50: > 500 mg/L (96 h static) Brachydanio rerio		EC50: 29 mg/L (24 h) Daphnia magna

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261). Should not be released into the environment.

Contaminated Packaging Do not re-use empty containers.

US EPA Waste Number D002 D008

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Lead - 7439-92-1	(hazardous constituent - no waste number)	Included in waste streams: F035, F037, F038, F039, K002, K003, K005, K046, K048, K049, K051, K052, K061, K062, K064, K065, K066, K069, K086, K100, K176	= 5.0 mg/L regulatory level	

California Hazardous Waste Codes 792

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California EHW	California Carc	California Hazardous Waste	California Waste - Part 2
Lead			Toxic	TCLP (for CA Toxicity): 5.0 mg/L
Sulfuric acid			Toxic Corrosive	
Calcium	Ignitable Reactive			

14. TRANSPORT INFORMATION

Note: Exempt from hazardous materials regulations per 49CFR173.159 (d).

DOT Description NOT REGULATED NON-SPILLABLE BATTERY

TDG Description Not regulated NON-SPILLABLE BATTERY

MEX Description Not regulated NON-SPILLABLE BATTERY

ICAO Description Not regulated NON-SPILLABLE BATTERY

IATA Description Not regulated NON-SPILLABLE BATTERY

IMDG/IMO Description Not regulated NON-SPILLABLE BATTERY

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL Not determined

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) . This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Lead	7439-92-1	70~80	0.1
Sulfuric acid	7664-93-9	15~25	1.0

SARA 311/312 Hazard Categories Acute
Health Hazard
Chronic Health Hazard
Fire Hazard
Sudden Release of Pressure Hazard
No
Reactive Hazard
No

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Lead		X	X	
Sulfuric acid	1000 lb			X

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following substances which are listed hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act:

Chemical Name	CAS-No	Weight %	HAPS data	VOC Chemicals	Class 1 Ozone Depletors	Class 2 Ozone Depletors
Lead	7439-92-1	70~80				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs
Lead	10 lb	
Sulfuric acid	1000 lb	1000 lb

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Lead	7439-92-1	Carcinogen Developmental Female Reproductive Male Reproductive
Sulfuric acid	7664-93-9	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Lead	X	X	X	X	X
Tin	X	X	X		
Calcium	X	X	X		
Sulfuric acid	X	X	X	X	X

International Regulations

Chemical Name	Carcinogen Status	Exposure Limits
Lead	A3	Mexico: TWA= 0.15 mg/m3
Tin		Mexico: TWA 2 mg/m3 Mexico: STEL 4 mg/m3
Sulfuric acid	A2	Mexico: TWA 1 mg/m3

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

D2A Very toxic materials E Corrosive material



Chemical Name	NPRI	
Lead	X	
Sulfuric acid	X	

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION

Prepared By 5th Floor, Xinbaohui Bldg., Nanhai Blvd.

Kevin Zhang, Nanshan, Shenzhen, China. 518054

86-0755-2606-7267

Issuing Date 01-Nov-2014

Revision Date 02-Mar-2015

Revision Note No information available

General Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet