HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : Hillyard Quick & Clean Jell Graffiti Remover

Material number : A00179

Manufacturer or supplier's details

Company : Hillyard Industries

Address : 302 North 4th Street

Joseph, MO 64502

Telephone : 816-233-1321 ext 8285

Emergency telephone numbers

For SDS Information : 816-233-1321 ext 8285

For a Medical Emergency :

For a Transportation : CHEMTREC 800-424-9300

Emergency

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	Aerosol containing a liquefied gas
Colour	tan, brown
Odour	solvent-like

GHS Classification

Flammable aerosols : Category 1
Gases under pressure : Liquefied gas
Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1

GHS Label element

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after

use.

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

Potential Health Effects

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans

ethanol 64-17-5

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

egual to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical Name	CAS-No.	Concentration [%]	
Distillates (petroleum), hydrotreated light (Vapour and gas)	64742-47-8	>= 30 - < 50	
Citrus, ext.	94266-47-4	>= 20 - < 30	
propane	74-98-6	>= 5 - < 10	
dimethoxymethane	109-87-5	>= 5 - < 10	
butane	106-97-8	>= 1 - < 5	
Alcohols, C9-11, ethoxylated	68439-46-3	>= 1 - < 5	
ethanol	64-17-5	>= 1 - < 5	

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

In case of skin contact : Call a physician if irritation develops or persists.

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes while removing contaminated

clothing and shoes.

Wash contaminated clothing before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes. Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Alcohol-resistant foam

Dry chemical Water spray jet

Unsuitable extinguishing

media

: High volume water jet

Hazardous combustion

products

: Carbon dioxide (CO2) Carbon monoxide

Smoke

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8. Do not breathe vapours or spray mist.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges.

Provide sufficient air exchange and/or exhaust in work rooms.

Container may be opened only under exhaust ventilation

hood.

Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Always replace cap after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects. No smoking.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.

Keep in a dry, cool and well-ventilated place.

Materials to avoid : Strong oxidizing agents

Do not store near acids.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light (Vapour and gas)	64742-47-8	TWA	500 ppm 2,000 mg/m3	OSHA Z-1
		TWA	400 ppm 1,600 mg/m3	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m3	OSHA P0
dimethoxymethane	109-87-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 3,100 mg/m3	NIOSH REL
		TWA	1,000 ppm 3,100 mg/m3	OSHA Z-1
		TWA	1,000 ppm 3,100 mg/m3	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0

Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

Hand protection

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

the workstation location.

Safety glasses

Skin and body protection : impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Colour : tan, brown
Odour : solvent-like

Odour Threshold : no data available
pH : not applicable
Melting point/freezing point : no data available
Boiling point : no data available

Flash point :

not applicable

Evaporation rate : no data available
Upper explosion limit : no data available
Lower explosion limit : no data available
Vapour pressure : no data available
Relative vapour density : no data available
Density : no data available

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : not determined

Partition coefficient: n-

octanol/water

: no data available

Auto-ignition temperature : not determined

Thermal decomposition : no data available

Viscosity

Viscosity, kinematic : no data available

Heat of combustion : 37.60 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Stable

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.

Conditions to avoid : Heat, flames and sparks.

Extremes of temperature and direct sunlight.

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

Incompatible materials : Acids

Strong oxidizing agents

Hazardous decomposition

products

: Carbon monoxide Carbon dioxide (CO2)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Components:

Alcohols, C9-11, ethoxylated:

Acute oral toxicity : LD50 Oral rat: 1,400 mg/kg

Skin corrosion/irritation

Product:

Remarks: May irritate skin.

Serious eye damage/eye irritation

Product:

Remarks: Eye irritation

Respiratory or skin sensitisation

Product:

Remarks: Causes sensitisation.

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

Distillates (petroleum), hydrotreated light (Vapour and gas):

Citrus, ext.:

propane:

dimethoxymethane:

butane:

Alcohols, C9-11, ethoxylated:

ethanol:

STOT - single exposure

no data available

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

Components:

Distillates (petroleum), hydrotreated light (Vapour and gas):

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available

Bioaccumulative potential

Product:

Partition coefficient: n-

octanol/water

Components:

butane :

Partition coefficient: n-

octanol/water

: Pow: 2.89

Mobility in soil

no data available

Other adverse effects

no data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of

: Remarks: no data available

Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks This product neither contains, nor was manufactured

with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A

+ B).

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to

aquatic life with long lasting effects.

Components:

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

Distillates (petroleum), hydrotreated light (Vapour and gas) :

Additional ecological

information

: no data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Dispose of in accordance with local regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):

UN1950, AEROSOLS, 2.1,

Transportation Regulation: IATA (Cargo Air):

UN1950, Aerosols, flammable, 2.1,

Transportation Regulation: IATA (Passenger Air):

UN1950, Aerosols, flammable, 2.1,

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, 2.1, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Sudden Release of Pressure Hazard

Acute Health Hazard

HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

SARA 302 : SARA 302: No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : SARA 313: This material does not contain any chemical

components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA

Title III, Section 313.

California Prop 65 This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

The components of this product are reported in the following inventories:

TSCA On TSCA Inventory

All components of this product are on the Canadian DSL.

On the inventory, or in compliance with the inventory

NZIoC Not in compliance with the inventory

PICCS On the inventory, or in compliance with the inventory IECSC On the inventory, or in compliance with the inventory


Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA GHS Label Information:

Hazard pictograms :





Signal word : Danger:

SAFETY DATA SHEET HILLYARD QUICK & CLEAN JELL GRAFFITI REMOVER HIL0105054

Version 1.0 Revision Date 02/19/2015 Print Date 06/02/2015

Hazard statements

Precautionary statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/ face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Take off contaminated clothing and wash before reuse.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122

°F.

Disposal: Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®,Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®,Rexodan®, Mykal™, and a number of private labeled brands.