

Printed: 03/26/2018 Revision: 03/26/2018

Page: 1 of 7

Supersedes Revision: 05/06/2015 MGI273004

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code: MORGAN-273-BULK

IPA 70% Product Name:

Morgan-Gallacher, Inc. **Phone Number: Company Name:**

8707 Millergrove Drive +1 (562)695-1232

Santa Fe Springs, CA 90670

Emergency Contact: CHEMTREC +1 (800)424-9300

Not intended for consumer use. For sale to, use and storage by service professionals **Intended Use:**

Recommended Use: Cleaning Solvent.

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Serious Eye Damage/Eye Irritation, Category 2A

Specific Target Organ Toxicity (single exposure), Category 3





GHS Signal Word: Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.

> Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness.

GHS Precaution Phrases: Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/.../ equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray.

Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Keep cool.

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin **GHS Response Phrases:**

> with plenty of water for 15 minutes. Get immediate medical advice/attention.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Get immediate medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing for 15 minutes.

Store container tightly closed in well-ventilated place.

Get immediate medical advice/attention.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Get immediate medical

advice/attention.

GHS Storage and Disposal

Phrases: Store locked up.

Dispose of contents/container in accordance to local, state and federal regulations.



Page: 2 of 7 Printed: 03/26/2018

Revision: 03/26/2018

Supersedes Revision: 05/06/2015

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

Potential Health Effects (Acute and Chronic):

Chronic: Prolonged or repeated skin contact may cause defatting and dermatitis. High concentrations may lead to central nervous system effects (drowsiness, dizziness,

nausea, headaches, paralysis and loss of consciousness).

Inhalation: May cause respiratory irritation. Inhalation of vapors may cause drowsiness and

dizziness. May cause narcotic effects in high concentration.

Skin Contact: May cause irritation with pain and stinging, especially if the skin is abraded.

Eye Contact: May cause eye irritation. May cause burning of eyes and flow of tears.

Ingestion: Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause central

nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Aspiration of material into the lungs may cause

chemical pneumonitis, which may be fatal.

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS # Hazardous Components (Chemical Name) Concentration

67-63-0 Isopropyl Alcohol 70.0 %

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

In Case of Inhalation: Remove from exposure and move to fresh air immediately. If not breathing, give artificial

respiration. Do NOT use mouth-to-mouth resuscitation. Get medical aid immediately.

In Case of Skin Contact: In case of contact, flush skin with plenty of water. Remove contaminated clothing and

shoes. Wash clothing before reuse. Get medical aid if irritation develops and persists.

In Case of Eye Contact: Flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and

lower eyelids. Remove contact lenses, if present and easy to do. Continue rinsing. Get

medical aid immediately.

In Case of Ingestion: Potential for aspiration if swallowed. Never give anything by mouth to an unconscious

person. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs naturally, have victim lean forward. Get medical aid immediately.

Note to Physician: Show this safety data sheet to the doctor in attendance. Treat symptomatically and

supportively.

5. FIRE FIGHTING MEASURES

Flash Pt: < 100.00 F

Explosive Limits: LEL: No data. UEL: No data.

Autoignition Pt: NA

Suitable Extinguishing Media: For large fires, use dry chemical, carbon dioxide, alcohol-resistant foam, or water spray.

For small fires, use carbon dioxide, dry chemical, dry sand, or alcohol-resistant foam.

Unsuitable Extinguishing

Media:

Do NOT use straight streams of water.

Fire Fighting Instructions: As in any fire, wear a self-contained breathing apparatus in pressure-demand,

MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form explosive mixtures with air. Flammable liquid and vapor. Cool containers with flooding quantities of water until well after fire is out. Vapors are heavier than air and may travel

to a source of ignition and flash back.

Flammable Properties and

Hazards:

EXTREMELY FLAMMABLE. High temperatures and fires may produce toxic:carbon and nitrogen oxides Carbon monoxide, Vapors can travel to a source of ignition and flash

back. Container explosion may occur under fire conditions.

Hazardous Combustion No data available.



Page: 3 of 7 Printed: 03/26/2018 Revision: 03/26/2018

Supersedes Revision: 05/06/2015

Products:

6. ACCIDENTAL RELEASE MEASURES

Protective Precautions, Protective Equipment and Emergency Procedures: Use proper personal protective equipment as indicated in Section 8.

Environmental Precautions: Steps To Be Taken In Case

Material Is Released Or Spilled:

Do not let product enter drains, sewers, watersheds or water systems.

Spills/Leaks: Provide ventilation. Remove all sources of ignition. A vapor suppressing foam may be used to reduce vapors. Use water spray to dilute spill to a non-flammable mixture. Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in

suitable container. Use a spark-proof tool.

7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Avoid contact with eyes, skin, and clothing. Avoid breathing dust, mist, or vapor. Use only with adequate ventilation. Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Take precautionary measures against static discharges. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Do not allow to evaporate to near dryness.

Precautions To Be Taken in Storing:

Store in a cool, dry, well-ventilated area away from incompatible substances. Keep away from heat, sparks and flame. Keep from contact with oxidizing materials. Do not store in direct sunlight. Store in a tightly closed container. Flammables-area. Protect containers against damage. Keep container closed when not in use.

Other Precautions:

Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Handle in accordance with good industrial hygiene and safety practice. Keep out of reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

CAS # Partial Chemical Name OSHA TWA ACGIH TWA Other Limits
67-63-0 Isopropyl Alcohol PEL: 400 ppm TLV: 200 ppm No data.
STEL: 400 ppm

Respiratory Equipment (Specify Type):

Avoid breathing vapors or mists. If airborne concentrations pose a health hazard or become irritating, use a NIOSH/MSHA-approved respirator, in the positive pressure

mode.

Eye Protection: Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Protective Gloves: Wear appropriate gloves to prevent skin exposure. Rubber or neoprene gloves.

Other Protective Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Engineering Controls (Ventilation etc.):

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits. Facilities storing or utilizing this material should be

equipped with an eyewash facility and a safety shower.

Work/Hygienic/Maintenance

-

Handle in accordance with good industrial hygiene and safety practice. Wash hands

Practices: before breaks and at the end of workday.



Page: 4 of 7 Printed: 03/26/2018

Revision: 03/26/2018

Supersedes Revision: 05/06/2015

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid

NA

Appearance and Odor: Appearance: Colorless.

Odor: alcohol-like.

pH: NA Melting Point: NA

Boiling Point: > 212.00 F **Flash Pt:** < 100.00 F

Evaporation Rate: NA

Flammability (solid, gas): No data available.

Explosive Limits: LEL: No data. UEL: No data.

Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): NA

Specific Gravity (Water = 1): 0.847 - 0.867

Density: NA
Solubility in Water: NA
Saturated Vapor NA

Concentration:

Octanol/Water Partition

No data.

Coefficient:

Percent Volatile: 100.0 % by weight.

Autoignition Pt: NA

Decomposition Temperature: No data.

Viscosity: NA

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid -

Ignition sources, Excess heat, flames and sparks.

Instability:

Incompatibility - Materials To Strong oxidizing agents, Strong acids, Strong bases, Amines, ammonia, ethylene oxide,

Avoid: isocyanates, acetaldehyde, chlorine, phosgene.

Hazardous Decomposition or High temperatures and fires may produce toxic:carbon and nitrogen oxides Carbon

Byproducts: monoxide, Carbon dioxide.

Possibility of Hazardous

Will occur [] Will not occur [X]

Reactions:

Conditions To Avoid - No data available.

Hazardous Reactions:



Page: 5 of 7 Printed: 03/26/2018 Revision: 03/26/2018

Supersedes Revision: 05/06/2015

11. TOXICOLOGICAL INFORMATION

Toxicological Information: Epidemiology: No information available.

Teratogenicity: No information available. Reproductive Effects: No data available. Mutagenicity: No information available.

Neurotoxicity: No data available.

Other Studies: CAS# 67-63-0:

Acute toxicity, LD50, Oral, Rat, 5045 mg/kg

CAS# 67-63-0: Isopropyl Alcohol: Acute toxicity, LDLO, Oral, Dog, 1537. MG/KG.

Acute toxicity, LDLO, Oral, Species: Cat, 6.000 ML/KG. Acute toxicity, LD50, Oral, Species: Rabbit, 6410. MG/KG.

Irritation or Corrosion: Other Studies: CAS# 67-63-0:

Standard Draize Test, Skin, Species: Rabbit, 500 mg Standard Draize Test, Eyes, Species: Rabbit, 100 mg, 24H

Carcinogenicity/Other

Information:

CAS# 67-63-0: Not listed by ACGIH, IARC, NTP, or CA Prop 65.

Carcinogenicity: NTP? No IARC Monographs? No OSHA Regulated? No

CAS # Hazardous Components (Chemical Name) NTP IARC ACGIH OSHA 67-63-0 Isopropyl Alcohol n.a. 3 A4 n.a.

12. ECOLOGICAL INFORMATION

General Ecological Information:

Ecotoxicity: IPA has a high biochemical oxygen demand and a potential to cause oxygen depletion in aqueous systems, a low potential to affect aquatic organisms, a low potential to affect secondary waste treatment microbial metabolism, a low potential to affect the germination of some plants, a high potential to biodegrade (low persistence) with unacclimated microorganisms from activated sludge.

Physical: THOD: 2.40 g oxygen/gCOD: 2.23 g oxygen/gBOD-5: 1.19-1.72 g oxygen/g.

Environmental: No information available.

Other: No information available.

CAS# 67-63-0: Isopropyl Alcohol: LC50, Brine Shrimp (Artemia salina), 278000.

UMOL/L, 24 H, Mortality.

LC50, Rotifer (Brachionus calyciflorus), 476000. UMOL/L, 24 H, Mortality.

Results of PBT and vPvB

assessment:

Other Studies: CAS# 67-63-0:

LC50, Water Flea (Daphnia magna), 10000 mg/L, 24H, Intoxication

LC50, Fathead Minnow (Pimephales promelas), 6550000 ug/L, 96H, Mortality

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method:

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR Parts 261. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification. Observe all

Federal, State, and local regulations.

RCRA P-Series: None listed. RCRA U-Series: None listed.

14. TRANSPORT INFORMATION



Page: 6 of 7 Printed: 03/26/2018 Revision: 03/26/2018

Supersedes Revision: 05/06/2015

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Isopropanol [or] Isopropyl alcohol. **DOT Hazard Class:** 3 FLAMMABLE LIQUID

UN/NA Number: UN1219 Packing Group: II



15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS # Hazardous Components (Chemical Name) S. 302 (EHS) S. 304 RQ S. 313 (TRI)

67-63-0 Isopropyl Alcohol No No Yes

This material meets the EPA [X] Yes [] No Acute (immediate) Health Hazard **'Hazard Categories' defined** [] Yes [X] No Chronic (delayed) Health Hazard

for SARA Title III Sections [X] Yes [] No Fire Hazard

311/312 as indicated: [] Yes [X] No Sudden Release of Pressure Hazard

[] Yes [X] No Reactive Hazard

CAS # Hazardous Components (Chemical Name) Other US EPA or State Lists

67-63-0 Isopropyl Alcohol CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No;

CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: No; MI CMR, Part 5: No; NJ EHS: Yes - 1076; NY Part 597: No; PA HSL:

Yes - E

16. OTHER INFORMATION

Revision Date: 03/26/2018

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer: date hereof, Morgan-Gallacher makes no warranty with respect thereto and expressly

disclaims all liability for reliance thereon. Such data is offered solely for your

While Morgan-Gallacher believes the statements set forth herein are accurate as of the

consideration, investigation, and verification.