

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Material name : A00239AH MST SEAS ATM HTHR HH 20net10

Material number : 000000000001001862

**Manufacturer or supplier's details**

Company : Zep Inc.

Address : 1310 Seaboard Industrial Blvd., NW  
Atlanta, GA 30318

Telephone : 404-352-1680

**Emergency telephone numbers****For SDS Information** : Compliance Services 1-877-428-9937**For a Medical Emergency** : 877-541-2016 Toll Free - All Calls Recorded**For a Transportation Emergency** : CHEMTREC: 800-424-9300 - All Calls Recorded.  
In the District of Columbia 202-483-7616**SECTION 2. HAZARDS IDENTIFICATION****Emergency Overview**

Appearance	Aerosol containing a liquefied gas
Colour	clear, colourless
Odour	characteristic

**GHS Classification**

Flammable aerosols : Category 1  
Gases under pressure : Liquefied gas  
Eye irritation : Category 2A  
Skin sensitisation : Category 1  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)

**GHS Label element**

Hazard pictograms



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H280 Contains gas under pressure; may explode if heated.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear eye protection/ face protection.  
P280 Wear protective gloves.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P363 Wash contaminated clothing before reuse.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Disposal:**

P501 Dispose of contents/container in accordance with local regulation.

**Potential Health Effects****Carcinogenicity:****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

**Hazardous components**

Chemical Name	CAS-No.	Concentration [%]
acetone	67-64-1	$\geq 70$ - $< 90$
propane	74-98-6	$\geq 10$ - $< 20$
butane	106-97-8	$\geq 5$ - $< 10$
eugenol	97-53-0	$\geq 0.1$ - $< 1$
cinnamaldehyde	104-55-2	$\geq 0.1$ - $< 1$

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Wash clothing before reuse.  
Call a physician if irritation develops or persists.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Remove contact lenses.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
DO NOT induce vomiting unless directed to do so by a physician or poison control center.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray jet
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon dioxide (CO<sub>2</sub>)  
Carbon monoxide  
Smoke
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : For safety reasons in case of fire, cans should be stored

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Sweep up or vacuum up spillage and collect in suitable container for disposal.

---

**SECTION 7. HANDLING AND STORAGE**

Advice on safe handling : Do not breathe vapours or spray mist.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Container may be opened only under exhaust ventilation hood.  
Always replace cap after use.  
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
No smoking.  
Observe label precautions.  
Keep in a dry, cool and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.

Materials to avoid : Oxidizing agents  
Store and keep away from bases and alkalies.

## A00239AH MST SEAS ATM HTHR HH 20net10

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
acetone	67-64-1	TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA Z-1
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA P0
propane	74-98-6	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA Z-1
		TWA	1,000 ppm 1,800 mg/m <sup>3</sup>	OSHA P0
butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	NIOSH REL
		TWA	800 ppm 1,900 mg/m <sup>3</sup>	OSHA P0

## Biological occupational exposure limits

Component	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
2-PROPANONE	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	50 mg/l	ACGIH BEI

## Personal protective equipment

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.  
Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection  
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Ensure that eyewash stations and safety showers are close to

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

	the workstation location. Safety glasses
Skin and body protection	: impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: Aerosol containing a liquefied gas
Colour	: clear, colourless
Odour	: characteristic
Odour Threshold	: no data available
pH	: not applicable
Melting point/freezing point	: no data available
Boiling point	: no data available
Flash point	: not applicable
Evaporation rate	: not determined
Flammability (solid, gas)	: Extremely flammable aerosol.
Upper explosion limit	: no data available
Lower explosion limit	: no data available
Vapour pressure	: no data available
Relative vapour density	: no data available
Density	: 0.795 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	: completely soluble
Solubility in other solvents	: not determined
Partition coefficient: n-octanol/water	: no data available
Auto-ignition temperature	: not determined
Thermal decomposition	: no data available
Viscosity	
Viscosity, kinematic	: no data available

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Oxidizing agents Amines Bases
Hazardous decomposition products	: Carbon monoxide Carbon dioxide (CO <sub>2</sub> )

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****cinnamaldehyde:**

Acute oral toxicity : LD50 Oral rat: 2,220 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Serious eye damage/eye irritation****Product:**

Remarks: Irritating to eyes.

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Germ cell mutagenicity**

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

no data available

**Carcinogenicity**

no data available

**Reproductive toxicity**

no data available

acetone:  
propane:  
butane:  
eugenol:  
cinnamaldehyde:

**STOT - single exposure**

no data available

**STOT - repeated exposure**

no data available

**Aspiration toxicity**

no data available

**Further information****Product:**

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

no data available

**Persistence and degradability**

no data available

**Bioaccumulative potential****Product:**

Partition coefficient: n- : Remarks: no data available  
octanol/water

**Components:****butane :**

Partition coefficient: n- : Pow: 2.89  
octanol/water

**cinnamaldehyde :**

Partition coefficient: n- : Pow: 1.83  
octanol/water

**Mobility in soil**



**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

no data available

**Other adverse effects**

no data available

**Product:**

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: no data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues	: Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	: Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION**

Transportation Regulation: 49 CFR (USA):  
ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel):  
UN1950, AEROSOLS, 2.1, - Limited quantity

Transportation Regulation: IATA (Cargo Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: IATA (Passenger Air):  
UN1950, Aerosols, flammable, 2.1, - Limited quantity

Transportation Regulation: TDG (Canada):  
UN1950, AEROSOLS, 2.1, - Limited quantity

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
acetone	67-64-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Sudden Release of Pressure Hazard  
Acute Health Hazard

**SARA 302** : SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**The components of this product are reported in the following inventories:**

<b>TSCA</b>	On TSCA Inventory
<b>DSL</b>	This product contains one or several components that are not on the Canadian DSL nor NDSL.
<b>AICS</b>	Not in compliance with the inventory
<b>NZIoC</b>	Not in compliance with the inventory
<b>PICCS</b>	Not in compliance with the inventory
<b>IECSC</b>	Not in compliance with the inventory

**Inventory Acronym and Validity Area Legend:**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

## A00239AH MST SEAS ATM HTHR HH 20net10


Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015

## Further information

## NFPA:



## HMIS III:

HEALTH	3
FLAMMABILITY	4
PHYSICAL HAZARD	2

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

## OSHA GHS Label Information:

Hazard pictograms



Signal word

: **Danger:**

Hazard statements

: Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statements

: **Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/ gas/ mist/ vapours/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye protection/ face protection. Wear protective gloves.  
**Response:** IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get medical advice/ attention. Wash contaminated clothing before reuse.  
**Storage:** Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.  
**Disposal:** Dispose of contents/container in accordance with local regulation.

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.

Zep Inc. markets products under well recognized and established brand names such as Zep®, Zep Commercial®, Zep Professional®, Enforcer®, National Chemical™, Selig™, Misty®, Next Dimension™, Petro®, i-Chem®, TimeMist®, TimeWick™, MicrobeMax®, Country Vet®, Konk®, Original Bike Spirits®, Blue Coral®, Black Magic®, Rain-X®, Niagara National™, FC Forward Chemicals®, Rexodan®, Mykal™, and a number of private labeled brands.

**A00239AH MST SEAS ATM HTHR HH 20net10**

Version 1.0

Revision Date 02/26/2015

Print Date 06/06/2015