

## SECTION – 1 CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME** Unbelievable!® Goo D-Solv-R **ITEM** UGDP

**PRODUCT USE** General Purpose Adhesive Remover

**COMPANY NAME** Core Products Co., Inc. **Office** (800) 825-2673  
 401 Industrial Rd **Fax** (903) 567-1346  
 Canton TX 75103 **Web** [www.coreproductsco.com](http://www.coreproductsco.com)

**EMERGENCY TELEPHONE NUMBER** **CHEMTREC** (800) 424-9300

## SECTION – 2 HAZARDS INFORMATION

**Physical Hazards** FLAMMABLE LIQUIDS-Category 3  
**Health Hazards** EYES-Category 2A; SKIN-Category 2; STOT SINGLE EXPOSURE-Category 3



Flammables



Irritant (skin and eye)  
Respiratory Tract Irritant

**WARNING** Flammable liquid and vapor, (Liquid does not sustain combustion, Not Regulated by DOT)  
 Causes serious eye irritation, Causes skin irritation, May cause respiratory irritation  
 May be harmful if swallowed, Do not get in eyes, on skin, or clothing, and avoid inhalation of mist, Do not smoke, eat or drink while using, Use personal protective equipment as required, Wash thoroughly after handling, Avoid release into the environment

## SECTION – 3 COMPOSITION INFORMATION

(Exact percentage of the listed chemicals of composition has been withheld as a trade secret)

CHEMICAL NAME	COMMON NAME AND SYNONYMS	CAS #	IMPURITIES	PERCENT
Synthetic Hydrocarbon	Supplier Proprietary	Unknown		8 - 12%
Glycol Ether DB	Diethylene Glycol Monobutyl Ether	112-34-5		50 - 80%
Acetone	2-propanone	67-64-1	Water < 0.5%	1 - 4%
Alcohol Ethoxylate	Alcohols, C9-11, ethoxylated	68439-46-3		3 - 8%

## SECTION – 4 FIRST AID MEASURES

**EYE CONTACT** Immediately flush eyes with cold water for at least 15 minutes while lifting upper and lower eyelids, Remove contact lenses if present and easy to do without injury to the eye and continue rinsing, If irritation persists obtain medical attention, preferably from an ophthalmologist

**SKIN CONTACT** Wash contaminated skin with plenty of soap and water, Remove any contaminated clothing and wash before reuse, If irritation occurs or persists obtain medical attention

**INHALATION** Move person to fresh air, if they have problem breathing, show signs of overexposure or feel unwell obtain medical attention

**INGESTION** DO NOT INDUCE VOMITING. If person is fully conscious, rinse mouth out and give one to two glasses of water to dilute and obtain immediate medical attention. If vomiting occurs, keep head below hips to prevent aspiration into the lungs

**Aspiration Hazard** Not considered to be an aspiration hazard

### ACUTE SYMPTOMS OF SINGLE OVEREXPOSURE

**Eyes** Can cause eye irritation  
**Skin** Can cause skin irritation  
**Inhalation** Mist may cause irritation, to respiratory tract  
**Ingestion** May be harmful if swallowed, Can cause irritation, of the mouth, throat, and esophagus, May affect target organs

### CHRONIC SYMPTOMS OF PROLONGED OR REPEATED OVEREXPOSURE

**Eyes** Causes serious eye irritation, redness, tearing, or pain  
**Skin** Causes skin irritation, burning, drying or cracking  
**Inhalation** Mist may cause irritation, to mucus membranes or respiratory tract  
**Ingestion** May be harmful if swallowed, Causes irritation, of the mouth, throat, and esophagus, Ingestion may cause vomiting which may be harmful if it enters airways, Ingestion may affect, liver, kidneys, central nervous system

**SECTION – 5 FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Does not sustain combustion, Use extinguishing media for surrounding fire
<b>Hazardous Decomposition</b>	Burning or thermal decomposition can produce, carbon monoxide, carbon dioxide, and other toxic fumes
<b>Reactive With</b>	Incompatible with, oxidizing agents, reducing agents, strong acids
<b>Explosion Hazards</b>	May flash if heated and ignited in an enclosed area
<b>Static Discharge</b>	Not expected to ignite product
<b>Mechanical Impact</b>	Not applicable
<b>Protective Equipment</b>	Use MSHA/NIOSH approved self-contained breathing apparatus and full protective gear

**SECTION – 6 ACCIDENTAL RELEASE MEASURES**

<b>Emergency Procedures</b>	Warn personnel to move away
<b>Personal Precautions</b>	Eliminate ignition sources and ventilate area, Avoid slipping on spilled product
<b>Protective Equipment</b>	Safety Glasses, Chemical Gloves and Rubber Boots
<b>Containment</b>	Use sand or inert non-combustible absorbent pads to prevent spill from spreading, Prevent spill from entering the environment
<b>Clean Up Procedures</b>	Small Spills: Use wet vacuum or mop and wringer to pick up spilled material then mop area with clean water Large Spills: Absorb spill with inert material, place in a chemical waste container, mop area with clean water
<b>Disposal</b>	Dispose of material in accordance with all State and Federal Guidelines and Regulations

**SECTION – 7 HANDLING AND STORAGE**

<b>Handling</b>	Keep away from incompatible materials, sparks, open flames or hot surfaces, Use appropriate safety equipment, Avoid eye and skin contact, Do not smoke, eat or drink while using, Wash thoroughly after handling, Avoid release to the environment
<b>Storage</b>	KEEP OUT OF REACH OF CHILDREN, Keep container closed when not in use, Store in a well-ventilated area and away from incompatible materials, Store below 49°C (120°F) and in accordance with Class II Combustible Liquids (GHS Category 3)
<b>Incompatible Materials</b>	Incompatible with, oxidizing agents, reducing agents, strong acids

**SECTION – 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****EXPOSURE LIMITS**

CHEMICAL NAME	ACGIH (TWA 8)	ACGIH (STEL)	OSHA PEL (TWA 8)	OSHA (CEIL)	Significant Exposure
Synthetic Hydrocarbon	Not Established		Not Established		EI,SI
Glycol Ether DB	10 ppm				EI
Alcohol Ethoxylate	None Established				EI
Acetone	500 ppm (A4)	750 ppm		1000 ppm (2400 mg/m³)	CNS, RT

**PERSONAL PROTECTIVE EQUIPMENT**Chemical Safety Glasses,  
Goggles or Face ShieldImpervious  
Chemical GlovesEye Wash  
(Recommended)**Ventilation**

General Ventilation

If exposure limits listed above are exceeded, or irritation is experienced, use a MSHA / NIOSH approved respirator

**HMIS HAZARD RATINGS**

Health	2
Flammability	2
Reactivity	0
Personal Protection	B

**SECTION – 9 PHYSICAL AND CHEMICAL PROPERTIES**

<b>Flash Point</b>	53.0°C (127.4°F) - TAG Closed Cup	<b>Specific Gravity / Density</b>	0.97
<b>Flammable Limits</b>	Does not sustain combustion (ASTM D4206)	<b>pH (± 0.3)</b>	6.6
<b>Auto-Ignition Temp.</b>	ND	<b>Viscosity</b>	ND
<b>Physical State</b>	Liquid	<b>Freeze Point</b>	< 0°C (32°F)
<b>Appearance</b>	Clear	<b>Boiling Point</b>	100°C (212°F)
<b>Odor</b>	Light Acetone	<b>Vapor Density (air=1)</b>	ND
<b>Odor Threshold</b>	ND	<b>Vapor Pressure (mm Hg)</b>	ND
<b>Solubility</b>	Immiscible	<b>Evaporation Rate (nBuAc=1)</b>	ND
<b>Volatiles</b>	< 94%	<b>Partition Coefficient</b>	ND
<b>VOC</b>	0.00	<b>Molecular Weight (g/mol)</b>	ND
<b>LVP-VOC</b>	69%	<b>Decomposition Temperature</b>	ND

**SECTION – 10 STABILITY AND REACTIVITY**

Reactivity (Specific Test Data)	None available
Chemical Stability	Stable when stored below 49°C (120°F)
Hazardous Polymerization	Will not occur
Conditions To Avoid	Heat sources, open flame or incompatible materials
Incompatible Materials	Incompatible with, oxidizing agents, reducing agents, strong acids
Thermal Decomposition	Burning or thermal decomposition can produce, carbon monoxide, carbon dioxide, and other toxic fumes

**SECTION – 11 TOXICOLOGICAL INFORMATION****ROUTES OF EXPOSURE**

Eyes (Yes), Skin (Yes), Inhalation (Yes "Mist"), Ingestion (Yes)

**ACUTE SYMPTOMS OF SINGLE OVEREXPOSURE**

Eyes	Can cause eye irritation
Skin	Can cause skin irritation
Inhalation	Mist may cause irritation, to respiratory tract
Ingestion	May be harmful if swallowed, Can cause irritation, of the mouth, throat, and esophagus, May affect target organs

**CHRONIC SYMPTOMS OF PROLONGED OR REPEATED OVEREXPOSURE**

Eyes	Causes serious eye irritation, redness, tearing, or pain
Skin	Causes skin irritation, burning, drying or cracking
Inhalation	Mist may cause irritation, to mucus membranes or respiratory tract
Ingestion	May be harmful if swallowed, Causes irritation, of the mouth, throat, and esophagus, Ingestion may cause vomiting which may be harmful if it enters airways, Ingestion may affect, liver, kidneys, central nervous system

Acute Tox Calculated      **Oral:** 5,923 mg/kg      **Dermal:** 3,880 mg/kg      **Inhaled:** > 50.0 mg/L

Acute Tox Category    Not applicable (Oral >5000 mg/kg), Not applicable (Dermal >2,000 mg/kg), Not applicable (Inhaled >50 mg/L) Vapors

**Additional Info**

Target Organs	Kidneys, Mucous Membranes, Respiratory Tract, Eyes (Lens or cornea), Lungs, Skin
Medical Conditions	Preexisting, eye, skin, liver, kidney, disorders may be aggravated by exposure to this product
Notes to Physician	In case of ingestion, gastric lavage with activated charcoal can be used promptly to prevent absorption

**CARCINOGENIC – This product contains concentrations above 0.1% of the following:**

<u>CHEMICAL NAME</u>	<u>NTP</u>	<u>ACGIH</u>	<u>IARC</u>	<u>GHS Category</u>
None Listed	NA	NA	NA	NA

**MUTAGENIC AND REPRODUCTIVE EFFECTS – This product contains concentrations above 0.1% of the following:**

<u>CHEMICAL NAME</u>	<u>Germ Cell Mutagenicity</u>	<u>Toxic to Reproduction</u>
None Listed	NA	NA

**COMPONENTS ACUTE TOXICITY**

<u>CHEMICAL NAME</u>	<u>Type</u>	<u>Form</u>	<u>Subject</u>	<u>Result Value</u>	<u>Exposure Time</u>	<u>GHS Category</u>
Glycol Ether DB	LD50	Oral	Rat	7,291 mg/kg	4 Hours (Vapor)	(>2000 mg/kg)
	LD50	Dermal	Rabbit	2,764 mg/kg		(>2000 mg/kg)
Acetone	LD50	Oral	Rat	5,800 mg/kg	4 Hours (Vapor)	(>2000 mg/kg)
	LD50	Inhaled	Rat	100.2 mg/L		(>20 mg/L)
	LD50	Dermal	Guinea pig	7,426 mg/kg		(>2000 mg/kg)
Alcohol Ethoxylate	LD50	Oral	Rat	> 2,000 mg/kg	4 Hours (Vapor)	(>2000 mg/kg)
	LD50	Dermal	Rabbit	> 2,000 mg/kg		(>2000 mg/kg)
Synthetic Hydrocarbon	LD50	Oral	Rat	> 5,000 mg/kg		(>2000 mg/kg)
	LC50	Rat	Inhalation	> 20 mg/L		(>20 mg/L)
	LD50	Rabbit	Dermal	>5,010 mg/kg		(>2000 mg/kg)

**SECTION – 12 ECOLOGICAL INFORMATION**

<u>CHEMICAL NAME</u>	<u>Type</u>	<u>Subject</u>	<u>Subject Latin</u>	<u>Result Value</u>	<u>Exposure Time</u>	<u>GHS Category</u>
Glycol Ether DB	LC50	Fish	(Leuciscus idus)	1,300 mg/L	96 Hours	4 (>100 mg/L)
	EC50	Water Flea	(Daphnia magna)	>100 mg/L	48 Hours	4 (>100 mg/L)
Acetone	LC50	Mosquito Fish	(Gambusia affinis)	13,000 mg/L	48 Hours	4 (>100 mg/L)
	LC50	Rainbow Trout	(Oncorhynchus mykiss)	5,540 mg/L	96 Hours	4 (>100 mg/L)
	EC50	Water Flea	(Daphnia magna)	8,800 mg/L	48 Hours	4 (>100 mg/L)
Alcohol Ethoxylate	LD50	Fathead minnow	(Pimephales promelas)	140 mg/L	96 Hours	4 (>100 mg/L)
	EC50	Water Flea	(Daphnia magna)	5.3 mg/L	48 Hours	2 (>1, ≤10 mg/L)
Synthetic Hydrocarbon	LC50	Fathead Minnow	(Pimephales promelas)	> 1,000 mg/L	96 Hours	4 (>100 mg/L)
<b>Presistence And Degradability</b>	This product is inherently biodegradable according to the OECD definition					
<b>Bioaccumulative Potential</b>	No data available					
<b>Mobility In Soil</b>	No data available					
<b>Other Adverse Effects</b>	Harmful to aquatic life					

**SECTION – 13 DISPOSAL CONSIDERATIONS**

**DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER**  
**Dispose of any waste in accordance with all State and Federal Guidelines and Regulations**

**ENVIRONMENTAL FATE**

Under RCRA rules, it is the responsibility of the user of the product to determine, at the time of disposal, whether the material is a hazardous waste

CONTAINER DISPOSAL - Triple rinse container then offer for recycling. If not available, puncture and dispose in a sanitary landfill

**SECTION – 14 TRANSPORT INFORMATION****DOT CLASSIFICATION**

<u>UN Number</u>	<u>Proper Shipping Name</u> <u>n.o.s. ( Chemicals ) or "Limits"</u>					
Not Regulated	Non Hazardous – Compounds Cleaning Liquid					
<u>Hazard Class</u>	<u>Packing Group</u>	<u>Label Codes</u>	<u>Reportable Quantity (lbs)</u>	<u>Response</u>	<u>Marine Pollutant</u>	<u>Hazard Label</u>
None	None	None	None	154	No	
<b>Additional Info:</b> Liquid does not sustain combustion by the prescribed procedure in the 49 CFR §173.120(a)(3)						

**IATA CLASSIFICATION**

<u>UN Number</u>	<u>UN Proper Shipping Name</u> <u>n.o.s. ( Chemicals ) or "Limits"</u>					
UN 1993	Flammable Liquid, n.o.s. (Acetone Solution )					
<u>Class</u>	<u>Packing Group</u>	<u>Enviro Hazard</u>	<u>ERG</u>	<u>Special Provisions</u>	<u>Labels Required</u>	<u>Subsidiary Risk</u>
3	III	No	3L		Flammable Liquid	-

Special precautions / marking:



**SECTION – 15 REGULATORY INFORMATION****TSCA**

CHEMICAL NAME	Sec 8(b) Inventory	Sec 8(d) Health And Safety	Sec 4(a) Chemical Test Rules	Sec 12(b) Export Notification
Glycol Ether DB	Yes			
Alcohol ethoxylate	Yes			
Acetone	Yes	Yes	Yes	Yes

**REPORTABLE QUANTITIES**

CHEMICAL NAME	EPCRA TPQ Sec 302	EPCRA RQ Sec 304	Reportable Quantity CERCLA RQ Sec 103	Emission Reporting TRI Sec 313	RCRA Code	RMP TQ Sec 112r
Glycol Ethers				Yes		
Acetone			5000		U002	

**SARA**

CHEMICAL NAME	Section 311 Hazardous Chemical	Section 311 / 312 Hazards Acute	Chronic	Flammable	Pressure	Reactive
Synthetic Hydrocarbon	Yes	Yes				
Glycol Ether DB	Yes	Yes	Yes			
Alcohol Ethoxylate	Yes	Yes				
Acetone	Yes	Yes	Yes	Yes		

**RIGHT TO KNOW**

STATE													
CHEMICAL NAME	CA	CT	FL	IL	LA	NJ	NY	PA	MI	MN	MA	RI	WI
Glycol Ether DB							Yes	Yes					
Acetone	Yes			Yes	Yes	Yes	Yes	Yes		Yes	Yes	Yes	

**CALIFORNIA**

CHEMICAL NAME	CAS #	WARNING! This product contains chemicals known to the state of California to cause:
		Birth Defects      Reproductive Harm      Carcinogen      Developmental
None Listed		

**CLEAN AIR WATER ACTS**

CHEMICAL NAME	CAS #	Clean Air Acts HAP	Ozone Class 1	Ozone Class 2	Clean Water Acts HS	PP	TP
None Listed							

**INTERNATIONAL REGULATIONS** – The components of this product are listed on the chemical inventories of the following countries:

CHEMICAL NAME	Australia	Canada	Europe (EINECS)	Japan	Korea	UK
Synthetic Hydrocarbon	Yes	Yes	Yes	Yes	Yes	Yes
Glycol Ether DB	Yes	Yes	Yes	Yes	Yes	Yes
Alcohol Ethoxylate	Yes	Yes	Yes	Yes	Yes	Yes
Acetone	Yes	Yes	Yes	Yes	Yes	Yes

**WHMIS Classification**

CHEMICAL NAME	DSL	Class	Description
Glycol Ether DB, Acetone, Synthetic Hydrocarbon	Yes	D-2B	Materials Causing Other Toxic Effects; Toxic Material
		B-3	Combustible Liquids; Flashpoint ≥ 37.8° C (100°F) ≤ 93.3°C (200°F)

## SECTION – 16

## OTHER INFORMATION

**SDS** **LEGEND DESCRIPTION****ACGIH** American Conference of Governmental Industrial Hygienists**CAS** Chemical Abstracts Service Registry**CEIL** Ceiling Limit (15 minutes)**CERCL** Comprehensive Environmental Response, Compensation, and Liability Act**CI** Cochlear Impairment**CNS** Central Nervous System**EC50** Concentration of a chemical that gives half-maximal response**EPA** Environmental Protection Agency**Eye** (EI = Irritation) (ED = Damage) (EV = Visual Impairment)**FBG** Full Bunker Gear**GHS** Globally Harmonized System**HAP** California Hazardous air pollutant Clean Air Act**HMIS-A** Safety Glasses**HMIS-B** Safety glasses, gloves**HMIS-C** Safety glasses, gloves, chemical apron**HMIS-D** Face shield, gloves, chemical apron**HMIS-E** Safety glasses, gloves, dust respirator**HMIS-F** Safety glasses, gloves, chemical apron, dust respirator**HMIS-G** Safety glasses, gloves, vapor respirator**HMIS-H** Splash goggles, gloves, chemical apron, vapor respirator**HMIS-I** Safety glasses, gloves, dust and vapor respirator**HMIS-J** Splash goggles, gloves, chemical apron, dust and vapor respirator**HMIS-K** Air line hood or mask, gloves, full chemical suit, boots**HMIS-X** Ask Supervisor**HS** California Hazardous Substance under the Clean Water Act**KD** Kidney Damage (nephropathy)**LC50** A concentration that is lethal to 50% of a given species in a given time**LD50** Dose that is lethal to 50% of a given species by a given route of exposure**LEL** Lower Explosive Limit**LD** Liver Damage**NA** Not Applicable**ND** Not Determined**NFPA** National Fire Protection Association**NIOSH** National Institute for Occupational Safety and Health**NE** Not Established**NTP** National Toxicology Program**OSHA** Occupational Safety and Health Administration**PEL** Permissible Exposure Limit (OSHA)**PNS** Peripheral Nervous System**PP** California Priority Pollutant under the Clean Water Act**REL** Recommended exposure limit (NIOSH)**RT** Upper Respiratory Tract**Skin** (SI = Irritation) (SD = Damage) (SA = Absorption) (SS = Sensitizer)**SARA** Superfund Amendments and Reauthorization Act**STEL** Short Term Exposure Limit (15 minutes)**TC Lo** Lowest concentration that is toxic to a given species in a given time**TD Lo** Lowest dose that is toxic to a given species**TLV** Threshold Limit Value (ACGIH)**TP** California Toxic Pollutant under the Clean Water Act**TSCA** Toxic Substances Control Act**TWA** Time Weighted Average (8 hours)**UEL** Upper Explosive LimitCore Products Co., Inc.

and nCites LLC have compiled the information herein from sources believed to be reliable and up-to-date, and is accurate to the best of our knowledge. However, we cannot give any guarantees regarding information from other sources or the completeness and expressly do not make warranties, nor assume any liability for its use. The information contained herein is provided for reference purposes only and is intended only for persons having relevant technical skills. Because conditions and manner of use are outside of our control, the user is responsible for determining the conditions of safe use of the product. Buyers and users assume all risk, responsibility and liability whatsoever for any and all injuries, losses, or damages to persons or property arising from the use of this product or information.

**Print Date** 1/22/2016**Supersedes Safety Data Sheet Dated**

1/1/2013