

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION	
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special- - Manufacturer's Name: AMREP, INC. Address: 990 Industrial Park Drive Marietta, GA 30062	HMS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B DOT Hazard Classification: Flammable Liquid, 3 Identity (trade name as used on label): MISTY CLEAR-CRETE
Date Prepared: 07/18/94 Prepared By: ES Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924	MSDS Number: R 842 Revision: - 6 NOTICE: JUDGMENT BASED ON INDIRECT TEST DATA

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
XYLENE	1330-20-7	Yes	100	100	d
TOLUENE	108-88-3	Yes	200	100	d
WARNING: This product contains a chemical or chemicals known to the State of California to cause birth defects or other reproductive harm.					

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
Boiling Point: >230°F Vapor Pressure: PSIG @ 70°F (Aerosols): N/A Vapor Density (Air = 1): >1 Solubility in Water: Negligible Appearance and Odor: Clear, colorless, lightly viscous liquid with aromatic odor.	Specific Gravity (H2O=1): 0.9 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/D Evaporation Rate (water = 1): >1 Water Reactive: No

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA	
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) N/A FLASH POINT AND METHOD USED (non-aerosols): 59°F TCC EXTINGUISHER MEDIA: Water fog, foam, dry chemical or CO2. Do not use direct waterstream. Unusual Fire & Explosion Hazards: Vapors are heavier than air & may accumulate in low or inadequately ventilated areas. Vapors may also travel along the ground to be ignited at locations distant from handling site. Flashback or flame to the handling site may occur.	Auto Ignition Temperature: N/D Flammability Limits in Air by % in Volume: % LEL: 1 % UEL: 1 SPECIAL FIRE FIGHTING PROCEDURES: Wear proper protective equipment including NIOSH approved self-contained breathing apparatus. Cool fire exposed containers, surrounding equipment & structures with water.

SECTION 4 - REACTIVITY HAZARD DATA	
STABILITY [X] STABLE [] UNSTABLE Incompatibility (Mat. to avoid): Strong oxidizing agents. Hazardous Decomposition Products: Oxides of carbon & unidentified organic compounds.	HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR Conditions to Avoid: Heat, sparks, open flame.

SECTION 5 - HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY: [X] INHALATION [X] INGESTION [] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS	
ACUTE EFFECTS: Toxicity: Overexposure can lead to CNS depression producing headache, dizziness, nausea and loss of consciousness. Inhalation: High concentrations or prolonged exposure to lower concentrations may be slightly irritating to mucous membranes. Prolonged inhalation of high concentrations may result in toxic effects listed above. Eye Contact: Slight irritation from short term contact. Prolonged & repeated contact more irritating. Skin Contact: Prolonged & repeated liquid contact can cause defatting and dryness of skin which may result in irritation and dermatitis. Ingestion: May result in vomiting. Aspiration of vomitus into lungs must be avoided as lung contact can result in chemical pneumonitis and pulmonary edema/hemorrhage. Absorption of ingested material may result in toxic effects listed above. CHRONIC EFFECTS: None known.	
Medical Conditions Generally Aggravated by Exposure: May further irritate pre-existing irritation.	

EMERGENCY FIRST AID PROCEDURES	
Eye Contact: Flush with water for 15 minutes. If irritation persists, get medical attention. Skin Contact: Remove contaminated clothing. Wash with soap and water. If irritation persists, get medical attention. Inhalation: Remove to fresh air. Provide oxygen if breathing is difficult, artificial respiration if not breathing. Get medical attention. Ingestion: DO NOT INDUCE VOMITING. Drink 3 to 4 glasses of water. Get immediate medical attention.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES	
Respiratory Protection (specify type): If exposure may or does exceed section 1 limits use a NIOSH approved air purifying respirator for organic vapors or atmosphere-supplying respirator.	
Protective Gloves: Solvent resistant.	Eye Protection: Chemical goggles.
Ventilation Requirements: Explosion proof ventilation as required to meet section 1 vapor concentrations.	
Other Protective Clothing & Equipment: Solvent resistant clothing as required to minimize skin contact. Eyewash station and safety shower.	
Hygienic Work Practices: Do not eat, drink or smoke in work area. Wash hands after handling.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE	
Steps To Be Taken If Material Is Spilled Or Released: WARNING: FLAMMABLE. Eliminate all ignition sources. Handling equipment must be grounded to prevent sparking. Contain spill. Keep out of surface waters & any sewers or water courses entering or leading to surface waters. Soak up with inert absorbent & place in properly labeled leak-proof containers for disposal.	
Waste Disposal Methods: Dispose of in accordance with all local, state and federal regulations.	
Precautions To Be Taken In Handling & Storage: Store in original shipping containers. Keep closed when not in use. Shelf life 1 year. Containers & equipment must be bonded & grounded when pouring or transferring.	
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Read & follow label directions. Do not weld, heat or drill on or near containers; even emptied containers can contain explosive vapors.	

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
 ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only