SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

PLEXUS® MA832 Adhesive

Registration number

Product registration number UFI: NV90-2065-S00P-W143

Synonyms None. SKU# 0533

Issue date 13-July-2023

Version number 04

Revision date 22-October-2025 21-October-2025 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name **ITW Performance Polymers**

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact person Customer Service Telephone number 353(61)771500

353(61)471285

Email customerservice.shannon@itwpp.com

Emergency phone number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General emergency 112 or 999 SDS/Product information may not be available for the Emergency

Non-emergency medical

helpline

111 SDS/Product information may not be available for the Emergency Service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies. The classification of the substance or mixture has been performed in accordance with ABNT NBR 14725.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids Category 2 H225 - Highly flammable liquid and

vapour.

Health hazards

H315 - Causes skin irritation. Skin corrosion/irritation Category 2 Serious eye damage/eye irritation H318 - Causes serious eye Category 1

damage.

Skin sensitisation H317 - May cause an allergic skin Category 1

reaction.

Specific target organ toxicity - single exposureCategory 3 respiratory tract irritation H335 - May cause respiratory

irritation.

Material name: PLEXUS® MA832 Adhesive SDS GREAT BRITAIN

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard

Category 3

H412 - Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate, methacrylic acid;

2-methylpropenoic acid

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

May cause an allergic skin reaction. H317 Causes serious eye damage. H318 May cause respiratory irritation. H335

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours. P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace. P272

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

IF ON SKIN: Wash with plenty of water. P302 + P352

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P303 + P361 + P353

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present P305 + P351 + P338

and easy to do. Continue rinsing.

Immediately call a POISON CENTRE/doctor. P310

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. P370 + P378

Storage

Store in a well-ventilated place. Keep container tightly closed. P403 + P233

Store in a well-ventilated place. Keep cool. P403 + P235

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

None.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC)

No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list

established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Material name: PLEXUS® MA832 Adhesive SDS GREAT BRITAIN

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	40 - 70	80-62-6 201-297-1	01-2119452498-28-0000	607-035-00-6	#
Classification: Flam. Liq. 2;H225, Acute Tox. 4;H332, Skin Irrit. 2;H315, Skin Sens. 1;H317, STOT SE 3;H335					
Specific Concentration Limits:	STOT SE	3;H335: C ≥ 10 %			
methacrylic acid; 2-methylpropenoic acid	3 - < 5	79-41-4 201-204-4	01-2119463884-26-0000	607-088-00-5	#
Classification Specific Concentration Limits:	1A;H314,	Eye Dam. 1;H318, ST	;H312, Acute Tox. 3;H331, OT SE 3;H335	Skin Corr.	D
Paraffin wax	1 - < 3	8002-74-2 232-315-6	-	-	#
Classification	: -				
Zinc oxide	< 1	1314-13-2 215-222-5	-	030-013-00-7	#
Classification	: Aquatic A	cute 1;H400, Aquatic (Chronic 1;H410		
phosphoric acid %, orthophosphoric acid %	< 0.2	7664-38-2 231-633-2	-	015-011-00-6	#
Classification	: Acute Tox 1;H318	. 4;H302, Acute Tox. 2	;H330, Skin Corr. 1B;H314,	Eye Dam.	В
Specific Concentration Limits:			Skin Irrit. 2;H315: 10 % ≤ C it. 2;H319: 10 % ≤ C < 25 %	•	
Other components below reportable levels	30 - 60				

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema

or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards Highly flammable liquid and vapour.

Material name: PLEXUS® MA832 Adhesive

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters
Special protective
equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

For emergency responders

Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tonnes; Upper-tier requirements

= 200 tonnes)

7.3. Specific end use(s)Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Material name: PLEXUS® MA832 Adhesive SDS GREAT BRITAIN

Occupational exposure limits

UK. OELs. Workplace Expos Components	sure Limits (WELs) (EH40/2005 (Fourt Type	th Edition 2020)), Table 1 Value	Form			
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	143 mg/m3				
,		40 ppm				
	TWA	72 mg/m3				
		20 ppm				
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m3				
		100 ppm				
	TWA	208 mg/m3				
		50 ppm				
Paraffin wax (CAS 8002-74-2)	STEL	6 mg/m3	Fume.			
	TWA	2 mg/m3	Fume.			
phosphoric acid %, orthophosphoric acid % (CAS 7664-38-2)	STEL	2 mg/m3				
(1)	TWA	1 mg/m3				
Zinc oxide (CAS 1314-13-2)	TWA	4 mg/m3	Respirable dust.			
		10 mg/m3	Inhalable dust.			
Biological limit values	No biological exposure limits noted for	r the ingredient(s).				
Recommended monitoring procedures	Follow standard monitoring procedures.					
Derived no effect levels (DNELs)	Not available.					
Predicted no effect concentrations (PNECs)	Not available.					
Exposure guidelines	Occupational Exposure Limits are not relevant to the current physical form of the product.					
8.2. Exposure controls						
Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.					
Individual protection measures, General information	such as personal protective equipmed Use personal protective equipment as according to the CEN standards and i equipment.	required. Personal protection				
Eye/face protection	Wear safety glasses with side shields (or goggles).					
Skin protection						
- Hand protection	Wear appropriate chemical resistant gloves.					
- Other	Wear appropriate chemical resistant clothing.					
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.					
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.					
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.					
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Furne scrubbers, filters or engineering					

requirements of environmental protection legislation. Fume scrubbers, filters or engineering

modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

Material name: PLEXUS® MA832 Adhesive

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Paste.
Physical state Liquid.
Form Paste.
Colour Off-white
Odour Fragrant
Odour threshold Not available.

Melting point/freezing point -48 °C (-54.4 °F) estimated Initial boiling point and boiling 100.5 °C (212.9 °F) estimated

Not available.

range

pН

Flash point 10.0 °C (50.0 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2.1 % estimated 8.2 % estimated

(%)

Vapour pressure 51.33 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 435 °C (815 °F) estimated

Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot explosive.Oxidising propertiesNot oxidising.

9.2. Other information

Density 0.94 g/cm3 estimated

Specific gravity 0.94 estimated

VOC <50 g/l Mixed

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash

point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents. Nitrates. Peroxides.

10.6. Hazardous No h

No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Material name: PLEXUS® MA832 Adhesive
0533 Version #: 04 Revision date: 22-October-2025 Issue date: 13-July-2023

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)

<u>Acute</u>

Inhalation

LC50 Rat 7.1 mg/l, 4 Hours

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

<u>Acute</u>

Oral

LD50 Rat 7800 mg/kg

phosphoric acid ... %, orthophosphoric acid ... % (CAS 7664-38-2)

Acute

Dermal

LD50 Rabbit 2740 mg/kg

Inhalation

LC50 Rabbit 1.689 mg/l, 1 Hours

Oral

LD50 Rat 1530 mg/kg

Zinc oxide (CAS 1314-13-2)

Acute

Inhalation

LC50 Mouse > 5.7 mg/l, 4 Hours

Oral

LD50 Rat > 5 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.

Carcinogenicity Not applicable.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative

potential

Material name: PLEXUS® MA832 Adhesive
0533 Version #: 04 Revision date: 22-October-2025 Issue date: 13-July-2023

Partition coefficient n-octanol/water (log Kow)

methacrylic acid; 2-methylpropenoic acid 0.93 methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 1.38

2-methylpropenoate

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB This

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC)

No 1907/2006, Annex XIII.

12.6. Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautionsDispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1133

14.2. UN proper shipping

ADHESIVES containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary hazard Label(s) 3
Hazard No. (ADR) 30
Tunnel restriction code D/E
14.4. Packing group III
14.5. Environmental No.

hazards

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary hazard Label(s) 3
14.4. Packing group III
14.5. Environmental No.

hazards

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. UN number UN1133

14.2. UN proper shipping ADHE

name

ADHESIVES containing flammable liquid

14.3. Transport hazard class(es)
Class 3

Class 3 Subsidiary hazard -

Material name: PLEXUS® MA832 Adhesive
0533 Version #: 04 Revision date: 22-October-2025 Issue date: 13-July-2023

Label(s) 3 14.4. Packing group Ш 14.5. Environmental No.

hazards

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. UN number UN1133

14.2. UN proper shipping

name

Adhesives containing flammable liquid, Limited Quantity

14.3. Transport hazard class(es)

3 Class **Subsidiary hazard** 14.4. Packing group Ш 14.5. Environmental No.

hazards

ERG Code 3L

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Allowed with restrictions. Cargo aircraft only

IMDG

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid, Limited Quantity

Not established.

name

14.3. Transport hazard class(es)

Class 3 Subsidiary hazard Ш 14.4. Packing group 14.5. Environmental hazards Marine pollutant No.

EmS

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.


14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; RID








0533 Version #: 04 Revision date: 22-October-2025 Issue date: 13-July-2023

IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

Material name: PLEXUS® MA832 Adhesive

nicals in Bulk.

SDS GREAT BRITAIN

IMDG: International Maritime Dangerous Goods.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TWA: Time Weighted Average.

Not available.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation

methods and test data, if available.

Full text of any statements, which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled. H331 Toxic if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision information SECTION 2: Hazards identification: Hazard statements

SECTION 2: Hazards identification: Main symptoms SECTION 4: First aid measures: 4.2. Most important symptoms and effects, both acute and delayed

SECTION 9: Physical and chemical properties: Form

SECTION 11: Toxicological information: Specific target organ toxicity - repeated exposure

HazReg Data: International Inventories

Training information

Disclaimer

Follow training instructions when handling this material.

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: PLEXUS® MA832 Adhesive

SDS GREAT BRITAIN