SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Plastic Steel® Putty (A) Resin

Other means of identification

SKU# 0100

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazardsSkin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 2A

Sensitization, skin Category 1

Specific target organ toxicity following single Category 3 narcotic effects

exposure

Environmental hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause drowsiness or dizziness.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only

outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the

workplace. Wear eye protection/face protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep

comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTRE/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists:

Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
FERROSILICON		8049-17-0	60 - 100
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)	Epoxy resin	25068-38-6	10 - 30
FIBROUS GLASS		65997-17-3	0.1 - 1
Other components below reportable	levels		1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed
General information

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

protect themselves. Wash contaminated clothing before reuse.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

General fire hazards

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good

industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

5 mg/m3

8. Exposure controls/personal protection

Occu	national	exposure	limite
Occu	pational	exposure	111111111111111111111111111111111111111

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)						
Components	Туре	Value	Form			
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.2 fibers/cm3	Fiber.			
		5 mg/m3	Total particulate.			

Canada, British Columbia OELs, (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
FIBROUS GLASS (CAS	TWA	0.2 fibers/cm3	Fiber.	
65007 17 2)				

65997-17-3)

5 mg/m3 Inhalable fibers.

Fiber, total

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
FIBROUS GLASS (CAS 65997-17-3)	TWA	5 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	Form	
FIBROUS GLASS (CAS 65997-17-3)	TWA	0.5 fibers/ml	Respirable fibers.	
,		5 mg/m3	Inhalable fraction.	

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components **Form**

	.) 0	1 4.14.0	_	
FIBROUS GLASS (CAS 65997-17-3)	TWA	1 fibers/cm3n	Fiber.	
		10 mg/m3	fibers, total dust	

Conada Saakatahawan AELa (Asaunational Haalth and Safaty Bagulationa, 1006, Table 21)

Components	Type	Value	Form	
FIBROUS GLASS (CAS 65997-17-3)	15 minute	10 mg/m3	Inhalable fraction.	
	8 hour	0.2 fibers/cc	Respirable fibers.	
		5 mg/m3	Inhalable fraction.	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines Appropriate engineering controls

Occupational Exposure Limits are not relevant to the current physical form of the product.

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. **Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

wear appropriate thermal protective clothing, when necessary.

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance Paste.

Physical stateNot available.FormPaste.ColourDark greyOdourSlight.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

320 °C (608 °F) estimated

Flash point > 204.0 °C (> 399.2 °F) Pensky-Martens Closed Cup

Evaporation rateNot available.Flammability (solid, gas)Not available.Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 2.80 g/cm3 **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 2.8

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidising agents.

Material name: DEVCON® Plastic Steel® Putty (A) Resin 0100 Version #: 01 Issue date: 01-May-2020

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Knowledge about health hazard is incomplete.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

FIBROUS GLASS (CAS 65997-17-3) Irritant

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

ACGIH Carcinogens

FIBROUS GLASS (CAS 65997-17-3)

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

FIBROUS GLASS (CAS 65997-17-3) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

FIBROUS GLASS (CAS 65997-17-3) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

FIBROUS GLASS (CAS 65997-17-3) Detected carcinogenic effect in animals.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulationsDispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: DEVCON® Plastic Steel® Putty (A) Resin 0100 Version #: 01 Issue date: 01-May-2020

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not established. Not applicable.

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

FIBROUS GLASS (CAS 65997-17-3)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Material name: DEVCON® Plastic Steel® Putty (A) Resin

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

01-May-2020 Issue date

Version No. 01

ITW Performance Polymers cannot anticipate all conditions under which this information and its Disclaimer

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information**

0100 Version #: 01 Issue date: 01-May-2020

Material name: DEVCON® Plastic Steel® Putty (A) Resin SDS CANADA 7/7

SAFETY DATA SHEET

1. Identification

Product identifier 0200J - Putty Hardener

Other means of identification

SKU# 5303NJ

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Skin corrosion/irritation Category 1B
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1

Environmental hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin

reaction. Causes serious eye damage.

Precautionary statement

Prevention Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Do not eat,

drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Response IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash it before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Material name: 0200J - Putty Hardener

5303NJ Version #: 04 Revision date: 04-May-2020 Issue date: 28-June-2019

63.05 % of the mixture consists of component(s) of unknown acute oral toxicity. 63.05 % of the mixture consists of component(s) of unknown acute inhalation toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aliphatic Amine		N/A	60 - 100
Benzyl alcohol		100-51-6	10 - 30
Silica, amorphous, fumed	Silica, amorphous, fumed, crystfree	112945-52-5	5 - 10
Titanium dioxide	Titanium dioxide	13463-67-7	0.5 - 1.5
Other components below repor	table levels		40 - 70

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control centre immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Call a physician or poison control centre immediately.

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If Ingestion

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

During fire, gases hazardous to health may be formed.

Foam. Powder. Carbon dioxide (CO2).

Specific hazards arising from the chemical

Special protective equipment

and precautions for firefighters

Move containers from fire area if you can do so without risk.

Do not use water jet as an extinguisher, as this will spread the fire.

equipment/instructions Specific methods

General fire hazards

Fire fighting

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Material name: 0200J - Putty Hardener

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid breathing

dust/fume/gas/mist/vapours/spray. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational ex	posure	limits
-----------------	--------	--------

110	ACCIH	Threshold	Limit	Values
uə.	ACGIR	Inresnoio	LIMIII	values

Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) Components Type Value

Titanium dioxide (CAS TWA 10 mg/m3

13463-67-7)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Titanium dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
,		10 ma/m3	Total dust.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value
Titanium dioxide (CAS	TWA	10 mg/m3
13463-67-7)		

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Туре	Value	
Titanium dioxide (CAS	TWA	10 mg/m3	
13463-67-7)			

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety) Components Type Value Form

Titanium dioxide (CAS	TWA	10 mg/m3	Total dust.
13463-67-7)			

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Туре	Value	
Titanium dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	8 hour	10 ma/m3	

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines Occupational Exposure Limits noted for the ingredient(s). Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

5303NJ Version #: 04 Revision date: 04-May-2020 Issue date: 28-June-2019

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Face shield is

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Material name: 0200J - Putty Hardener

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing

should not be allowed out of the workplace.

9. Physical and chemical properties

Paste. **Appearance**

Not available. Physical state Paste. **Form** White Colour Amine Odour

Odour threshold Not available. Not available. pН

Melting point/freezing point -15.2 °C (4.64 °F) estimated Initial boiling point and boiling

range

205.3 °C (401.54 °F) estimated

110.0 °C (230.0 °F) estimated Flash point

Evaporation rate Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

Not available.

Not available. Explosive limit - lower (%) Not available. Explosive limit - upper

(%)

Vapour pressure 0.13 hPa estimated

Not available. Vapour density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 436 °C (816.8 °F) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

1.16 g/cm3 estimated Density

Explosive properties Not explosive.

Combustible IIIB estimated Flammability class

Oxidising properties Not oxidising. Percent volatile 18.01 % estimated Specific gravity 1.16 estimated VOC 18.01 % estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Material name: 0200J - Putty Hardener 5303NJ Version #: 04 Revision date: 04-May-2020 Issue date: 28-June-2019 Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid

Contact with incompatible materials.

Incompatible materials

Strong oxidising agents.

Hazardous decomposition

Ottorig oxidisitig agents.

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

Eve contact Causes serious eye damage.

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

Benzyl alcohol (CAS 100-51-6)

Acute Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat 1000 mg/l, 8 Hours

Silica, amorphous, fumed (CAS 112945-52-5)

Acute Oral

LD50 Rat > 22500 mg/kg

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

Causes serious eye damage.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Tita- -- in -- -- -- (OAO 40400 07)

Titanium dioxide (CAS 13463-67-7) Irritant

Respiratory sensitisationDue to partial or complete lack of data the classification is not possible. **Skin sensitisation**May cause an allergic skin reaction.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

ACGIH Carcinogens

Titanium dioxide (CAS 13463-67-7)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Titanium dioxide (CAS 13463-67-7)

Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silica, amorphous, fumed (CAS 112945-52-5)

3 Not classifiable as to carcinogenicity to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible. **Specific target organ toxicity -**Due to partial or complete lack of data the classification is not possible.

single exposure

Specific target organ toxicity - repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Material name: 0200J - Putty Hardener
5303NJ Version #: 04 Revision date: 04-May-2020 Issue date: 28-June-2019

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Benzyl alcohol 1.1

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN2735

UN proper shipping name

Transport hazard class(es)

AMINES, LIQUID, CORROSIVE, N.O.S. (Aliphatic Amine), Limited Quantity

Class 8 Subsidiary risk Ш Packing group

Environmental hazards Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN2735

UN proper shipping name

Amines, liquid, corrosive, n.o.s. (Aliphatic amine)

Transport hazard class(es)

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. 8L **ERG Code**

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN2735 **UN number**

AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S. **UN proper shipping name**

(Aliphatic amine), Limited Quantity

Transport hazard class(es)

8 **Class** Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant Nο F-A, S-B **EmS**

Material name: 0200J - Putty Hardener

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established. Not applicable.

IATA



IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (FINECS)	No

Material name: 0200J - Putty Hardener
5303NJ Version #: 04 Revision date: 04-May-2020 Issue date: 28-June-2019

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Taiwan Chemical Substance Inventory (TCSI)

"A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date28-June-2019Revision date04-May-2020

Version No. 04

Disclaimer

Taiwan

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: 0200J - Putty Hardener SDS CANADA

No