SAFETY DATA SHEET

1. Identification

Product identifier **PLEXUS® PC120**

Other means of identification

SKU# IP120

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name **ITW Performance Polymers**

Address 30 Endicott Street

Danvers, MA 01923

United States

Telephone **Customer Service** 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available. Contact person **EHS** Department

Emergency phone number Chemtrec 800-424-9300

> 703-527-3887 International

2. Hazard(s) identification

Physical hazards Flammable liquids Category 2 **Health hazards** Acute toxicity, oral Category 4 Serious eye damage/eye irritation Category 2

> Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word

Hazard statement Highly flammable liquid and vapor. Harmful if swallowed. Causes serious eye irritation. May

cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair):

> Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical

advice/attention. In case of fire: Use appropriate media to extinguish.

SDS US Material name: PLEXUS® PC120 1/8 Storage Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise classified (HNOC)

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
IPA - Isopropyl Alcohol		67-63-0	90 - 100
BIS(METHACRYLOYLOXYETHYL) HYDROGEN PHOSPHATE		32435-46-4	2.5 - 10
Other components below reportable levels			0.1 - 1

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the

lungs. Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and

delayed

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Indication of immediate medical attention and special treatment

needed

water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with

General information

Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid breathing mist/vapors. Avoid contact with eyes. Avoid prolonged exposure. When using, do not eat, drink or smoke. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below

recommended exposure limits. If exposure limits have not been established, maintain airborne

levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor

cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Keep away from food and drink. Always observe good personal

hygiene measures, such as washing after handling the material and before eating, drinking,

and/or smoking. Routinely wash work clothing and protective equipment to remove

contaminants.

9. Physical and chemical properties

Appearance Liquid.

Physical state Liquid.
Form Liquid.
Color Red
Odor Solvent.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling 180.5 °F (82.5 °C)

range

Flash point

53.0 °F (11.7 °C) Tag Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) 2 %
Explosive limit - upper (%) 12 %

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 0.80 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Flammable IB estimated

Oxidizing properties Not oxidizing.

Specific gravity 0.8 estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoidAvoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause drowsiness or dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness or dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and

central nervous system effects. Harmful if swallowed.

Skin corrosion/irritation Not applicable.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Dispose of this material and its container to hazardous or special waste collection point.

> Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international

regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container

is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1219

UN proper shipping name Isopropanol solution, Limited Quantity

Transport hazard class(es)

3 Class Subsidiary hazard 3 Label(s) Packing group Ш

Environmental hazards

Marine pollutant No.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions IB2, T4, TP1 Packaging exceptions 4b. 150 202 Packaging non bulk Packaging bulk 242

IATA

UN number UN1219

UN proper shipping name Isopropanol solution, Limited Quantity

Transport hazard class(es)

Class 3 Subsidiary hazard Packing group Ш **Environmental hazards** No. **ERG Code** 3L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN1219

SDS US Material name: PLEXUS® PC120

UN proper shipping name

Isopropanol solution, Limited Quantity

Transport hazard class(es)

Class 3 Subsidiary hazard Ш Packing group

Environmental hazards

Marine pollutant No. **EmS** F-E. S-D

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.


Not established.

Transport in bulk according to

Annex II of MARPOL 73/78 and the IBC Code

DOT: IMDG





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910,1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Yes

Classified hazard categories

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

Hazard not otherwise classified (HNOC)

IP120 Version #: 05 Revision date: 03-28-2025 Issue date: 07-16-2019

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 07-16-2019 **Revision date** 03-28-2025

Version # 05

Health: 2 **HMIS®** ratings

> Flammability: 3 Physical hazard: 0

Health: 2 NFPA ratings

> Flammability: 3 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

SDS US Material name: PLEXUS® PC120