# SAFETY DATA SHEET

#### 1. Identification

**Product identifier Chockfast Red Resin** 

Other means of identification

SKU# GP107R Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information Company name **ITW Performance Polymers** 

**Address** 35 Brownridge Road

Unit 1

Halton Hills, ON L7G 0C6

**Customer Service Contact person** 215-855-8450 Telephone number 215-855-4688 Fax number

**Emergency Number** 800-424-9300 (CHEMTREC)

Supplier Not available.

### 2. Hazard identification

Physical hazards Flammable liquids Category 4 **Health hazards** Acute toxicity, oral Category 4 Acute toxicity, dermal Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Category 2

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Label elements



Signal word Warning

**Hazard statement** Combustible liquid. Harmful if swallowed. Harmful in contact with skin. Causes skin irritation.

May cause an allergic skin reaction. May be harmful if inhaled. Toxic to aquatic life. Toxic to

Category 2

aquatic life with long lasting effects.

**Precautionary statement** 

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye

1/9

protection/face protection/hearing protection.

SDS CANADA Material name: Chockfast Red Resin

IF SWALLOWED: Call a POISON CENTRE/doctor if you feel unwell. Rinse mouth. IF ON SKIN: Response

> Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Storage Store in a well-ventilated place.

None.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Supplemental information

Other hazards None known.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Epoxy Resin: Reaction probisphenol A and epichlorol (refer to epichlorohydrin)		25068-38-6	80 - 100
Xylene	XYLENE	1330-20-7	1 - 5
Ethyl benzene		100-41-4	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

> advice/attention if you feel unwell. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the

lungs. Get medical advice/attention if you feel unwell.

Most important

symptoms/effects, acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis, Rash.

Indication of immediate medical attention and special treatment needed

General information

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated

clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

The product is combustible, and heating may generate vapours which may form explosive vapour/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

Material name: Chockfast Red Resin

GP107R Version #: 12 Revision date: 27-January-2025 Issue date: 25-March-2019

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

#### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not taste or swallow. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

### 8. Exposure controls/personal protection

### Occupational exposure limits

**US. ACGIH Threshold Limit Values (TLV)** 

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	TWA	20 ppm

Canada. Alberta OELs (Occupat Components	ional Health & Safety Code, Sch Type	nedule 1, Table 2), as amended Value
Ethyl benzene (CAS 100-41-4)	STEL	543 mg/m3
		125 ppm
	TWA	434 mg/m3
		100 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

Material name: Chockfast Red Resin 3/9

GP107R Version #: 12 Revision date: 27-January-2025 Issue date: 25-March-2019

# Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

## Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	TWA	20 ppm

# Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs

<b>Publication (New Brunswic</b>	k Regulation 91-191)
Componento	Type

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

# Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

# Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended

Components	Туре	Value
Ethyl benzene (CAS 100-41-4)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

# Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended Components Type Value

	.71.	
Ethyl benzene (CAS 100-41-4)	15 minute	125 ppm
	8 hour	100 ppm
Xylene (CAS 1330-20-7)	15 minute	150 ppm
	8 hour	100 ppm

### **Biological limit values**

**ACGIH Biological Exposure Indices (BEI)** 

Components	Value	Determinant	Specimen	Sampling Time
Ethyl benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

<sup>\* -</sup> For sampling details, please see the source document.

# Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Face shield is recommended.

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using do not smoke. Keep away from food and drink. Always observe good personal

hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

# 9. Physical and chemical properties

Physical state Liquid. Form Liquid.

ColourColourless to light yellow.OdourAromatic. Hydrocarbon-like.

Melting point/freezing point Boiling point or initial boiling point and boiling range

138 °C (280.4 °F)

Not available.

Flammability Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%) Flash point

65.6 °C (150.0 °F) Pensky-Martens Closed Cup

Auto-ignition temperature Not available.

Decomposition temperature Not available.

**pH** 7

Kinematic viscosity Not available.

Solubility

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water) (log value)

Vapour pressure 5.6 hPa estimated

Density and/or relative density Not available.

Vapour density 3.5

Particle characteristics Not available.

Other information

**Evaporation rate** 0.6

Material name: Chockfast Red Resin

Explosive properties Not explosive.

Flammability class Combustible IIIA estimated
Combustible IIIA estimated

Oxidising properties Not oxidising.

GP107R Version #: 12 Revision date: 27-January-2025 Issue date: 25-March-2019

Specific gravity 1.2 VOC 52 g/l

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong acids. Strong oxidising agents. Halogens.

**Hazardous decomposition** 

products

Carbon oxides.

# 11. Toxicological information

#### Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash.

## Information on toxicological effects

Harmful in contact with skin. Harmful if swallowed. **Acute toxicity** 

Components **Species Test Results** 

Ethyl benzene (CAS 100-41-4)

**Acute** 

Dermal

LD50 Rabbit 17800 mg/kg

Oral

LD50 Rat 3500 mg/kg

Xylene (CAS 1330-20-7)

**Acute** Dermal

Rabbit

LD50 > 43 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Components in this product have been shown to cause birth defects and reproductive disorders

in laboratory animals.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Material name: Chockfast Red Resin GP107R Version #: 12 Revision date: 27-January-2025 Issue date: 25-March-2019 **Aspiration hazard** Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

### 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

 Ethyl benzene
 3.15

 Xylene
 3.12 - 3.2

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

## 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not

allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code**The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues / unused

Contaminated packaging

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner.

Since emptied containers may retain product residue, follow label warnings even after container

is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

### **TDG**

Not regulated as dangerous goods.

### **IATA**

UN number UN3082

UN proper shipping name

Transport hazard class(es)

Environmentally hazardous substance, liquid, n.o.s. (Epoxy Resin)

Class 9
Subsidiary hazard Packing group III
Environmental hazards Yes

ERG Code 9L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN3082

UN proper shipping name E

Transport hazard class(es)

Environmentally hazardous substances, liquid, n.o.s. (Epoxy Resin), MARINE POLLUTANT

Class 9
Subsidiary hazard Label(s) 9
Packing group III

Environmental hazards

Marine pollutant Yes

EmS Not assigned.


**Special precautions for user** Read safety instructions, SDS and emergency procedures before handling.

Material name: Chockfast Red Resin
GP107R Version #: 12 Revision date: 27-January-2025 Issue date: 25-March-2019

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

IATA; IMDG



## Marine pollutant



**General information** 

IMDG Regulated Marine Pollutant.

# 15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

### **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

**Greenhouse Gases** 

Not listed.

**Precursor Control Regulations** 

Not regulated.

#### International regulations

**Stockholm Convention** 

Not applicable.

**Rotterdam Convention** 

Not applicable.

**Kyoto Protocol** 

Not applicable.

**Montreal Protocol** 

Not applicable.

**Basel Convention** 

Not applicable.

### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes

Material name: Chockfast Red Resin

GP107R Version #: 12 Revision date: 27-January-2025 Issue date: 25-March-2019

Country(s) or region Inventory name On inventory (yes/no)\*

European Inventory of Existing Commercial Chemical Europe

Substances (EINECS)

New Zealand Inventory

European List of Notified Chemical Substances (ELINCS) Europe No Inventory of Existing and New Chemical Substances (ENCS) Japan Yes

Korea Existing Chemicals List (ECL) Yes

Philippines Philippine Inventory of Chemicals and Chemical Substances Yes

(PICCS)

Yes Taiwan Taiwan Chemical Substance Inventory (TCSI) United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

### 16. Other information

New Zealand

Issue date 25-March-2019 **Revision date** 27-January-2025

Version No. 12

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

> product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

**Revision information** Hazard identification: Hazard statement

Hazard identification: Response

Composition / Information on Ingredients: Disclosure Overrides

Physical & Chemical Properties: Multiple Properties

Toxicological information: Acute toxicity Toxicological information: Ingestion Toxicological information: Skin contact Ecological information: Other adverse effects

Disposal considerations: Waste from residues / unused products

Other information: References

HazReg Data: International Inventories

SDS CANADA Material name: Chockfast Red Resin

Yes

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).