SAFETY DATA SHEET

1. Identification

Product identifier PLEXUS® MA422 Adhesive

Other means of identification

SKU# 0420

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923 United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 2Health hazardsAcute toxicity, inhalationCategory 4Skin corrosion/irritationCategory 2Serious eye damage/eye irritationCategory 1

Sensitization, skin

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Category 1A

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Highly flammable liquid and vapor. Causes skin irritation. May cause an allergic skin reaction.

Causes serious eye damage. Harmful if inhaled. May cause respiratory irritation.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly

closed. Ground/bond container and receiving equipment. Use explosion-proof

electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear

protective gloves/eye protection/face protection.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire:

Use appropriate media to extinguish.

Storage Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

0420 Version #: 02 Revision date: 05-04-2020 Issue date: 06-18-2019

Hazard(s) not otherwise classified (HNOC)

Supplemental information

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Methyl Methacrylate		80-62-6	60 - 80
METHACRYLIC ACID		79-41-4	2.5 - 10
Other components below re	eportable levels		20 - 40

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Highly flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

7. Handling and storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not get this material in contact with eyes. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
Methyl Methacrylate (CAS 80-62-6)	PEL	410 mg/m3	
		100 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
METHACRYLIC ACID (CAS 79-41-4)	TWA	20 ppm	
Methyl Methacrylate (CAS 80-62-6)	STEL	100 ppm	
	TWA	50 ppm	
US. NIOSH: Pocket Guide to Chemical	Hazards		
Components	Туре	Value	
METHACRYLIC ACID (CAS 79-41-4)	TWA	70 mg/m3	

Material name: PLEXUS® MA422 Adhesive

SDS US

US. NIOSH: Pocket Guide to Chemical Hazards

Value Components Type 20 ppm Methyl Methacrylate (CAS **TWA** 410 mg/m3 80-62-6) 100 ppm

No biological exposure limits noted for the ingredient(s). **Biological limit values**

Exposure guidelines

US - California OELs: Skin designation METHACRYLIC ACID (CAS 79-41-4) Can be absorbed through the skin.

US - Tennessee OELs: Skin designation

METHACRYLIC ACID (CAS 79-41-4) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

METHACRYLIC ACID (CAS 79-41-4) Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Paste. Physical state Liquid. Paste. **Form** Off-white Color Odor Fragrant Odor threshold Not available. рΗ Not available.

Melting point/freezing point -54.4 °F (-48 °C) estimated Initial boiling point and boiling 212.9 °F (100.5 °C) estimated

range

Flash point 50.0 °F (10.0 °C) estimated

Not available. **Evaporation rate** Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

2.1 % estimated

(%)

Flammability limit - upper

12.5 % estimated

(%)

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

Vapor pressure 28 mm Hg @ 68 F

Not available. Vapor density Relative density Not available.

Solubility(ies)

Not available. Solubility (water) Partition coefficient Not available.

(n-octanol/water)

Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

0.95 g/cm3 estimated Density

Explosive properties Not explosive.

Flammable IB estimated Flammability class

Oxidizing properties Not oxidizing. Specific gravity 0.95 estimated

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates. Peroxides.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rash.

Information on toxicological effects

Harmful if inhaled. **Acute toxicity**

Components **Species Test Results**

METHACRYLIC ACID (CAS 79-41-4)

Acute Dermal

LD50 Rabbit 500 mg/kg

Inhalation

LC50 Rat 7.1 mg/l, 4 Hours

Oral

LD50 Rat 1060 mg/kg

Methyl Methacrylate (CAS 80-62-6)

Acute

Inhalation

LC50 Mouse 18.5 mg/l, 2 Hours

Material name: PLEXUS® MA422 Adhesive

SDS US 0420 Version #: 02 Revision date: 05-04-2020 Issue date: 06-18-2019

Species Test Results Components

Oral

LD50 Rat 7800 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

ACGIH sensitization

METHYL METHACRYLATE (CAS 80-62-6) Dermal sensitization

Respiratory sensitization Due to partial or complete lack of data the classification is not possible.

May cause an allergic skin reaction. Skin sensitization

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Carcinogenicity Due to partial or complete lack of data the classification is not possible.

IARC Monographs. Overall Evaluation of Carcinogenicity

Methyl Methacrylate (CAS 80-62-6) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. Aspiration hazard

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

The product is not classified as environmentally hazardous. However, this does not exclude the **Ecotoxicity**

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

No data is available on the degradability of any ingredients in the mixture. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

METHACRYLIC ACID 0.93 Methyl Methacrylate 1.38

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the Disposal instructions

> material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

SDS US 6/9

14. Transport information

DOT

UN1133 **UN number**

UN proper shipping name Adhesives, containing a flammable liquid, Limited Quantity

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) **Packing group** Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

B1, B52, IB3, T2, TP1 Special provisions

Packaging exceptions 150 173 Packaging non bulk Packaging bulk 242

IATA

UN1133 **UN number**

Adhesives containing flammable liquid, Limited Quantity **UN proper shipping name**

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш **Environmental hazards** No. **ERG Code** 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Not established.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1133

UN proper shipping name ADHESIVES containing flammable liquid, Limited Quantity

Transport hazard class(es)

Class 3 Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant No. F-E, S-D **EmS**


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

DOT; IMDG





15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Methyl Methacrylate (CAS 80-62-6)

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Methyl Methacrylate (CAS 80-62-6) Listed.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Methyl Methacrylate (CAS 80-62-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Yes

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eve damage or eve irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

Hazard not otherwise classified (HNOC)

Flammable (gases, aerosols, liquids, or solids)

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Methyl Methacrylate 80-62-6 60 - 80

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Methyl Methacrylate (CAS 80-62-6)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Contains component(s) regulated under the Safe Drinking Water Act.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl Methacrylate (CAS 80-62-6) Low priority

US state regulations

California Proposition 65



WARNING: This product can expose you to N,n-dimethyl-p-toluidine, which is known to the State of California to cause cancer, and Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene Glycol (CAS 107-21-1) Listed: June 19, 2015

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Methyl Methacrylate (CAS 80-62-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

 Issue date
 06-18-2019

 Revision date
 05-04-2020

Version # 02

HMIS® ratings Health: 2

Flammability: 3 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 3 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material

designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information Toxicological information: Ingestion

0420 Version #: 02 Revision date: 05-04-2020 Issue date: 06-18-2019

SAFETY DATA SHEET

1. Identification

Product identifier PLEXUS® MA422/425 EU Activator

Other means of identification

SKU# 0693

Recommended useNot available. **Recommended restrictions**None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers

Address 30 Endicott Street

Danvers, MA 01923

United States

Telephone Customer Service 978-777-1100

Website www.itwperformancepolymers.com

E-mail Not available.

Contact person EHS Department

Emergency phone number Chemtrec 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A Sensitization, skin Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May

cause respiratory irritation.

Precautionary statement

Prevention Avoid breathing mist/vapors. Wash thoroughly after handling. Use only outdoors or in a

well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear

eye protection/face protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable

for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

Material name: PLEXUS® MA422/425 EU Activator

0693 Version #: 03 Revision date: 06-23-2020 Issue date: 04-09-2019

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Benzyl 3-isobutyryloxy-1-isopropyl-2,2-dim ethylpropyl Phthalate		16883-83-3	20 - 40
DIBUTYL MALEATE		105-76-0	20 - 40
Dibenzoyl Peroxide		94-36-0	10 - 20
ISODECYL BENZOATE		131298-44-7	1 - 10
Magnesium Sulphate		7487-88-9	1 - 10
Oxirane, Methyl-, Polymer With Oxirane, Monobutyl Ether		9038-95-3	1 - 10
Other components below reportable	e levels		20 - 40

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Ingestion

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

General information

j

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	туре	value	
Dibenzoyl Peroxide (CAS 94-36-0)	PEL	5 mg/m3	
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3	
US. NIOSH: Pocket Guide to Che	mical Hazards		
Componento	Time	Value	

Components	Туре	Value	
Dibenzoyl Peroxide (CAS 94-36-0)	TWA	5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational Exposure Limits are not relevant to the current physical form of the product.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant clothing. Other

Respiratory protection Chemical respirator with organic vapor cartridge and full facepiece. Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Paste. Physical state Liquid. **Form** Paste.

Material name: PLEXUS® MA422/425 EU Activator

3/7 0693 Version #: 03 Revision date: 06-23-2020 Issue date: 04-09-2019

Color Blue Odor Slight.

Odor threshold Not available.

pН Neutral

Melting point/freezing point 217.4 °F (103 °C) estimated

Initial boiling point and boiling Not available.

range

Flash point

285.8 °F (141.0 °C) estimated

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

Not available.

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure 0.0004 hPa estimated

Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Slightly soluble Partition coefficient Not available.

(n-octanol/water)

176 °F (80 °C) estimated **Auto-ignition temperature**

Decomposition temperature Not available. Viscosity Not available.

Other information

Density 1.08 g/cm3 **Explosive properties** Not explosive.

Combustible IIIB estimated Flammability class

Oxidizing properties Not oxidizing.

Specific gravity 1.08

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible

materials.

Alcohols, Amines, Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eve contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Material name: PLEXUS® MA422/425 EU Activator

SDS US 4/7 Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity Not known.

Components Species Test Results

Causes serious eve irritation.

Dibenzoyl Peroxide (CAS 94-36-0)

Acute Oral

LD50 Rat 7710 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Dibenzoyl Peroxide (CAS 94-36-0)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Dibenzoyl Peroxide 3.46

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Material name: PLEXUS® MA422/425 EU Activator

SDS US 5 / 7

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910,1200.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

Dibenzovl Peroxide (CAS 94-36-0) % 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Dibenzoyl Peroxide (CAS 94-36-0) Listed.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Yes

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard categories

Skin corrosion or irritation Serious eye damage or eye irritation

Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name **CAS** number % by wt. Dibenzoyl Peroxide 94-36-0 10 - 20

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including STYRENE, which is known to the State of California to cause cancer, and 1,2-BENZENEDICARBOXYLIC ACID, DI-C9-11-BRANCHED ALKYL ESTERS, C10-RICH, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

2-Propenenitrile; Acrylonitrile, Cyanoethylene Listed: July 1, 1987

(CAS 107-13-1)

STYRENE (CAS 100-42-5) Listed: April 22, 2016

Material name: PLEXUS® MA422/425 EU Activator 0693 Version #: 03 Revision date: 06-23-2020 Issue date: 04-09-2019

California Proposition 65 - CRT: Listed date/Developmental toxin

1,2-BENZENEDICARBOXYLIC ACID, Listed: April 20, 2007

DI-C9-11-BRANCHED ALKYL ESTERS, C10-RICH

(CAS 68515-49-1)

BIS(2-PROPYLHEPTYL) PHTHALATE Listed: April 20, 2007

(CAS 53306-54-0)

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Magnesium Sulphate (CAS 7487-88-9)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

 Issue date
 04-09-2019

 Revision date
 06-23-2020

Version # 03

HMIS® ratings Health: 2

Flammability: 1 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 1 Instability: 0

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or

in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

0693 Version #: 03 Revision date: 06-23-2020 Issue date: 04-09-2019

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).