SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Flexane® 80 Putty Resin

Other means of identification

SKU# 15821

Recommended use Not available. Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information **ITW Performance Polymers** Company name

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Customer Service Contact person 978-777-1100 Telephone number

Fax E-mail

Emergency telephone

number

800-424-9300

Not available. **Supplier**

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, inhalation Category 4

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, respiratory Category 1 Sensitization, skin Category 1A Carcinogenicity Category 2

Specific target organ toxicity following single

exposure

Specific target organ toxicity following Category 2

repeated exposure

Environmental hazards Not classified.

Label elements



Signal word

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful

if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. Suspected of causing cancer. May cause damage to organs through

Category 3 respiratory tract irritation

prolonged or repeated exposure.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the

workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wear

respiratory protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep Response

> comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing, IF exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a POISON

CENTRE/doctor. Take off contaminated clothing and wash it before reuse.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Polyether Polyol		N/A	60 - 100
METHYLENE BIS(4-CYCLOHEXYLISOCYANATE)		5124-30-1	15 - 40
4,4'-DIPHENYLMETHANE DIISOCYANATE		101-68-8	1 - 5
Diphenylmethane Diisocyanate [isomers And Homologues]		9016-87-9	1 - 5
Methylenediphenyl Diisocyanate (mdi)		26447-40-5	1 - 5
Other components below reportable l	evels		1 - 5

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delaved

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may

cause chronic effects.

Indication of immediate medical attention and special

treatment needed **General information** Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

(show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

The product is immiscible with water and will spread on the water surface.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.005 ppm
METHYLENE BIS(4-CYCLOHEXYLISOC YANATE) (CAS 5124-30-1)	TWA	0.005 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.05 mg/m3	
		0.005 ppm	
Diphenylmethane Diisocyanate [isomers And Homologues] (CAS 9016-87-9)	TWA	0.07 mg/m3	
		0.005 ppm	
METHYLENE BIS(4-CYCLOHEXYLISOC YANATE) (CAS 5124-30-1)	TWA	0.05 mg/m3	
		0.005 ppm	

Material name: DEVCON® Flexane® 80 Putty Resin 15821 Version #: 01 Issue date: 03-February-2020

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Safety Regulation 296/97, as amen Components	Туре	Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	Ceiling	0.01 ppm	
	TWA	0.005 ppm	
Diphenylmethane Diisocyanate [isomers And Homologues] (CAS 9016-87-9)	Ceiling	0.01 ppm	
	TWA	0.005 ppm	
METHYLENE BIS(4-CYCLOHEXYLISOC (ANATE) (CAS 5124-30-1)	Ceiling	0.01 ppm	
, ,	TWA	0.005 ppm	
Methylenediphenyl Diisocyanate (mdi) (CAS 26447-40-5)	Ceiling	0.01 ppm	
	TWA	0.005 ppm	
Canada. Manitoba OELs (Reg. 217/	2006, The Workplace Safety A	nd Health Act)	
Components	Туре	Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	TWA	0.005 ppm	
METHYLENE BIS(4-CYCLOHEXYLISOC YANATE) (CAS 5124-30-1)	TWA	0.005 ppm	
Canada. Ontario OELs. (Control of Components	Exposure to Biological or Che Type	mical Agents) Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	Ceiling	0.02 ppm	
,	TWA	0.005 ppm	
METHYLENE BIS(4-CYCLOHEXYLISOC YANATE) (CAS 5124-30-1)	Ceiling	0.02 ppm	
, ,	TWA	0.005 ppm	
Canada. Quebec OELs. (Ministry o	f Labor - Regulation respecting	occupational health and safety)	
Components	Туре	Value	
1,4'-DIPHENYLMETHANE DIISOCYANATE (CAS I 01-68-8)	TWA	0.051 mg/m3	
·		0.005 ppm	
METHYLENE BIS(4-CYCLOHEXYLISOC /ANATE) (CAS 5124-30-1)	TWA	0.054 mg/m3	
-, ()		0.005 ppm	
Canada. Saskatchewan OELs (Occ Components	upational Health and Safety Ro Type	egulations, 1996, Table 21) Value	
4,4'-DIPHENYLMETHANE DIISOCYANATE (CAS 101-68-8)	15 minute	0.015 ppm	
•	8 hour	0.005 ppm	
METHYLENE BIS(4-CYCLOHEXYLISOC YANATE) (CAS 5124-30-1)	15 minute	0.015 ppm	

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value

8 hour 0.005 ppm

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - British Columbia OELs: Skin designation

4,4'-DIPHENYLMETHANE DIISOCYANATE Can be absorbed through the skin.

(CAS 101-68-8)

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapour c

Skin protection

Chemical respirator with organic vapour cartridge and full facepiece.

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Liquid.

Physical state Liquid. Form Liquid.

Colour Clear colorless or nearly colorless

Odour Musty

Odour threshold Not available. pH Not available.

Melting point/freezing point 25 °C (77 °F) estimated

Initial boiling point and boiling

range

Not available.

Flash point 175.0 °C (347.0 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressure

0.00002 hPa estimated

Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) insoluble

Partition coefficient (n-octanol/water)

Not available.

Not available. **Auto-ignition temperature Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Density 1.04 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising. 1.04 estimated Specific gravity

VOC 0 g/I

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Alcohols. Amines. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Inhalation

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eve irritation.

Knowledge about health hazard is incomplete. Ingestion

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Coughing. Difficulty in breathing. Skin irritation. May cause

redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Harmful if inhaled. Acute toxicity

Components **Species Test Results**

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE) (CAS 5124-30-1)

Acute Dermal

LD50 Rabbit > 10000 mg/kg

Oral

LD50 Rat 1065 mg/kg

Causes skin irritation. Skin corrosion/irritation Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Canada - British Columbia OELs: Respiratory or skin sensitiser

4,4'-DIPHENYLMETHANE DIISOCYANATE Capable of causing respiratory, dermal or conjunctival

(CAS 101-68-8)

Diphenylmethane Diisocyanate [isomers And

Homologues] (CAS 9016-87-9)

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE)

(CAS 5124-30-1)

Capable of causing respiratory, dermal or conjunctival sensitization.

Capable of causing respiratory, dermal or conjunctival

sensitization.

sensitization.

Methylenediphenyl Diisocyanate (mdi) (CAS 26447-40-5) Capable of causing respiratory, dermal or conjunctival

sensitization.

Material name: DEVCON® Flexane® 80 Putty Resin 15821 Version #: 01 Issue date: 03-February-2020 Canada - Quebec OELs: Sensitizer

4,4'-DIPHENYLMETHANE DIISOCYANATE

(CAS 101-68-8)

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE) Sensitiser.

(CAS 5124-30-1)

Respiratory sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

4,4'-DIPHENYLMETHANE DIISOCYANATE

3 Not classifiable as to carcinogenicity to humans.

(CAS 101-68-8)

Diphenylmethane Diisocyanate [isomers And

3 Not classifiable as to carcinogenicity to humans.

Homologues] (CAS 9016-87-9)

Methylenediphenyl Diisocyanate (mdi) (CAS 26447-40-5) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Sensitiser.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

May cause damage to organs through prolonged or repeated exposure.

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard Chronic effects

Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

METHYLENE BIS(4-CYCLOHEXYLISOCYANATE) 6.11

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not established.

Annex II of MARPOL 73/78 and

the IBC Code

Material name: DEVCON® Flexane® 80 Putty Hesin 15821 Version #: 01 Issue date: 03-February-2020

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date 03-February-2020

Version No. 01

Disclaimer ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Flexane® 80 Putty Resin 15821 Version #: 01 Issue date: 03-February-2020