# SAFETY DATA SHEET

### 1. Identification

Product identifier Insulcast 116FRFC - Part B

Other means of identification

SKU# IE118H

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Performance Polymers
Address 130 Commerce Drive
Montgomeryville, PA 18936

**United States** 

**Telephone** Customer Service 215-855-8450

Website www.itwperformancepolymers.com

**E-mail** Not available. **Contact person** EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Acute toxicity, dermal Category 4

Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 1
Sensitization, skin Category 1
Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 2

long-term hazard

OSHA defined hazards Not classified.

Label elements

**Environmental hazards** 



Signal word Danger

Hazard statement Harmful in contact with skin. Causes severe skin burns and eye damage. May cause an allergic

skin reaction. Causes serious eye damage. Very toxic to aquatic life. Toxic to aquatic life with long

lasting effects.

**Precautionary statement** 

Prevention Do not breathe mist or vapor. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if

you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Take off

contaminated clothing and wash before reuse. Collect spillage.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

53.74% of the mixture consists of component(s) of unknown acute oral toxicity. 68.95% of the mixture consists of component(s) of unknown acute inhalation toxicity.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
ALUMINA TRIHYDRATE			30 - 60
Aluminum Trihydrate		21645-51-2	20 - 40
POLYAMINES AND FATTY ACIDS REACTANT		68953-36-6	10 - 30
1-(2-aminoethyl)piperazine		140-31-8	5 - 10
nonyl phenol		84852-15-3	3 - 7
TETRAETHYLENEPENTAMINE		112-57-2	1 - 5
Other components below reportable	levels		1 - 5

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

blindness could result.

Remove contaminated clothing immediately and wash skin with soap and water. Chemical burns Skin contact

must be treated by a physician. Get medical advice/attention if you feel unwell. In case of eczema

or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

During fire, gases hazardous to health may be formed.

Do not use water jet as an extinguisher, as this will spread the fire.

present and easy to do. Continue rinsing. Get medical attention immediately. Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

**General information** 

Ingestion

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may

include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

General fire hazards No unusual fire or explosion hazards noted.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Insulcast 116FRFC - Part B IE118H Version #: 04 Revision date: 06-25-2018 Issue date: 03-13-2014

# Methods and materials for containment and cleaning up

This material is classified as a water pollutant under the Clean Water Act and should be prevented from contaminating soil or from entering sewage and drainage systems which lead to waterways.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

### **Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Aluminum Trihydrate (CAS 21645-51-2)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Values Components	s Type	Value	Form
Aluminum Trihydrate (CAS 21645-51-2)	TWA	1 mg/m3	Respirable fraction.
US. Workplace Environmental Exp	oosure Level (WEEL) Guides		
Components	Туре	Value	Form
TETRAETHYLENEPENTA MINE (CAS 112-57-2)	TWA	5 mg/m3	Aerosol.
		1 ppm	Aerosol.

#### **Biological limit values**

No biological exposure limits noted for the ingredient(s).

#### **Exposure guidelines**

# **US WEEL Guides: Skin designation**

TETRAETHYLENEPENTAMINE (CAS 112-57-2) Can be absorbed through the skin.

# Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

# Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles) and a face shield. Face shield is Eye/face protection

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Material name: Insulcast 116FRFC - Part B

SDS US

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

# 9. Physical and chemical properties

Liquid. **Appearance** Physical state Liquid. Liquid. **Form** Color Grey

Odor Ammoniacal. **Odor threshold** Not available. Not available. Not available. Melting point/freezing point Initial boiling point and boiling Not available.

range

> 300.0 °F (> 148.9 °C) Flash point

**Evaporation rate** 0.7 BuAc Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. Vapor pressure 5.1 mm Hg

3.6 Vapor density

Relative density Not available.

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available. (n-octanol/water)

Not available. **Auto-ignition temperature Decomposition temperature** Not available. Not available. **Viscosity** 

Other information

Density 12.60 lb/gal **Explosive properties** Not explosive.

Flammability class Combustible IIIB estimated

**Oxidizing properties** Not oxidizing.

1.51 Specific gravity VOC < 1 %

# 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Material name: Insulcast 116FRFC - Part B

IE118H Version #: 04 Revision date: 06-25-2018 Issue date: 03-13-2014

**Incompatible materials** Alkaline metals. Peroxides. Phenols.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

#### Information on likely routes of exposure

**Inhalation** May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

**Skin contact** Causes severe skin burns. Harmful in contact with skin. May cause an allergic skin reaction.

Eye contact Causes serious eye damage.

Ingestion Causes digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

**Acute toxicity** Harmful in contact with skin.

Components Species Test Results

Aluminum Trihydrate (CAS 21645-51-2)

Acute Oral

LD50 Rat > 5000 mg/kg

nonyl phenol (CAS 84852-15-3)

Acute Dermal

LD50 Rabbit 2140 mg/kg

Oral

LD50 Rat 1600 mg/kg

TETRAETHYLENEPENTAMINE (CAS 112-57-2)

Acute Dermal

LD50 Rabbit 0.66 g/kg

Oral

LD50 Rat 2.1 g/kg

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

**Carcinogenicity** Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

Not classified.

repeated exposure

**Aspiration hazard** Not an aspiration hazard.

Material name: Insulcast 116FRFC - Part B
IE118H Version #: 04 Revision date: 06-25-2018 Issue date: 03-13-2014

**Chronic effects** Prolonged inhalation may be harmful.

12. Ecological information

**Ecotoxicity** Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

nonyl phenol 5.71 TETRAETHYLENEPENTAMINE 1.503

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code D002: Waste Corrosive material [pH <=2 or =>12.5, or corrosive to steel]

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

**DOT** 

UN number UN3066

UN proper shipping name

Transport hazard class(es)

Paint, MARINE POLLUTANT

Class 8
Subsidiary risk Label(s) 8
Packing group III

**Environmental hazards** 

Marine pollutant Yes

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B52, IB3, T4, TP1, TP29

Packaging exceptions 154
Packaging non bulk 173
Packaging bulk 241

IATA

UN number UN3066 UN proper shipping name Paint

Transport hazard class(es)

Class 8
Subsidiary risk Packing group III
Environmental hazards Yes
ERG Code 8L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

s tot user ricad saicty instructions, obo and one

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IE118H Version #: 04 Revision date: 06-25-2018 Issue date: 03-13-2014

#### **IMDG**

**UN number** UN3066

UN proper shipping name PAINT, MARINE POLLUTANT

Transport hazard class(es)

Class 8
Subsidiary risk Packing group ||||

Environmental hazards

Marine pollutant Yes EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code





# IATA; IMDG



### Marine pollutant



**General information** IMDG Regulated Marine Pollutant. DOT Regulated Marine Pollutant.

# 15. Regulatory information

**US federal regulations**This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

nonyl phenol (CAS 84852-15-3) 1.0 % One-Time Export Notification only.

TSCA Chemical Action Plans, Chemicals of Concern

nonyl phenol (CAS 84852-15-3)

Nonylphenol (NP) and Nonylphenol Ethoxylates (NPEs) Action Plan

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

# SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

nonyl phenol (CAS 84852-15-3) % 1.0

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

nonyl phenol (CAS 84852-15-3) Listed.

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

Classified hazard categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

SARA 313 (TRI reporting)

**CAS** number **Chemical name** % by wt. nonyl phenol 84852-15-3 3 - 7

# Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

# **US state regulations**

#### California Proposition 65



WARNING: This product can expose you to chemicals including Ethyl Benzene, which is known to the State of

California to cause cancer. For more information go to www.P65Warnings.ca.gov.

# California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethyl Acrylate (CAS 140-88-5) Listed: July 1, 1989 Ethyl Benzene (CAS 100-41-4) Listed: June 11, 2004

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

IE118H Version #: 04 Revision date: 06-25-2018 Issue date: 03-13-2014

United States & Puerto Rico

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

03-13-2014 Issue date **Revision date** 06-25-2018

Version # 04

Health: 3 HMIS® ratings

Flammability: 1 Physical hazard: 1

Health: 3 NFPA ratings

Flammability: 1 Instability: 1

**Disclaimer** ITW Performance Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance

for safe handling, use, processing, storage, transportation, disposal and release.

This document has undergone significant changes and should be reviewed in its entirety. **Revision information** 

Material name: Insulcast 116FRFC - Part B

SDS US IE118H Version #: 04 Revision date: 06-25-2018 Issue date: 03-13-2014