SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Plexus MA3940LH Adhesive

of the mixture

Registration number

Product registration number UFI: D220-00D1-W00M-QY37

Synonyms None. SKU# Z0015

Issue date 14-August-2023

Version number 02

Revision date 30-June-2025 Supersedes date 14-August-2023

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name **ITW Performance Polymers**

Address Bay 150

Shannon Industrial Estate

Co. Clare, Ireland

Division

Telephone Phone 353(61)771500

e-mail customerservice.shannon@itwpp.com

Contact person Not available.

1.4. Emergency telephone

number

Emergency Number 44(0)1235 239 670

General emergency 112 or 999 SDS/Product information may not be available for the Emergency

Service.

Non-emergency medical

helpline

111 SDS/Product information may not be available for the Emergency Service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

Flammable liquids H225 - Highly flammable liquid Category 2

and vapour.

Health hazards

Skin corrosion/irritation H315 - Causes skin irritation. Category 2 Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Skin sensitisation Category 1 H317 - May cause an allergic skin

reaction.

Specific target organ toxicity - single

exposure

H335 - May cause respiratory Category 3 respiratory tract irritation

irritation.

2.2. Label elements

Material name: Plexus MA3940LH Adhesive Z0015 Version #: 02 Revision date: 30-June-2025 Issue date: 14-August-2023

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate,

2-METHYL-2-PROPENOIC ACID METHYL ESTER POLYMER WITH 1,3-BUTADIENE AND ETHENYLBENZENE, methacrylic acid; 2-methylpropenoic acid, TRIMETHYLOLPROPANE

TRIMETHACRYLATE, ethanediol; ethylene glycol

Hazard pictograms



Signal word Danger

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

Precautionary statements

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P235 Keep cool.

P240 Ground and bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing mist/vapours. P264 Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Response

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a POISON CENTRE/doctor if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention. P337 + P313 If eye irritation persists: Get medical advice/attention. P362 + P364 Take off contaminated clothing and wash it before reuse. P370 + P378 In case of fire: Use appropriate media to extinguish.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Supplemental label information 67.9999999954 % of the mixture consists of component(s) of unknown acute dermal toxicity.

> 67.9999999994 % of the mixture consists of component(s) of unknown acute inhalation toxicity. 70.99999999999 % of the mixture consists of component(s) of unknown acute hazards

to the aquatic environment.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

> (EC) No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list established in accordance with REACH Article 59(1) for having endocrine disrupting properties at

a concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Material name: Plexus MA3940LH Adhesive SDS GREAT BRITAIN

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate	30-60%	80-62-6 201-297-1	01-2119452498-28-0000	607-035-00-6	#
	1;H317, ST	OT SE 3;H335	H332, Skin Irrit. 2;H315, Sk	in Sens.	D
Specific Concentration Limits	:5101 SE 3	;H335: C ≥ 10 %			
2-METHYL-2-PROPENOIC ACID METHYL ESTER POLYMER WITH 1,3-BUTADIENE AND ETHENYLBENZENE	10-30%	25053-09-2 -	-	-	
Classification	:-				
methacrylic acid; 2-methylpropenoic acid	1-5%	79-41-4 201-204-4	01-2119463884-26-0000	607-088-00-5	#
Classification: Acute Tox. 4;H302, Acute Tox. 4;H312, Acute Tox. 3;H331, Skin Corr. 1A;H314, Eye Dam. 1;H318, STOT SE 3;H335					D
Specific Concentration Limits	:STOT SE 3	;H335: C ≥ 1 %			
TRIMETHYLOLPROPANE TRIMETHACRYLATE	1-5%	3290-92-4 221-950-4	-	-	
Classification	:-				
ethanediol; ethylene glycol	0.10-0.99 %	107-21-1 203-473-3	-	603-027-00-1	#
Classification	Acute Tox.	4:H302			

Other components below reportable

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Take off all contaminated clothing immediately. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

centre or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Highly flammable liquid and vapour.

Material name: Plexus MA3940LH Adhesive
Z0015 Version #: 02 Revision date: 30-June-2025 Issue date: 14-August-2023

SDS GREAT BRITAIN

5.1. Extinguishing media Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Vapours may form explosive mixtures with air. Vapours may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can

do so without risk.

Specific methodsUse standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Ventilate closed spaces before entering them. Avoid breathing mist/vapours. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS (Lower-tier requirements = 50 tonnes; Upper-tier requirements = 200 tonnes)

7.3. Specific end use(s)

Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Material name: Plexus MA3940LH Adhesive SDS GREAT BRITAIN

Occupational exposure limits

UK. OELs. Workplace Exposure Lir Components	mits (WELs) (EH40/2005 (Fou Type	urth Edition 2020)), Table 1 Value	Form
ethanediol; ethylene glycol (CAS 107-21-1)	STEL	104 mg/m3	Vapour.
		40 ppm	Vapour.
	TWA	52 mg/m3	Vapour.
		10 mg/m3	Particulate.
		20 ppm	Vapour.
methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)	STEL	143 mg/m3	
		40 ppm	
	TWA	72 mg/m3	
		20 ppm	
methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)	STEL	416 mg/m3	
		100 ppm	
	TWA	208 mg/m3	
		50 ppm	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.
 - Other Wear appropriate chemical resistant clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures When using do not smoke. Always observe good personal hygiene measures, such as washing

after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should

not be allowed out of the workplace.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to

acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Paste.

Material name: Plexus MA3940LH Adhesive

Z0015 Version #: 02 Revision date: 30-June-2025 Issue date: 14-August-2023

Physical state Liquid. Form Liquid.

Colour White, Off-white. Odour Slight. Pungent. **Odour threshold** Not available. рΗ Not available.

Melting point/freezing point -48 °C (-54.4 °F) estimated

Initial boiling point and boiling

range

101 °C (213.8 °F)

10.0 °C (50.0 °F) Tag closed cup Flash point

Evaporation rate Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits 2.1 % estimated Explosive limit - lower (%)

Explosive limit - upper

(%)

8.2 % estimated

Vapour pressure 28 hPa Not available. Vapour density

Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 435 °C (815 °F) estimated

Decomposition temperature Not available. Not available. **Viscosity Explosive properties** Not explosive. Oxidising properties Not oxidising.

9.2. Other information

Density 0.92 g/cm3 0.92 Specific gravity

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents. Nitrates. Peroxides.

10.6. Hazardous decomposition No hazardous decomposition products are known.

products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. May cause respiratory irritation. Skin irritation. May cause redness and pain. May cause

an allergic skin reaction. Dermatitis. Rash.

Material name: Plexus MA3940LH Adhesive Z0015 Version #: 02 Revision date: 30-June-2025 Issue date: 14-August-2023

11.1. Information on toxicological effects

Acute toxicity Not known.

Test Results Components **Species**

ethanediol; ethylene glycol (CAS 107-21-1)

<u>Acute</u> Dermal

LD50 Rabbit 9530 mg/kg

methacrylic acid; 2-methylpropenoic acid (CAS 79-41-4)

Acute Inhalation

LC50 Rat 7.1 mg/l, 4 Hours

methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 2-methylpropenoate (CAS 80-62-6)

Oral

LD50 Rat 7800 mg/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible.

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not applicable.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the

environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow) ethanediol; ethylene glycol

-1.36methacrylic acid; 2-methylpropenoic acid 0.93 methyl methacrylate; methyl 2-methylprop-2-enoate; methyl 1.38

2-methylpropenoate

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation

(EC) No 1907/2006, Annex XIII.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Material name: Plexus MA3940LH Adhesive

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container

is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid (vapour pressure at 50 °C more than 110 kPa)

name

14.3. Transport hazard class(es)

Class 3
Subsidiary hazard Label(s) 3
Hazard No. (ADR) 33
Tunnel restriction code D/E
14.4. Packing group II
14.5. Environmental hazards No.

14.6. Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

RID

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid (having a flash-point below 23 °C and viscous

name according to 2.2.3.1.4) (vapour pressure at 50 °C more than 110 kPa)

14.3. Transport hazard class(es)

Class 3
Subsidiary hazard Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards No.

14.6. Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

ADN

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary hazard Label(s) 3
14.4. Packing group ||
14.5. Environmental hazards No.

14.6. Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

IATA

14.1. UN number UN1133

14.2. UN proper shipping Adhesives containing flammable liquid

name

14.3. Transport hazard class(es)

Class 3
Subsidiary hazard
14.4. Packing group II

14.5. Environmental hazards No.
ERG Code 3L

14.6. Special precautions for Read safety instructions, SDS and emergency procedures before handling.

user

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

IMDG

14.1. UN number UN1133

14.2. UN proper shipping ADHESIVES containing flammable liquid

name

14.3. Transport hazard class(es)

Class **Subsidiary hazard** 14.4. Packing group Ш 14.5. Environmental hazards

Marine pollutant No. F-E. S-D **EmS**

14.6. Special precautions for Read safety instructions, SDS and emergency procedures before handling.

14.7. Transport in bulk according Not established.

to Annex II of MARPOL 73/78 and

the IBC Code

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended -Conditions of restriction given for the associated entry number should be considered

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

ANNEX 1, PART 1 Categories of dangerous substances

Hazard categories in accordance with Regulation (EC) No 1272/2008

- P5a, b or c FLAMMABLE LIQUIDS

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization. IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TWA: Time Weighted Average.

vPvB: Very persistent and very bioaccumulative.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements. which are not written out in full under sections 2 to 15

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H331 Toxic if inhaled. H332 Harmful if inhaled.

H335 May cause respiratory irritation.

Revision information

Composition / Information on Ingredients: Ingredients

SECTION 8: Exposure controls/personal protection: Eye/face protection SECTION 8: Exposure controls/personal protection: Respiratory protection

HazReg Data: International Inventories

Training information

Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: Plexus MA3940LH Adhesive

SDS GREAT BRITAIN