SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Brushable Ceramic Red Resin

Other means of identification

SKU# 0117

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to

aquatic life.

Precautionary statement

Prevention Avoid breathing mist/vapours. Wash thoroughly after handling. Contaminated work clothing

should not be allowed out of the workplace. Avoid release to the environment. Wear eye

protection/face protection. Wear protective gloves.

Response IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Storage Not available.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

Material name: DEVCON® Brushable Ceramic Red Resin

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Aluminium oxide		1344-28-1	40 - < 50
Epoxy Resin: reaction product of Bisphenol A and epichlorohydrin (refer to epichlorohydrin)		25068-38-6	40 - < 50
Other components below reportable	e levels		3 - 7

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Move containers from fire area if you can do so without risk.

Special protective equipment

and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

Material name: DEVCON® Brushable Ceramic Red Resin

7. Handling and storage

Precautions for safe handling Avoid breathing mist/vapours. Avoid contact with eyes, skin, and clothing. Provide adequate

ventilation. Wear appropriate personal protective equipment. Avoid release to the environment.

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components **Type** Value TWA Aluminium oxide (CAS 10 mg/m3

1344-28-1)

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs

Publication (New Brunswick Regulation 91-191)

Components Value Type Aluminium oxide (CAS TWA 10 mg/m3 1344-28-1)

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended Components **Form Type** Value Aluminium oxide (CAS **TWA** 10 mg/m3 Total dust. 1344-28-1)

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended Components Value **Type** Aluminium oxide (CAS 15 minute 20 mg/m3 1344-28-1)

Biological limit values

No biological exposure limits noted for the ingredient(s). Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety

shower.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Face shield is recommended. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. Hand protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants. Contaminated work clothing should not be allowed out of the

workplace.

9. Physical and chemical properties

Appearance Viscous. Liquid.

Physical state Liquid.

Viscous. Liquid. **Form**

Colour Red. Odour Slight. Not available. **Odour threshold** pН Not available. Melting point/freezing point Not available. Initial boiling point and boiling

range

320 °C (608 °F) estimated

Flash point 129.4 °C (265.0 °F) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper Not available.

(%)

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density 1.15 g/cm3 estimated

Explosive properties Not explosive.

Flammability class Combustible IIIB estimated

Oxidising properties Not oxidising.

Specific gravity 1.15 estimated

VOC <50 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis, Rash.

Information on toxicological effects

Acute toxicity Not known.

Material name: DEVCON® Brushable Ceramic Red Resin

Species Test Results Components

Aluminium oxide (CAS 1344-28-1)

Acute Oral

LD50 Rat > 5000 mg/kg

Skin corrosion/irritation Serious eye damage/eye Causes skin irritation.

Causes serious eye irritation.

irritation

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Aluminium oxide (CAS 1344-28-1) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity

ACGIH Carcinogens

Aluminium oxide (CAS 1344-28-1) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Aluminium oxide (CAS 1344-28-1) Not classifiable as a human carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Persistence and degradability

Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Mobility in soil

No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not established.

Inventory name

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Country(s) or region

International Inventories

		(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
Australia	Australian Inventory of Industrial Chemicals (AICIS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Issue date29-May-2019Revision date01-August-2023

Version No. 07

United States & Puerto Rico

Material name: DEVCON® Brushable Ceramic Red Resin

On inventory (yes/no)*

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Revision information

Physical & Chemical Properties: Multiple Properties

SAFETY DATA SHEET

1. Identification

Product identifier DEVCON® Brushable Ceramic Red Hardener

Other means of identification

SKU# 5491

Recommended use Not available. **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Company name ITW Performance Polymers

Address 35 Brownridge Rd

Unit 1

Halton Hills, ON L7G 0C6

Contact personCustomer ServiceTelephone number978-777-1100

Fax E-mail

Emergency telephone

number

800-424-9300

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Acute toxicity, oral Category 4

Acute toxicity, inhalation

Skin corrosion/irritation

Serious eye damage/eye irritation

Sensitization, skin

Category 1

Category 1

Category 1

Environmental hazards Not classified.

Label elements



Signal word Danger

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin

reaction. Causes serious eye damage. Harmful if inhaled.

Precautionary statement

Prevention Do not breathe mist/vapours. Wash thoroughly after handling. Do not eat, drink or smoke when

using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye

protection/face protection.

Response Rinse mouth. IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair):

Take off immediately all contaminated clothing. Rinse skin with water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. If skin irritation or rash occurs: Get medical

advice/attention. Take off contaminated clothing and wash it before reuse.

Storage Store locked up

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

1/8

Supplemental information None.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Benzyl alcohol		100-51-6	20 - < 30
Formaldehyde, Polymer With Benzenamine, Hydrogenated		135108-88-2	20 - < 30
Benzene-1,3-dimethaneamine		1477-55-0	10 - < 20
4,4'-methylenedicyclohexaneamine		1761-71-3	1 - < 3
Other components below reportable I	evels		30 - < 40

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

InhalationRemove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Call a poison centre or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Call a physician

or poison control centre immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or poison control centre immediately.

Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Ingestion

Foam. Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions

equipment/instructions
Specific methods

General fire hazards

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: DEVCON® Brushable Ceramic Red Hardener
5491 Version #: 07 Revision date: 01-August-2023 Issue date: 29-May-2019

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Do not breathe mist/vapours. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Avoid prolonged exposure. When using, do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

V-1...

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH	Threshold Limit	Values ((TLV)

Components	Туре	Value
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.018 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended Components Type Value Benzene-1,3-dimethaneami Ceiling 0.1 mg/m3

ne (CAS 1477-55-0)

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value
Benzene-1,3-dimethaneami	Ceiling	0.1 mg/m3
ne (CAS 1477-55-0)		

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act), as amended Components Type Value

Benzene-1,3-dimethaneami Ceiling 0.018 ppm ne (CAS 1477-55-0)

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	туре	value
Benzene-1,3-dimethaneami ne (CAS 1477-55-0)	Ceiling	0.1 mg/m3

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended Components Type Value

Benzene-1,3-dimethaneami	Ceiling	0.1 mg/m3
ne (CAS 1477-55-0)		

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended Components Type Value

Benzene-1,3-dimethaneami Ceiling 0.1 mg/m3 ne (CAS 1477-55-0)

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21), as amended Components Type Value

Benzene-1,3-dimethaneami Ceiling 0.1 mg/m3 ne (CAS 1477-55-0)

Biological limit values

No biological exposure limits noted for the ingredient(s).

Material name: DEVCON® Brushable Ceramic Red Hardener

Exposure guidelines

Canada - Alberta OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Danger of cutaneous absorption

Canada - Ontario OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Can be absorbed through the skin.

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Benzene-1,3-dimethaneamine (CAS 1477-55-0)

Danger of cutaneous absorption

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency

shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield. Face shield is

recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing

should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.
Form Liquid.
Colour Amber.

Odour Ammoniacal.
Odour threshold Not available.
pH Not available.

Melting point/freezing point -15.2 °C (4.64 °F) estimated
Initial boiling point and boiling 205.3 °C (401.54 °F) estimated

range

Flash point 100.0 °C (212.0 °F) estimated

Evaporation rateNot available.Flammability (solid, gas)Not applicable.Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available. **Explosive limit - upper** Not available.

(%)

Vapour pressure 0.13 hPa estimated

Vapour density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 436 °C (816.8 °F) estimated

Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Density 1.09 g/cm3 estimated

Not explosive. **Explosive properties**

Combustible IIIB estimated Flammability class

Not oxidising. **Oxidising properties** Specific gravity 1.09 estimated

VOC 0 g/l

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerisation does not occur.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidising agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes severe skin burns. May cause an allergic skin reaction.

Causes serious eye damage. Eye contact

Ingestion Causes digestive tract burns. Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result.

Information on toxicological effects

Harmful if inhaled. Harmful if swallowed. **Acute toxicity**

Components **Species Test Results**

Benzyl alcohol (CAS 100-51-6)

Acute Dermal

LD50 Rabbit 2000 mg/kg

Inhalation

LC50 Rat > 4.177999999999999 mg/l, 4 Hours

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitisation Canada - Alberta OELs: Irritant

Benzene-1,3-dimethaneamine (CAS 1477-55-0) Irritant

Respiratory sensitisation Not a respiratory sensitiser.

Skin sensitisation May cause an allergic skin reaction.

5491 Version #: 07 Revision date: 01-August-2023 Issue date: 29-May-2019

Material name: DEVCON® Brushable Ceramic Red Hardener

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not available.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Prolonged inhalation may be harmful. **Chronic effects**

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability Bioaccumulative potential

No data is available on the degradability of any ingredients in the mixture.

Partition coefficient n-octanol / water (log Kow)

Benzyl alcohol 1.1

No data available. Mobility in soil

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of **Disposal instructions**

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

TDG

UN number UN2735

UN proper shipping name Transport hazard class(es)

AMINES, LIQUID, CORROSIVE, N.O.S. (Benzene-1,3-dimethaneamine), Limited Quantity

Class 8 Subsidiary risk Packing group Ш No. **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number UN2735

UN proper shipping name Transport hazard class(es) Amines, liquid, corrosive, n.o.s. (Benzene-1,3-dimethaneamine), Limited Quantity

Class 8 Subsidiary risk Ш Packing group **Environmental hazards** No. **ERG Code** 8L

Other information

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Passenger and cargo

aircraft

Allowed with restrictions.

Material name: DEVCON® Brushable Ceramic Red Hardener

5491 Version #: 07 Revision date: 01-August-2023 Issue date: 29-May-2019

Cargo aircraft only

Allowed with restrictions.

IMDG

UN number UN2735

UN proper shipping name AMINES, LIQUID, CORROSIVE, N.O.S. or POLYAMINES, LIQUID, CORROSIVE, N.O.S.

(Benzene-1,3-dimethaneamine), Limited Quantity

Transport hazard class(es)

Class 8
Subsidiary risk Packing group ||||

Environmental hazards

Marine pollutant

No.

EmS F-A, S-B

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Not established.


Annex II of MARPOL 73/78 and

the IBC Code

IATA



IMDG; TDG



15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information

29-May-2019 Issue date 01-August-2023 **Revision date**

Version No.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.

Material name: DEVCON® Brushable Ceramic Red Hardener

8/8 5491 Version #: 07 Revision date: 01-August-2023 Issue date: 29-May-2019

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).