SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

DEVCON® Aluminum Putty (F) Resin

Registration number

Product registration number UFI: G110-X039-700P-RV3F

Synonyms None. SKU# 0102

Issue date 02-July-2025

Version number 02

Revision date 04-July-2025 02-July-2025 Supersedes date

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company name **ITW Performance Polymers**

Address Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82

Contact person Customer Service 353(61)771500 Telephone number

353(61)471285

Email customerservice.shannon@itwpp.com

Emergency phone number 44(0) 1235 239 670 (24 hours)

1.4. Emergency telephone number

General emergency 112 or 999 SDS/Product information may not be available for the Emergency

Non-emergency medical

helpline

111 SDS/Product information may not be available for the Emergency Service.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies. The classification of the substance or mixture has been performed in accordance with ABNT NBR 14725.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation Category 2 H315 - Causes skin irritation.

Serious eye damage/eye irritation Category 2 H319 - Causes serious eye

irritation.

Specific target organ toxicity - repeated Category 2 H373 - May cause damage to

exposure organs through prolonged or

repeated exposure.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Calcium carbonate

Hazard pictograms



Signal word Warning

Hazard statements

H315 Causes skin irritation.
H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Prevention

P260 Do not breathe mist/vapours.
P264 Wash thoroughly after handling.
P280 Wear eye protection/face protection.

P280 Wear protective gloves.

Response

P302 + P352 IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P314 Get medical advice/attention if you feel unwell.
P332 + P313 If skin irritation occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage Not available.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

99.384 % of the mixture consists of component(s) of unknown acute inhalation toxicity.

2.3. Other hazards This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC)

No 1907/2006, Annex XIII. The mixture does not contain any substances included in the list

established in accordance with REACH Article 59(1) for having endocrine disrupting properties at a

concentration equal to or greater than 0.1% by weight.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Epoxy Resin: reaction product of bisphenol A and epichlorohydrin (refer to epichlorohydrin)	15 - 40	25068-38-6 -	01-2119456619-26-0000	-	
Classification:	Skin Irrit. 2	2;H315, Eye Irrit. 2;H3	319		
Calcium carbonate	10 - 30	1317-65-3 215-279-6	-	-	#
Classification:	-				

Other components below reportable

0.1 - 1

levels

List of abbreviations and symbols that may be used above

ATE: Acute toxicity estimate.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Union workplace exposure limit(s).

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and

delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media Suitable extinguishing

media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters Special protective

equipment for firefighters Special fire fighting

Move containers from fire area if you can do so without risk.

procedures Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Do not breathe mist/vapours. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not touch or walk through spilled material.

For emergency responders

Keep unnecessary personnel away. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe mist/vapours. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene

practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Observe industrial sector guidance on best practices.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SDS GREAT BRITAIN

Occupational exposure limits

UK. OELs. Workplace Exposure Limits (WELs) (EH40/2005 (Fourth Edition 2020)), Table 1

ComponentsTypeValueFormCalcium carbonate (CASTWA4 mg/m3Respirable.

4 mg/m3 Respirable dust.

10 mg/m3 Inhalable dust.

10 mg/m3 Inhalable

Biological limit valuesNo biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

1317-65-3)

(DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

Other
 Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

Environmental exposure

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or engineering modifications to the process equipment may be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Paste.
Physical state Liquid.

Form Liquid. Paste.

ColourGrey.OdourSlight.

Odour threshold Not available.

pH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

320 °C (608 °F) estimated

Flash point >204.4 °C (>399.9 °F)

129.4 °C (265.0 °F) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Material name: DEVCON® Aluminum Putty (F) Resin
0102 Version #: 02 Revision date: 04-July-2025 Issue date: 02-July-2025

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit – upper

(%)

Not available.

Vapour pressureNot available.Vapour densityNot available.Relative densityNot available.

Solubility(ies)

Viscosity

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)
Auto-ignition temperature

Decomposition temperature

Not available. Not available. Not available. Not explosive.

Not oxidising.

Oxidising properties 9.2. Other information

Explosive properties

Density 1.93 g/cm3 estimated

Specific gravity 1.93 estimated

VOC 0 g/l

SECTION 10: Stability and reactivity

10.1. ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoidContact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

vision. Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory sensitisationDue to partial or complete lack of data the classification is not possible. **Skin sensitisation**Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.CarcinogenicityDue to partial or complete lack of data the classification is not possible.Reproductive toxicityDue to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - Du

single exposure

Due to partial or complete lack of data the classification is not possible.

Material name: DEVCON® Aluminum Putty (F) Resin
0102 Version #: 02 Revision date: 04-July-2025 Issue date: 02-July-2025

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazardDue to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information May cause allergic respiratory and skin reactions.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative

potential

No data available.

Partition coefficient n-octanol/water (log Kow)

Not available.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC)

No 1907/2006, Annex XIII.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code

The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Discourage

sewage disposal. Waste should not be disposed of by release to sewers. Dispose of contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number UN3082

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)

name

14.3. Transport hazard class(es)

Class 9
Subsidiary hazard Label(s) 9
Hazard No. (ADR) 90
Tunnel restriction code R. Packing group |||

14.4. Packing group III
14.5. Environmental Ye

hazards

Yes

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number UN3082

14.2. UN proper shipping

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)

name

14.3. Transport hazard class(es)

Class 9
Subsidiary hazard Label(s) 9

14.4. Packing group III **14.5. Environmental** Yes

hazards

14.6. Special precautions

for user

Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number UN3082

14.2. UN proper shipping ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Epoxy resin)

name

14.3. Transport hazard class(es)

Class 9
Subsidiary hazard Label(s) 9
14.4. Packing group III
14.5. Environmental Yes

hazards

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG


14.1. - 14.6.: Not regulated as dangerous goods.

Not established.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

ADN; ADR; RID



Marine pollutant



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Retained direct EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use, as amended - Conditions of restriction given for the associated entry number should be considered

Not listed.

Other regulations

This product is classified and labelled in accordance with the retained CLP Regulation (EC) No 1272/2008, as amended for Great Britain. This Safety Data Sheet is compiled in accordance with REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758.

Follow the requirements of the Control of Substances Hazardous to Health Regulations 2002 [SI 2002/2677], as amended, when using this material.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations

ADN: European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

Not available.

IMDG: International Maritime Dangerous Goods.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit. TWA: Time Weighted Average.

vPvB: Very persistent and very bioaccumulative.

References

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any statements, which are not written out in full

under sections 2 to 15

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Revision information Training information Transport Information: Material Transportation Information Follow training instructions when handling this material.

Disclaimer

ITW Performance Polymers cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release.