

PROFESSIONAL STRENGTH

JASCO

SEMI-PASTE

PREMIUM PAINT & EPOXY REMOVER

FAST
15
MIN

NON-METHYLENE CHLORIDE FORMULA

STRIPS MULTIPLE LAYERS FAST

Use on Wood, Metal, Concrete and Masonry
Brushable - Clings to Surfaces
Water-Rinsable



ANGER! FLAMMABLE. VAPORS
MAY CAUSE FLASH FIRE OR IGNITE
EXPLOSIVELY. HARMFUL OR FATAL
IF SWALLOWED. VAPOR HARMFUL.
EYE AND SKIN IRRITANT.

Read entire label prior to use or storage.

¡PELIGRO! INFLAMABLE. LOS VAPORES
PUEDEN CAUSAR UN INCENDIO O
INCENDIO EXPLOSIVO. DANINO O LETAL SI
LO INGERE. VAPOR NOCIVO. IRRITANTE
PARA LOS OJOS Y LA PIEL.

Lea toda la etiqueta antes de usar o almacenar este producto.

ONE QUART (946 mL)

PATENT PENDING

J10228

DIRECTIONS FOR USE: 1. Shake well. 2. Pour into metal container. Apply thick coat with paint brush to small area (up to 3 ft. x 3 ft.). Brush in one direction. 3. Leave area and after 15 minutes test scrape small area to see if finish is ready for removal. Gently scrape loosened finish in direction of wood grain with plastic stripping tool. Use a toothbrush, toothpick, or stripping brush to remove old finish from recesses. Repeat application for stubborn finishes. 4. Use a clean abrasive pad dipped in after wash or mineral spirits to loosen remaining finish and remove residue. Surface should be completely clean and dry before refinishing.

IMPORTANT: Do not apply to floors or large surface areas because fire and health risks will increase. Keep container closed when not in use. Always wear chemical-splash goggles and chemical-resistant gloves when handling. A dust mask does not protect against vapors. Dispose of product within 3 months of opening.

DANGER! FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. TO REDUCE FIRE RISK: ENSURE ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS. Do not use in small, enclosed areas. If using indoors, cross ventilate work area and maintain fresh air movement by opening windows and doors. STOP work and leave area if strong odor is noticed or you experience dizziness. **IF WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION.** Extinguish all flames, pilot lights, stoves, heaters, electric motors and all other sources of ignition before use. Do not use until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing or other sources.

DANGER! HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. VAPOR HARMFUL. Contains Dimethyl Carbonate and Xylene. Reports have associated repeated and prolonged over-exposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid contact with skin, eyes, and clothing.

⚠ CA WARNING: Can expose you to Ethylbenzene, a carcinogen, and Methanol, a reproductive toxicant. See www.P65Warnings.ca.gov.

FIRST AID: IF SWALLOWED, do not induce vomiting. Immediately call Poison Control Center (1-800-222-1222), hospital or physician for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get immediate medical attention. **IN CASE OF SKIN CONTACT,** immediately wash with soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Remover • Max VOC: 50%.
Not for sale or use in California.

Latex	* Strips 5 layers in 15 minutes
Oil/Alkyd	Strips 5 layers in 45 minutes

Sold by:

©2025 W.M. Barr & Company, Inc., Memphis TN 38113

www.jasco-help.com. All rights reserved.

Label design is a trademark of W.M. Barr & Company, Inc.

QJPR001 J10228



IMPORTANTE: No aplicar en pisos ni superficies extensas, ya que aumentarán los riesgos de incendio y para la salud. Mantenga el envase cerrado cuando no esté en uso. Use siempre gafas protectoras contra salpicaduras de productos químicos y guantes resistentes a productos químicos al manipularlos. Una mascarilla antipolvo no protege contra los vapores. Deseche el producto en un plazo de 3 meses tras su apertura.

¡PELIGRO! INFLAMABLE. LOS VAPORES PUEDEN PROVOCAR UN INCENDIO REPENTINO O ENCENDERSE EXPLOSIVAMENTE. PARA REDUCIR EL RIESGO DE INCENDIO: ASEGURE UNA VENTILACIÓN ADECUADA PARA EVITAR LA ACUMULACIÓN DE VAPORES. No lo use en espacios pequeños y cerrados. Si lo usa en interiores, ventile el área de trabajo y mantenga una circulación de aire fresco abriendo ventanas y puertas. DETENGA el trabajo y abandone el área si nota un olor fuerte o experimenta mareos. Si el ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO UTILICE ESTE PRODUCTO. MANTÉNGALO ALEJADO DEL CALOR, LAS CHISPAS, LAS LLAMAS Y TODAS LAS DEMÁS FUENTES DE IGNICIÓN. Apague todas las llamas, pilotos, estufas, calentadores, motores eléctricos y cualquier otra fuente de ignición antes de usar. No lo use hasta que se hayan disipado todos los vapores. No fume. Manténgalo alejado de enchufes e interruptores eléctricos. Tenga cuidado con la electricidad estática generada por la ropa sintética u otras fuentes.

¡PELIGRO! DANINO O MORTAL SI SE INGERE. IRRITANTE DE OJOS Y PIEL. VAPOR DANINO. Contiene carbonato de dimetil y xileno. Los informes han asociado la sobreexposición repetida y prolongada a los solventes con daños neurológicos y otros daños fisiológicos. Uso indebido intencional de este producto por concentrar e inhalar los vapores puede ser dañino o fatal. Evite el contacto con la piel, los ojos y la ropa.

⚠ CA ADVERTENCIA: Puede exponerlo al etilbenceno, un carcinógeno, y al metanol, un tóxico reproductivo. Vea www.P65Warnings.ca.gov.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, no induzca el vómito. Llame inmediatamente al Centro de Control de Envenenamientos (1-800-222-1222), al hospital o al médico para recibir instrucciones. **EN CASO DE CONTACTO CON LOS OJOS,** lave inmediatamente con agua, retire cualquier lente de contacto, continúe enjuagando con agua durante al menos 15 minutos, luego obtenga atención médica inmediata. **EN CASO DE CONTACTO CON LA PIEL,** lave inmediatamente con agua y jabón. Si la irritación persiste, obtenga atención médica.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

Categoría de producto: Removedor de Pintura • Max VOC: 50%
No está a la venta o uso en California.

For assistance call: the Barr Help Line 1-844-969-1377
Monday-Friday, 8:00am - 4:30pm Central Time