

AMERICA'S #1 SOLVENT BRAND

Klean
Strip®

Made With
Mineral Spirits

PAINT THINNER

CLEANS & THINS



THINS

Oil-Based Paint,
Stain & Varnish



CLEANS

Brushes &
Equipment



Learn More!

DANGER!
HARMFUL OR FATAL IF SWALLOWED.
EYE IRRITANT.
Read entire label prior to use or storage.

ONE GALLON (3.785 L)

¡PELIGRO!
DAÑINO O MORTAL POR INGESTIÓN.
IRRITA LOS OJOS.
Lea toda la etiqueta antes de usar o almacenar
este producto.

J9961

Klean-Strip® Paint Thinner effectively thins oil-based paint, stain and varnish. It can also be used to clean brushes and equipment immediately after use.

DIRECTIONS FOR USE: Follow the paint product manufacturer's instructions for the proper amount of paint thinner required. We recommend starting with 4 ounces per gallon. Do not use more than recommended. Add gradually and stir thoroughly until desired consistency is obtained. Do not use as a thinner for latex paint or other water based coatings, lacquer or shellac. To remove fresh oil-based coatings, agitate brush or roller in Paint Thinner until all visible residue is dissolved. Then rinse using fresh Paint Thinner. Press out excess and lay flat to dry.

DANGER! HARMFUL OR FATAL IF SWALLOWED. EYE IRRITANT. Contains Petroleum Distillates. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** Do not swallow. Avoid contact with eyes and prolonged contact with skin.

FIRST AID: IF SWALLOWED, call physician immediately. Do not induce vomiting. Call a Poison Control Center at 1-800-222-1222 or hospital emergency room. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention. **IN CASE OF PROLONGED SKIN CONTACT,** wash thoroughly with soap and water. If irritation persists, get medical attention.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Thinner • **Max VOC:** 3%

Not for sale or use in the South Coast Air Quality Management District (SCAQMD)

For more ingredient information:

Visit www.barringredients.com
or call at 1-833-880-5319

For assistance:

Call the Barr Help Line 1-800-398-3892
Monday through Friday, 8:00am to 4:30pm CT

GKPT94002CA / J9962



©2022, W.M. Barr & Co., Inc.
Memphis, TN 38113
www.kleanstrip.com

INSTRUCCIONES DE USO: Siga las instrucciones del fabricante del producto de pintura en cuanto a la cantidad correcta de diluyente de pintura requerido. Recomendamos comenzar con 4 onzas por galón. No use más de lo recomendado. Agregue gradualmente y agite ampliamente hasta obtener la consistencia deseada. No utilice como diluyente en pintura de látex ni en otros recubrimientos, lacas o gomas lacas a base de agua. Para remover recubrimientos frescos a base de aceite, agite la brocha o el rodillo dentro del diluyente de pintura hasta que se disuelva todo el residuo visible. Luego enjuague usando adelgazante para pintura nuevo. Presione para extraer el exceso y déjelo secar en una superficie plana horizontal.

¡PELIGRO! DAÑINO O MORTAL POR INGESTIÓN. IRRITA LOS OJOS. Contiene destilados de petróleo. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.** No ingerir. Evite el contacto con los ojos y el contacto prolongado con la piel.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, llame a un médico inmediatamente. No induzca el vómito. Llame al centro de control toxicológico al 1-800-222-1222 o a una sala de emergencias de un hospital. **SI EL PRODUCTO ENTRA EN CONTACTO CON LOS OJOS,** enjuague de inmediato con agua, quítese los lentes de contacto en caso de llevar alguno, continúe enjuagando con agua durante al menos 15 minutos y a continuación obtenga asistencia médica. **EN CASO DE CONTACTO PROLONGADO CON LA PIEL,** lave de inmediato minuciosamente con agua y jabón. Si persiste la irritación, solicite atención médica.

MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.

Categoría de producto: Diluyente de pintura
COV máx.: 3%

No se permite la venta o uso en el Distrito de Control de la Calidad del Aire de la Costa Sur (SCAQMD).