

AMERICA'S #1 STRIPPER BRAND



# PREMIUM STRIPPER

STRIPS PAINT, EPOXY & POLYURETHANE FROM WOOD, METAL & MASONRY

WORKS IN  
15  
MINUTES

## FAST

Removes Multiple Layers Without Raising Wood Grain



## BRUSHABLE

Thick Formula Clings to Surface



Learn More!



**DANGER!** HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. EYE & SKIN IRRITANT. Read entire label prior to use or storage.

**¡PELIGRO!** NOCIVO O LETAL SI SE INGIERE. VAPOR NOCIVO. INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. IRRITANTE PARA LOS OJOS Y LA PIEL. Lea toda la etiqueta antes de usar o almacenar este producto.

ONE GALLON (3.785 L)

J10011

**DIRECTIONS FOR USE:** 1. Shake well. 2. Pour into a metal container and apply a thick coat with a paint brush to a small area. Brush in one direction only. Leave the area and let the stripper do the work. 3. After 15 minutes, test scrape a small area to see if finish is ready for removal. Remove loosened finish by gently scraping in direction of wood grain with a plastic stripping tool. A toothbrush, toothpick or stripping brush will help remove old finish buried in recesses. Multiple coats or stubborn finishes may require repeat application. 4. Use a clean abrasive pad dipped in After Wash or Odorless Mineral Spirits to loosen remaining finish and remove any residue. Surface should be completely clean and dry before refinishing.

**IMPORTANT:** Do not apply to floors or large surface areas because fire and health safety risks will increase dramatically. Always wear chemical-splash goggles and chemical-resistant gloves when handling this product. A dust mask does not provide protection against vapors. Dispose of product within 3 months of opening.

**DANGER! HARMFUL OR FATAL IF SWALLOWED. VAPOR HARMFUL. EYE AND SKIN IRRITANT.** Contains Dimethyl Carbonate and Xylene. Reports have associated repeated and prolonged over-exposure to solvents with neurological and other physiological damage. The risk to your health depends on the level and duration of exposure. Avoid breathing vapors or mist and contact with skin, eyes, and clothing. Do not swallow.

**DANGER! FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION.** Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience dizziness – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.**

**⚠ WARNING:** This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**FIRST AID: IF SWALLOWED,** do not induce vomiting. Call physician immediately. Call a Poison Control Center at 1-800-222-1222, or hospital emergency room for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get immediate medical attention. **IN CASE OF SKIN CONTACT,** immediately wash with soap and water. If irritation persists, get medical attention.

**KEEP OUT OF REACH OF CHILDREN.**

Product Category: Paint Remover • Max VOC: 50%

Not for sale or use in California.

PATENT PENDING

GKPS300 / J10012



©2022, W.M. Barr & Co., Inc.  
Memphis, TN 38113  
[www.kleanstrip.com](http://www.kleanstrip.com)

**INSTRUCCIONES DE USO:** 1. Agítelo bien. 2. Vierta en un recipiente metálico y aplique una capa gruesa con una brocha en un área pequeña. Pase la brocha en una sola dirección. Salga del área y deje actuar el removedor. 3. Después de 15 minutos, pruebe raspando una área pequeña para ver si el acabado está listo para removerse. Remueva el acabado aflojado raspando suavemente en la dirección de la fibra de la madera con una herramienta plástica removedora. Un cepillo de dientes, un palillo o un cepillo con cerdas de metal ayudará a eliminar el acabado viejo de los recovecos. Múltiples capas o acabados resistentes podrían requerir una aplicación repetida. 4. Utilice una almohadilla abrasiva limpia bañada en After Wash o en aguarrás mineral inodoro para aflojar el acabado restante y remover cualquier residuo. La superficie debe estar completamente limpia y seca antes de aplicar el nuevo acabado.

**IMPORTANTE:** No aplique a pisos ni a áreas grandes ya que el riesgo de incendio y los riesgos a la salud incrementarán dramáticamente. Siempre use gafas de protección contra salpicaduras de sustancias químicas y guantes resistentes a los productos químicos cuando maneje este producto. Una máscara para el polvo no otorga protección contra los vapores. Deseche el producto dentro de los 3 meses posteriores a la apertura.

**¡PELIGRO! DAÑO O MORTAL POR INGESTIÓN. VAPOR DAÑINO. IRRITA LOS OJOS Y LA PIEL.** Contiene carbonato de dimetilo y xileno. Ciertos informes asocian la sobreexposición repetida y prolongada a solventes con daños neurológicos y otros daños fisiológicos. El riesgo a la salud depende del nivel y de la duración de la exposición. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos y la ropa. No debe ingerirse.

**¡PELIGRO! INFLAMABLE. LOS VAPORES PUEDEN PROVOCAR COMBUSTIONES SÚBITAS O INFLAMARSE DE MANERA EXPLOSIVA. MANTÉNGASE LEJOS DEL CALOR, CHISPAS, LLAMAS Y OTRAS FUENTES DE IGNICIÓN.** Extinga todas las llamas y pilotos, y apague las estufas, calentadores, motores eléctricos y cualquier otra fuente de ignición durante su uso y hasta que se hayan disipado los vapores. No fumar. Mantenerlo lejos de tomacorrientes e interruptores eléctricos. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USE ÚNICAMENTE CON UNA VENTILACIÓN ADECUADA PARA EVITAR LA ACUMULACIÓN DE VAPORES.** No use en áreas donde los vapores se puedan acumular y concentrarse tales como sótanos, cuartos de baño y áreas pequeñas y encerradas. Si se utiliza bajo techo, abra todas las ventanas y las puertas y mantenga una ventilación cruzada de aire fresco en movimiento a través del área de trabajo. Si nota un olor fuerte o se marea – DETÉNGASE –, la ventilación es inadecuada. Abandone el área de inmediato. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.**

**⚠ ADVERTENCIA:** Este producto puede exponerlo al etilbenceno, el cual, de acuerdo con el Estado de California, puede causar cáncer, y al metanol, el cual, de acuerdo con el Estado de California, puede causar defectos congénitos y otros daños reproductivos. Para más información, visite [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN,** no induzca el vómito. Llame a un médico inmediatamente. Llame al centro de control toxicológico al 1-800-222-1222, o a la sala de emergencias de un hospital para más instrucciones. **SI EL PRODUCTO ENTRA EN CONTACTO CON LOS OJOS,** enjuague de inmediato con agua, quítese los lentes de contacto en caso de llevarlos, continúe enjuagando con agua durante al menos 15 minutos y a continuación obtenga asistencia médica de inmediato. **EN CASO DE CONTACTO CON LA PIEL,** lave de inmediato con jabón y agua. Si persiste la irritación, solicite atención médica.

**MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

Categoría de producto: Removedor de pintura • COV máx.: 50%

For assistance: Call the Barr Help Line 1-800-398-3892 Monday through Friday, 8:00am to 4:30pm CT

Latex	• Strips 5 layers in 15 minutes
Oil/Alkyd	• Strips 5 layers in 45 minutes



IMPORTADOR SERVICIOS HOME DEPOT S. de R.L. de C.V.  
RICARDO MARGANI  
805 SANTA ENGRACIA  
SAN PEDRO GARZA GARCIA,  
Nuevo León, C.P. 66267, MÉXICO R.F.C.  
SHD-940509-458, TEL. 81 55 70 00