Page: 1 of 8

SAFETY DATA SHEET Klean Strip Green Denatured Alcohol

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Klean Strip Green Denatured Alcohol

Company Name: W. M. Barr Phone Number:

2105 Channel Avenue (901)775-0100 Memphis. TN 38113

Web site address: www.wmbarr.com

Emergency Contact: 3E 24 Hour Emergency Contact (800)451-8346 **Information:** W.M. Barr Customer Service (800)398-3892

Intended Use: Heater Fuel
Product Code: QKGA75003

2. HAZARDS IDENTIFICATION

Flammable Liquids, Category 2

Acute Toxicity: Inhalation, Category 4
Acute Toxicity: Skin, Category 3

Serious Eye Damage/Eye Irritation, Category 2A

Carcinogenicity, Category 2

Toxic To Reproduction, Category 2

Specific Target Organ Toxicity (single exposure), Category 2
Specific Target Organ Toxicity (repeated exposure), Category 1









GHS Signal Word: Danger

GHS Hazard Phrases: Highly flammable liquid and vapor.

Toxic in contact with skin.

Causes serious eye irritation.

Harmful if inhaled.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs.

Causes damage to organs through prolonged or repeated exposure.

GHS Precautionary Phrases: Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe gas/mist/vapors/spray. Wash hands thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Use personal protective equipment as required.

GHS Response Phrases: IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): P361: Remove/Take off immediately all contaminated clothing.

Rinse skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical attention/advice.

Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

Call a POISON CENTER or doctor/physician if you feel unwell.

Get medical attention/advice if you feel unwell.

Specific measures see label.

If eye irritation persists, get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire, use dry powder chemical to extinguish.

GHS Storage and Disposal

Phrases:

Store in cool/well-ventilated place. Store locked up.

Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Medical Conditions Generally Diseases of the liver.

Aggravated By Exposure:

3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Hazardous Components (Chemical Name)	Concentration
64-17-5	Ethyl alcohol {Ethanol}	80.0 -100.0 %
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	3.0 -7.0 %
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	1.0 -5.0 %
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	0.1 -1.0 %
142-82-5	Hentane	0.1 -1.0 %

Additional Chemical

Specific percentage of composition is being withheld as a trade secret.

Information

4. FIRST AID MEASURES

Emergency and First Aid

Procedures:

Inhalation:

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or

artificial respiration until medical assistance can be rendered.

Skin Contact:

Wash with soap and water while removing contaminated clothing. If symptoms persist

seek medical advice.

Eye Contact:

Flush with large quantities of water for at least 15 minutes. Get medical attention.

Ingestion:

Call your poison control center, hospital emergency room or physician immediately for

instructions to induce vomiting.

Do not induce vomiting without medical advice. Never give anything by mouth to an

unconscious person.

Signs and Symptoms Of

Exposure:

Unconsciousness. Narcosis. Cyanosis (blue tissue condition, nails, lips, and/or skin).

Decrease in

motor functions. Behavioral changes. Edema. Liver enlargement. Jaundice. Proteinuria.

Birth

Licensed to W.M. Barr and Company

GHS format

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

defects. Sterility.

Poison. This product contains methanol. Methanol is metabolized to formaldehyde and Note to Physician:

> formic acid. These metabolites may cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used as an antidote. Methanol is effectively removed by

hemodialysis. Call your local poison control center for further instructions.

5. FIRE FIGHTING MEASURES

OSHA Class IB

55.00 F Method Used: Unknown Flash Pt: **Explosive Limits:** LEL: 3.3 % UEL: 19%

685.00 F **Autoignition Pt:**

Suitable Extinguishing Media: Use carbon dioxide, dry powder, alcohol-resistant foam, or water spray.

Unsuitable Extinguishing

Media:

Do not use water jet as an extinguisher

Fire Fighting Instructions: Self-contained respiratory protection should be provided for fire fighters fighting fires in

> buildings or confined area. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

Flashback of vapors possible over considerable distance.

Hazardous Combustion Fire may produce irritating, corrosive and/or toxic gases.

Products:

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or

Spilled:

Clean-up:

Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources,

keep flares, smoking or flames out of hazard area.

Small spills:

Take up liquid with sand, earth or other noncombustible absorbent material and place in

a plastic container where applicable.

Large spills:

Dike far ahead of spill for later disposal.

Do not flush into surface water or sanitary sewer system.

7. HANDLING AND STORAGE

Precautions To Be Taken in

Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty.

Dispose of empty container according to all regulations. Do not reuse this container.

Precautions To Be Taken in

Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store

near flames or at elevated temperatures.

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

8. EXPOSURE CONTROLS/PERSONAL PROTECTION
O. EXI OSUNE CONTINUES/I ENSONAL I NOTECTION

CAS#	Chemical Name	Jurisdiction	Recommended Exposure Limits	Notations
64-17-5	Ethyl alcohol {Ethanol}	ACGIH TLV	TLV: 1000 ppm	
		OSHA PELs	PEL: 1000 ppm	
	Methanol {Methyl alcohol; Wood alcohol}	ACGIH TLV	TLV: 200 ppm STEL: 250 ppm	
		OSHA PELs	PEL: 200 ppm	
141-78-6 (Ethyl acet	Acetic acid, ethyl ester ate}	ACGIH TLV	TLV: 400 ppm	
		OSHA PELs	PEL: 400 ppm	
	Methyl isobutyl ketone Isopropylacetone; MIBK; -pentanone}	ACGIH TLV	TLV: 20 ppm STEL: 75 ppm	
-		OSHA PELs	PEL: 100 ppm	
142-82-5	Heptane	ACGIH TLV	TLV: 400 ppm STEL: 500 ppm	
		OSHA PELs	PEL: 500 ppm	
Respirato	ory Equipment Fo		d work place and other regular users. Use o	only with adequate

Respiratory Equipment

(Specify Type):

ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

Eye Protection:

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

Protective Gloves:

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

Other Protective Clothing:

Various application methods can dictate the use of additional protective safety

equipment, such as impermeable aprons, etc., to minimize exposure.

Engineering Controls (Ventilation etc.):

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering -- Stop -- ventilation is inadequate. Leave area immediately.

Work/Hygienic/Maintenance Practices:

A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area.

Wash hands thoroughly after use.

Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that

cannot be decontaminated, such as gloves or shoes.

Page: 5 of 8

SAFETY DATA SHEET **Klean Strip Green Denatured Alcohol**

Revision: 03/19/2020

Supersedes Revision: 08/01/2018

9. PHYSI	CAL AND C	CHEMICAL	. PROPERTIES

Physical States: [] Gas [X] Liquid [] Solid

Clear, water white, thin liquid Appearance and Odor:

pH: No data. Melting Point: No data. **Boiling Point:** 174.20 F

Flash Pt: 55.00 F Method Used: Unknown

~ 2 (BuAC=1) **Evaporation Rate:** Flammability (solid, gas): No data available.

LEL: 3.3 % **Explosive Limits:** UEL: 19%

~ 44 MM HG at 20.0 C Vapor Pressure (vs. Air or

mm Hg):

Vapor Density (vs. Air = 1): ~ 1.6

Specific Gravity (Water = 1): 0.789 - 0.83at 60.0 F

Bulk density: 6.75 LB/GA Solubility in Water: miscible

Solubility Notes: Completely soluble in water.

Octanol/Water Partition No data.

Coefficient:

Percent Volatile: 100.0 % by weight. VOC / Volume: 789.0000 G/L 685.00 F Autoignition Pt: **Decomposition Temperature:** No data. No data. Viscosity:

10. STABILITY AND REACTIVITY

Stability: Unstable [] Stable [X]

Conditions To Avoid -

Heat, flames and sparks. Avoid temperatures exceeding the flash point.

Instability:

Incompatibility - Materials To Incompatible with strong oxidizing agents.

Avoid:

Hazardous Decomposition or Decomposition may produce carbon monoxide, carbon dioxide, and possibly other

unidentified organic compounds. Byproducts:

Will occur [] **Possibility of Hazardous** Will not occur [X]

Reactions:

Conditions To Avoid -No data available.

Hazardous Reactions:

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

11. TOXICOLOGICAL INFORMATION

Toxicological Information: This product has not

This product has not been tested as a whole. Refer to section 2 for acute and chronic

health effects. CAS# 64-17-5:

Acute toxicity, LD50, Oral, Rat, 7060. MG/KG.

Result:

Lungs, Thorax, or Respiration:Other changes.

- Toxicology and Applied Pharmacology, Academic Press, Inc., 1 E. First St., Duluth, MN

55802, Vol/p/yr: 16,718, 1970

CAS# 141-78-6:

Standard Draize Test, Eyes, Human, 400.0 PPM.

Result:

Liver: Hepatitis (hepatocellular necrosis), zonal.

- Journal of Industrial Hygiene and Toxicology, Vol/p/yr: 25,282, 1943

CAS# 108-10-1:

Standard Draize Test, Eyes, Species: Rabbit, 40.00 MG, Severe.

Result:

Effects on Newborn: Growth statistics (e.g., reduced weight gain).

Effects on Newborn: Behavioral.

- Union Carbide Data Sheet, Union Carbide Corp., 39 Old Ridgebury Rd., Danbury, CT

06817, Vol/p/yr: 4/25, 1958

Carcinogenicity/Other

Information: IARC 2

IARC 1 - Carcinogenic to humans

IARC 2B - Possibly Carcinogenic to Humans ACGIH A4 - Not Classifiable as a Human

Carcinogen.

CAS#	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA	
64-17-5	Ethyl alcohol {Ethanol}	n.a.	1	A4	n.a.	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	n.a.	n.a.	n.a.	n.a.	
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	n.a.	n.a.	n.a.	n.a.	
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	n.a.	2B	n.a.	n.a.	
142-82-5	Heptane	n.a.	n.a.	n.a.	n.a.	

12. ECOLOGICAL INFORMATION

General Ecological

Information:

This product has not been tested as a whole.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

Waste Disposal Method: D001

14. TRANSPORT INFORMATION

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

LAND TRANSPORT (US DOT):

DOT Proper Shipping Name: Ethyl alcohol

DOT Hazard Class: 3 FLAMMABLE LIQUID

UN/NA Number: UN1170 Packing Group: II



Additional Transport Information:

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists					
CAS # 64-17-5	Hazardous Components (Chemical Name) Ethyl alcohol {Ethanol}	S. 302 (EHS) No	S. 304 RQ No	S. 313 (TRI) No	
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood alcohol}	No	Yes 5000 LB	Yes	
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	No	Yes 5000 LB	No	
108-10-1	Methyl isobutyl ketone {Hexone; Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	No	Yes 5000 LB	Yes	
142-82-5	Heptane	No	No	No	
CAS#	Hazardous Components (Chemical Name)	Other US EPA or S	State Lists		
64-17-5	Ethyl alcohol {Ethanol}	TSCA: Inventory			
67-56-1	Methanol {Methyl alcohol; Carbinol; Wood	CAA HAP,ODC: HAP: VHAP			
	alcohol}	TSCA: Inventory			
		CA PROP.65: Yes: RDTox.			
141-78-6	Acetic acid, ethyl ester {Ethyl acetate}	TSCA: Inventory			
108-10-1	Methyl isobutyl ketone {Hexone;	CAA HAP,ODC: HAP: VHAP			
	Isopropylacetone; MIBK; 4-Methyl-2-pentanone}	TSCA: Inventory			
		CA PROP.65: Yes: Canc+RDTox.			
142-82-5	Heptane	TSCA: Inventory, 4	Test, 8A PAIR		

Additional Regulatory Information Regulatory Information

Statement:

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

All components of this material are listed on the TSCA Inventory or are exempt.

Page: 8 of 8

SAFETY DATA SHEET Klean Strip Green Denatured Alcohol

Revision: 03/19/2020 Supersedes Revision: 08/01/2018

16. OTHER INFORMATION

Revision Date: 03/19/2020

Preparer Name: W.M. Barr EHS Department (901)775-0100

Additional Information About No data available.

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.