

Formulated to meet low VOC limits; see warnings on label.
Formulado para cumplir con los límites bajos de VOC; ver advertencias en la etiqueta.

AMERICA'S #1 SOLVENT BRAND

Klean
Strip®

PAINT THINNER

CLEANS & THINS



THINS

Oil-Based Paint,
Stain & Varnish



CLEANS

Brushes &
Equipment



Learn More!

DANGER! EXTREMELY FLAMMABLE.
VAPORS MAY CAUSE FLASH FIRES OR
IGNITE EXPLOSIVELY. VAPOR HARMFUL.
EYE IRRITANT.

Read entire label prior to use or storage.

ONE QUART (946 mL)

¡PELIGRO! EXTREMADAMENTE
INFLAMABLE. LOS VAPORES PUEDEN
PROVOCAR COMBUSTIONES SUBITAS O
INFLAMARSE DE MANERA EXPLOSIVA.
VAPOR DAÑINO. IRRITA LOS OJOS.

Lea toda la etiqueta antes de usar o almacenar este
producto.

J9919

DIRECTIONS FOR USE: Follow product manufacturer's instructions for adding paint thinner. Use sparingly as paint thinner will cause coatings to become flammable.

IMPORTANT: Do not spread this product over surface areas greater than 1 sq. foot because fire and health safety risks will increase dramatically. Do not use to clean or flush spray equipment. Paint Thinner may soften or damage plastics, synthetics, and many other finishes.

DANGER! VAPOR HARMFUL. EYE IRRITANT. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Do not take internally. Avoid breathing of vapors or mist and contact with skin, eyes or clothing.

DANGER! USE WITH CAUTION: THIS PRODUCT IS EXTREMELY FLAMMABLE. THINNED COATINGS MAY BECOME EXTREMELY FLAMMABLE. FOLLOW ALL CAUTIONS BELOW WHEN USING THINNED COATINGS. DO NOT USE TO CLEAN OR FLUSH SPRAY EQUIPMENT.

VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Contains Acetone and Petroleum Distillates. Keep container tightly closed when not in use. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE OUTDOORS IN AN OPEN AREA.** It is dangerous to use this product indoors. If you must use indoors, **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.**

Cross-ventilate work area by opening all windows and doors and circulating fresh air through the work area to reduce vapor accumulation. Do not smoke. Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms or small enclosed areas. Whenever possible, use outdoors in an open air area. If any odor is noticed or you experience dizziness, headache, nausea or eye-watering – STOP – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** Always wear chemical-splash goggles and chemical-resistant gloves when handling this product. A dust mask does not provide protection against vapors.

FIRST AID: IF SWALLOWED, call physician immediately. Call the Poison Control Center at 1-800-222-1222 or hospital emergency room for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention. **IN CASE OF SKIN CONTACT,** irritation may result. Immediately wash with soap and water.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Thinner • Max VOC: 25 g/L

For assistance: Call the Barr Help Line 1-800-398-3992
Monday through Friday, 8:00am to 4:30pm CT

For more ingredient information: Visit www.barringredients.com
or call 1-833-880-5319

OKPT1045C / J10221



©2025, W.M. Barr & Co., Inc.
Memphis, TN 38113
www.kleanstrip.com

INSTRUCCIONES DE USO: Sigas las instrucciones del fabricante del producto para agregar el diluyente de pintura. Utilice con moderación, ya que el diluyente de pintura puede provocar recubrimientos que lleguen a ser inflamables.

IMPORTANTE: No rocíe este producto en áreas mayores a 1 pie cuadrado (0.093 m²) ya que el riesgo de incendio y los riesgos a la salud se incrementarán dramáticamente. No lo utilice para limpiar ni enjuagar el equipo rociador. El diluyente de pintura puede ablandar o dañar plásticos, superficies sintéticas y muchos otros acabados.

¡PELIGRO! VAPOR DAÑINO. IRRITA LOS OJOS. Ciertos informes asocian la sobreexposición repetida y prolongada a los solventes con daños neurológicos y otros daños fisiológicos. El uso indebido intencional de este producto para concentrar e inhalar de manera deliberada sus vapores puede resultar dañino o mortal. No ingerir. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos o la ropa.

¡PELIGRO! USE CON PRECAUCIÓN: ESTE PRODUCTO ES EXTREMADAMENTE INFLAMABLE. LOS RECURRIMIENTOS DILUIDOS PUEDEN HACERSE EXTREMADAMENTE INFLAMABLES. SIGA TODAS LAS PRECAUCIONES INDICADAS A CONTINUACIÓN CUANDO MANEJE RECURRIMIENTOS DILUIDOS. NO LO UTILICE PARA LIMPIAR NI ENJUAGAR EL EQUIPO ROCIADOR.

LOS VAPORES PUEDEN PROVOCAR COMBUSTIONES SUBITAS O INFLAMARSE DE MANERA EXPLOSIVA. MANTENGASE LEJOS DEL CALOR, CHISPAS, LLAMAS Y OTRAS FUENTES DE IGNICIÓN. Contiene acetona y destilados de petróleo. Mantenga el recipiente bien cerrado cuando no esté en uso. Extinga todas las llamas y pilotos, y apague las estufas, calentadores, motores eléctricos y cualquier otra fuente de ignición durante su uso y hasta que se hayan disipado los vapores. No fumar. Manténgase lejos de tomacorrientes e interruptores eléctricos. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USE AL AIRE LIBRE EN UN ÁREA ABIERTA.**

Es peligroso usar este producto en interiores. Si debe usarlo bajo techo, **USE ÚNICAMENTE CON UNA VENTILACIÓN ADECUADA PARA EVITAR LA ACUMULACIÓN DE VAPORES.** Ventile el área de trabajo abriendo todas las ventanas y puertas y haciendo circular aire fresco a través del área de trabajo para reducir la acumulación de vapor. No fumar. No use en áreas donde los vapores se puedan acumular y concentrarse tales como sótanos, cuartos de baño o áreas pequeñas y encerradas. Siempre que sea posible utilícelo en el exterior, en una zona al aire libre. Si nota algún olor o se marea, tiene dolor de cabeza, náuseas u ojos llorosos –**¡DETÉNGASE!**– la ventilación es inadecuada. **Abandone el área de inmediato. SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.** Siempre use gafas de protección contra salpicaduras de sustancias químicas y guantes resistentes a los productos químicos cuando maneje este producto. Una mascarilla para el polvo no otorga protección contra los vapores.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, llame a un médico inmediatamente. Llame al centro de control toxicológico al 1-800-222-1222 o a la sala de emergencias de un hospital para más instrucciones. **SI EL PRODUCTO ENTRA EN CONTACTO CON LOS OJOS,** enjuague de inmediato con agua, quítese las lentes de contacto en caso de llevar alguno, continúe enjuagando con agua durante al menos 15 minutos y a continuación obtenga asistencia médica de inmediato. **EN CASO DE CONTACTO CON LA PIEL,** puede resultar en irritación. Lávese inmediatamente con agua y jabón.

MANTENGASE FUERA DEL ALCANCE DE LOS NIÑOS.

Categoría de producto: Diluyente de pintura • COV máx.: 25 g/L