

Klean  
Strip

# KWIK-STRIP™

## FAST PAINT & VARNISH STRIPPER

NON-METHYLENE CHLORIDE FORMULA



works in  
**15**  
minutes

**STRIPS MULTIPLE  
LAYERS FAST**

For use on Wood,  
Metal & Masonry  
Convenient - Excellent  
for Smaller Projects  
Will Not Raise Wood Grain



**DANGER! FLAMMABLE. VAPORS  
MAY CAUSE FLASH FIRE OR IGNITE  
EXPLOSIVELY. HARMFUL OR FATAL  
IF SWALLOWED. VAPOR HARMFUL.  
EYE AND SKIN IRRITANT.**

Read entire label prior to use or storage.

NET WT 16 OZ (453 g)

**¡PELIGRO! INFLAMABLE. LOS  
VAPORES PUEDEN CAUSAR UN INCENDIO  
O INCENDIO EXPLOSIVO. DAÑINO O  
LETAL SI LO INGIERE. VAPOR NOCIVO.  
IRRITANTE PARA LOS OJOS Y LA PIEL.**

Lea toda la etiqueta antes de usar  
o almacenar este producto.

**PATENT PENDING**

**DIRECTIONS FOR USE:** 1. Wear chemical-resistant gloves and chemical splash goggles. 2. Shake well. Hold can in an upright position approximately 12" to 14" from surface. Point arrow on top of button away from you. Using a back-and-forth motion, apply a generous but even coat of remover to one small area at a time (up to 3 ft. x 3 ft.) because health safety risks will increase dramatically when used over large areas. 3. Allow time for remover to work. Do not rush job. Test a small area to see if finish is ready for removal. 4. Scrape off loosened finish by gently working in the direction of wood grain with a chemical-resistant plastic scraper. Wipe off sludge with rough cloth or medium steel wool. Repeat application if finish is particularly stubborn.

**HELPFUL TIPS:** Protect surrounding area from overspray with a heavy plastic drop cloth. Do not use on linoleum, plastic, rubber, asphalt, tile, fiberglass or other synthetics. Removers may harm these surfaces. For best results, use in temperatures between 65°F and 85°F, and away from strong breeze and hot sun. If spray tip becomes clogged, remove from can and hold under hot water. Replace tip making sure arrow is aimed away from you. **CLEAN UP:** Clean up used rags, paper and waste promptly. The work area and tools can be cleaned up with soap and water. Wash arms and hands with cold water and soap. **DISPOSAL:** If container is corroded, rusted or shows signs of deterioration, dispose of product. Dispose of empty cans and leftover product at your local household hazardous waste collection facility. If one is not available, dispose of in accordance with federal, state and local regulations.

**DANGER! CONTENTS UNDER PRESSURE.** Do not puncture or incinerate. Do not store at or expose to temperatures above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.

**IMPORTANT:** Do not apply to floors or any other large surface areas because fire and health safety risks will increase dramatically. Always wear chemical-splash goggles and chemical-resistant gloves when handling this product. A dust mask does not provide protection against vapors.

**DANGER! FLAMMABLE. VAPORS MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION.**

Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORS.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience dizziness - STOP - ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.**

**DANGER! HARMFUL OR FATAL IF SWALLOWED. EYE AND SKIN IRRITANT. VAPOR HARMFUL.** Contains Dimethyl Carbonate, Xylene and aerosol propellant. Reports have associated repeated and prolonged over-exposure to solvents with neurological and other physiological damage. The risk to your health depends on the level and duration of exposure. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Avoid breathing vapors or mist and contact with skin, eyes, and clothing. Do not swallow.

**WARNING:** This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**FIRST AID: IF SWALLOWED,** do not induce vomiting. Immediately call the Poison Control Center (1-800-222-1222), hospital emergency room or physician for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get immediate medical attention. **IN CASE OF SKIN CONTACT,** immediately wash with soap and water. If irritation persists, get medical attention.

**KEEP OUT OF REACH OF CHILDREN. • DO NOT USE TO STRIP BATHTUBS.**

Product Category: Paint Remover • Max VOC: 50%  
Not for sale or use in California.

Product # EKWS964

©2019 W.M. Barr & Co., Inc.  
Memphis, TN 38113

[www.kleanstrip.com](http://www.kleanstrip.com). All rights reserved.  
Label design is a trademark of W.M. Barr & Co., Inc.

Latex \*Strips 5 layers in 15 minutes  
Oil/Aldyd \*Strips 5 layers in 45 minutes



For assistance call:  
The Barr Help Line 1-800-398-3892  
Monday - Friday, 8:00am - 4:30pm CT



**INSTRUCCIONES PARA EL USO:** 1. Use guantes resistentes a productos químicos y gafas protectoras contra productos químicos. 2. Agite bien. Sosteniendo en posición vertical, aproximadamente de 12" a 14" de la superficie. Apunte la flecha en la parte de enfrente del botón en dirección contraria a su cuerpo. Use un movimiento de allá para acá, aplique una capa gruesa y uniforme del removedor a un área pequeña a la vez. Las 3 pies por 3 pies porque los riesgos para la salud aumentarán dramáticamente cuando se usen en áreas grandes. 3. Permita un tiempo para que el removedor trabaje. Pruebe con calma, asegure en un área pequeña para ver si el acabado está listo para ser retirado. 4. Retire el acabado frotando suavemente en la dirección de la veta de la madera con un raspador plástico resistente a químicos. Limpie con trapos ásperos con el estropajo de acero medio. Las capas o acabados difíciles pueden requerir que repita la aplicación. Si el agujero del moco se tapa, retire el bazo y sosténgalo hacia abajo caliente.

**CONSEJOS ÚTILES:** Proteja las áreas adyacentes con un plástico grueso. No lo use en linóleo, plástico, caucho, asfalto, fibra de vidrio o en otros sintéticos. Para obtener mejores resultados, use en superficies a temperaturas entre los 65°F y 85°F y lejos de la luz fuerte y la luz directa del sol. Si el agujero del moco se tapa, retire el bazo y sosténgalo hacia abajo caliente. Coloque nuevamente en el bazo asegurándose que la flecha apunte en dirección contraria a su cuerpo. Limpie los trapos usados, el papel y los desperdicios prontamente. El área de trabajo y las herramientas pueden impregnarse con agua y jabón. Lávese las manos con agua fría y jabón. **DESECHO:** Si el contenedor presenta corrosión, óxido o muestra signos de deterioro, deséchelo. Deséchelo las latas vacías y el producto remanente en las instalaciones de recolección de desechos peligrosos para uso en casa que haya en su localidad. Si no hubiera uno disponible, deséchelo de acuerdo con los reglamentos federales, estatales y locales.

**¡PELIGRO! CONTENIDO BAJO PRESIÓN.** No pinche ni incinere. No almacenar ni exponer a temperaturas superiores a 120° F. La exposición al calor o la exposición prolongada al sol pueden causar estallidos.

**IMPORTANTE:** No aplique en pisos ni en otras superficies grandes porque los riesgos de incendio y seguridad aumentarán drásticamente. Siempre use gafas de protección contra salpicaduras de sustancias químicas y guantes resistentes a los productos químicos cuando maneje este producto. Una mascarilla antipolvo no brinda protección contra vapores.

**¡PELIGRO! INFLAMABLE. LOS VAPORES PUEDEN CAUSAR UN INCENDIO O INCENDIO EXPLOSIVO. MANTÉNGASE FUERA DEL CALOR, CHISPAS, LLAMAS Y TODAS LAS DEMÁS FUENTES DE IGNICIÓN.** Apague todas las llamas y luces piloto, y apague todas las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición durante el uso y hasta que todos los vapores se hayan ido. No fume. Mantener alejado de enchufes eléctricos e interruptores. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USE ÚNICAMENTE CON VENTILACIÓN ADECUADA PARA EVITAR LA EXISTENCIA DE VAPORES.** No lo use en áreas donde los vapores se puedan acumular y concentrar, como sótanos, baños y áreas pequeñas y cerradas. Si lo usa en el interior, abra todas las ventanas y puertas y mantenga una ventilación cruzada de aire fresco en movimiento en el área de trabajo. Si se nota un fuerte olor o si experimenta mareos - DETÉNGASE - la ventilación es inadecuada. Salga del área inmediatamente. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.** Una mascarilla antipolvo no brinda protección contra los vapores.

**¡PELIGRO! NOCIVO O LETAL SI SE INGIERE. IRRITANTE PARA LOS OJOS Y LA PIEL. VAPOR NOCIVO.** Contiene dimetil carbonato, xileno y propulsor de aerosol. Los informes han asociado la sobreexposición repetida y prolongada a solventes con daños neurológicos y otros daños fisiológicos. El riesgo para su salud depende del nivel y la duración de la exposición. El uso indebido intencional de este producto al concentrar e inhalar vapores deliberadamente puede ser dañino o fatal. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos y la ropa. No debe ingerirse.

**ADVERTENCIA:** Este producto puede exponerlo al etilbenceno, que en el estado de California es cancerígeno, y al metanol, que el estado de California considera que causa defectos de nacimiento u otros daños reproductivos. Para obtener más información, vaya a [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN,** no induzca el vómito. Llame inmediatamente al Centro de Control de Envenenamientos (1-800-222-1222), a la sala de emergencias del hospital o al médico para recibir instrucciones. **EN CASO DE CONTACTO CON LOS OJOS,** lave inmediatamente con agua, retire cualquier lente de contacto, continúe enjuagando con agua durante al menos 15 minutos, luego obtenga atención médica inmediata. **EN CASO DE CONTACTO CON LA PIEL,** lave inmediatamente con agua y jabón. Si la irritación persiste, obtenga atención médica.

**MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.  
NO LO UTILICE PARA DESMONTAR BAÑERAS.**

Categoría de producto: Removedor de Pintura • COV Máx.: 50%

No está a la venta o uso en California.

IMPORTADOR SERVIDOS HOME DEPOT, S. de R.L. de C.V.  
RICARDO MARGAN GOS, SANTA ENGRACIA,  
SAN PEDRO GARZA GARCIA, Nuevo León, C.P. 66267.  
MEXICO R.F.C. SHD-940609-158 TEL 81 55 70 00

J9097

