**Klean Strip Odorless Mineral Spirits for CARB** 

Revision: 11/22/2022

Page: 1 of 6

Printed: 11/22/2022

Supersedes Revision: 11/21/2022

### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Klean Strip Odorless Mineral Spirits for CARB

W. M. Barr **Company Name:** 

> 2105 Channel Avenue Memphis, TN 38113

Web site address: www.wmbarr.com

3E 24 Hour Emergency Contact **Emergency Contact:** (800)451-8346

Information: W.M. Barr Customer Service (800)398-3892

Intended Use: General Purpose Degreaser

**Product Code:** GKSP94214CA, QKSP94005CA, GKSP94006CA, GKSP94006PCA, QKSP945CA

# 2. HAZARDS IDENTIFICATION

#### **Aspiration Toxicity, Category 1**



**GHS Signal Word:** Danger

**GHS Hazard Phrases:** H304: May be fatal if swallowed and enters airways.

H336: May cause drowsiness or dizziness.

**GHS Precautionary Phrases:** 

GHS Response Phrases: P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

GHS Storage and Disposal

P405: Store locked up.

Phrases:

P501: Dispose of contents/container according to local, state and federal regulations.

OSHA Regulatory Status:

This material is classified as hazardous under OSHA regulations.

**Potential Health Effects** 

(Acute and Chronic):

INHALATION:

Vapor harmful. Danger of serious damage to health by prolonged exposure through

inhalation.

SKIN CONTACT:

Prolonged skin contact may cause skin irritation and/or dermatitis.

EYE CONTACT:

Liquid contact may cause irritation.

INGESTION:

Harmful or fatal if swallowed. May cause gastrointestinal irritation, nausea, vomiting, and

diarrhea.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged overexposure to solvents with

neurological and other physiological damage.

TARGET ORGANS: skin, central nervous system

PRIMARY ROUTES OF ENTRY: inhalation, skin contact

Medical Conditions Generally None known.

Aggravated By Exposure:

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

Printed: 11/22/2022 **Klean Strip Odorless Mineral Spirits for CARB** Revision: 11/22/2022

Supersedes Revision: 11/21/2022

Page: 2 of 6

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

CAS# **Hazardous Components (Chemical Name)** Concentration

Hydrotreated light distillate (petroleum, mineral 64742-47-8

spirits)

4. FIRST AID MEASURES

**Emergency and First Aid** 

Skin:

Procedures:

Wash the skin thoroughly with water and soap, if available, while removing contaminated

clothing. Seek medical attention if irritation develops or persists.

100.0 %

Eyes:

Immediately begin to flush eyes with water, remove any contact lens. Continue to flush

the eyes for at least 15 minutes. Seek medical attention.

Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult,

give oxygen. Get immediate medical attention.

Ingestion:

If swallowed, do NOT induce vomiting. Seek immediate medical attention. Call a physician, hospital emergency room, or poison control center immediately. Never give

anything by mouth to an unconscious person.

Signs and Symptoms Of

**Exposure:** 

See Potential Health Effects.

## 5. FIRE FIGHTING MEASURES

NFPA Class IIIB Flammability Classification:

Flash Pt: 203.00 F Method Used: Pensky-Marten Closed Cup

**Explosive Limits:** LEL: 0.6 % UEL: 5.5 %

> 428.00 F Autoignition Pt:

Suitable Extinguishing Media: Use carbon dioxide, dry powder, foam, or water spray / fog.

Unsuitable Extinguishing None known.

Media:

Self-contained respiratory protection should be provided for fire fighters fighting fires in Fire Fighting Instructions:

> buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have

been exposed to intense heat or flame.

Flammable Properties and

Hazards:

**Hazardous Combustion** 

Carbon monoxide, carbon dioxide

**Products:** 

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

**GHS** format

**Klean Strip Odorless Mineral Spirits for CARB** 

Revision: 11/22/2022

Page: 3 of 6

Printed: 11/22/2022

Supersedes Revision: 11/21/2022

#### 6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Released Or Spilled:

Isolate the immediate area. Prevent unauthorized entry. Eliminate all sources of ignition in area and downwind of the spill area. Stay upwind, out of low areas, and ventilate closed spaces before entering. All equipment used when handling this product must be grounded or non-sparking. Do not touch or walk through spilled material. Stop leak if you can do so without risk. Prevent entry into waterways, sewers, or confined areas. A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand, or other non-combustible material and transfer to compatible containers. For large spills, dike ahead of the spill for possible collection and reuse or disposal.

## 7. HANDLING AND STORAGE

Precautions To Be Taken in Handling:

Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.

Do not use near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

Ensure all equipment is electrically grounded before beginning transfer operations.

Avoid prolonged skin contact.

Precautions To Be Taken in Storing:

Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near any source of heat or open flame, furnace areas, pilot lights, stoves, etc.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Chemical Name Notations** CAS# Jurisdiction **Recommended Exposure Limits** 64742-47-8 Hydrotreated light ACGIH TLV TLV: 200 mg/m3 distillate (petroleum, mineral spirits)

Respiratory Equipment (Specify Type):

For use in areas with inadequate ventilation or fresh air, wear a properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors.

For OSHA controlled work places and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding the appropriate TLV.

A dust mask does not provide protection against vapors.

Eye Protection: Chemical splash goggles should be worn to prevent eye contact.

Protective Gloves: Wear gloves with as much resistance to the chemical ingredients as possible. Glove

> materials such as nitrile rubber may provide protection. Glove selection should be based on chemicals being used and conditions of use. Consult your glove supplier for

additional information. Gloves contaminated with product should be discarded and not

reused.

Other Protective Clothing: Various application methods can dictate use of additional protective safety equipment,

> such as impermeable aprons, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such

as gloves or shoes.

**Engineering Controls** (Ventilation etc.):

Use process enclosures, local exhaust ventilation, or other engineering controls to

control airborne levels below recommended exposure limits.

Use only with adequate ventilation to prevent buildup of vapors. Do not use in areas where vapors can accumulate and concentrate, such as basements, bathrooms or small

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

**GHS** format

Klean Strip Odorless Mineral Spirits for CARB

Revision: 11/22/2022

Page: 4 of 6

Printed: 11/22/2022

Supersedes Revision: 11/21/2022

enclosed areas. Whenever possible, use outdoors in an open air area. If using indoors open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea or eye-watering -- STOP -- ventilation is inadequate. Leave area immediately and move to fresh air.

Work/Hygienic/Maintenance Wash hands thoroughly after use and before eating, drinking, or smoking.

Practices:

Do not eat, drink, or smoke in the work area.

Facilities storing or handling this material should be equipped with an emergency eyewash and safety shower.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**Physical States:** [ ] Gas [X] Liquid [ ] Solid Appearance and Odor:

Clear, colorless mild hydrocarbon odor. Odor threshold not determined.

N.D.

-56.20 F Melting Point:

443.00 F - 473.00 F **Boiling Point:** 

Flash Pt: 203.00 F Method Used: Pensky-Marten Closed Cup

**Evaporation Rate:** 0.19 (BuAC=1) Flammability (solid, gas): NFPA Class IIIB

LEL: 0.6 % **Explosive Limits:** UEL: 5.5 %

Vapor Pressure (vs. Air or

mm Hg):

0.2 MM HG at 68.0 F

Vapor Density (vs. Air = 1):  $4.5 \, Air = 1$ 

Specific Gravity (Water =

at 25.0 C 0.769 - 0.805

1):

:Hq

Density: 6.4 - 6.7 LB/GL Not established Bulk density:

Solubility in Water: Insoluble

Saturated Vapor N.D.

Concentration:

Octanol/Water Partition ND

Coefficient:

Percent Volatile: 100.0 % by weight. VOC / Volume: 0.5000 % WT > 428.00 F Autoignition Pt:

Decomposition

Temperature:

Viscosity: 1.6 CPS

Particle Size: Not established Heat Value: Not established

Product category, general purpose degreaser, is not a VOC as defined by the California a\_fld\_hdr[9]:

Licensed to W.M. Barr and Company: MIRS SDS, (c) A V Systems, Inc.

**Klean Strip Odorless Mineral Spirits for CARB** 

Printed: 11/22/2022 Revision: 11/22/2022

Page: 5 of 6

Supersedes Revision: 11/21/2022

A4

Air Resources Board (CARB).

ND = Not determined. NE = Not Established.

Information with regard to primary physical hazard:

### 10. STABILITY AND REACTIVITY

Stability: Unstable [ ] Stable [ X ]

**Conditions To Avoid -**

Instability:

Incompatibility - Materials To Incompatible with oxidizing agents.

Avoid:

Hazardous Decomposition or Thermal decomposition may produce carbon monoxide and carbon dioxide.

**Byproducts:** 

Possibility of Hazardous

Will occur [ ]

Will not occur [X]

Reactions:

Conditions To Avoid - Hazardous Reactions:

## 11. TOXICOLOGICAL INFORMATION

**Toxicological Information:** Refer to section 2 for acute and chronic effects.

**Chronic Toxicological** 

Effects:

Carcinogenicity/Other ACGIH A4 - Not Classifiable as a Human Carcinogen.

Information:

CAS # Hazardous Components (Chemical Name) NTP IARC ACGIH OSHA

64742-47-8 Hydrotreated light distillate (petroleum, mineral spirits)

### 12. ECOLOGICAL INFORMATION

General Ecological

This product has not been tested as a whole.

Information:

### 13. DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose in accordance with applicable local, state, and federal regulations.

### 14. TRANSPORT INFORMATION

#### LAND TRANSPORT (US DOT):

**DOT Proper Shipping Name:** 

DOT Hazard Class: UN/NA Number:

Additional Transport

Information:

The shipper / supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion,

or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

Klean Strip Odorless Mineral Spirits for CARB

Printed: 11/22/2022 Revision: 11/22/2022

Page: 6 of 6

Supersedes Revision: 11/21/2022

15. REGULATORY INFORMATION

EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists

CAS# **Hazardous Components (Chemical Name)** S. 302 (EHS) S. 304 RQ S. 313 (TRI)

64742-47-8 Hydrotreated light distillate (petroleum, mineral No No

spirits)

CAS# **Hazardous Components (Chemical Name)** Other US EPA or State Lists

64742-47-8 Hydrotreated light distillate (petroleum, mineral TSCA: Inventory

spirits)

Additional Regulatory

Information

Regulatory Information

Statement:

This product is regulated by the United States Consumer Product Safety Commission and is subject to certain labeling requirements under the Federal Hazardous Substances Act. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS). The product label also includes other important information, including directions for use, and should always be read in its entirety prior to using the product.

All components of this material are listed on the TSCA Inventory or are exempt.

#### **16. OTHER INFORMATION**

11/22/2022 11/21/2022 **Revision Date: Previous revision:** 

W.M. Barr EHS Department Preparer Name: (901)775-0100

**Additional Information About** 

This Product:

Company Policy or

Disclaimer:

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.