

INSTRUCCIONES DE USO: Siga las instrucciones del fabricante del recubrimiento en cuanto a la cantidad correcta de diluyente de laca requerido. Recomendamos comenzar con una proporción de 4 onzas por galón. No use más de lo recomendado por el fabricante. Cuando use como un limpiador, vierta una pequeña cantidad en un contenedor de vidrio o de metal.

IMPORTANTE: No aplique a pisos ni a áreas grandes ya que el riesgo de incendio y los riesgos a la salud incrementarán dramáticamente. No lo utilice para limpiar ni enjuagar el equipo rociador. No debe utilizarse como diluyente automotriz.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE. LOS VAPORES PUEDEN PROVOCAR COMBUSTIONES SÚBITAS O INFLAMARSE DE MANERA EXPLOSIVA. MANTÉNGASE LEJOS DEL CALOR, CHISPAS, LLAMAS Y OTRAS FUENTES DE IGNICIÓN. Extinga todas las llamas y pilotos, y apague las estufas, calentadores, motores eléctricos y cualquier otra fuente de ignición durante su uso y hasta que se hayan disipado los vapores. No fumar. Mantenerlo lejos de tomacorrientes e interruptores eléctricos. Tenga cuidado con la electricidad estática generada por la ropa sintética y otras fuentes. **USE ÚNICAMENTE CON UNA VENTILACIÓN ADECUADA PARA EVITAR LA ACUMULACIÓN DE VAPORES.** No use en áreas donde los vapores se puedan acumular y concentrarse tales como sótanos, cuartos de baño y áreas pequeñas y encerradas. Si se utiliza bajo techo, abra todas las ventanas y las puertas y mantenga una ventilación cruzada de aire fresco en movimiento a través del área de trabajo. Si nota un fuerte olor o si experimenta mareos – **DETÉNGASE** – la ventilación es inadecuada. Abandone el área de inmediato. **SI EL ÁREA DE TRABAJO NO ESTÁ BIEN VENTILADA, NO USE ESTE PRODUCTO.** Una máscara para el polvo no otorga protección contra los vapores.

¡PELIGRO! NOCIVO EN CASO DE INGESTIÓN. VAPOR DAÑINO. IRRITA LOS OJOS. Contiene éter 2-propanona y éter de glicol. Ciertos informes asocian la sobreexposición repetida y prolongada a los solventes con daños neurológicos y otros daños fisiológicos. El uso indebido intencional de este producto para concentrar e inhalar de manera deliberada sus vapores puede resultar dañino o mortal. No ingerir. Evite respirar los vapores o la niebla y el contacto con la piel, los ojos o la ropa.

PRIMEROS AUXILIOS: EN CASO DE INGESTIÓN, llame a un médico inmediatamente. Llame al centro de control toxicológico al 1-800-222-1222 o a la sala de emergencias de un hospital para más instrucciones. **EN CASO DE CONTACTO CON LOS OJOS,** enjuague de inmediato con agua, quítese los lentes de contacto en caso de llevar alguno, continúe enjuagando con agua durante al menos 15 minutos, y a continuación obtenga asistencia médica de inmediato. **EN CASO DE CONTACTO CON LA PIEL** puede resultar en irritación. Lávese inmediatamente con agua y jabón. **MANTÉNGASE FUERA DEL ALCANCE DE LOS NIÑOS.**

Categoría de producto: Diluyente de pintura

COV máx.: 25 g/l



FLAMMABLE LIQUID

3

ATENCIÓN
Cuando está vacío, podría
contener vapores
explosivos. No corte,
perfore ni suelde en o
cerca de este recipiente.

ATTENTION
When empty, may
contain explosive vapors.
Do not cut, puncture or
weld on or near this
container.

UN1263, PAINT RELATED MATERIAL

AMERICA'S #1 SOLVENT BRAND

Klean
Strip®

LACQUER
THINNER
CLEANS PROJECT TOOLS


IMPROVES
Flow & Leveling


HELPS
Resist Blushing


Learn More!

DANGER! EXTREMELY FLAMMABLE.
VAPORES MAY CAUSE FLASH FIRES OR IGNITE
EXPLOSIVELY. HARMFUL IF SWALLOWED.
VAPOR HARMFUL. EYE IRRITANT.
Read entire label prior to use or storage.

¡PELIGRO! EXTREMADAMENTE INFLAMABLE.
LOS VAPORES PUEDEN PROVOCAR
COMBUSTIONES SÚBITAS O INFLAMARSE DE
MANERA EXPLOSIVA. NOCIVO EN CASO DE
INGESTIÓN. VAPOR DAÑINO. IRRITA LOS OJOS.
Lea toda la etiqueta antes de usar o almacenar este producto.

FIVE GALLONS (18.925 L)

Klean-Strip® Lacquer Thinner is a high-solvency, fast-drying thinner for lacquer. Cleans tools and equipment after a lacquer project.

DIRECTIONS FOR USE: Follow the coating manufacturer's instructions for the proper amount of Lacquer Thinner required. We recommend starting with a ratio of 4 ounces per gallon. Do not use more than recommended by the manufacturer. When using as a cleaner, pour a small amount in a glass or metal container.

IMPORTANT: Do not apply to floors or large surface areas because fire and health safety risks will increase dramatically. Do not use to clean or flush spray equipment. Not for use as an automotive thinner.

DANGER! EXTREMELY FLAMMABLE. VAPORES MAY CAUSE FLASH FIRE OR IGNITE EXPLOSIVELY. KEEP AWAY FROM HEAT, SPARKS, FLAME, AND ALL OTHER SOURCES OF IGNITION. Extinguish all flames and pilot lights, and turn off all stoves, heaters, electric motors and all other sources of ignition during use and until all vapors are gone. Do not smoke. Keep away from electrical outlets and switches. Beware of static electricity generated by synthetic clothing and other sources. **USE ONLY WITH ADEQUATE VENTILATION TO PREVENT BUILDUP OF VAPORES.** Do not use in areas where vapors can accumulate and concentrate such as basements, bathrooms and small, enclosed areas. If using indoors, open all windows and doors and maintain a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience any dizziness – **STOP** – ventilation is inadequate. Leave area immediately. **IF THE WORK AREA IS NOT WELL VENTILATED, DO NOT USE THIS PRODUCT.** A dust mask does not provide protection against vapors.

DANGER! HARMFUL IF SWALLOWED. VAPOR HARMFUL. EYE IRRITANT. Contains 2-propanone and glycol ethers. Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. Intentional misuse of this product by deliberately concentrating and inhaling vapors can be harmful or fatal. Do not swallow. Avoid breathing of vapors or mist and contact with skin, eyes or clothing.

FIRST AID: IF SWALLOWED, call physician immediately. Call a Poison Control Center at 1-800-222-1222 or hospital emergency room for instructions. **IN CASE OF EYE CONTACT,** immediately flush with water, remove any contact lens, continue flushing with water for at least 15 minutes, then get medical attention. **IN CASE OF SKIN CONTACT,** irritation may result. Immediately wash with soap and water.

KEEP OUT OF REACH OF CHILDREN.

Product Category: Paint Thinner • **Max VOC:** 25 g/l

For assistance: Call the Barr Help Line at 1-800-398-3892
Monday through Friday 8:00am to 4:30pm CT

For more ingredient information:
Visit www.barringredients.com or call at 1-833-880-5319



©2023, W.M. Barr & Co., Inc.
Memphis, TN 38113
www.kleanstrip.com

CML170SC / J10053



0 30192 17031 1