Safety Data Sheet

1. IDENTIFICATION

Product identifier: PIPW11627
Other Name: UV Matte Coating for Digital
Recommended use of the chemical and restrictions on use:
UV Printing
Manufacturer: Magnum Inks & Coatings
Address: 355 Wright Drive Middletown, Ohio 45044
Telephone Number: 877-460-8406 (M-F 8am – 5pm EST)
Emergency phone number: Call CHEMTREC Day or Night 1-800-424-9300

2. HAZARD(S) IDENTIFICATION

Classification:
GHS Classification: Skin Category 2
Eye Category 2
Skin Sensitizer Category 1
STOTRE2
Carcinogenicity Category 2

Label Elements:

Signal word: Warning

Symbol(s):

Hazard statement(s)

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H351 Suspected of causing cancer
H373 May cause damage to organs (kidney, liver) through prolonged or repeated exposure.

Precautionary statement(s)

P260 Do not breathe dust/fumes/gas/mist/vapors/spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.
P362+P364 Take off contaminated clothing and wash before reuse.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

13. COMPOSITION/INFORMATION ON INGREDIENTS

For Mixtures:

Chemical name	CAS No. and other unique identifiers	Concentration
Monomer	15625-89-5	35-45%
Bisphenol-A diacrylate oligomer	55818-57-0	05-15%
Monomer	42978-66-5	10-20%
Methyl diethanolamine	105-59-9	04-08%
Photoinitiator	119-61-9	04-08%
Acrylated Resin	2156-97-0	1.0-3.0%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Not expected to be a hazard due to low volatility under standard conditions. Inhalation of mist or vapor may cause irritation of respiratory tract.

Skin contact: Remove contaminated clothing and wash contact area with soap and water and flush with lukewarm water for 15 minutes. Pay particular attention to hair, nose, ears and other areas not easily cleaned. If sticky, a waterless cleaner may be used. Obtain emergency medical attention.

Eye contact: Flush with plenty of water for at least 20-30 minutes. Remove contact lenses if present and easy to do. Retract eyelids often. Obtain emergency medical attention if pain, blinking, tears or redness persist.

Ingestion: If appreciable quantities have been swallowed, seek medical attention. DO NOT INDUCE VOMITING! Obtain emergency medical attention.

Most important symptoms/effects, acute and delayed: Causes skin and eye irritation. May cause allergic skin reaction.

Indication of immediate medical attention and special treatment, if necessary: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

S. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use dry chemical, foam or carbon dioxide.

Specific hazards arising from the chemical: High temperatures, inhibitor depletion, accidental impurities, or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during runaway polymerization. Avoid the use of a stream of water to conh·ol fires since frothing can occur.

Special protective equipment and precautions for firefighters: Do not enter fire area without proper protection. See Section 10 - Stability and Reactivity. Fight fire from a safe distance/protected location. Heat/impurities may increase temperature/build pressure/rupture closed containers, spreading fire, increasing risk of burns/injuries. Water jet may be ineffective in firefighting due to low solubility. Use water spray/fog for cooling. Pressure relief system may plug with solids, increasing risk of overpressure. Notify authorities if liquid enters sewer/public waters.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Spilled or released material may polymerize and release heat/gases. Extinguish all ignition sources and ventilate the area. Wear protective equipment during clean-up. Move leaking containers to a ventilated area. Stop discharge, if it can be performed safely, and contain the material. Soak up small spill with inert solids (such as vermiculite, clay) and sweep/shovel into suitable vented disoposal container. Wash spill area with a strong detergent and water solution; rinse with water but minimize water use during clean-up.

Environmental precautions: Dike and recover large spill. Prevent entry into natural bodies of water. Do not allow to enter sewers/surface or ground water. For spills on water, contain/minimize dispersion and collect. Dispose/report per regulatory requirements.

Methods and materials for containment and cleaning up: Provide adequate ventilation during clean-up. Dispose of absorbed material in accordance with regulations.

7. HANDLING AND STORAGE

Precautions for safe handling: Pouring, transfer and processing of this material do not require heating. However, product may be heated to l 40°F for not more than 24 hours. Overheating may compromise product quality and/or result in an uncontrolled hazardous polymerization. If product freezes, heat as indicated above and mix gently to redistribute the inhibitor. Product should be consumed in its entirety after heating/melting to avoid multiple "re-heats" which may affect product quality or result in product degradation. The product's inhibitors require the presence of dissolved oxygen. Maintain, at a minimum, the original headspace in the product container and do not blanket or mix with oxygen-free gas as it renders the inhibitor ineffective. Ensure air space (oxygen) is present during heating/melting. Prevent contamination by foreign materials. Prevent moisture contact. Use only non-sparking tools and limit storage time.

Conditions for safe storage, including any incompatibilities: Avoid prolonged (longer than shelf-life) storage temperatures above 100°F. Store in tightly closed containers in a properly vented storage area away from heat, sparks, open flame, strong oxidizers, radiation, and other initiators. Containers should be stored away from heat. Keep containers tightly closed. Shelf life is 6 months from receipt. Maintain bulk storage temperatures between 60-80°F.

S. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Proprietary mixture	OSHA PEL	None established
	ACGIH TLV	None established

Appropriate engineering controls: Safety showers, eyewash stations and adequate ventilation. If handling results in aerosol or vapor generation, local exhaust ventilation is recommended.

Individual protection measures, such as personal protective equipment:
Respiratory protection: If exposure exceeds the occupational exposure limit, use NIOSH/MSHA-approved respiratory protection equipment as specified in the NIOSH/OSHA I98I occupational health guidelines for chemical hazards. If this material is handled at elevated temperature or under mist-fonning conditions, NIOSH/MSHA-approved respiratory protection equipment should be used.

Skin protection: Impervious gloves (neoprene) must be worn. Gloves should be removed and replaced immediately if there is any indication of degradation or chemical breakthrough. Remove gloves immediately after use. Wash hands with soap and water.

Eye protection: Eye protection such as safety glasses with side shields, chemical splash goggles and/or face shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles or vapor. Contact lenses should not be worn.

Other: Use chemically resistant apron or other impervious clothing to avoid prolonged or repeated skin contact. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use "Good Manufacturing Practices" when using this material.

19. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): viscous liquid
Odor: slight acrylic

Odor threshold: Not detennined	**nH:** Not determined
Meltin!! noint/frcezin!!noint: Not determined	**Initial boilin!! noint and boilin!!ran!!e:** > 300°F
Flash point: > 200°F	**Evaporation rate:** Slower than butyl acetate
Flammability (solid, 2as): Not flammable	
Flammable limits: LEL: Not annlicable	**UEL:** Not annlicable
Vanor nressure: Not determined	**Vaoor densitv:** Heavier than **air.**
Relative densitv: >1.0	**Solubilin•(iesl:** Not determined
Partition coefficient: n-octanol/water: Not detennined	**Auto-ignition temperature:** Not applicable
Decomoosition temoerature: Not determined	Viscosity: Not determined

J10. STABILITY AND REACTIVITY

Reactivity: Normally stable but will react with light and heat.
Chemical stability: Normally stable but may become unstable with removal of inhibitor.
Possibility of hazardous reactions: No hazardous reactions when stored and handled according to instructions. This product is chemically stable.
Conditions to avoid: High temperatures, localized heat sources (i.e. drum or band heaters), oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing, inert gases, storage> 140°F, loss of dissolved air, loss of polymerization inhibitor, contamination with incompatible materials.
Incompatible materials: Polymerizationinitiators, including peroxides, strongoxidizing agents,strongreducers, free radical initiators, oxygen scavengers, copper, copper alloys, carbon steel, iron, rust, nickel, cobalt, strong bases, ultraviolet light and/or sunlight.
Hazardous decomposition products: Acrid smoke-fumes/carbon monoxide/carbon dioxide and perhaps other toxic vapors may be released during a fire involving this product

11. TOXICOLOGICAL INFORMATION

Acute effects of exposure:

Inhalation: Respiratory tract irritation hazard
Ingestion: Slight ingestion hazard
Skin contact: Skin irritant
Eye contact: Severe eye irritant

Chronic effects: May damage fertility or the unborn child.

Numerical measures of toxicity: Not determined

Carcinogenicity: Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

Chemical Name	ACGIB	IARC	NTP	OSHA
Trimethylolpropane Tricacrylate 15625-89-5		Group 2B		X

Legend

IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X -Present

12. ECOLOGICAL INFORMATION

Ecotoxicity: No data available
Persistence and degradability: No data available
Bioaccumulative potential: No data available
Mobility in soil: No data available
Other adverse effects: No data available

t3. DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging. Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied. Do not cut, weld, braze, solder, drill, grind, or expose containers to heat, flame, spark, or other sources of ignition. Contaminated packaging may exhibit hazards.

t4. TRANSPORT INFORMATION

UN number: Not regulated
UN proper shipping name: Not regulated
Transport hazard classes(es): Not regulated
Packing group, if applicable: Not regulated

Environmental hazards: Not regulated

Transport in bulk (according to Annex II ofMARPOL 73/78 and the IBC Code): Not regulated

15. REGULATORY INFORMATION

Safety, health, and environmental regulations specific for the product in question.

CERCLA:

SARA Hazard Category (311/312)

Pursuant to Section 311/312 of SARA Title III, the physical and health hazards categories for this product are identified below:

Fire Hazard:	NO
Sudden Release of Pressure Hazard:	NO
Reactivity Hazard:	YES
Immediate (Acute) Health Hazard:	YES
Delayed (Chronic) Health Hazard:	YES

SARA313

This product does not contain any substance listed in Section 313 at or above the de minimis level.

EPA TSCA Inventory

The chemical compounds of this product are contained on the Section 8(B) Chemical Substance Inventory List (40CFR710).

California (Proposition 65): This product contains a component or components known to the state of California to cause cancer or reproductive toxicity.

Trimethylolpropane triacrylate	15625-89-5	<45%
Bisphenol-A	80-05-7	< 50 ppm
Toluene	108-88-3	<0.07%
Benzophenone	119-61-9	<6%

16. OTHER INFORMATION

Hazardous Material Information System (U.S.A.)

Health: 2
Fire: 1
Reactivity: 2
Personal Protection: D

Caution: HMIS® ratings are based on a 0-4 rating scale, with O representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200 or OSHA 2012 Hazcom Standard, the preparer may choose to provide them. HMIS®ratings are to be used with a fully implemented HMIS®program.

SDS Revision History:
Date of preparation: 04/17/2015
Date of last revision: 11/24/2025

NOTICE

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.