

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

* 1 Identification

Product identifier**Product name:** Cyan UV LED Adherent Ink**Article number:** 0C01xx**Details of the supplier of the safety data sheet**

CET Color

4450 Commerce Dr. SW

Atlanta, GA 30336 - USA

1-404-228-1259

Manufacturer/Supplier:

CET Color

4450 Commerce Dr. SW

Atlanta, GA 30336

USA

Emergency telephone number: CHEMTREC 1-800-424-9300

2 Hazard(s) identification

Classification of the substance or mixture

Acute Tox. 4 H302 Harmful if swallowed.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Repr. 1B H360 May damage fertility or the unborn child.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

Label elements**GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).**Hazard pictograms**

GHS05 GHS07 GHS08

Signal word Danger**Hazard-determining components of labeling:**

4-(1-oxo-2-propenyl)-morpholine

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

2H-Azepin-2-one, 1-ethenylhexahydro-

3,3,5-Trimethylcyclohexyl acrylate

Isobournyl Acrylate

hexamethylene diacrylate

Tetrahydrofurfuryl Acrylate

propylidynetrimethanol, propoxylated, esters with acrylic acid

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

Hazard statements

Harmful if swallowed.
Causes skin irritation.
Causes serious eye damage.
May cause an allergic skin reaction.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Call a poison center/doctor if you feel unwell.
If on skin: Wash with plenty of water.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Rinse mouth.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:

5117-12-4 4-(1-oxo-2-propenyl)-morpholine	10 - 25%
STOT RE 2, H373; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317	
86178-38-3 3,3,5-Trimethylcyclohexyl acrylate	10 - 25%
Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1B, H317; STOT SE 3, H336	
5888-33-5 Isobornyl Acrylate	10 - 25%
Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide	10 - 25%
Repr. 2, H361	
2235-00-9 2H-Azepin-2-one, 1-ethenylhexahydro-	2.5 - 10%
STOT RE 1, H372; Acute Tox. 4, H302; Acute Tox. 4, H312; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
13048-33-4 hexamethylene diacrylate	2.5 - 10%
Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317	
2399-48-6 Tetrahydrofurfuryl Acrylate	2.5 - 10%
Repr. 1B, H360; Skin Corr. 1C, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1, H317; Flam. Liq. 4, H227	

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid
Eye Irrit. 2A, H319; Skin Sens. 1, H317

2.5 - 10%

4 First-aid measures

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Immediately call a doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents: Use fire fighting measures that suit the environment.

Special hazards arising from the substance or mixture No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Not required.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

Prevent formation of aerosols.

Information about protection against explosions and fires: Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Control parameters

Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

13048-33-4 hexamethylene diacrylate

WEEL Long-term value: 1 mg/m³

DSEN

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

Information on basic physical and chemical properties

General Information

Appearance:

Form:

Liquid

Color:

Cyan

Odor:

Characteristic

Odor threshold:

Not determined.

pH-value:

Not determined.

Change in condition

Melting point/Melting range:

Undetermined.

Boiling point/Boiling range:

107 °C (224.6 °F)

Flash point:

Not applicable.

Flammability (solid, gaseous):

Not applicable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not selfigniting.

Danger of explosion:

Product does not present an explosion hazard.

Explosion limits:

Lower:

Not determined.

Upper:

Not determined.

Vapor pressure:

Not determined.

Density:

Not determined.

Relative density

Not determined.

Vapor density

Not determined.

Evaporation rate

Not determined.

Solubility in / Miscibility with

Water:

Fully miscible.

Partition coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic:

Not determined.

Kinematic:

Not determined.

Other information

No further relevant information available.

10 Stability and reactivity

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects

Acute toxicity:

LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 < 1,115 mg/kg

Dermal LD50 > 10,956 mg/kg

5117-12-4 4-(1-oxo-2-propenyl)-morpholine

Oral LD50 500 mg/kg (ATE)

2235-00-9 2H-Azepin-2-one, 1-ethenylhexahydro-

Oral LD50 500 mg/kg (ATE)

Dermal LD50 1,100 mg/kg (ATE)

13048-33-4 hexamethylene diacrylate

Oral LD50 > 5,000 mg/kg (rat)

Dermal LD50 > 3,000 mg/kg (rab)

2399-48-6 Tetrahydrofurfuryl Acrylate

Oral LD50 928 mg/kg (rat)

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid

Oral LD50 > 2,000 mg/kg (rat)

Primary irritant effect:

on the skin: Irritant to skin and mucous membranes.

on the eye: Strong irritant with the danger of severe eye injury.

Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

Carcinogenic categories

IARC (International Agency for Research on Cancer)

105-60-2 1,6-hexanolactam: 3

108-88-3 Toluene: 3

123-35-3 Myrcene: 2B

100-41-4 ethylbenzene: 2B

127-19-5 N,N-dimethylacetamide: 2B

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

12 Ecological information

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Ecotoxicological effects:

Remark: Toxic for fish

Additional ecological information:

General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

Waste treatment methods

Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number

DOT

not regulated

IMDG, IATA

UN3082

UN proper shipping name

DOT

not regulated

IMDG

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (3,3,5-Trimethylcyclohexyl acrylate, Isobournyl Acrylate),
MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S. (3,3,5-Trimethylcyclohexyl acrylate, Isobournyl Acrylate)

Transport hazard class(es)

DOT

Class

not regulated

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

IMDG, IATA



Class	9 Miscellaneous dangerous substances and articles
Label	9
Packing group	
DOT	not regulated
IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
Special precautions for user	Warning: Miscellaneous dangerous substances and articles
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	

IMDG

Limited quantities (LQ)

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (3,3,5-TRIMETHYLCYCLOHEXYL ACRYLATE, ISOBOURNYL ACRYLATE), 9, III

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA

Section 355 (extremely hazardous substances):

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

5117-12-4 4-(1-oxo-2-propenyl)-morpholine: ACTIVE

86178-38-3 3,3,5-Trimethylcyclohexyl acrylate: ACTIVE

5888-33-5 Isobournyl Acrylate: ACTIVE

75980-60-8 Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide: ACTIVE

2235-00-9 2H-Azepin-2-one, 1-ethenylhexahydro-: ACTIVE

13048-33-4 hexamethylene diacrylate: ACTIVE

53879-54-2 propylidynetrimethanol, propoxylated, esters with acrylic acid: ACTIVE

Hazardous Air Pollutants

108-88-3 Toluene

100-41-4 ethylbenzene

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

Proposition 65

Chemicals known to cause cancer:

123-35-3 Myrcene

100-41-4 ethylbenzene

127-19-5 N,N-dimethylacetamide

Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

127-19-5 N,N-dimethylacetamide

Chemicals known to cause developmental toxicity:

108-88-3 Toluene

127-19-5 N,N-dimethylacetamide

Carcinogenic categories

EPA (Environmental Protection Agency)

108-88-3 Toluene: II

110-82-7 cyclohexane: I

100-41-4 ethylbenzene: D

TLV (Threshold Limit Value established by ACGIH)

105-60-2 1,6-hexanolactam: A5

108-88-3 Toluene: A4

100-41-4 ethylbenzene: A3

127-19-5 N,N-dimethylacetamide: A4

NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS05

GHS07

GHS08

Signal word Danger

Hazard-determining components of labeling:

4-(1-oxo-2-propenyl)-morpholine

Diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

2H-Azepin-2-one, 1-ethenylhexahydro-

3,3,5-Trimethylcyclohexyl acrylate

Isobornyl Acrylate

hexamethylene diacrylate

Tetrahydrofurfuryl Acrylate

propylidynetrimethanol, propoxylated, esters with acrylic acid

Hazard statements

Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause an allergic skin reaction.

May damage fertility or the unborn child.

Causes damage to organs through prolonged or repeated exposure.

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Get medical advice/attention if you feel unwell.

Rinse mouth.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H227 Combustible liquid.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H361 Suspected of damaging fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012

Printing date 05/18/2021

Version: 1.0

Reviewed on 05/18/2021

Product name: Cyan UV LED Adherent Ink

OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 1B: Reproductive toxicity – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

*** Data compared to the previous version altered.**

— US —